

NORDICA MATT

FULL-MATT HOUSE PAINT



WOODEN SURFACES OUTDOORS




Stylish full-matt weather resistance

NORDICA MATT is a full-matt house paint with Nordica-class weather resistance. The combination of the paint's high quality ingredients results in a paint film that has a hard surface but is still flexible. The paint film is dirt-repellent and remains clean better than an ordinary house paint.

As a result of dirt-repellence, excellent colour durability and weather resistance, NOR-DICA MATT House Paint provides an extremely long-lasting protection for a wooden house. It is suitable for new primed wooden surfaces and those previously coated with acrylate or oil paint, such as exterior walls, facial boards and weatherboards.

There is very little absorption of water into NORDICA MATT paint film, resulting in reduced moisture expansion and subsequent cracking. However, the paint film will allow diffusion, meaning that normal structural moisture can escape through a wall.





NORDICA MATT Full-matt house paint

Water-borne acrylate house paint providing a full-matt surface that is dirt-repellent and protects wooden surfaces. Suitable for new primed and previously with acrylate or oil paint coated wooden surfaces, such as exterior cladding panels, weather-boards and wooden fences.

Gloss group: 6, full-matt. **Spreading capacity:** Sawn timber 5–7 m²/l, planed timber 8–10 m²/l. **Application method:** Brush, spray gun. **Drying time:** Touch dry in an hour, a second coat can be applied in four hours. **Colour (tintability):** Base paints 1, 3 and 5, and black pre-tinted shade. Can be tinted with the tones in the Exterior painting colour chart range. **Recommended primer:** NORDICA PRIMER. **Package sizes:** 0.45 l, 0.9 l, 2.7 l, 9 l, 18 l. **Paint product group:** 461 (MaalausRYL 2012).



TEKNOS OY

Takkatie 3, P.O.Box 107, Fl-00371 Helsinki, Finland Tel. (09) 506 091, Fax (09) 5060 9501 www.teknos.com

