

PANEELISEINÄMAALI

Beautiful and durable protection for
wood panel and log surfaces



INDOOR WOOD PANEL AND LOG SURFACES



Beautiful and durable protection for panel and log walls

PANEELISEINÄMAALI is a breathable, water-borne paint for all wood wall surfaces indoors. It can be used to create a new look, even for darkened surfaces, quickly and easily. A stunning, silk-matt surface and wash resistance ensure a durable and stylish end result.

PANEELISEINÄMAALI is easy to apply and evens out well. The surface dries quickly and can be repainted after three hours. The composition of the paint effectively prevents extracts in the wood from penetrating. PANEELISEINÄMAALI is superbly suited for use as a primer and a topcoat, so no separate knotting lacquer or primer is required. Suitable for use in dry areas as well as in washrooms and changing rooms, and holiday homes that are cold and humid during the winter. PANEELISEINÄMAALI can be tinted using all of the colours on the Indoor Painting colour chart.



BREATHABLE



PREVENTS COLOUR BLEEDING

Only two coats are necessary, and no separate primer is required!



How to paint a panel or log wall:

1. Thoroughly clean all dust, grease and dirt from the surfaces. Remove any old paint that is flaking off the surface. Use RENSA SUPER Paint Cleaner to clean previously painted or varnished surfaces.
2. If necessary, use SILORA D Quick Filler to repair holes and scratches. Sand down any filled-in areas evenly.
3. Thoroughly mix the paint. Apply a primer coat of undiluted PANEELISEINÄMAALI to untreated wood surfaces. No other primer or knotting lacquer is required. Use a synthetic fibre brush of the same width as the panel. Begin by delimiting the edges of the wall and the ceiling and floor boundaries.
4. Apply one or two topcoats of PANEELISEINÄMAALI to primed and previously treated surfaces. Coat the panels or logs one at a time using parallel strokes.
5. Wash the painting tools, first using water. Then use a cleaning agent to ensure that the bristles remain soft. Finally, rinse with water.
6. Recycle all waste appropriately. When the packaging is empty and dry, it can be recycled.



PANEELISEINÄMAALI Paint for panel walls

Water-borne acrylic dispersion paint for wood surfaces. For priming and topcoating new and previously varnished or painted panel and timber walls indoors.

Gloss group: 5, matt. Colour: PM1 (white) and PM3. Can be tinted using all of the colours on the indoor colour chart. Coverage: 10 m²/l. Package sizes: 2.7 l and 9 l. Low-emission. The product has been granted the best emission class (M1) for building materials.

M1

EMISSION CLASS FOR BUILDING MATERIAL

10
m²/l



TIPS

- If you are taking a break from painting, place your tools in a plastic bag and seal it so that it is air-tight. This will ensure that you do not need to wash the tools.
- Masking tape should be removed before the paint dries completely – this ensures that the tape does not take dried paint with it.
- Under normal conditions, the product forms a final film at 3–4 weeks, when the surface attains its final hardness and durability. Before this, the coated surface should be handled with care.



We make it durable

Teknos is a Finnish family company that was established in 1948. Its diverse product selection includes paints and surface treatment products for wood, mineral surfaces and metal, for both indoor and outdoor applications.

Uncompromising product development, strong experience and continuous learning have made Teknos the leading expert in its field. Our high-quality products and useful tips are available to everyone who is looking for the best possible end-results.