

SUPERLATEKSI

SPECIAL ACRYLATE



ADHESION AND HEAT-RESISTANCE FOR INDOOR SURFACES

Superlateksi

Adheres to all surfaces

Teknos' Superlateksi is a handy, reliable special paint for interior surfaces. Thanks to Superlateksi's excellent adhesion, you will not need a separate primer when using this paint, which can even be applied directly to challenging surfaces. Excellent heat and wash-resistance ensure that, even in the toughest conditions, surfaces treated with Superlateksi stay good looking and do not yellow.

Surfaces requiring adhesion	Superlateksi
Brick walls	★★★★★
Galvanised/zinc-coated air ducts	★★★★★
Varnished wood surfaces e.g. (panel roof)	★★★★★
Playing area markings for sports mats	★★★★★
Plastic pipes (sewage)	★★
Interior walls	★★★★★
Galvanised/zinc-coated interior sheet-metal surfaces	★★★★★
Plastic coated interior steel panels	★★★★★

Surfaces requiring heat resistance	Superlateksi
"Rocket stove"	★★★★
Exterior surface of fireplace	★★★★★
Radiators and pipes	★★★★★
Firewall	★★★★★

Excellent ★★★★★

Good ★★★★

Possible ★★

Not recommended –



A MATTE SPECIAL ACRYLATE

A waterborne acrylate dispersion paint for interior spaces. Excellent adhesion, smooth application, and wash and heat-resistance. Can be applied without adhesive primer even on challenging surfaces.

Gloss group: 5, matte. **Spreading capacity:** 8-10 m²/l. **Tint:** Base paints 1 and 3, can be tinted to obtain the shades shown on Interior Colour Cards. **Paint product group:** 314, MaalausRYL 2012 (Paint product group 32, MaalausRYL 2001). **Package sizes:** 0.9 l, 2.7 l, 9 l and 18 l.