

## DECLARATION OF PERFORMANCE

no 0033

for product **SILOKSAN ANTI-CARB**

1. Unique identification code of the product-type:  
EN 1504-2: ZA.1d and ZA.1e
2. Intended use/es:  
Surface protection products – Coatings  
Ingress protection (1.3)  
Moisture control (2.2)  
Increasing resistivity (8.2)
3. Manufacturer:  
Teknos Oy  
Takkatie 3, P.O. Box 107  
FI-00371 Helsinki, Finland
4. System/s of assessment and verification of constancy of performance:  
system 2+
5. Harmonised standard:  
EN 1504-2: 2005

Notified body/ies:

Eurofins Expert Services Oy, identification number 0809  
Certificate of conformity of the factory production control 0809-CPR-1063

6. Declared performance/s:


Essential characteristics	Performance	Harmonised Technical specification
Linear shrinkage	NPD	
Coefficient of thermal expansion	NPD	
Cross cut	NPD	
Permeability to CO <sub>2</sub>	Requirement: $s_D(\text{CO}_2) > 50 \text{ m}$	
Water vapour permeability	Class I: $s_D < 5 \text{ m}$	
Capillary absorption and permeability to water	Requirement: $w < 0,1 \text{ kg/m}^2\text{h}^{0,5}$	EN 1504-2:2004
Thermal compatibility	NPD	
Resistance to thermal shock	NPD	
Chemical resistance	NPD	
Crack bridging ability	NPD	
Adhesion strength by pull off test	Requirement: Rigid system without trafficking: $\geq 1,0 \text{ (0,7) N/mm}^2$	
Reaction to fire	NPD	
Skid resistance	NPD	
Artificial weathering	NPD	
Antistatic behaviour	NPD	
Adhesion on wet concrete	NPD	
Dangerous substances	See safety data sheet	

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Helsinki 05.02.2026



Harri Lipsonen  
Director, Product Development



Artem Vochev  
Director, Product Development