

according to 1907/2006/EC, Article 31

1170725

Reviewed on: 30/06/2021 Printing date: 01/07/2021

SECTION 01: Identification of the substance/mixture and of the company undertaking

- 1.1 Product identifier
- · Trade name:
- ALPOCRYL KF 5372 BASE TR
 - Article number / Safety Data Sheet:
 - 1.2 Relevant identified uses of the substance or mixture and uses advised against
 - Application of the substance / the preparation

Coating material

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
- Teknos AG
- Industriestrasse 7

LI-9487 Gamprin-Bendern

T +423 375 94 00

F +423 375 94 99

- Further information obtainable from:
- Product safety department. e-mail address: li-sdb@teknos.com
- 1.4 Emergency telephone number:
- Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

SECTION 02: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 - H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 - H315 Causes skin irritation.

STOT SE 3 - H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms





GHS02

GHS07

- Signal word Warning
- Hazard-determining components of labelling:
 - n-butyl acetate
- Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

EUH208 Contains methyl methacrylate. May produce an allergic reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P302+P352 IF ON SKIN: Wash with plenty of water.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(continued on page 2)



according to 1907/2006/EC, Article 31

1170725

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: ALPOCRYL KF 5372 BASE TR

(continued of page 1)

%

P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

- · 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT:
- Not applicable.
- vPvB:

Not applicable.

SECTION 03: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- Description:

CAS Number

Mixture of substances listed below with nonhazardous additions.

• Dangerous components:

123-86-4	n-butyl acetate	25,00- 40,00
	EC number: 204-658-1	•
	Record number 01-2119485493-29	
	Flam. Liq. 3 - H226; STOT SE 3 -	
	H336	
1330-20-7	xylene	15,00- 25,00
	EC number: 215-535-7	
	Record number 01-2119488216-32	
	🍑 Flam. Liq. 3 - H226; 🖖 Acute Tox.	
	4 - H312, Acute Tox. 4 - H332, Skin Irrit. 2	
	- H315	
100-41-4	ethylbenzene	1,00- 5,00
	EC number: 202-849-4	
	Record number 01-2119489370-35	
	♦ Flam. Liq. 2 - H225; ♦ STOT RE 2 -	
	H373, Asp. Tox. 1 - H304; 💠 Acute Tox. 4	
	- H332	
80-62-6	methyl methacrylate	0,50- 1,00
	EC number: 201-297-1 Record number 01-2119452498-28	
	★ Flam. Liq. 2 - H225; ♦ Skin Irrit.	
	2 - H315, Skin Sens. 1 - H317, STOT SE 3 -	
	H335	
3030-47-5	bis(2-dimethylaminoethyl)(methyl)amine	0,00- 0,50
	EC number: 221-201-1	2,22
	Record number 01-2119979537-18	
	🧇 Skin Corr. 1B - H314; 🧇 Acute Tox.	
	3 - H311; 💠 Acute Tox. 4 - H302	
112-07-2	2-butoxyethyl acetate	1,00- 5,00
	EC number: 203-933-3	
	Record number 01-2119475112-47	
	Acute Tox. 4 - H312, Acute Tox. 4 -	
	H332	
67-68-5	dimethyl sulfoxide	0,00- 0,50
	EC number: 200-664-3	
	Skin Irrit. 2 - H315, Eye Irrit. 2 -	(continued on page 2)
		(continued on page 3)

CH -

**TEKNOS

according to 1907/2006/EC, Article 31

1170725

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: ALPOCRYL KF 5372 BASE TR

(continued of page 2)

H319

SECTION 04: First aid measures

- 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water.

· After swallowing:

Do not induce vomiting; call for medical help immediately.

Information for doctor:

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 05: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 06: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

• 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

СН



according to 1907/2006/EC, Article 31

1170725

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: ALPOCRYL KF 5372 BASE TR

(continued of page 3)

SECTION 07: Handling and storage

- · Handling:
- 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Take note of emission threshold.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

• Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

· Information about storage in one common storage facility:

Not required.

• Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s)

No further relevant information available.

SECTION 08: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

MAK

Short-term value	960	mg/m3
	200	ppm
Long-term value	480	mg/m3
	100	ppm

SSc;

1330-20-7 xylene

MAK

Short-term value	870	mg/m3
	200	ppm
Long-term value	435	mg/m3
	100	ppm

HB;

100-41-4 ethylbenzene

MAK

Short-term value	220	mg/m3
	50	ppm
Long-term value	220	mg/m3
	50	nnm

H OI B;

80-62-6 methyl methacrylate

MAK

 Short-term value
 420
 mg/m3

 100
 ppm

 Long-term value
 210
 mg/m3 (continued on page 5)

СН



according to 1907/2006/EC, Article 31

1170725

Reviewed on: 30/06/2021 Printing date: 01/07/2021

			(continued of page
		50	ppm
	S SSc;		
112-07-2 MAK	2-butoxyethyl acc	etate	
	Short-term value	132	mg/m3
		20	ppn
	Long-term value	66	mg/m3
		10	ppm
	H B SSc;		
67-68-5	dimethyl sulfoxio	le	
MAK			
	Short-term value	320	mg/m3
		100	ppm
	Long-term value	160	mg/m3
		50	ppn
- Ingradic	H; ents with biological limit values		
1330-20-		•	
BAT	/ Aylelle		
DAI	2 g/l		
	Untersuchungsmaterial: Uri	in	
	-	positionsende bzw. Schichtende	
	Biol. Parameter: Methylhipp		
100-41-4			
BAT			
	600 mg/g Kreatinin		
	Untersuchungsmaterial: Uri	in	
	Probennahmezeitpunkt: Exp	positionsende bzw. Schichtende	
	Biol. Parameter: Mandelsäu	re plus Phenylglyoxylsäure	
112-07-2	2-butoxyethyl acc	etate	
BAT			
	150 mg/g Kreatinin		
	Untersuchungsmaterial: Uri		
		positionsende bzw. Schichtende, bei	
		nehreren vorangegangenen Schichten	
	Biol. Parameter: 2-Butoxyes	ssigsäure (nach Hydrolyse)	

- 8.2 Exposure controls
- Personal protective equipment:

General protective and hygienic measures:
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.

The lists valid during the making were used as basis.

Immediately remove all soiled and contaminated clothing

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Suitable respiratory protective device recommended.

(continued on page 6)



according to 1907/2006/EC, Article 31

1170725

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: ALPOCRYL KF 5372 BASE TR

(continued of page 5)

- Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the
 preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the
 preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates
 of diffusion and the degradation Protective gloves Impervious gloves
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
 - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
 - The determined penetration times according to EN 374 part III are not performed under practical conditions.
- Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.
- · Eye protection: Safety glasses Tightly sealed goggles
- · Body protection: Protective work clothing

SECTION 09: Physical and chemical properties				
9.1 Information on basic physical and chemical properties				
Appearance				
Appearance:				
Form:	Liquid			
Colour:	According to product specifica			
Odour:	Characteristic Characteristic			
Odour threshold:	Not determined.			
Change in condition				
Initial boiling point and boiling range:	124 °C			
Flash point:	27 °C			
Flammability (solid, gas):	Not applicable.			
Ignition temperature:	371 °C			
Decomposition temperature:	Not determined.			
Auto-ignition temperature:	Not determined.			
Explosive properties:	Not determined.			
Explosion limits:				
Lower:	1 Vol %			
Upper:	7 Vol %			
Vapour pressure:	at 20 °C 6,7000 mbar at 50 °C 55,0000 mbar			
Density:	1,0300 g/cm3			
Solubility in / Miscibility with				
water:	Not determined.			
Viscosity:				
	Not determined.			
	at 20 °C 140 - 190 s DIN 4 mm			
2 Other information No further relevant information available.				

SECTION 10: Stability and reactivity

- 10.1 Reactivity
- No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
 - No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions

(continued on page 7)

according to 1907/2006/EC, Article 31



1170725

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: **ALPOCRYL KF 5372 BASE TR**

(continued of page 6)

No dangerous reactions known.

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:

No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity
- LD/LC50 values relevant for classification:

n-butyl acetate

Oral, LD50: 13100 mg/kg (rat) Dermal, LD50: >5000 mg/kg (Rabbit) Inhalative, LC50/4h: >21 mg/l (rat) Oral, LD50: 4300 mg/kg (rat) Dermal, LD50: 2000 mg/kg (Rabbit) Oral, LD50: 3500 mg/kg (rat) Dermal, LD50: 17800 mg/kg (Rabbit) Oral, LD50: 7872 mg/kg (rat) Oral, LD50: 5050 mg/kg (rat) Oral, LD50: 2460 mg/kg (rat) Dermal, LD50: 3400 mg/kg (Rabbit) Oral, LD50: 2400 mg/kg (rat) Dermal, LD50: 1580 mg/kg (Rabbit) Oral, LD50: 10000 mg/kg (rat) Oral, LD50: 526 mg/kg (rat) Oral, LD50: 14500 mg/kg (rat)

1330-20-7 xylene 100-41-4 ethylbenzene 80-62-6 methyl methacrylate

868-77-9 2-hydroxyethyl methacrylate

78-83-1 butanol

112-07-2 2-butoxyethyl acetate

silicon dioxide, chemically prepared 7631-86-9

7447-41-8 lithium chloride 67-68-5 dimethyl sulfoxide

Primary irritant effect:

Skin corrosion/irritation

No irritant effect.

- Serious eye damage/irritation
- No irritating effect.
- Respiratory or skin sensitisation

No sensitising effects known.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

No further relevant information available.

12.2 Persistence and degradability

No further relevant information available.

Behaviour in environmental systems:

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- PRT:

Not applicable.

vPvB:

(continued on page 8)



according to 1907/2006/EC, Article 31

1170725

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: ALPOCRYL KF 5372 BASE TR

(continued of page 7)

Not applicable.

· 12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · European and swiss waste code

80

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01

wastes from MFSU and removal of paint and varnish

08 01 11

waste paint and varnish containing organic solvents or other hazardous substances $% \left(1\right) =\left(1\right) +\left(1\right) +$

- · Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

SECTION 14: Transport information

• 14.1 UN-Number

 ADR
 UN1263

 IMDG
 UN1263

 IATA
 UN1263

· 14.2 UN proper shipping name

ADR 1263 PAINT
IMDG PAINT
IATA PAINT

• 14.3 Transport hazard class(es)

ADR

Class 3 Flammable liquids.

Label



IMDG

Class 3 Flammable liquids.

Label



IATA

Class 3 Flammable liquids.

(continued on page 9)



according to 1907/2006/EC, Article 31

1170725

Reviewed on: 30/06/2021 Printing date: 01/07/2021

> PRODUCT: **ALPOCRYL KF 5372 BASE TR**

> > (continued of page 8)

Label



14.4 Packing group

ADR Ш **IMDG** Ш IATA Ш

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user Warning: Flammable liquids.

Danger code (Kemler):

EMS Number: F-E,S-E

- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
- Transport/Additional information:

Not applicable.

Excepted quantities (EQ):

Limited quantities (LQ)

5L

Transport category

3

Tunnel restriction code

D/E

Remarks:

ADR/RID 2.2.3.1.5 (<= 450 l)

IMDG

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Remarks:

IMDG 2.3.2.5 (<= 30 l)

· UN "Model Regulation":

UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3, 40

- National regulations:
- · Classification according to VbF:

- Technical instructions (air):
- Class Share in %

29,96 III ΙI 19,39

- · Waterhazard class:
- Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

CH

Page: 10 / 10

MATERIAL SAFETY DATA SHEET



according to 1907/2006/EC, Article 31

1170725

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: ALPOCRYL KF 5372 BASE TR

(continued of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.
H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Department issuing MSDS:

Environment protection department.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids,

Austria)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative * Data compared to the previous version altered.