

4074107

Reviewed on: 11/07/2022

Printing date: 11/07/2022

SECTION 01: Identification of the substance/mixture and of the company undertaking

• 1.1 Product identifier

- *Trade name:*
ALPOCRYL LH 5356
- Article number / Safety Data Sheet:
535600
- *1.2 Relevant identified uses of the substance or mixture and uses advised against*
- Application of the substance / the preparation
Coating material

• 1.3 Details of the supplier of the safety data sheet

- *Manufacturer/Supplier:*
Teknos AG
Industriestrasse 7
LI-9487 Gamprin-Bendern
T +423 375 94 00
F +423 375 94 99
- *Further information obtainable from:*
Product safety department. e-mail address: li-sdb@teknos.com
- *1.4 Emergency telephone number:*
Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

SECTION 02: Hazards identification

- *2.1 Classification of the substance or mixture*
- Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 - H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 - H315 Causes skin irritation.
STOT SE 3 - H336 May cause drowsiness or dizziness.

- *2.2 Label elements*
- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms



GHS02 GHS07

- Signal word
Warning

- Hazard-determining components of labelling:
n-butyl acetate
- Hazard statements
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
EUH208 Contains methyl methacrylate. May produce an allergic reaction.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- * Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P302+P352 IF ON SKIN: Wash with plenty of water.

(continued on page 2)

according to 1907/2006/EC, Article 31

4074107

Reviewed on: 11/07/2022

Printing date: 11/07/2022

PRODUCT : ALPOCRYL LH 5356

(continued of page 1)

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

• **2.3 Other hazards**• *Results of PBT and vPvB assessment*

• PBT:

Not applicable.

• vPvB:

Not applicable.

SECTION 03: Composition/information on ingredients• **3.2 Chemical characterization: Mixtures**• *Description:*

Mixture of substances listed below with nonhazardous additions.

• *Dangerous components:*

CAS Number		%
123-86-4	n-butyl acetate EC number: 204-658-1 Record number 01-2119485493-29 ⚠ Flam. Liq. 3 - H226; ⚠ STOT SE 3 - H336; EUH066	25,00- 40,00
1330-20-7	xylene EC number: 215-535-7 Record number 01-2119488216-32 ⚠ Flam. Liq. 3 - H226; ⚠ Acute Tox. 4 - H312, Acute Tox. 4 - H332, Skin Irrit. 2 - H315	10,00- 25,00
100-41-4	ethylbenzene EC number: 202-849-4 Record number 01-2119489370-35 ⚠ Flam. Liq. 2 - H225; ⚠ STOT RE 2 - H373, Asp. Tox. 1 - H304; ⚠ Acute Tox. 4 - H332	1,00- 5,00
80-62-6	methyl methacrylate EC number: 201-297-1 Record number 01-2119452498-28 ⚠ Flam. Liq. 2 - H225; ⚠ Skin Irrit. 2 - H315, Skin Sens. 1 - H317, STOT SE 3 - H335	0,0015- 0,50
112-07-2	2-butoxyethyl acetate EC number: 203-933-3 Record number 01-2119475112-47 ⚠ Acute Tox. 4 - H312, Acute Tox. 4 - H332	1,00- 5,00
13463-67-7	titanium dioxide EC number: 236-675-5 Record number 01-2119489379-17 ⚠ Carc. 2 - H351	10,00- 25,00

• *Additional information:*

For the wording of the listed risk phrases refer to section 16.

NL

(continued on page 3)

4074107

Reviewed on: 11/07/2022

Printing date: 11/07/2022

PRODUCT : ALPOCRYL LH 5356

(continued of page 2)

SECTION 04: First aid measures

- 4.1 Description of first aid measures
- * **After inhalation:**
In case of unconsciousness place patient stably in side position for transportation.
- * **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- * **After eye contact:**
Rinse opened eye for several minutes under running water.
- **After swallowing:**
Do not induce vomiting; call for medical help immediately.
- **Information for doctor:**
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 05: Firefighting measures

- 5.1 Extinguishing media
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:**
Water with full jet
- 5.2 Special hazards arising from the substance or mixture
Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters
- **Protective equipment:**
Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 06: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- * **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
- * In case of seepage into the ground inform responsible authorities.
- * In case of gas release or seepage into the ground inform responsible authorities.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

NL

(continued on page 4)

4074107

Reviewed on: 11/07/2022

Printing date: 11/07/2022

PRODUCT : ALPOCRYL LH 5356

(continued of page 3)

SECTION 07: Handling and storage

- **Handling:**
- * 7.1 *Precautions for safe handling*
- * Open and handle receptacle with care.
Take note of emission threshold.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- *Information about fire - and explosion protection:*
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- * Prevent impact and friction.
- 7.2 *Conditions for safe storage, including any incompatibilities*
- **Storage:**
- *Requirements to be met by storerooms and receptacles:*
Store only in the original receptacle.
- *Information about storage in one common storage facility:*
Not required.
- *Further information about storage conditions:*
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)**
No further relevant information available.

SECTION 08: Exposure controls/personal protection

- 8.1 *Control parameters*
- *Ingredients with limit values that require monitoring at the workplace:*

1330-20-7 xylene

WGW

Short-term value	442	mg/m3
	100	ppm
Long-term value	210	mg/m3
	47	ppm

technisch mengsel

100-41-4 ethylbenzene

BGW

Short-term value	430	mg/m3
	100	ppm
Long-term value	215	mg/m3
	50	ppm

H

WGW

Short-term value	430	mg/m3
	98	ppm
Long-term value	215	mg/m3
	49	ppm

80-62-6 methyl methacrylate

BGW

Long-term value	40	mg/m3
	10	ppm

WGW

Short-term value	410	mg/m3
	100	ppm

(continued on page 5)

according to 1907/2006/EC, Article 31

4074107

Reviewed on: 11/07/2022

Printing date: 11/07/2022

PRODUCT : ALPOCRYL LH 5356

(continued of page 4)

Long-term value		205	mg/m3
		50	ppm
112-07-2	2-butoxyethyl acetate		
WG			
Short-term value		333	mg/m3
		50	ppm
Long-term value		135	mg/m3
		20	ppm

- *Additional information:*

The lists valid during the making were used as basis.

- *8.2 Exposure controls*

- **Personal protective equipment:**

- *General protective and hygienic measures:*

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

- *Respiratory protection: Suitable respiratory protective device recommended.*

• *Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Protective gloves Impervious gloves*

- *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- *Penetration time of glove material*

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- *Eye protection: Safety glasses*

- *Body protection: Protective work clothing*

SECTION 09: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance****Appearance:**

Form:	Liquid
Colour:	According to product specifica
Odour:	Characteristic Characteristic
Odour threshold:	Not determined.

Change in condition

Initial boiling point and boiling range: 124 °C

Flash point: 27 °C

Flammability (solid, gas): Not applicable.

Ignition temperature: 425 °C

Decomposition temperature: Not determined.

Auto-ignition temperature: Not determined.

Explosive properties: Not determined.

Explosion limits:

Lower: 1 Vol %

(continued on page 6)

according to 1907/2006/EC, Article 31

4074107

Reviewed on: 11/07/2022

Printing date: 11/07/2022

PRODUCT : ALPOCRYL LH 5356

(continued of page 5)

Upper:	7 Vol %
Vapour pressure:	at 20 °C 6,7000 mbar at 50 °C 55,0000 mbar
Density:	1,1500 g/cm3
Solubility in / Miscibility with water:	Not determined.
Viscosity:	250 - 350 mPa.s
-	Not determined.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
No dangerous reactions known.
- **10.4 Conditions to avoid**
No further relevant information available.
- **10.5 Incompatible materials:**
No further relevant information available.
- **10.6 Hazardous decomposition products:**
No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:**
 - 123-86-4 n-butyl acetate**
Oral, LD50: 13100 mg/kg (rat)
Dermal, LD50: >5000 mg/kg (Rabbit)
Inhalative, LC50/4h: >21 mg/l (rat)
 - 1330-20-7 xylene**
Oral, LD50: 4300 mg/kg (rat)
Dermal, LD50: 2000 mg/kg (Rabbit)
 - 100-41-4 ethylbenzene**
Oral, LD50: 3500 mg/kg (rat)
Dermal, LD50: 17800 mg/kg (Rabbit)
 - 80-62-6 methyl methacrylate**
Oral, LD50: 7872 mg/kg (rat)
 - 868-77-9 2-hydroxyethyl methacrylate**
Oral, LD50: 5050 mg/kg (rat)
 - 108-88-3 toluene**
Oral, LD50: 5000 mg/kg (rat)
Dermal, LD50: 12124 mg/kg (Rabbit)
Inhalative, LC50/4h: 5320 mg/l (mouse)
 - 112-07-2 2-butoxyethyl acetate**
Oral, LD50: 2400 mg/kg (rat)
Dermal, LD50: 1580 mg/kg (Rabbit)
 - 7631-86-9 silicon dioxide, chemically prepared**
Oral, LD50: 10000 mg/kg (rat)
 - 7447-41-8 lithium chloride**
Oral, LD50: 526 mg/kg (rat)
 - 67-68-5 dimethyl sulfoxide**

(continued on page 7)

4074107

Reviewed on: 11/07/2022

Printing date: 11/07/2022

PRODUCT : ALPOCRYL LH 5356

(continued of page 6)

- * Oral, LD50: 14500 mg/kg (rat)
- * **108-65-6 2-methoxy-1-methylethyl acetate**
- * Oral, LD50: 8532 mg/kg (rat)
- * Inhalative, LC50/4h: 35,7 mg/l (rat)
- * **64742-95-6 Solvent naphtha (petroleum), light arom.**
- * Oral, LD50: >6800 mg/kg (rat)
- * Dermal, LD50: >3400 mg/kg (Rabbit)
- * Inhalative, LC50/4h: >10,2 mg/l (rat)
- * **50-00-0 formaldehyde**
- * Oral, LD50: >200 mg/kg (rat)
- * **13463-67-7 titanium dioxide**
- * Oral, LD50: >20000 mg/kg (rat)
- * Dermal, LD50: >10000 mg/kg (Rabbit)
- * Inhalative, LC50/4h: >6,82 mg/l (rat)
- * **78-83-1 butanol**
- * Oral, LD50: 2460 mg/kg (rat)
- * Dermal, LD50: 3400 mg/kg (Rabbit)
- * **140-88-5 ethyl acrylate**
- * Oral, LD50: 800 mg/kg (rat)
- * Dermal, LD50: 1834 mg/kg (Rabbit)
- * Inhalative, LC50/4h: 2180 mg/l (rat)
- * **Primary irritant effect:**
- * Skin corrosion/irritation
- * Irritant to skin and mucous membranes.
- * Serious eye damage/irritation
- * No irritating effect.
- * **Respiratory or skin sensitisation**
- * No sensitising effects known.
- * **Additional toxicological information:**
- * The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
- * Irritant
- * **11.2 Information on other hazards**
- * **Endocrine disrupting properties**
- * 541-02-6 decamethylcyclotetrasiloxane : II
- * 556-67-2 octamethylcyclotetrasiloxane : II; III

SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity:
No further relevant information available.
- **12.2 Persistence and degradability**
No further relevant information available.
- **Behaviour in environmental systems:**
- **12.3 Bioaccumulative potential**
No further relevant information available.
- **12.4 Mobility in soil**
No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:**
Not applicable.
- **vPvB:**
Not applicable.
- **12.6 Other adverse effects**
No further relevant information available.

NL

(continued on page 8)

4074107

Reviewed on: 11/07/2022

Printing date: 11/07/2022

PRODUCT : ALPOCRYL LH 5356

(continued of page 7)

SECTION 13: Disposal considerations• **13.1 Waste treatment methods**• **European and swiss waste code**

08

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01

wastes from MFSU and removal of paint and varnish

08 01 11

waste paint and varnish containing organic solvents or other hazardous substances

• **Uncleaned packaging:**• **Recommendation:**

Disposal must be made according to official regulations.

SECTION 14: Transport information• **14.1 UN-Number**

ADR UN1263

IMDG UN1263

IATA UN1263

• **14.2 UN proper shipping name**

ADR 1263 PAINT

IMDG PAINT

IATA PAINT

• **14.3 Transport hazard class(es)**

ADR

Class 3 Flammable liquids.

Label

3



IMDG

Class 3 Flammable liquids.

Label

3



IATA

Class 3 Flammable liquids.

Label

3

• **14.4 Packing group**

ADR III

IMDG III

(continued on page 9)

4074107

Reviewed on: 11/07/2022

Printing date: 11/07/2022

PRODUCT : ALPOCRYL LH 5356

(continued of page 8)

IATA III• **14.5 Environmental hazards:**

Not applicable.

• **14.6 Special precautions for user**

Warning: Flammable liquids.

Danger code (Kemler): 30**EMS Number:** F-E,S-E• **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

• **Transport/Additional information:**

Not applicable.

Excepted quantities (EQ): E1**Limited quantities (LQ)** 5L**Transport category** 3**Tunnel restriction code** D/E**IMDG****Limited quantities (LQ)** 5L**Excepted quantities (EQ)** E1• **UN "Model Regulation":**

UN 1263 PAINT, 3, III

* **SECTION 15: Regulatory information**• **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

* None of the ingredients is listed.

• REGULATION (EU) 2019/1148

• Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

* None of the ingredients is listed.

• Annex II - REPORTABLE EXPLOSIVES PRECURSORS

* None of the ingredients is listed.

• REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3, 40

• **National regulations:**• *Technical instructions (air):*

• Class Share in %

* III 33,18

* II 16,35

I

• **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Relevant phrases**

* EUH066 Repeated exposure may cause skin dryness or cracking.

* H225 Highly flammable liquid and vapour.

* H226 Flammable liquid and vapour.

* H304 May be fatal if swallowed and enters airways.

* H312 Harmful in contact with skin.

* H315 Causes skin irritation.

* H317 May cause an allergic skin reaction.

* H332 Harmful if inhaled.

(continued on page 10)

according to 1907/2006/EC, Article 31

4074107

Reviewed on: 11/07/2022

Printing date: 11/07/2022

PRODUCT : ALPOCRYL LH 5356
(continued of page 9)

- | | | |
|---|------|--|
| * | H335 | May cause respiratory irritation. |
| * | H336 | May cause drowsiness or dizziness. |
| * | H351 | Suspected of causing cancer. |
| * | H373 | May cause damage to organs through prolonged or repeated exposure. |

- **Department issuing MSDS:**

Environment protection department.

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

- * Data compared to the previous version altered.