Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Malta

SAFETY DATA SHEET



AQUACOAT 2650-06 - RAL 9010

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: AQUACOAT 2650-06 - RAL 9010

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

 Telephone number
 : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	lo signal word.	
Hazard statements	lo known significant effects or critical hazards.	
Precautionary statements		
Prevention	lot applicable.	
Response	lot applicable.	
Storage	lot applicable.	
Disposal	lot applicable.	
Supplemental label elements	Contains adipohydrazide, 2-mercaptoethanol, 1,2-benzisothiazol-3(2H)-one e eaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] e-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an aller eaction. Bafety data sheet available on request. Varning! Hazardous respirable droplets may be formed when sprayed. Do r preathe spray or mist. Contains biocidal products for in-can preservation: Bl Bronopol and C(M)IT/MIT (3:1) and DTBMA and MBIT.	and rgic not

: 27/11/2023 Date of previous issue

SECTION 2: Hazards identification

Annex XVII - Restrictions	1	
on the manufacture,		
placing on the market and		
use of certain dangerous		
substances, mixtures and		
articles		

2.3 Other hazards

Product meets the criteria : for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do :

Product meets the criteria
for PBT or vPvB according: This mixture does not contain any substances that are assessed to be a PBT or a
vPvB.

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures Product/ingredient name	: Mixture	%	Classification	Specific Conc. Limits, M-factors	Туре
				and ATEs	
Manium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
3-Butoxypropan-2-ol	REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319	-	[1]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
2-mercaptoethanol	EC: 200-464-6 CAS: 60-24-2	<0.1	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 2, H361 STOT RE 2, H373 Aquatic Acute 1, H400	ATE [Oral] = 244 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 3 mg/l M [Acute] = 1	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: C \geq 0.6% Eye Dam. 1, H318: C \geq 0.6%	[1]
Date of issue/Date of revision	: 27/11/2023 Date	e of previous is	sue : 30/09/2022	Version :1.01	1 2/14
AQUACOAT 2650-06 - RAL S				Label No :7439	

SECTION 3: Composition/information on ingredients		
	See Section 16 for the full text of the H statements declared above.	Eye Irrit. 2, H319: 0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the : In a fire or if heated, a pressure increase will occur and the container may burst. substance or mixture

Date of issue/Date of revision	: 27/11/2023	Date of previous issue	: 30/09/2022	Version	: 1.01	3/14
AQUACOAT 2650-06 - RAL 9010				Label No	74394	1

SECTION 5: Firefighting measures		
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Date of issue/Date of revision AQUACOAT 2650-06 - RAL 9010

: 27/11/2023 Date of previous issue

SECTION 7: Handling and storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations : Not available. **Industrial sector specific** : Not available. solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
No exposure limit value known.	

Biological exposure indices

Product/ingredient name		Exposure indices		
No exposure indices known.				
Recommended monitoring procedures	European Stand assessment of e values and mea atmospheres - (of exposure to c (Workplace atm for the measure	Id be made to monitoring standards, such as the following: dard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit isurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be		

DNELs/DMELs

Туре	Exposure	Value	Population	Effects
DNEL	Long term Inhalation	147 mg/m ³	Workers	Systemic
DNEL	Long term Oral	12.5 mg/ kg bw/day	General population	Systemic
DNEL	Long term Dermal	22 mg/kg bw/day	General	Systemic
DNEL	Long term Inhalation	43 mg/m ³	General	Systemic
DNEL	Long term Dermal	52 mg/kg bw/day	Workers	Systemic
DNEL	Short term Dermal	50 %	General population	Local
DNEL	Long term Dermal	50 %	General	Local
DNEL	Short term Dermal	50 %	Workers	Local
DNEL	Long term Dermal	50 %	Workers	Local
DNEL	Long term Inhalation	17.5 mg/m ³	Workers	Systemic
DNEL	Short term Oral	0.025 mg/ kg bw/day	General population	Systemic
DNEL	Long term Oral	0.025 mg/	General	Systemic
DNEL	Short term Dermal	0.05 mg/ kg bw/day	Workers	Systemic
11/2023	Date of previous issue		022 I	l /ersion : 1.01 5/1
	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	DNELLong term InhalationDNELLong term OralDNELLong term DermalDNELLong term InhalationDNELLong term DermalDNELShort term DermalDNELShort term DermalDNELLong term DermalDNELShort term DermalDNELShort term DermalDNELShort term DermalDNELShort term DermalDNELShort term DermalDNELShort term OralDNELShort term OralDNELLong term OralDNELShort term Dermal	DNELLong term Inhalation147 mg/m³DNELLong term Oral12.5 mg/ kg bw/dayDNELLong term Dermal22 mg/kg bw/dayDNELLong term Dermal22 mg/kg bw/dayDNELLong term Inhalation43 mg/m³DNELLong term Dermal52 mg/kg bw/dayDNELShort term Dermal50 %DNELShort term Dermal50 %DNELShort term Dermal50 %DNELLong term Dermal50 %DNELLong term Dermal50 %DNELShort term Oral0.025 mg/ kg bw/dayDNELLong term Oral0.025 mg/ kg bw/dayDNELShort term Dermal0.025 mg/ kg bw/dayDNELShort term Dermal0.05 mg/ kg bw/day	DNELLong term Inhalation147 mg/m³WorkersDNELLong term Oral12.5 mg/ kg bw/dayGeneral populationDNELLong term Dermal22 mg/kg bw/dayGeneral populationDNELLong term Inhalation43 mg/m³General populationDNELLong term Dermal52 mg/kg bw/dayWorkersDNELLong term Dermal52 mg/kg bw/dayWorkersDNELShort term Dermal50 %General populationDNELShort term Dermal50 %General populationDNELShort term Dermal50 %WorkersDNELLong term Dermal50 %WorkersDNELShort term Dermal50 %WorkersDNELLong term Dermal50 %WorkersDNELShort term Oral0.025 mg/ kg bw/dayGeneral populationDNELShort term Oral0.025 mg/ kg bw/dayGeneral populationDNELShort term Dermal0.05 mg/ kg bw/dayGeneral population

AQUACOAT 2650-06 - RAL 9010

Label No :74394

	DNEL	Long term Dermal	0.05 mg/	Workers	Systemic
			kg bw/day		-,
	DNEL	Short term	0.17 mg/m ³	Workers	Systemic
		Inhalation	J		-,
	DNEL	Long term	0.17 mg/m ³	Workers	Systemic
		Inhalation	- J.		,
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/	General	Systemic
			kg bw/day	population	-
	DNEL	Long term Dermal	0.966 mg/	Workers	Systemic
			kg bw/day		-
	DNEL	Long term	1.2 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Long term	6.81 mg/m ³	Workers	Systemic
		Inhalation			
reaction mass of: 5-chloro-2-methyl-	DNEL	Long term	0.02 mg/m ³	General	Local
4-isothiazolin-3-one [EC no.		Inhalation		population	
247-500-7] and 2-methyl-2H-					
isothiazol-3-one [EC no. 220-239-6]					
(3:1)			0.00 m m/m 3		
	DNEL	Long term Inhalation	0.02 mg/m ³	workers	Local
	DNEL	Short term	0.04 mg/m ³	General	Local
	DINLL	Inhalation	0.04 mg/m	population	LUCAI
	DNEL	Short term	0.04 mg/m ³		Local
	DINEL	Inhalation	0.04 mg/m	Workers	Local
	DNEL	Long term Oral	0.09 mg/	General	Systemic
		Long tonn ordi	kg bw/day	population	e yotonno
	DNEL	Short term Oral	0.11 mg/	General	Systemic
			kg bw/day	population	- ,

PNECs

No PNECs available

8.2 Exposure controls						
Appropriate engineering controls	-	Good general ventilation should be sufficient to control worker exposure to airborn contaminants.				
Individual protection meas	<u>ures</u>					
Hygiene measures	:	before eating, smoking and usin Appropriate techniques should b Wash contaminated clothing before	Vash hands, forearms and face thoroughly after handling chemical products, efore eating, smoking and using the lavatory and at the end of the working period. ppropriate techniques should be used to remove potentially contaminated clothing. Vash contaminated clothing before reusing. Ensure that eyewash stations and afety showers are close to the workstation location.			
Eye/face protection	:	assessment indicates this is nec gases or dusts. If contact is pos	afety eyewear complying with an approved standard should be used when a risk ssessment indicates this is necessary to avoid exposure to liquid splashes, mists, ases or dusts. If contact is possible, the following protection should be worn, nless the assessment indicates a higher degree of protection: safety glasses with ide-shields.			
Skin protection						
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard shou be worn at all times when handling chemical products if a risk assessment indicate this is necessary.				
		Recommendations : Wear suita	able gloves tested to EN374.			
		> 8 hours (breakthrough time):	Nitrile gloves. thickness > 0.3 mm			
		Not recommended	polyvinyl alcohol (PVA) gloves			
Body protection	:		or the body should be selected based on the task wolved and should be approved by a specialist			
Other skin protection	:		dditional skin protection measures should be g performed and the risks involved and should be handling this product.			

SECTION 8: Exposure controls/personal protection

•	• •
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Colour	: White.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name	°C	°F	Method
water	100	212	
3-Butoxypropan-2-ol	171	339.8	OECD 103

Flammability : N	lot available.
------------------	----------------

Lower and upper explosion	: Lower: Not applicable.
limit	Upper: Not applicable.

2

ż

Flash point

: Closed cup: >100°C (>212°F)

Auto-ignition temperature

Ingredient name	°C	°F	Method
Propylenglycoldimethylether	165	329	
3-Butoxypropan-2-ol	260	500	EU A.15

Decomposition temperature	1	Not available.
рН	:	8 to 8.8
Viscosity	:	Not available.
Solubility(ies)	:	
Not available.		
Solubility in water	:	Not available.
Partition coefficient: n-octanol/		Not applicable

Partition coefficient: n-octanol/	\$ Not applicable.
water	

Vapour pressure

	Vapour Pressure at 20°C		Vapour		ur pressure at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
3-Butoxypropan-2-ol	1.05	0.14	OECD 104			
Relative density	: Not	available.	•	·	·	·
Density	: 1.2	g/cm³				
/apour density	: Not	available.				
Explosive properties	: Not	available.				
te of issue/Date of revision	: 27/11/2	2023 Date	of previous issue	: 30/09/2022		Version : 1.01

AQUACOAT 2650-06 - RAL 9010

SECTION 9: Physical and chemical properties

Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stabilit	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
<mark>3</mark> -Butoxypropan-2-ol	LD50 Dermal	Rabbit	3100 mg/kg	-
2-mercaptoethanol	LD50 Oral	Rat	244 mg/kg	-
1,2-benzisothiazol-3(2H)-	LD50 Oral	Rat	1020 mg/kg	-
one				
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin-	LD50 Oral	Rat	53 mg/kg	-
3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-				
3-one [EC no. 220-239-6] (3: 1)				

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Route	ATE value
Not available.	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Manium dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
3-Butoxypropan-2-ol	Skin - Moderate irritant	Rabbit	-	-	-
2-mercaptoethanol	Eyes - Severe irritant	Rabbit	-	2 mg	-
1,2-benzisothiazol-3(2H)-one	Skin - Mild irritant	Human	-	48 hours 5 %	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Severe irritant	Human	-	0.01 %	-
Conclusion/Summary	: Based on available data, the	classification cr	iteria are	not met.	
Sensitisation					
Conclusion/Summary	: Based on available data, the classification criteria are not met.				

SECTION 11: Toxicological information

Mutagenicity

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Conclusion/Summary	: Based on available data, the classification criteria are not met.
Reproductive toxicity	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Teratogenicity	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Specific target organ toxicit	<u>r (single exposure)</u>

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-mercaptoethanol	Category 2	-	-

Aspiration hazard

Not available.

Information on likely routes : Not available. of exposure Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

: 27/11/2023

Date of issue/Date of revision	
AQUACOAT 2650-06 - RAL 9	010

SECTION 11: Toxicological information

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
inanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - <i>Daphnia pulex</i> - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.36 mg/l Marine water Acute EC50 3.7 mg/l	Algae - Skeletonema Costatum Daphnia - Daphnia Magna	72 hours 48 hours
	Acute LC50 1.9 mg/l Fresh water Acute NOEC 0.15 mg/l Marine water	Fish - Onorhynchus Mykiss Algae - Skeletonema Costatum	96 hours 72 hours

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
7,2-benzisothiazol-3(2H)-one	EU	24 % - 28 days		-	-
Conclusion/Summary : This product has not been tested for biodegradation.					
Product/ingredient name	Aquatic half-life		Photolysis	6	Biodegradability
2-benzisothiazol-3(2H)-one	-		-		Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
 Butoxypropan-2-ol 2-mercaptoethanol 1,2-benzisothiazol-3(2H)-one 	1.2	-	Low
	-0.056	-	Low
	-	3.2	Low

12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

: 27/11/2023 Date of previous issue

SECTION 13: Disposal considerations

13.1 Waste treatment metho	ds
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	 Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
European waste catalogue (EWC)	: 080112
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
SECTION 14: Transp	oort information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not relevant/applicable due to nature of the product. bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Date of issue/Date of revision AQUACOAT 2650-06 - RAL 9010

: 27/11/2023 Date of previous issue

	on the manufacture, placing on the market and use of certain dangerous
substances, mixtures and	<u>articles</u>
Labelling	:
Other EU regulations	
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Explosive precursors	: Not applicable.
Ozone depleting substant Not listed.	<u>ces (1005/2009/EU)</u>
Prior Informed Consent (Not listed.	<u>PIC) (649/2012/EU)</u>
Persistent Organic Pollut Not listed.	<u>ants</u>
Seveso Directive This product is not controlle	ed under the Seveso Directive.
International regulations Chemical Weapon Conven Not listed.	tion List Schedules I, II & III Chemicals
Montreal Protocol Not listed.	
Stockholm Convention on Not listed.	Persistent Organic Pollutants
Rotterdam Convention on Not listed.	Prior Informed Consent (PIC)
UNECE Aarhus Protocol o Not listed.	n POPs and Heavy Metals

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations	and :	ATE = Acute Toxicity Estimate
acronyms		CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
		1272/2008]
		DMEL = Derived Minimal Effect Level
		DNEL = Derived No Effect Level
		EUH statement = CLP-specific Hazard statement
		N/A = Not available
		PBT = Persistent, Bioaccumulative and Toxic
		PNEC = Predicted No Effect Concentration
		RRN = REACH Registration Number
		SGG = Segregation Group
		vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Date of issue/Date of revision	: 27/11/2023	Date of previous issue	: 30/09/2022	Version : 1.01 12/14
AQUACOAT 2650-06 - RAL 9010				Label No :7/4394

SECTION 16: Other information

Not classified.

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
Date of issue/ Date of	: 27/11/2023
revision	
Date of previous issue	e : 30/09/2022
Version	: 1.01

QUACOAT 2650-06 RAL 9010

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision AQUACOAT 2650-06 - RAL 9010

: 27/11/2023 Date of previous issue