Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Malta

SAFETY DATA SHEET



AQUACOAT 2650-06 - RAL 9010

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : AQUACOAT 2650-06 - RAL 9010

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

 Telephone number
 : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	1	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Contains adipohydrazide, adipohydrazide, 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and Bronopol and C(M)IT/MIT (3:1) and DTBMA and MBIT.

: 10/07/2025 Date of previous issue

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

: Mixture	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре	
REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]	
REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319	-	[1]	
EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1B, H317 Aquatic Chronic 2, H411	-	[1]	
REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	≤0.3	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]	
EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C $\geq 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]	
EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$	[1]	
	Identifiers REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8 EC: 213-999-5 CAS: 1071-93-8 REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8 EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6 EC: 911-418-6 CAS: 55965-84-9	Identifiers%REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 $\geq 10 - \leq 25$ REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8 ≤ 3 EC: 213-999-5 CAS: 1071-93-8 <1 REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8 ≤ 0.3 REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8 ≤ 0.3 EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6 <0.036 EC: 911-418-6 CAS: 55965-84-9 <0.0015	Identifiers%ClassificationREACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 $\geq 10 - \leq 25$ Carc. 2, H351 (inhalation)REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8 ≤ 3 Skin Irrit. 2, H315 Eye Irrit. 2, H319EC: 213-999-5 CAS: 1071-93-8 ≤ 1 Skin Sens. 1B, H317 Aquatic Chronic 2, H411REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8 ≤ 0.3 Skin Sens. 1, H317 Aquatic Chronic 2, H411REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8 ≤ 0.3 Skin Sens. 1, H317 Aquatic Chronic 2, H411REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8 ≤ 0.036 Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H317 Aquatic Chronic 1, H410EC: 2911-418-6 CAS: 55965-84-9 Index: 613-167-00-5 < 0.0015 Acute Tox. 3, H301 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	Identifiers % Classification Specific Conc. Limits, M-factors and ATEs REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 ≥10 - ≤25 Carc. 2, H351 (inhalation) - REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8 ≤3 Skin Irrit. 2, H315 Eye Irrit. 2, H319 - EC: 213-999-5 CAS: 1071-93-8 <1	

SECTION 3: Composition/information on ingredients			
		See Section 16 for the full text of the H statements declared above.	Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the : In a fire or if heated, a pressure increase will occur and the container may burst. substance or mixture

SECTION 5: Firefighting measures		
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

SECTION 7: Handling and storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

: Not available.
: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational ex	posure	<u>limits</u>
-----------------	--------	---------------

Biological exposure indices Product/ingredient name Exposure indices No exposure indices known. Exposure indices known. Recommended monitoring orocedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedure for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.	Product/ingredient name		Exposure limit values
Product/ingredient name Exposure indices No exposure indices known. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy). European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents). European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedure for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required. DNELs/DMELs Result Product/ingredient name Result Iffanium dioxide DNEL - General population - Long term - Inhalation 170 µg/m ³ Effects: Local 3-Butoxypropan-2-ol DNEL - General population - Long term - Oral 12.5 mg/kg bw/day Effects: Systemic 3-Butoxypropan-2-ol DNEL - General population - Long term - Oral 12.5 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Dermal 22 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Inhalation 170 µg/m ³ Effects: Systemic DNEL - General population - Long term - Inhalation 13 mg/m ³ Effects: Systemic DNEL - General population - Long term - Inhalation 43 mg/m ³ Effects: Systemic	No exposure limit value known.		
No exposure indices known. Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 4042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedure for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required. DNELs/DMELs Result Product/ingredient name Iffanium dioxide Result Jone L - General population - Long term - Inhalation 28 µg/m ³ Effects: Local DNEL - Workers - Long term - Inhalation 170 µg/m ³ Effects: Systemic 3-Butoxypropan-2-ol DNEL - General population - Long term - Oral 12.5 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Dermal 22 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Inhalation 43 mg/m ³ Effects: Systemic DNEL - General population - Long term - Inhalation 43 mg/m ³ Effects: Systemic DNEL - Workers - Long term - Inhalation 43 mg/m ³ Effects: Systemic	Biological exposure indices		
Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedure for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required. DNELs/DMELs Product/ingredient name If anium dioxide Result DNEL - Workers - Long term - Inhalation 28 µg/m ³ Effects: Local DNEL - Workers - Long term - Inhalation 170 µg/m ³ Effects: Systemic 3-Butoxypropan-2-ol DNEL - General population - Long term - Oral 12.5 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Dermal 22 mg/kg bw/day 22 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Inhalation 170 µg/m ³ 125 mg/kg bw/day Effects: Systemic	Product/ingredien	t name	Exposure indices
brocedures European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy). European Standard EN 1402 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents). European Standard EN 1402 (Workplace atmospheres - General requirements for the performance of procedure for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required. DNELs/DMELs Product/ingredient name Manipud Result DNEL - General population - Long term - Inhalation 170 µg/m³ Effects: Local 3-Butoxypropan-2-ol DNEL - General population - Long term - Oral 12.5 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Dermal 22 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Dermal 23 mg/m³ Effects: Systemic DNEL - General population - Long term - Inhalation 170 µg/m³ Effects: Systemic DNEL - General population - Long term - Dermal 22 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Inhalation 43 mg/m³ Effects: Systemic DNEL - Workers - Long term - Inhalation 43 mg/m³	No exposure indices known.		
Product/ingredient name Result Iffanium dioxide DNEL - General population - Long term - Inhalation 28 µg/m³ Effects: Local DNEL - Workers - Long term - Inhalation 170 µg/m³ Effects: Local 3-Butoxypropan-2-ol DNEL - General population - Long term - Oral 12.5 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Dermal 22 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Dermal 22 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Inhalation 43 mg/m³ Effects: Systemic DNEL - General population - Long term - Dermal 22 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Inhalation 43 mg/m³ Effects: Systemic DNEL - General population - Long term - Dermal 23 mg/kg bw/day Effects: Systemic	Recommended monitoring procedures	European Stand assessment of e values and mea atmospheres - C of exposure to c (Workplace atm for the measure documents for n	lard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit surement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 ospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance
Imanium dioxide DNEL - General population - Long term - Inhalation 28 µg/m³ Effects: Local DNEL - Workers - Long term - Inhalation 170 µg/m³ Effects: Local DNEL - General population - Long term - Oral 3-Butoxypropan-2-ol DNEL - General population - Long term - Oral 12.5 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Dermal 22 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Dermal DNEL - General population - Long term - Inhalation 43 mg/m³ Effects: Systemic DNEL - General population - Long term - Inhalation DNEL - General population - Long term - Inhalation 52 mg/kg bw/day Effects: Systemic DNEL - Workers - Long term - Inhalation 43 mg/m³ Effects: Systemic DNEL - Workers - Long term - Inhalation 43 mg/m³ Effects: Systemic DNEL - Workers - Long term - Dermal 52 mg/kg bw/day Stemp	DNELs/DMELs		
170 μg/m³ Effects: Local 3-Butoxypropan-2-ol DNEL - General population - Long term - Oral 12.5 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Dermal 22 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Dermal 22 mg/kg bw/day Effects: Systemic DNEL - General population - Long term - Inhalation 43 mg/m³ Effects: Systemic DNEL - Workers - Long term - Dermal 52 mg/kg bw/day	-		DNEL - General population - Long term - Inhalation 28 µg/m ³
12.5 mg/kg bw/day <u>Effects</u> : Systemic DNEL - General population - Long term - Dermal 22 mg/kg bw/day <u>Effects</u> : Systemic DNEL - General population - Long term - Inhalation 43 mg/m ³ <u>Effects</u> : Systemic DNEL - Workers - Long term - Dermal 52 mg/kg bw/day			170 μg/m³
22 mg/kg bw/day <u>Effects</u> : Systemic DNEL - General population - Long term - Inhalation 43 mg/m ³ <u>Effects</u> : Systemic DNEL - Workers - Long term - Dermal 52 mg/kg bw/day	3-Butoxypropan-2-ol		12.5 mg/kg bw/day
43 mg/m ³ <u>Effects</u> : Systemic DNEL - Workers - Long term - Dermal 52 mg/kg bw/day			22 mg/kg bw/day
52 mg/kg bw/day			43 mg/m ³
			52 mg/kg bw/day

: 10/07/2025 Date of previous issue

SECTION 8: Exposure controls/personal protection

DNEL - Workers - Long term - Inhalation 147 mg/m³ Effects: Systemic

adipohydrazide

adipohydrazide

1,2-benzisothiazol-3(2H)-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) **DNEL - Workers - Long term - Inhalation** 17.5 mg/m³ <u>Effects</u>: Systemic

DNEL - Workers - Long term - Inhalation 17.5 mg/m³ <u>Effects</u>: Systemic

DNEL - General population - Long term - Dermal 0.345 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Long term - Dermal 0.966 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation 1.2 mg/m³ <u>Effects</u>: Systemic

DNEL - Workers - Long term - Inhalation 6.81 mg/m³ <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation 0.02 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation 0.02 mg/m³ Effects: Local

DNEL - General population - Short term - Inhalation 0.04 mg/m³ <u>Effects</u>: Local

DNEL - Workers - Short term - Inhalation 0.04 mg/m³ Effects: Local

DNEL - General population - Long term - Oral 0.09 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Oral 0.11 mg/kg bw/day <u>Effects</u>: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Date of issue/Date of revision AQUACOAT 2650-06 - RAL 9010 : 10/07/2025 Date of previous issue

SECTION 8: Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: White.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name		°C	°F	Method
water		100	212	
3-Butoxypropan-2-ol		171	339.8	OECD 103
Flammability	: Not ava	ilable.		
Lower and upper explosion limit		Not applicable. Not applicable.		
Flash point	: Closed	cup: >100°C (>21	2°F)	
Auto-ignition temperature	:			

: 10/07/2025 Date of previous issue

Ingredient name	°C	°F	Method	
propylenglycoldimethylether	165	329		
3-Butoxypropan-2-ol	260	500	EU A.15	
ecomposition temperature H /iscosity folubility(ies) Not available.	: Not available. : ₿ to 8.8 [Conc. (% v : Not available. :	v/w): 100%]		
Solubility in water	: Not available.			
Partition coefficient: n-octanol/ vater	: Not applicable.			

Vapour pressure

	Vapour Pressure at 20°C		V	apour pres	sure at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
3-Butoxypropan-2-ol	1.05	0.14	OECD 104			
Relative density	: Not	available.				
Density	: 1.2	g/cm³				
/apour density	: Not	available.				
Particle characteristics						
Median particle size	: Not	applicable.				
2 Other information						
9.2.1 Information with reg	ard to physic	al hazard cl	asses			
Explosive properties	: Not	available.				
Ovidiaina nanonantian	• Not	availabla				

Oxidising properties : Not available.

2

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients	
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: No specific data.	
10.5 Incompatible materials	: No specific data.	
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

♂-Butoxypropan-2-ol

Result

Rabbit - Dermal - LD50 3100 mg/kg

1,2-benzisothiazol-3(2H)-one

Rat - Oral - LD50 1020 mg/kg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Rat - Oral - LD50 53 mg/kg <u>Toxic effects</u>: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration -Respiratory depression

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
₿-Butoxypropan-2-ol	N/A	3100	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	53	50	N/A	0.5	N/A

Skin corrosion/irritation

Product/ingredient name

titanium dioxide

3-Butoxypropan-2-ol

1,2-benzisothiazol-3(2H)-one

Result

Human - Skin - Mild irritant Duration of treatment/exposure: 72 hours Amount/concentration applied: 300 ug I

Rabbit - Skin - Moderate irritant

Human - Skin - Severe irritant

Amount/concentration applied: 0.01 %

Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Conclusion/Summary [Product] : Not available.

Ingredient name

Conclusion/Summary

3-Butoxypropan-2-ol

Slightly irritating to the skin.

Serious eye damage/eye irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation Not available.

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

<u>Specific target organ toxicity (single exposure)</u> Not available.

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard		
Not available.		
Information on likely routes of	of exposure	
Not available.		
Potential acute health effects	<u>)</u>	
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Symptoms related to the phy	sical, chemical and toxicological characteristics	
Eye contact	: No specific data.	
Inhalation	: No specific data.	
Skin contact	: No specific data.	
Ingestion	: No specific data.	
Delayed and immediate effec	ts as well as chronic effects from short and long-term ex	<u>posure</u>
Short term exposure		
Potential immediate effects	: Not available.	
Date of issue/Date of revision	: 10/07/2025 Date of previous issue : 27/11/2023	Version : 2 10
AQUACOAT 2650-06 - RAL 901	0	Label No : 122143

10/17

SECTION 11: Toxicological information

Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Conclusion/Summary [Pro	duct] : Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The pr

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity	
Product/ingredient name	Result
Manium dioxide	Acute - LC50 - Marine water Fish - Mummichog - <i>Fundulus heteroclitus</i> >1000000 μg/l [96 hours] <u>Effect</u> : Mortality
	Acute - LC50 - Fresh water Crustaceans - Water flea - <i>Ceriodaphnia dubia</i> - Neonate <u>Age</u> : <24 hours 3 mg/l [48 hours] <u>Effect</u> : Mortality
1,2-benzisothiazol-3(2H)-one	Acute - LC50 - Fresh water OECD [Fish, Acute Toxicity Test] Fish - Trout - <i>Onorhynchus Mykiss</i> 1.9 mg/l [96 hours]
	Acute - EC50 OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - <i>Daphnia Magna</i> 3.7 mg/l [48 hours]
	Acute - EC50 - Marine water OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.36 mg/l [72 hours]
	Acute - NOEC - Marine water OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.15 mg/l [72 hours]
Conclusion/Summary [Product]	: Not available.

Date of issue/Date of revision AQUACOAT 2650-06 - RAL 9010 : 10/07/2025 Date of previous issue

SECTION 12: Ecological information

12.2 Persistence and degradability

Product/ingredient name

1,2-benzisothiazol-3(2H)-one

Result EU 24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-benzisothiazol-3(2H)-one	-	-	Inherent
12.3 Bioaccumulative potentia	al	•	
Product/ingredient name	LogPow	BCF	Potential
Butoxypropan-2-ol 1,2-benzisothiazol-3(2H)-one	1.2	- 3.2	Low Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
₿-Butoxypropan-2-ol	1.5	28.6002
adipohydrazide	1.7	55.2165
adipohydrazide	1.7	55.2165
1,2-benzisothiazol-3(2H)-one	1.9	73.142

Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	Μ	т	vPvM	vP	vM
titanium dioxide	No	No	No	No	No	No	No
3-Butoxypropan-2-ol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Mobility

: Not available.

Conclusion/Summary

: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
3-Butoxypropan-2-ol	No	N/A	N/A	No	N/A	N/A	N/A
adipohydrazide	No	N/A	N/A	No	N/A	N/A	N/A
adipohydrazide	No	N/A	N/A	No	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	No	N/A	No	No	No	N/A	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	N/A	N/A	No	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

SECTION 12: Ecological information

Product/ingredient name	PBT	Ρ	В	т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
3-Butoxypropan-2-ol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

```
Conclusion/Summary [Product]
```

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	 Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
European waste catalogue (EWC)	: 080112
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
Date of issue/Date of reve AQUACOAT 2650-06		Date of previous issue	: 27/11/2023	Version : 2 13/17 Label No : 12/22143

SECTION 14: Transport information					
14.3 Transport hazard class(es)	-	-	-	-	
14.4 Packing group	-			-	
14.5 Environmental hazards	No.	No.	No.	No.	

: Not relevant/applicable due to nature of the product.

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are user

the event of an accident or spillage.

upright and secure. Ensure that persons transporting the product know what to do in

14.7 Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous

substances, mixtures and article	<u>es</u>
Labelling :	
Other EU regulations	
Industrial emissions : I (integrated pollution prevention and control) - Air	Not listed
Industrial emissions : I (integrated pollution prevention and control) - Water	Not listed
Explosive precursors : I	Not applicable.
Ozone depleting substances (I	<u>EU 2024/590)</u>
Not listed.	
Prior Informed Consent (PIC) (649/2012/EU)
Not listed.	
Persistent Organic Pollutants Not listed.	
Seveso Directive	
This product is not controlled und	ler the Seveso Directive.
International regulations	
Chemical Weapon Convention L	<u>ist Schedules I, II & III Chemicals</u>

Not listed.

Date of issue/Date of revision AQUACOAT 2650-06 - RAL 9010 : 10/07/2025 Date of previous issue

SECTION 15: Regulatory information

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety	: Not applicable.
assessment	

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number
	RRN = REACH Registration Number SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Not classified.

.....

Full text of abbreviated H statements

<mark>⊮</mark> 301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A

Date of issue/Date of revision	: 10/07/2025	Date of previous issue	: 27/11/2023	Version	:2	15/17
AQUACOAT 2650-06 - RAL 9010				Label No	1221	43

SECTION 16: Other information					
Skin Sens. 1B	SKIN SENSITISATION - Category 1B				
Date of issue/ Date of revision	: 10/07/2025				
Date of previous issue	: 27/11/2023				
Version	: 2				
	AQUACOAT 2650-06_RAL 9010 RAL 9010				

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision AQUACOAT 2650-06 - RAL 9010

: 10/07/2025 Date of previous issue