Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET



AQUACOAT 2650-33 - BASE 1

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: AQUACOAT 2650-33 - BASE 1

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

responsible for this SDS National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number: In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	1	No signal word.
Hazard statements	1	No known significant effects or critical hazards.
Precautionary statements		
Prevention	1	Not applicable.
Response	1	Not applicable.
Storage	1	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Contains adipohydrazide, adipohydrazide, 2-mercaptoethanol, 1,2-benzisothiazol-3 (2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and Bronopol and C(M)IT/MIT (3:1) and DTBMA and MBIT.

: 27/10/2023 Date of previous issue

SECTION 2: Hazards identification

Annex XVII - Restrictions	:
on the manufacture,	
placing on the market and	
use of certain dangerous	
substances, mixtures and	
articles	
use of certain dangerous substances, mixtures and	

2.3 Other hazards

Product meets the criteria : for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do :

not result in classification

Product meets the criteria
for PBT or vPvB according: This mixture does not contain any substances that are assessed to be a PBT or a
vPvB.

: None known.

SECTION 3: Composition/information on ingredients

Product/ingredient name	: Mixture	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Manium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
3-Butoxypropan-2-ol	REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319	-	[1]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	≤0.3	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
2-mercaptoethanol	EC: 200-464-6 CAS: 60-24-2	<0.1	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 2, H361 STOT RE 2, H373 Aquatic Acute 1, H400	ATE [Oral] = 244 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 3 mg/l M [Acute] = 1	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5	[1]

SECTION 3: Composition/information on ingredients

SECTION 5. Composition/mormation on ingredients				
	Ad Hi El Se th st	quatic Chronic 1, l410 :UH071	mg/l Skin Corr. 1C, H314: C ≥ 0.6% Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: 0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	:	Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptomsEye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, prot	ective equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for o	ontainment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s) **Recommendations**

: Not available.

Industrial sector specific solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient n	ame	Exposure limit values
Feaction mass of: 5-chloro-2-met 4-isothiazolin-3-one [EC no. 247- 2-methyl-2H-isothiazol-3-one [EC 220-239-6] (3:1)	500-7] and	Regulation on Limit Values - MAC (Austria, 4/2021). [] Skin sensitiser. TWA: 0.05 mg/m ³ 8 hours.
No exposure limit value known.		
No exposure limit value known.		
No exposure limit value known.		
No exposure limit value known.		
β -Butoxypropan-2-ol		Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). Absorbed through skin. STEL: 550 mg/m ³ 15 minutes. TWA: 270 mg/m ³ 8 hours. TWA: 49.14 ppm 8 hours. STEL: 100.1 ppm 15 minutes.
No exposure limit value known.		
No exposure limit value known.		
No exposure limit value known.		
No exposure limit value known.		
No exposure limit value known.		
√,2-benzisothiazol-3(2H)-one		DFG MAC-values list (Germany, 10/2021). Skin sensitiser.
No exposure limit value known.		
No exposure limit value known.		
No exposure limit value known.		
Date of issue/Date of revision	: 27/10/2023	Date of previous issue : 30/09/2022 Version : 1.08 5/18

SECTION 8: Exposure controls/personal protection			
No exposure limit value known.	1		
No exposure limit value known.			
No exposure limit value known.			
2-mercaptoethanol	Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2021). TWA: 1 mg/m³ 8 hours.		
No exposure limit value known.			
No exposure limit value known.			
No exposure limit value known.			
No exposure limit value known.			
No exposure limit value known.			
No exposure limit value known.			
No exposure limit value known.			
No exposure limit value known.			
No exposure limit value known.			
No exposure limit value known.			
No exposure limit value known.			
Peaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	SUVA (Switzerland, 1/2021). Skin sensitiser.		
	STEL: 0.4 mg/m ³ 15 minutes. Form: Inhalable fraction		
No exposure limit value known.	TWA: 0.2 mg/m ³ 8 hours. Form: Inhalable fraction		
Biological exposure indices			
Product/ingredient name	Exposure indices		
No exposure indices known.			
No exposure indices known.			
No exposure indices known.			
No exposure indices known.			
No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known. No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known. No exposure indices known. No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known.			
No exposure indices known. No exposure indices known.			

: 27/10/2023 Date of previous issue

SECTION 8: Exposure controls/personal protection		
No exposure indices known.		

: Reference should be made to monitoring standards, such as the following: **Recommended monitoring** European Standard EN 689 (Workplace atmospheres - Guidance for the procedures assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
3-Butoxypropan-2-ol	DNEL	Long term Inhalation	147 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	12.5 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	22 mg/kg	General	Systemic
	DNEL	Long term Inhalation	bw/day 43 mg/m³	population General population	Systemic
	DNEL	Long term Dermal	52 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	50 %	General population	Local
	DNEL	Long term Dermal	50 %	General	Local
	DNEL	Short term Dermal	50 %	Workers	Local
	DNEL	Long term Dermal	50 %	Workers	Local
adipohydrazide	DNEL	Long term Inhalation	17.5 mg/m ³		Systemic
adipohydrazide	DNEL	Long term Inhalation	17.5 mg/m³	Workers	Systemic
2-mercaptoethanol	DNEL	Short term Oral	0.025 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.025 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.05 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0.05 mg/ kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	0.17 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	0.17 mg/m ³	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/ kg bw/day	Workers	Systemic
e of issue/Date of revision : 27/	10/2023	Date of previous issue	: 30/09/20	122	Version : 1.08 7/1
UACOAT 2650-33 - BASE 1	10/2023	Date of previous issue	. 50/09/20		bel No :52668

	DNEL	Long term	1.2 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Long term Inhalation	6.81 mg/m ³	Workers	Systemic
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL	Long term Inhalation	0.02 mg/m ³	General population	Local
(5.1)	DNEL	Long term Inhalation	0.02 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	0.04 mg/m ³	General population	Local
	DNEL	Short term Inhalation	0.04 mg/m ³		Local
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/ kg bw/day	General population	Systemic

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborn contaminants.		
Individual protection measu	res			
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.		
Skin protection				
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.		
		Recommendations : Wear suitable gloves tested to EN374.		
		> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm		
		Not recommended polyvinyl alcohol (PVA) gloves		
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.		
		Filter type (spray application): A P		
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		

: 27/10/2023 Date of previous issue

: 30/09/2022

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: White.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and	:
boiling range	

Ingredient name	°C	°F	Method
water	100	212	
3-Butoxypropan-2-ol	171	339.8	OECD 103

Flammability

: Not available.

Lower and upper explosion	: Lower: Not applicable.
limit	Upper: Not applicable.
Flash point	: Closed cup: >100°C (>212°F)

Flash point

ŝ,

Auto-ignition	temperature
---------------	-------------

Ingredient name	°C	°F	Method			
Propylenglycoldimethylether	165	329				
3-Butoxypropan-2-ol	260	500	EU A.15			

Decomposition temperature	÷	Not available.
рН	:	8 to 8.8
Viscosity	:	Not available.
Solubility(ies)	:	
Not available.		
Solubility in water	:	Not available.
Deutition coefficients a setemal/		Not applicable

Partition coefficient: n-octanol/	1	Not applicable.
water		

ŝ,

Vapour pressure

	Va	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
3-Butoxypropan-2-ol	1.05	0.14	OECD 104				

Relative density	: Not available.
Density	: 1.2 g/cm ³
Vapour density	: Not available.
Explosive properties	: Not available.
Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stability and reactivity					
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
10.2 Chemical stability	: The product is stable.				
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.				
10.4 Conditions to avoid	: No specific data.				
10.5 Incompatible materials	: No specific data.				
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.				

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3-Butoxypropan-2-ol	LD50 Dermal	Rabbit	3100 mg/kg	-
2-mercaptoethanol	LD50 Oral	Rat	244 mg/kg	-
1,2-benzisothiazol-3(2H)-	LD50 Oral	Rat	1020 mg/kg	-
one				
reaction mass of: 5-chloro-	LD50 Oral	Rat	53 mg/kg	-
2-methyl-4-isothiazolin-				
3-one [EC no. 247-500-7]				
and 2-methyl-2H-isothiazol-				
3-one [EC no. 220-239-6] (3:				
1)				
Conclusion/Summary	Based on available data, t	the classification crite	eria are not met.	

Acute toxicity estimates

Route	ATE value
Not available.	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation	
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300	-	
				ug l		
3-Butoxypropan-2-ol	Skin - Moderate irritant	Rabbit	-	-	-	
2-mercaptoethanol	Eyes - Severe irritant	Rabbit	-	2 mg	-	
1,2-benzisothiazol-3(2H)-one		Human	-	48 hours 5 %	-	
reaction mass of: 5-chloro-	Skin - Severe irritant	Human	-	0.01 %	-	
2-methyl-4-isothiazolin-						
3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-						
3-one [EC no. 220-239-6] (3:						
1)						
,						
Conclusion/Summary : Based on available data, the classification criteria are not met.						
Sensitisation						
Conclusion/Summary	Conclusion/Summary : Based on available data, the classification criteria are not met.					
<u>Mutagenicity</u>						
Conclusion/Summary : Based on available data, the classification criteria are not met.						
<u>Carcinogenicity</u>						
It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.						
Conclusion/Summary : Based on available data, the classification criteria are not met.						

SECTION 11: Toxicological information

Reproductive toxicity

Con	clusi	on/Si	Jmm	arv
	oraor	011100		.

ary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
₽-mercaptoethanol	Category 2	-	-

Aspiration hazard

Not available.

Information on likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	1	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
e al ellie gement,	
Mutagenicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting propertiesNot available.11.2.2 Other informationNot available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - <i>Daphnia pulex -</i> Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.36 mg/l Marine water	Algae - Skeletonema Costatum	72 hours
	Acute EC50 3.7 mg/l	Daphnia - <i>Daphnia Magna</i>	48 hours
	Acute LC50 1.9 mg/l Fresh water	Fish - Onorhynchus Mykiss	96 hours
	Acute NOEC 0.15 mg/l Marine water	Algae - Skeletonema Costatum	72 hours

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
7,2-benzisothiazol-3(2H)-one	EU	24 % - 28 days		-	-
Conclusion/Summary : This product has not been tested for biodegradation.					
Product/ingredient name	Aquatic half-life		half-life Photolysis		Biodegradability
2-benzisothiazol-3(2H)-one			-		Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
ℬ-Butoxypropan-2-ol	1.2	-	Low
2-mercaptoethanol	-0.056	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

2

13.1 Waste treatment methods

Product

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Version : 1.08 12/18 Label No : 52668

SECTION 13: Disposal considerations

Hazardous waste	: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
European waste catalogue (EWC)	: 080112
Packaging	
Methods of disposal	 The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in user the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO

: Not relevant/applicable due to nature of the product.

instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

÷.

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Labelling

Other EU regulations

Industrial emissions : Not listed (integrated pollution prevention and control) -Air

: 27/10/2023 Date of previous issue · 30/09/2022

Explosive precursors : Not applicable. Ozone depleting substances (1005/2009/EU) Not listed. Prior Informed Consent (PIC) (649/2012/EU) Not listed. Persistent Organic Pollutants Not listed. Seveso Directive This product is not controlled under the Seveso Directive. lational regulations Austria VbF class : Not regulated. Limitation of the use of : Permitted. organic solvents Czech Republic Storage code : IV Denmark Danish fire class : IV-1 Executive Order No. 1795/2015 Ingredient name Annex I Section A Annex I Section E MAL-code : 0-1	Industrial emissions	: Not listed		
Water Explosive precursors : Not applicable. Oxone depleting substances (1005/2009/EU) Not listed. Prior Informed Consent (PIC) (649/2012/EU) Not listed. Bersistent Organic Pollutants Not listed. Seveso Directive This product is not controlled under the Seveso Directive. Lational regulations Austria VbF class : Not regulated. Limitation of the use of : Permitted. organic solvents : Cach Republic Storage code : IV Denmark : Listed Protection based on MAL : According to the regulations on work involving coded products, the following stipulation sapply to the use of personal protective equipment: General: : Gloves must be worn for all work that may result in solling. Apron/ coveralis/protective clothing must be worn work involving coded product. A face shield must be worn in work involving spatering if a full mask is not required. In all spraying operations in which there is return spray, the following must be worn respiratory protective and and arm protectors/apron/coveralis/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside t spray zone. - Arm protectors				
Ozone depleting substances (1905/2009/EU) Not listed. Prior Informed Consent (PIC) (649/2012/EU) Not listed. Persistent Organic Pollutants Not listed. Seveso Directive This products is not controlled under the Seveso Directive. Lational regulations Austria VDF class : Not regulated. Limitation of the use of : Permitted. organic solvents : Cech Republic Storage code : IV Dennish fire class : IV-1 Executive Order No. 1725/2015 Ingredient name Annex I Section A Annex I Section FE MAL-code : 0-1 Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment: Converall: Cloves must be worn in orall work that may result in solling, Apron/ coveralls/protective clothing must be worn involving spatienting if a full mask is not required. In the case, other recommended use of eye protecton is not required. In the case, other recommended use of eye protectors is not required. In the case, other recommended use of eye protectors is not required. In the case, other recommended use of eye protectors is not required. In the case, other recommended use of eye protector is not required. In the case, other recommended use of eye pro	Water			
Prior Informed Consent (PIC) (649/2012/EU) Not listed. Persistent Organic Pollutants Not listed. Seveso Directive This product is not controlled under the Seveso Directive. lational regulations Austria VbF class : Not regulated. Limitation of the use of : Permitted. organic Solvents Czech Republic Storage code : IV Denins fire class : IV-1 Executive Order No. 1795/2015 Ingredient name Annex 1 Section A MAL-code : 0-1 Protection based on MAL : According to the regulations on work involving coded products, the followin stiplations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in solling. Apron/ coveralis/protective clothing must be worn when solling is ogreat that regular we clothes do not adequately protect skin against contract with the product. A face shield must be worn involving gratering if a full mask is not required. In the case, other recommended use of eye protections in sol required. In the case, other recommended use of eye protectors is not required. In the case, other recommended use of eye protectors is not required. In the case, other recommended use of eye protectors is not required. In the case, other recommended use of eye protectors is not required. In the case, other recommended use of eye protectoris is not required. In the case, other reco	Explosive precursors	: Not applicable.		
Prior Informed Consent (PIC) (649/2012/EU) Not listed. Persistent Organic Pollutants Not listed. Seveso Directive This product is not controlled under the Seveso Directive. lational regulations Austria VDF class : Organic Solvents Czech Republic Storage code : Darins fire class : Ingredient name Annex 1 Section A Manex 1 Section A Annex 1 Section E Wall-code : Protection based on MAL : According to the regulations on work involving coded products, the following students apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in solling. Apron/ coveralis/protective clothing must be worn when solling is so great that regular we clothes do not adequately protect sin against contact with the product. A face sheld must be worn in which there is return spray. the following must be worn respiratory protections and arm protectors/apron/coveralis/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside t spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilitites of the combined-cabin, spray-cabin and spray-boot	Ozone depleting substance	es (1005/2009/EU)		
Not listed. Persistent Organic Pollutants Not listed. Seveso Directive This product is not controlled under the Seveso Directive. Lational regulations Austria VDF class i Not regulated. Limitation of the use of Permitted. organic solvents Czech Republic Storage code i IV Denmark Danish fire class i IV-1 Executive Order No. 1795/2015 Ingredient name AL-code i 0-1 Protection based on MAL. Ceneral: Gloves must be worn for all work that may result in solling. Apron/ coveralls/protective clothing must be worn work involving is so great that regular w clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In th case, other recommended use of eye protection is not required. In th case, other recommended use of eye protections is outside t spray zone Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray- cabin and spray-booth type where the operator is working in side the spray zone Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cat or booth.	Not listed.			
Not listed. Seveso Directive This product is not controlled under the Seveso Directive. Liational regulations Austria VDF class : Not regulated. Limitation of the use of Permitted. organic solvents Czech Republic Storage code : IV Denmark Danish fire class : IV-1 Executive Order No. 1795/2015 Ingredient name Fanium dioxide 0-1 MAL-code : 0-1 Protection based on MAL. Ceneral: Gloves must be worn for all work that may result in solling. Apron/ coveralis/protective clothing must be worn whork onling is so great that required. In the case, often recommended use of eye protectors/apron/coveralis/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* facilities of the combined-cabin, spray-cabin and spray booths, if the operator is outside t spray zone Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray zone and during spraying outside a closed facility, cat or booth.		<u>C) (649/2012/EU)</u>		
This product is not controlled under the Seveso Directive. Iational regulations Austria VDF class ! Not regulated. Limitation of the use of creating of the sevent of the seven of the sevent of the sevent of the sevent of the sevent of the s	-	<u>nts</u>		
This product is not controlled under the Seveso Directive. Iational regulations Austria VDF class ! Not regulated. Limitation of the use of creating of the sevent of the seven of the sevent of the sevent of the sevent of the sevent of the s	Seveso Directive			
tational regulations Austria VbF class : Not regulated. Limitation of the use of organic solvents : Permitted. Storage code : IV Denmark : Denmark Danish fire class : IV-1 Executive Order No. 1795/2015 Ingredient name Annex I Section A Annex I Section F MAL-code : 0-1 Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular word be not adequately protets kina gainst contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protection is not required. In the case, other recommended use of eye protection is not required. In the case, other recommended use of eye protections is not required. In all spraying operations in which there is return spray, the following must be wor sa instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside t spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-cabin and spray-cabin and spray-booth type where the operator is working		under the Seveso Directive		
Austria VPF class : Not regulated. Llimitation of the use of organic solvents : Permitted. Czech Republic : Storage code : IV Storage code : IV.1 Executive Order No. 1795/2015 : Interpretation of the use of organic solvents Ingredient name Annex I Section A Annex I Section E MAL-code : 0-1 Protection based on MAL : According to the regulations on work involving coded products, the followin stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soliling. Apron/ coveralls/protective clothing must be worn work soling is so great that regular wore clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protection is not required. In the case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be wor respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside t spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spra	•			
VbF class : Not regulated. Limitation of the use of organic solvents : Permitted. Organic solvents : Permitted. Storage code : IV Demmark : Not regulated. Danish fire class : IV-1 Executive Order No. 1795/2015 : Annex I Section A Ingredient name Annex I Section A MAL-code : 0-1 Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular wore clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protection is not required. In the case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be wor respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside t spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside				
Limitation of the use of : Permitted. organic solvents Czech Republic Storage code : IV Denmark Danish fire class : IV-1 Executive Order No. 1795/2015 Ingredient name Annex 1 Section A Annex 1 Section E Mal.code : 0-1 Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in solling. Apron/ coveralls/protective clothing must be worn when solling is o great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be worn respiratory protections and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside t spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray- cabin and spray-booth type where the operator is working inside the spray zone. - Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cat or booth.		: Not regulated.		
Storage code : IV Denmark Danish fire class : IV-1 Executive Order No. 1795/2015 Ingredient name Annex I Section A Annex I Section E MAL-code : 0-1 Protection based on MAL : According to the regulations on work involving coded products, the followin stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protection is not required. In the case, other recommended use of eye protection is not required. In the case, other recommended use of eye protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside the spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. - Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cat or booth.		•		
Denmark Danish fire class : IV-1 Executive Order No. 1795/2015 Ingredient name Annex 1 Section A Annex 1 Section E MAL-code : 0-1 Protection based on MAL : According to the regulations on work involving coded products, the followin stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside t spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. - Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cat or booth.	Czech Republic			
Danish fire class : IV-1 Executive Order No. 1795/2015 Ingredient name Annex 1 Section A Annex 1 Section E Iffanium dioxide Listed - MAL-code : 0-1 Protection based on MAL : According to the regulations on work involving coded products, the followin stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soling. Apron/coveralls/protective clothing must be worn when soling is so great that regular wore clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protections in sort required. In all spraying operations in which there is return spray, the following must be worr respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside t spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. - Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cat or booth.	Storage code	: IV		
Executive Order No. 1795/2015 Ingredient name Annex I Section A Annex I Section F Iffanium dioxide Listed - MAL-code : 0-1 Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work of a dequately protect skin agains contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be worr respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside t spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is or spray booths where the operator is or spray booths where the operator is inside the spray zone. - Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cat or booth.	<u>Denmark</u>			
Ingredient name Annex I Section A Annex I Section E Iffanium dioxide Listed - MAL-code : 0-1 Protection based on MAL : According to the regulations on work involving coded products, the followin stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be worr respiratory protector and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside t spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. - Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cat or booth.	Danish fire class	: IV-1		
Mainum dioxide Listed - MAL-code : 0-1 : According to the regulations on work involving coded products, the followin stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be wor respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside the spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. - Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cat or booth.	Executive Order No. 1795/2	<u>015</u>		
MAL-code : 0-1 Protection based on MAL : According to the regulations on work involving coded products, the followin stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be worr respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside the spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. - Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone. - Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone.	Ingredient name		Annex I Section A	Annex I Section B
Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be worr respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside the spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. - Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cator booth.	tit anium dioxide		Listed	-
 Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment: General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be worr respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside the spray zone. Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cat or booth. 	MAL codo	: 0.1		
 coveralls/protective clothing must be worn when solling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In the case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be worn respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside the spray zone. Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cat or booth. 	Protection based on MAL	stipulations apply to the use	of personal protective equi	oment:
respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed. MAL-code: 0-1 Application: When spraying in existing* spray booths, if the operator is outside t spray zone. - Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray- cabin and spray-booth type where the operator is working inside the spray zone. - Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cat or booth.		coveralls/protective clothing m clothes do not adequately prot	ust be worn when soiling is so ect skin against contact with th volving spattering if a full mask	great that regular wor e product. A face
 Application: When spraying in existing* spray booths, if the operator is outside t spray zone. Arm protectors must be worn. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cab or booth. 			e of eye protection is not require	ed.
During non-atomising spraying in existing* facilities of the combined-cabin, spray- cabin and spray-booth type where the operator is working inside the spray zone. - Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cab or booth.		case, other recommended use In all spraying operations in wh respiratory protection and arm	nich there is return spray, the fo	ollowing must be worr
 cabin and spray-booth type where the operator is working inside the spray zone. Gas filter mask must be worn. During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cab or booth. 		case, other recommended use In all spraying operations in wh respiratory protection and arm appropriate or as instructed. MAL-code: 0-1 Application: When spraying	nich there is return spray, the fo protectors/apron/coveralls/pro	ollowing must be worr tective clothing as
During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cab or booth.		case, other recommended use In all spraying operations in wh respiratory protection and arm appropriate or as instructed. MAL-code: 0-1 Application: When spraying spray zone.	nich there is return spray, the fo protectors/apron/coveralls/pro in existing* spray booths, if the	ollowing must be worr tective clothing as
operator is inside the spray zone and during spraying outside a closed facility, cat or booth.		 case, other recommended use In all spraying operations in wh respiratory protection and arm appropriate or as instructed. MAL-code: 0-1 Application: When spraying spray zone. Arm protectors must be worn During non-atomising spraying 	nich there is return spray, the fo protectors/apron/coveralls/pro in existing* spray booths, if the n. g in existing* facilities of the cor	ollowing must be worr tective clothing as operator is outside th nbined-cabin, spray-
- Full mask with combined filter, coveralls and hood must be worn.		 case, other recommended use In all spraying operations in wh respiratory protection and arm appropriate or as instructed. MAL-code: 0-1 Application: When spraying spray zone. Arm protectors must be worn During non-atomising spraying cabin and spray-booth type wh 	nich there is return spray, the fo protectors/apron/coveralls/pro in existing* spray booths, if the n. g in existing* facilities of the cor here the operator is working ins	ollowing must be worr tective clothing as operator is outside th nbined-cabin, spray-
		 case, other recommended use In all spraying operations in wh respiratory protection and arm appropriate or as instructed. MAL-code: 0-1 Application: When spraying spray zone. Arm protectors must be worr During non-atomising spraying cabin and spray-booth type wh Gas filter mask must be worr During all spraying where atom operator is inside the spray zo 	hich there is return spray, the for protectors/apron/coveralls/pro in existing* spray booths, if the n. g in existing* facilities of the cor here the operator is working ins n. hisation occurs in cabins or spr	ollowing must be worr tective clothing as operator is outside th mbined-cabin, spray- ide the spray zone.
te of issue/Date of revision : 27/10/2023 Date of previous issue : 30/09/2022 Version : 1.08 14/		 case, other recommended use In all spraying operations in wh respiratory protection and arm appropriate or as instructed. MAL-code: 0-1 Application: When spraying spray zone. Arm protectors must be worn During non-atomising spraying cabin and spray-booth type wh Gas filter mask must be worn During all spraying where atom operator is inside the spray zo or booth. 	hich there is return spray, the for protectors/apron/coveralls/pro in existing* spray booths, if the n. g in existing* facilities of the cor- here the operator is working ins n. hisation occurs in cabins or spr ne and during spraying outside	ollowing must be worr tective clothing as operator is outside th mbined-cabin, spray- ide the spray zone.
QUACOAT 2650-33 - BASE 1 Label No :52668	ate of issue/Date of revision	 case, other recommended use In all spraying operations in wh respiratory protection and arm appropriate or as instructed. MAL-code: 0-1 Application: When spraying spray zone. Arm protectors must be worn During non-atomising spraying cabin and spray-booth type wh Gas filter mask must be worn During all spraying where atom operator is inside the spray zo or booth. Full mask with combined filter 	hich there is return spray, the for protectors/apron/coveralls/pro in existing* spray booths, if the n. g in existing* facilities of the cor here the operator is working ins n. hisation occurs in cabins or spr ne and during spraying outside er, coveralls and hood must be	ollowing must be worr tective clothing as operator is outside th mbined-cabin, spray- ide the spray zone.

SECTION 15: Regulatory information

		Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.
		Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.
		Caution The regulations contain other stipulations in addition to the above.
		*See Regulations.
Restrictions on use		Not to be used by professional users below 18 years of age. See the National
		Working Environment Authorities Executive Order regarding Young People At Work.
List of undesirable substances	:	Not listed
Finland		
<u>France</u>		_
Social Security Code, Articles L 461-1 to L 461-7	:	3-Butoxypropan-2-ol RG 84
Reinforced medical surveillance	:	Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable
<u>Germany</u>		
Storage class (TRGS 510)		
Hazardous incident ordina		-
•		nder the Germany Hazardous Incident Ordinance.
Hazard class for water	- 1	
Technical instruction on air quality control	ł	A-Luft Number 5.2.5: 28.8%
AOX	:	The product contains organically bound halogens and can contribute to the AOX value in waste water.
<u>Italy</u>		
D.Lgs. 152/06	:	Not determined.
<u>Netherlands</u>		
Water Discharge Policy (ABM)	:	A(3) Hazardous for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A
<u>Norway</u>		
<u>Sweden</u>		
Switzerland		
VOC content	÷	Exempt.
International regulations		
Chemical Weapon Conventi Not listed.	<u>on</u>	List Schedules I, II & III Chemicals
Montreal Protocol		
Not listed.		
Stockholm Convention on P Not listed.	<u>'er</u>	sistent Organic Pollutants
Rotterdam Convention on P Not listed.	<u>ric</u>	r Informed Consent (PIC)
UNECE Aarhus Protocol on	<u>P(</u>	Ps and Heavy Metals
Date of issue/Date of revision		: 27/10/2023 Date of previous issue : 30/09/2022 Version : 1.08 15/18

AQUACOAT 2650-33 - BASE 1

SECTION 15: Regulatory information

Not listed.

15.2 Chemical safety assessment

: Not applicable.

SECTION 16: Other information

Indicates information	that has changed from previously issued version.
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

		-		
	ACUTE TOXICITY - Category 2			
	ACUTE TOXICITY - Category 3			
	ACUTE TOXICITY - Category 4			
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1			
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1			
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2			
Carc. 2	CARCINOGENICITY - Category 2			
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1			
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2			
Repr. 2	REPRODUCTIVE TOXICITY - Category 2			
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C			
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2			
Skin Sens. 1	SKIN SENSITISATION - Category 1			
Skin Sens. 1A	SKIN SENSITISATION - Category 1A			
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Ca	tegory 2		
Date of issue/ Date of	: 27/10/2023			
revision				
Date of previous issue	: 30/09/2022			
Version	: 1.08			
Date of issue/Date of revision	n : 27/10/2023 Date of previous issue : 30/09/2022	Version	: 1.08	16/18
AOUACOAT 2650 22	· · · · · · · · · · · · · · · · · · ·	abel No		
AQUACOAT 2650-33 - 1		.auei NO	.000	

SECTION 16: Other information

AQUACOAT 2650-33_BASE 1

BASE 1

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision AQUACOAT 2650-33 - BASE 1 : 27/10/2023 Date of previous issue

: 30/09/2022