Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - United Kingdom: Northern Ireland

SAFETY DATA SHEET



AQUACOAT 2650-33 - BASE 3

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	

: AQUACOAT 2650-33 - BASE 3

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

responsible for this SDS National contact

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	1	No signal word.
Hazard statements	1	No known significant effects or critical hazards.
Precautionary statements		
Prevention	1	Not applicable.
Response	1	Not applicable.
Storage	1	Not applicable.
Disposal	1	Not applicable.
Supplemental label elements	:	Contains adipohydrazide, 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Safety data sheet available on request. Contains biocidal products for in-can preservation: BIT and C(M)IT/MIT (3:1) and DTBMA and Bronopol and MBIT.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
2.3 Other hazards		

: 10/07/2025 Date of previous issue

SECTION 2: Hazards identification

 Product meets the criteria
 : This mixture does not contain any substances that are assessed to be a PBT or a

 for PBT or vPvB according
 vPvB.

 to Regulation (EC) No.
 1907/2006, Annex XIII

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3 -Butoxypropan-2-ol	REACH #: 01-2119475527-28 EC: 225-878-4	≤3			
	CAS: 5131-66-8 Index: 603-052-00-8		Skin Irrit. 2, H315 Eye Irrit. 2, H319	and ATEs -	[1]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤3	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤3	Eye Irrit. 2, H319	-	[1] [2]
adipohydrazide	EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1B, H317 Aquatic Chronic 2, H411	-	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: $C \ge 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	
Date of issue/Date of revision	: 10/07/2025 Date	e of previous is	sue : 27/10/2023	Version : 2	2/18

SECTION 3: Composition/information on ingredients See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures			
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.		
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.		
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. 		
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.		

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms			
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: No specific data.		
Ingestion	: No specific data.		

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

: Use an extinguishing agent suitable for the surrounding fire.
: None known.
from the substance or mixture
: In a fire or if heated, a pressure increase will occur and the container may burst.
: Decomposition products may include the following materials: carbon dioxide carbon monoxide

5.3 Advice for firefighters

Date of issue/Date of revision	: 10/07/2025	Date of previous issue	: 27/10/2023	Version : 2	3/18
AQUACOAT 2650-33 - BASE 3				Label No :1/2214	45

SECTION 5: Firefighting measures

-	-	
Special protective actions for fire-fighters	the	omptly isolate the scene by removing all persons from the vicinity of the incident if ere is a fire. No action shall be taken involving any personal risk or without itable training.
Special protective equipment for fire-fighters	bre mo co	e-fighters should wear appropriate protective equipment and self-contained eathing apparatus (SCBA) with a full face-piece operated in positive pressure ode. Clothing for fire-fighters (including helmets, protective boots and gloves) nforming to European standard EN 469 will provide a basic level of protection for emical incidents.

SECTION 6: Accidental release measures

live equipment and emergency procedures	
Evacuate surrounding areas. Keep unnecessary and unprotected personnel f entering. Do not touch or walk through spilt material. Put on appropriate pers	rom
nformation in Section 8 on suitable and unsuitable materials. See also the	
and sewers. Inform the relevant authorities if the product has caused environing	
tainment and cleaning up	
material and place in an appropriate waste disposal container. Dispose of via	
water courses, basements or confined areas. Wash spillages into an effluent creatment plant or proceed as follows. Dispose of via a licensed waste dispos contractor. Contain and collect spillage with non-combustible, absorbent mate g. sand, earth, vermiculite or diatomaceous earth and place in container for dis	al erial e.
See Section 8 for information on appropriate personal protective equipment.	
: 1 E E F F : 1 I ii ii ii ii ii ii ii ii ii i	 Available taken involving any personal risk or without suitable training Evacuate surrounding areas. Keep unnecessary and unprotected personnel f entering. Do not touch or walk through spilt material. Put on appropriate pers protective equipment. If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". Avoid dispersal of spilt material and runoff and contact with soil, waterways, dr and sewers. Inform the relevant authorities if the product has caused environe pollution (sewers, waterways, soil or air). Containment and cleaning up Stop leak if without risk. Move containers from spill area. Absorb with an iner material and place in an appropriate waste disposal container. Dispose of via licensed waste disposal contractor. Stop leak if without risk. Move containers from spill area. Prevent entry into s water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent mater g. sand, earth, vermiculite or diatomaceous earth and place in container for dis according to local regulations. See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s) Recommendations

: Not available.

Date of issue/Date of revision: 10/07/2025Date of previous issue: 27/10/2023VeAQUACOAT 2650-33 - BASE 3Labeletee

SECTION 7: Handling and storage

Industrial sector specific : Not available. solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
-Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin.
	STEL 15 minutes: 50 ppm. TWA 8 hours: 25 ppm. STEL 15 minutes: 246 mg/m ³ . TWA 8 hours: 123 mg/m ³ .
2-(2-butoxyethoxy)ethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m ³ . STEL 15 minutes: 15 ppm. STEL 15 minutes: 101.2 mg/m ³ .

Biological exposure indices

Product/ingredient	t name		Exposure ind	ices	
P-Butoxyethanol		EH40/2005 BMGVs (United Kingdom (UK), 1/2020) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.			
Recommended monitoring procedures	European Star assessment of values and me atmospheres - of exposure to (Workplace ath for the measur	uld be made to monitor dard EN 689 (Workpla exposure by inhalation asurement strategy) E Guide for the application chemical and biologica mospheres - General re ement of chemical age methods for the determ	ce atmospheres - to chemical agen uropean Standard on and use of proc al agents) Europea equirements for the nts) Reference to	Guidance for the ts for comparison wit EN 14042 (Workplace edures for the asses an Standard EN 482 e performance of pro- national guidance	ce sment cedures
DNELs/DMELs					
Product/ingredient name		Result			
3∕ -Butoxypropan-2-ol		DNEL - Genera 12.5 mg/kg bw/c <u>Effects</u> : System		ng term - Oral	
		DNEL - Genera 22 mg/kg bw/da <u>Effects</u> : System		ng term - Dermal	
		DNEL - Genera 43 mg/m³ <u>Effects</u> : System		ng term - Inhalation	
		DNEL - Worker 52 mg/kg bw/da <u>Effects</u> : System		ermal	
		DNEL - Worker 147 mg/m³ <u>Effects</u> : System	s - Long term - In ic	halation	
2-Butoxyethanol		DNEL - Genera 6.3 mg/kg bw/da	I population - Loi ay	ng term - Oral	
Date of issue/Date of revision	: 10/07/2025	ate of previous issue	: 27/10/2023	Version : 2	5/18
QUACOAT 2650-33 - BASE 3				Label No :122	145

	Effects: Systemic
	DNEL - General population - Short term - Oral 26.7 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 59 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 98 mg/m ³ <u>Effects</u> : Systemic
	DNEL - General population - Short term - Inhalation 147 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Short term - Inhalation 246 mg/m³ <u>Effects</u> : Local
	DNEL - General population - Short term - Inhalation 426 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Short term - Inhalation 1091 mg/m ³ <u>Effects</u> : Systemic
2-(2-butoxyethoxy)ethanol	DNEL - General population - Long term - Oral 6.25 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 67.5 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Short term - Inhalation 101.2 mg/m³ <u>Effects</u> : Local
adipohydrazide	DNEL - Workers - Long term - Inhalation 17.5 mg/m ³ <u>Effects</u> : Systemic
1,2-benzisothiazol-3(2H)-one	DNEL - General population - Long term - Dermal 0.345 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 0.966 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 1.2 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 6.81 mg/m ³ <u>Effects</u> : Systemic
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL - General population - Long term - Inhalation 0.02 mg/m ³ <u>Effects</u> : Local

: 10/07/2025 Date of previous issue

SECTION 8: Exposure controls/personal protection

DNEL - Workers - Long term - Inhalation 0.02 mg/m³ Effects: Local

DNEL - General population - Short term - Inhalation 0.04 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation 0.04 mg/m³ Effects: Local

DNEL - General population - Long term - Oral 0.09 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Oral 0.11 mg/kg bw/day <u>Effects</u>: Systemic

PNECs

Not available.

8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	<u>ires</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P

SECTION 8: Exposure controls/personal protection

Environmental exposure	
controls	

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Colourless.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name	°C	°F	Method
water	100	212	
3-Butoxypropan-2-ol	171	339.8	OECD 103

Flammability	4	Not available.
Lower and upper explosion limit	:	Lower: Not applicable. Upper: Not applicable.
Flash point	1	Closed cup: >100°C (>212°F)

2

2

Auto-ignition temperature

Ingredient name	°C	°F	Method
2-butoxyethoxy)ethanol	210	410	DIN 51794
2-Butoxyethanol	230	446	DIN 51794

Decomposition temperature	: Not available.
рН	∶ <mark>8</mark> ″to 8.9 [Conc. (% w/w): 100%]
Viscosity	: Not available.
Solubility(ies)	:
Not available.	
Solubility in water	: Not available.
Partition coefficient: n-octanol/	: Not applicable.

water

Vapour pressure

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
3-Butoxypropan-2-ol	1.05	0.14	OECD 104			
Relative density	: Not	available.			-	
Density	: 1 g/	cm³				
/apour density	: Not	available.				
Particle characteristics						
Median particle size	: Not	applicable.				

9.2 Other information

9.2.1 Information with regard to physical hazard classes

SECTION 9: Physical and chemical properties

Explosive properties	: Not available.
Oxidising properties	: Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	No specific data.
10.5 Incompatible materials	:	No specific data.
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Product/ingredient name B-Butoxypropan-2-ol	<mark>Result</mark> Rabbit - Dermal - LD50 3100 mg/kg
2-(2-butoxyethoxy)ethanol	Rabbit - Dermal - LD50 2700 mg/kg
	Rat - Oral - LD50 4500 mg/kg <u>Toxic effects</u> : Behavioral - Tetany Lung, Thorax, or Respiration - Dyspnea Liver - Other changes
1,2-benzisothiazol-3(2H)-one	Rat - Oral - LD50 1020 mg/kg
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Rat - Oral - LD50 53 mg/kg <u>Toxic effects</u> : Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredien	it name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Date of issue/Date of revision	: 10/07/2025	Date of previous issue	: 27/10	//2023	Version	:2 9/18
AQUACOAT 2650-33 - BASE 3					Label No :	122145

SECTION 11: Toxicological information

AQUACOAT 2650-33	113862.0	N/A	N/A	284.7	N/A		
3-Butoxypropan-2-ol	N/A	3100	N/A	N/A	N/A		
2-Butoxyethanol	1200	N/A	N/A	3	N/A		
2-(2-butoxyethoxy)ethanol	4500	2700	N/A	N/A	N/A		
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21		
reaction mass of: 5-chloro-2-methyl-4-isoth	niazolin- 53	50	N/A	0.5	N/A		
3-one [EC no. 247-500-7] and 2-methyl-2H	-						
isothiazol-3-one [EC no. 220-239-6] (3:1)							

Skin corrosion/irritation

Product/ingredient name

3-Butoxypropan-2-ol

2-Butoxyethanol

1,2-benzisothiazol-3(2H)-one

Result

Rabbit - Skin - Moderate irritant

Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg

Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Conclusion/Summary [Product] : Not available.

Ingredient name Butoxypropan-2-ol

Serious eye damage/eye irritation Product/ingredient name

2-Butoxyethanol

2-(2-butoxyethoxy)ethanol

Conclusion/Summary

Slightly irritating to the skin.

Human - Skin - Severe irritant

Amount/concentration applied: 0.01 %

Result

Rabbit - Eyes - Moderate irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant Amount/concentration applied: 100 mg

Rabbit - Eyes - Moderate irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 20 mg

Rabbit - Eyes - Severe irritant Amount/concentration applied: 20 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Date of issue/Date of revision AQUACOAT 2650-33 - BASE 3 : 10/07/2025 Date of previous issue

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure) Not available.

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard			
Not available.			
Information on likely routes	of	exposure	
Not available.			
Potential acute health effect	ts		
Eye contact	1	No known significant effects or critical hazards.	
Inhalation	:	No known significant effects or critical hazards.	
Skin contact	:	No known significant effects or critical hazards.	
Ingestion	1	No known significant effects or critical hazards.	
Symptoms related to the ph	ysi	cal, chemical and toxicological characteristics	
Eye contact	:	No specific data.	
Inhalation	:	No specific data.	
Skin contact	1	No specific data.	
Ingestion	:	No specific data.	
Delayed and immediate effe	cts	as well as chronic effects from short and long-term exposi-	ure
Short term exposure			
Potential immediate effects	:	Not available.	
Potential delayed effects	1	Not available.	
Long term exposure			
Potential immediate effects	:	Not available.	
Potential delayed effects	:	Not available.	
Potential chronic health effe	ecte	<u>s</u>	
Not available.			
Conclusion/Summary [Pro	odu	ct] : Not available.	
General	:	No known significant effects or critical hazards.	
Carcinogenicity	:	No known significant effects or critical hazards.	
Date of issue/Date of revision		: 10/07/2025 Date of previous issue : 27/10/2023	Version

AQUACOAT 2650-33 - BASE 3

SECTION 11: Toxicological information

Mutagenicity

- : No known significant effects or critical hazards.
- **Reproductive toxicity**
- : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity	
Product/ingredient name P-Butoxyethanol	Result Acute - LC50 - Marine water Fish - Inland silverside - Menidia beryllina Size: 40 to 100 mm 1250000 µg/l [96 hours] Effect: Mortality Acute - LC50 - Marine water
	Crustaceans - Common shrimp, sand shrimp - <i>Crangon</i> <i>crangon</i> 800000 μg/l [48 hours] <u>Effect</u> : Mortality
2-(2-butoxyethoxy)ethanol	Acute - LC50 - Fresh water Fish - Bluegill - <i>Lepomis macrochirus</i> <u>Size</u> : 33 to 75 mm 1300000 μg/l [96 hours] <u>Effect</u> : Mortality
1,2-benzisothiazol-3(2H)-one	Acute - LC50 - Fresh water OECD [Fish, Acute Toxicity Test] Fish - Trout - <i>Onorhynchus Mykiss</i> 1.9 mg/l [96 hours]
	Acute - EC50 OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - <i>Daphnia Magna</i> 3.7 mg/l [48 hours]
	Acute - EC50 - Marine water OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.36 mg/l [72 hours]
	Acute - NOEC - Marine water OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.15 mg/l [72 hours]
Conclusion/Summary [Product] : I	Not available.
12.2 Persistence and degradability	
Product/ingredient name	Result

1,2-benzisothiazol-3(2H)-one

Result ΕU 24% [28 days]

: 10/07/2025 Date of previous issue

SECTION 12: Ecological information

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability			
7,2-benzisothiazol-3(2H)-one	-	-	Inherent			

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-Butoxypropan-2-ol	1.2	-	Low
2-Butoxyethanol	0.81	-	Low
2-(2-butoxyethoxy)ethanol	1	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
ℬ-Butoxypropan-2-ol	1.5	28.6002
2-Butoxyethanol	1.8	67.3685
2-(2-butoxyethoxy)ethanol	1.6	36.5981
adipohydrazide	1.7	55.2165
1,2-benzisothiazol-3(2H)-one	1.9	73.142

Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	Μ	т	vPvM	vP	vM
♂-Butoxypropan-2-ol	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
2-(2-butoxyethoxy)ethanol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Mobility Conclusion/Summary

: Not available.

: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
3-Butoxypropan-2-ol	No	N/A	N/A	No	N/A	N/A	N/A
2-Butoxyethanol	No	N/A	N/A	No	N/A	N/A	N/A
2-(2-butoxyethoxy)ethanol	No	N/A	N/A	No	N/A	N/A	N/A
adipohydrazide	No	N/A	N/A	No	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	No	N/A	No	No	No	N/A	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	N/A	N/A	No	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

: 10/07/2025 Date of previous issue

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
3-Butoxypropan-2-ol	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
2-(2-butoxyethoxy)ethanol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

```
Conclusion/Summary [Product]
```

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Ρ	ro	dι	ict
_	_		

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	 Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
European waste catalogue (EWC)	: 080112
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
Date of issue/Date of rev	ision : 10/07/2025	Date of previous issue	: 27/10/2023	Version : 2 14/18
AQUACOAT 2650-33 - BASE 3				Label No : 1/22145

SECTION 14: Transport information				
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

: Not relevant/applicable due to nature of the product. 14.7 Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous

substances, mixtures and articles

Product/ingredient name		%	Designation [Usage]			
2-(2-butoxyethoxy)ethanol		≤3	55 [Consumer paint]			
Labelling	:					
<u> Dther EU regulations</u>						
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed					
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed					
Explosive precursors	: Not applicab					
Ozone depleting substance Not listed.	es (EU 2024/590	<u>((</u>				
Prior Informed Consent (Ple Not listed.	<u>C) (649/2012/El</u>	(ר				
Persistent Organic Pollutar Not listed.	<u>nts</u>					
Seveso Directive						
This product is not controlled	under the Seve	so Directive.				
nternational regulations						
Chemical Weapon Convention	on List Schedu	<u>les I, II & III (</u>	Chemicals			
te of issue/Date of revision	: 10/07/2025	Date of previo	us issue : 27/10/2023	Version	:2	15/18

SECTION 15: Regulatory information

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

applicable.

assessment

SECTION 16: Other information

Indicates information t	hat has changed from previously issued version.
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) N 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Not classified.

Full text of abbreviated H statements

F 301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2		
Acute Tox. 3	ACUTE TOXICITY - Category 3		
Acute Tox. 4	ACUTE TOXICITY - Category 4		
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1		
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1		
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2		
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1		
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2		
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C		
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2		
Skin Sens. 1A	SKIN SENSITISATION - Category 1A		
Date of issue/Date of rev	ision : 10/07/2025 Date of previous issue : 27/10/2023	Version : 2	16/18

No.

SECTION 16: Other information			
Skin Sens. 1B	SKIN SENSITISATION - Category 1B		
Date of issue/ Date of revision	: 10/07/2025		
Date of previous issue	: 27/10/2023		
Version	: 2		
	AQUACOAT 2650-33_BASE 3		
Notice to veeder			

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision AQUACOAT 2650-33 - BASE 3 : 10/07/2025 Date of previous issue

: 27/10/2023

Version : 2 18/18 Label No : 1/22145