Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

## **SAFETY DATA SHEET**



AQUAPRIMER 2900-02 - TST 100739 BLACK

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1	Produc	t identifier

Product name

: AQUAPRIMER 2900-02 - TST 100739 BLACK

**1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use**: Paint.

#### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

## responsible for this SDS

#### National contact

Teknos (UK) Limited, 7 Longlands Rd, Bicester, Oxfordshire OX26 5AH, United Kingdom. Tel. +44 (0) 1869 208005.

## **1.4 Emergency telephone number**

National advisory body/Poison Centre

Telephone number : NHS: 111

## **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Product definition : Mixture

## **Classification according to UK CLP/GHS**

Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	1	P273 - Avoid release to the environment.
Response	1	Not applicable.
Storage	1	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	Contains 3-iodo-2-propynyl-butyl carbamate, 1,2-benzisothiazol-3(2H)-one and 2-Methyl-1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Contains biocidal products for dry film and in-can preservation: IPBC and BIT and DTBMA and MBIT. Risk of skin sensitisation.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.

## **SECTION 2: Hazards identification**

#### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

## **SECTION 3: Composition/information on ingredients**

	lixture			1
Product/ingredient name	Identifiers	%	Classification	Туре
Polymeric alkoxylate	-	≤3	Acute Tox. 4, H302	[1]
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤3	Eye Irrit. 2, H319	[1] [2]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	<1	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
Propylene glycol	REACH #: 01-2119456809-23 EC: 200-338-0 CAS: 57-55-6	≤1	Not classified.	[2]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]
2-aminoethanol	EC: 205-483-3 CAS: 141-43-5 Index: 603-030-00-8	≤0.1	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1] [2]
1,2-dichlorobenzene	EC: 202-425-9 CAS: 95-50-1	<0.1	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) See Section 16 for the full text of the H statements declared above.	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

## **SECTION 3: Composition/information on ingredients**

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

4.1 Description of first aid m	ieasures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

## 4.2 Most important symptoms and effects, both acute and delayed

<u>Over-exposure signs/symptoms</u>				
Eye contact	: No specific data.			
Inhalation	: No specific data.			
Skin contact	: No specific data.			
Ingestion	: No specific data.			

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.

## **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	-	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising fi	ron	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures			
6.1 Personal precautions, pro	oteo	ctive equipment and emergency procedures	
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.	
6.3 Methods and material for	со	ntainment and cleaning up	
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	-	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.	
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.	

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

**Recommendations** 

: Not available.

Date of issue/Date of revision : 14/11/2023 Date of previous issue AQUAPRIMER 2900-02 - TST 100739 BLACK

## **SECTION 7: Handling and storage**

Industrial sector specific solutions

: Not available.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Occupational exposure limits	
2-(2-butoxyethoxy)ethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020).
	TWA: 10 ppm 8 hours.
	STEL: 15 ppm 15 minutes.
	TWA: 67.5 mg/m³ 8 hours.
	STEL: 101.2 mg/m <sup>3</sup> 15 minutes.
2-Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
	through skin.
	STEL: 50 ppm 15 minutes.
	TWA: 25 ppm 8 hours.
	STEL: 246 mg/m <sup>3</sup> 15 minutes.
	TWA: 123 mg/m <sup>3</sup> 8 hours.
Propylene glycol	EH40/2005 WELs (United Kingdom (UK), 1/2020).
	TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Particulate
	TWA: 474 mg/m <sup>3</sup> 8 hours. Form: total vapour and particulates
	TWA: 150 ppm 8 hours. Form: total vapour and particulates
2-aminoethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
	through skin.
	STEL: 7.6 mg/m <sup>3</sup> 15 minutes.
	STEL: 3 ppm 15 minutes.
	TWA: 1 ppm 8 hours.
1.2 dieblarebanzene	TWA: 2.5 mg/m <sup>3</sup> 8 hours.
1,2-dichlorobenzene	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
	through skin.
	STEL: 306 mg/m <sup>3</sup> 15 minutes.
	STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours.
	TWA: 25 ppm 6 hours. TWA: 153 mg/m <sup>3</sup> 8 hours.

#### **Biological exposure indices**

Product/ingredient name	Exposure indices		
Butoxyethanol	EH40/2005 BMGVs (United Kingdom (UK), 8/2018) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.		
Recommended monitoring : Reference should be made to appropriate monitoring standards. Reference to			

procedures indication of hazardous substances will also be required.

## **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2-(2-butoxyethoxy)ethanol	DNEL	Long term Oral	6.25 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term	67.5 mg/m <sup>3</sup>	Workers	Local
		Inhalation			
	DNEL	Short term	101.2 mg/	Workers	Local
		Inhalation	m³		
2-Butoxyethanol	DNEL	Long term Oral	6.3 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Short term Oral	26.7 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term	59 mg/m³	General	Systemic
		Inhalation		population	
	DNEL	Long term	98 mg/m³	Workers	Systemic
		Inhalation			
	DNEL	Short term	147 mg/m³	General	Local
		Inhalation		population	
	DNEL	Short term	246 mg/m <sup>3</sup>	Workers	Local
		Inhalation			
te of issue/Date of revision : 14/11/2023 Date of previous issue : 04/10/2022 Version : 1.01 5/16					
UAPRIMER 2900-02 - TST 100739	BLACK			La	bel No :38820

•		-			
	DNEL	Short term	426 mg/m <sup>3</sup>	General	Systemic
		Inhalation		population	
	DNEL	Short term	1091 mg/	Workers	Systemic
		Inhalation	m³		
Propylene glycol	DNEL	Long term	10 mg/m³	General	Local
		Inhalation		population	
	DNEL	Long term	10 mg/m <sup>3</sup>	Workers	Local
		Inhalation	U U		
	DNEL	Long term	50 mg/m <sup>3</sup>	General	Systemic
		Inhalation	<u>-</u>	population	- ,
	DNEL	Long term	168 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			- ) - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1
3-iodo-2-propynyl-butyl carbamate	DNEL	Long term	0.023 mg/	Workers	Systemic
	DIVEC	Inhalation	m <sup>3</sup>	WORKERS	Oysternie
	DNEL	Short term	0.07 mg/m <sup>3</sup>	Workers	Systemic
	DNLL	Inhalation	0.07 mg/m	VIOREIS	Systemic
			$1.16 m a/m^{3}$	Workoro	
	DNEL	Short term	1.16 mg/m <sup>3</sup>	workers	Local
		Inhalation	4 4 9 4 2		
	DNEL	Long term	1.16 mg/m <sup>3</sup>	Workers	Local
		Inhalation			
	DNEL	Long term Dermal	2 mg/kg	Workers	Systemic
			bw/day		
2-aminoethanol	DNEL	Long term	0.18 mg/m <sup>3</sup>	General	Systemic
		Inhalation		population	
	DNEL	Long term	0.28 mg/m <sup>3</sup>	General	Local
		Inhalation	-	population	
	DNEL	Long term	0.51 mg/m <sup>3</sup>	Workers	Local
		Inhalation	Ũ		
	DNEL	Long term	1 mg/m³	Workers	Systemic
		Inhalation	<u> </u>		,
	DNEL	Long term Oral	1.5 mg/kg	General	Systemic
			bw/day	population	- ) - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1
	DNEL	Long term Dermal	1.5 mg/kg	General	Systemic
	DITE	Long toni Donna	bw/day	population	eyetenne
	DNEL	Long term Dermal	3 mg/kg	Workers	Systemic
	DINCL	Long term Derma	bw/day	VVOIKEI3	Oysternic
,2-dichlorobenzene	DNEL	Long term Oral	0.6 mg/kg	General	Systemic
,z-dicilioroberizene	DNLL	Long term Oral	bw/day	population	Systemic
		Long torm Dormal		General	Sustamia
	DNEL	Long term Dermal	0.6 mg/kg		Systemic
			bw/day	population	Curata mia
	DNEL	Long term	1 mg/m³	General	Systemic
		Inhalation		population	
	DNEL	Long term Dermal	1.2 mg/kg	Workers	Systemic
			bw/day		
	DNEL	Short term Oral	3 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Short term Dermal	3 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term	4.2 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	Ĭ		-
	DNEL	Short term	5 mg/m³	General	Systemic
		Inhalation	3	population	,
	DNEL	Short term Dermal	6 mg/kg	Workers	Systemic
			bw/day		0,0001110
	DNEL	Short term	$21 \text{ mg/m}^3$	Workers	Systemic
			2 ·	11011013	Cysternie
		Inhalation			-

#### **PNECs**

No PNECs available

#### 8.2 Exposure controls

## Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

## **SECTION 8: Exposure controls/personal protection**

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations :Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

## 9.1 Information on basic physical and chemical properties

Date of issue/Date of revision	: 14/11/2023	B Date of previou	is issue : 04/10	/2022	Version	: 1.01	7/16
Flash point	: Closed	l cup: >100°C (>	•212°F)				
Upper/lower flammability or explosive limits		Not applicable. Not applicable.					
Flammability (solid, gas)	: Not ava	ailable.					
2-(2-butoxyethoxy)ethanol		225 to 227.6	437 to 441.7				
water		100	212				
Ingredient name		°C	°F	Method			
Initial boiling point and boiling range	:						
Melting point/freezing point	: Not ava	ailable.					
Odour threshold	: Not ava	ailable.					
Odour	: Slight						
Colour	: Black.						
Physical state	: Liquid.						
<u>Appearance</u>							

AQUAPRIMER 2900-02 - TST 100739 BLACK

## **SECTION 9: Physical and chemical properties**

2

Auto-ignition temperature :						
Ingredient name	Ingredient name		°F	Method		
2-(2-butoxyethoxy)ethanol		210	410	DIN 51794		
Decomposition temperature	: Not av	vailable.				
рН	: Not av	vailable.				
Viscosity	: Not av	vailable.				
Solubility(ies)	:					
Not available.						
Solubility in water	: Not av	vailable.				
Partition coefficient: n-octanol/ water	: Not a	oplicable.				

#### Vapour pressure

	Va	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
2-(2-butoxyethoxy)ethanol	0.022	0.0029					
Relative density	: Not	available.					
Density	: 1 g/	cm <sup>3</sup>					
Vapour density	: Not	: Not available.					
Explosive properties	: Not	: Not available.					
Oxidising properties	: Not	available.					
Particle characteristics							
Median particle size	: Not	applicable.					

## SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

11.1 Information on toxicological effects Acute toxicity

## **SECTION 11: Toxicological information**

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-butoxyethoxy)ethanol	(2-butoxyethoxy)ethanol LD50 Dermal		2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-
Propylene glycol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
3-iodo-2-propynyl-butyl carbamate	LC50 Inhalation Dusts and mists	Rat	0.67 g/m <sup>3</sup>	4 hours
	LC50 Inhalation Dusts and mists	Rat	0.763 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	400 mg/kg	-
2-aminoethanol	LD50 Oral	Rat	1720 mg/kg	-
1,2-dichlorobenzene	LC50 Inhalation Vapour	Rat	8150 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>10 g/kg	-
	LD50 Oral	Rat	500 mg/kg	-

## Conclusion/Summary Acute toxicity estimates

: Based on available data, the classification criteria are not met.

# RouteATE valueOral45454.55 mg/kg<br/>208.65 mg/l

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-(2-butoxyethoxy)ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	
	Eyes - Severe irritant	Rabbit	-	20 mg	-
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
Propylene glycol	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Human	-	168 hours	-
				500 mg	
	Skin - Mild irritant	Woman	-	96 hours 30	-
				%	
	Skin - Moderate irritant	Child	-	96 hours 30	-
				% C	
	Skin - Moderate irritant	Human	-	72 hours 104	-
		Ditt		mg I	
3-iodo-2-propynyl-butyl	Eyes - Severe irritant	Rabbit	-	-	-
carbamate	Europa Courses imiteent	Dahkit		050	
2-aminoethanol	Eyes - Severe irritant	Rabbit	-	250 ug	-
1.0 diablarahan	Skin - Moderate irritant	Rabbit	-	505 mg	-
1,2-dichlorobenzene	Eyes - Mild irritant	Rabbit	-	0.5 minutes	-
				100 mg	

## Conclusion/Summary

: Based on available data, the classification criteria are not met.

#### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
3-iodo-2-propynyl-butyl carbamate	skin	Guinea pig	Not sensitizing

## **Conclusion/Summary**

: Based on available data, the classification criteria are not met.

#### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
3-iodo-2-propynyl-butyl carbamate	-	Experiment: In vitro Subject: Bacteria	Negative

Date of issue/Date of revision: 14/11/2023AQUAPRIMER 2900-02 - TST 100739 BLACK

: 14/11/2023 Date of previous issue

## **SECTION 11: Toxicological information**

Conclusion/Summary

: Based on available data, the classification criteria are not met.

#### **Carcinogenicity**

: Based on available data, the classification criteria are not met.

## Conclusion/Summary Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
3-iodo-2-propynyl-butyl carbamate	Negative	-	Negative	Rabbit - Female	Oral: 20 mg/kg	13 days; 7 days per week
	Positive	-	Negative	Rabbit - Female	Oral: 50 mg/kg	13 days; 7 days per week

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

## **Teratogenicity**

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl-butyl carbamate	Negative - Oral	Rabbit - Female	50 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

## Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-aminoethanol	Category 3	-	Respiratory tract irritation
1,2-dichlorobenzene	Category 3	-	Respiratory tract irritation

## Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
3-iodo-2-propynyl-butyl carbamate	Category 1	-	larynx

## Aspiration hazard

Not available.

Information on likely routes of exposure	1	Not available.
Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	;	No known significant effects or critical hazards.

## Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	i no specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effect	<mark>cts as well as c</mark> h	nronic effects from sho	ort and long-term e	xposure
Short term exposure				
Potential immediate effects	: Not available	9.		
Potential delayed effects	: Not available	Э.		
Date of issue/Date of revision	: 14/11/2023	Date of previous issue	:04/10/2022	Version

AQUAPRIMER 2900-02 - TST 100739 BLACK

## **SECTION 11: Toxicological information**

<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

#### Other information

: Not available.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-(2-butoxyethoxy)ethanol	Acute LC50 1300000 µg/l Fresh water	Fish - Bluegill - <i>Lepomis</i>	96 hours
		macrochirus	
2-Butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - Water flea - <i>Daphnia</i>	48 hours
		magna	
	Acute LC50 800000 µg/l Marine water	Crustaceans - Common shrimp,	48 hours
	Aguta LOEO 1250000 ug/l Marina watar	sand shrimp - Crangon crangon	96 hours
	Acute LC50 1250000 µg/l Marine water	Fish - Inland silverside - Menidia beryllina	90 nours
Propylene glycol	Acute EC50 19300 mg/l Fresh water	Algae - Algae	96 hours
	Acute EC50 43500 mg/l Fresh water	Daphnia - Daphnia - Daphnia	48 hours
		magna	To nouro
	Acute LC50 18340000 µg/l Fresh water	-	48 hours
		Ceriodaphnia dubia	-
	Acute LC50 40613 mg/l Fresh water	Fish - Trout - Oncorhynchus	96 hours
		mykiss	
3-iodo-2-propynyl-butyl	Acute EC50 0.022 mg/l Fresh water	Algae - Algae - Scenedemus	72 hours
carbamate		subspicatus	
	Acute EC50 0.16 mg/l Fresh water	Daphnia - Daphnia - <i>Daphnia</i>	48 hours
		magna	0.01
	Acute LC50 0.067 mg/l Fresh water	Fish - Trout - Oncorhynchus	96 hours
	Aguta NOEC 0.040 mg/l Ereah water	<i>mykiss</i> Fish - Trout - <i>Oncorhynchus</i>	96 hours
	Acute NOEC 0.049 mg/l Fresh water	mykiss	90 110015
	Chronic NOEC 0.05 mg/l Fresh water	Daphnia - Daphnia - <i>Daphnia</i>	21 days
		Magna	21 00 35
2-aminoethanol	Acute EC50 8.42 mg/l Fresh water	Algae - Green algae -	72 hours
		Desmodesmus subspicatus	
	Acute LC50 >100000 µg/l Marine water	Crustaceans - Common shrimp,	48 hours
		sand shrimp - Crangon crangon	
		- Adult	
	Acute LC50 170 mg/l Fresh water	Fish - Goldfish - Carassius	96 hours
		auratus	
1,2-dichlorobenzene	Acute EC50 12.8 mg/l Fresh water	Algae - Diatom -	72 hours
		Phaeodactylum tricornutum	00 h a
	Acute EC50 2200 μg/l Fresh water	Algae - Green algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 0.74 mg/l Fresh water	Daphnia - Water flea - Daphnia	48 hours
	Acute ECOU 0.74 mg/r r resh water	magna	40 110015
	Acute LC50 4.52 ppm Marine water	Crustaceans - Opossum shrimp	48 hours
		- Americamysis bahia	
	Acute LC50 1.4 mg/l Fresh water	Fish - Catla - <i>Gibelion catla</i>	96 hours
	Chronic NOEC 630 µg/l Fresh water	Daphnia - Water flea - Daphnia	21 days
		· · · ·	
te of issue/Date of revision	: 14/11/2023 Date of previous issue	: 04/10/2022 Version	:1.01 <b>11/1</b>
QUAPRIMER 2900-02 - TST		Label No	-38820

AQUAPRIMER 2900-02 - TST 100739 BLACK

Label No :38820

## SECTION 12: Ecological information

**Conclusion/Summary** 

: Harmful to aquatic life with long lasting effects.

## 12.2 Persistence and degradability

Conclusion/Summary	: This product has not been	tested for biodegradation.	
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ropylene glycol 3-iodo-2-propynyl-butyl carbamate	-	-	Readily Not readily

## 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
<ul> <li>2-(2-butoxyethoxy)ethanol</li> <li>2-Butoxyethanol</li> <li>Propylene glycol</li> <li>3-iodo-2-propynyl-butyl</li> </ul>	1 0.81 -1.07 >1	- - - -	Low Low Low Low
carbamate 2-aminoethanol 1,2-dichlorobenzene	-1.31 3.38	- 150 to 230	Low Low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

## 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## **12.6 Other adverse effects** : No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

13.1 Waste treatment meth	ods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	: 080111*
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

#### **SECTION 14: Transport information ADR/RID ADN** IMDG ΙΑΤΑ 14.1 UN number Not regulated. Not regulated. Not regulated. Not regulated. 14.2 UN proper \_ \_ shipping name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 No. No. No. No. **Environmental** hazards

## **14.6 Special precautions for user**: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## 14.7 Transport in bulk : Not relevant/applicable due to nature of the product. according to IMO instruments

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>UK (GB)/REACH</u>

## Annex XIV - List of substances subject to authorisation

## Annex XIV

None of the components are listed.

## Substances of very high concern

None of the components are listed.

## **Ozone depleting substances**

Not listed.

## Prior Informed Consent (PIC)

Not listed.

#### Persistent Organic Pollutants Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

#### No listed substance

Seveso Directive

This product is not controlled under the Seveso Directive.

## EU regulations

Industrial emissions : Not listed (integrated pollution prevention and control) -Air

## **SECTION 15: Regulatory information**

Industrial emissions : I (integrated pollution prevention and control) - Water	Not listed
International regulations	
Chemical Weapon Convention L Not listed.	<u>ist Schedules I, II &amp; III Chemicals</u>
Montreal Protocol Not listed.	
Stockholm Convention on Persi Not listed.	stent Organic Pollutants
Rotterdam Convention on Prior Not listed.	Informed Consent (PIC)
UNECE Aarhus Protocol on POF Not listed.	Ps and Heavy Metals
15.2 Chomical actaty	This product contains substances for which Chamical Sofety A

15.2 Chemical safety	1	This product contains substances for which Chemical Safety Assessments are still
assessment		required.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.			
Abbreviations and acronyms	: ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative		

#### Procedure used to derive the classification

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

## Full text of abbreviated H statements

<b>H</b> 302	Harmful if swallowed.			
H312	Harmful in contact with skin.			
H314	Causes severe skin burns and eye damage.			
H315	Causes skin irritation.			
H317	May cause an allergic skin reaction.			
H318	Causes serious eye damage.			
H319	Causes serious eye irritation.			
H331	Toxic if inhaled.			
H332	Harmful if inhaled.			
H335	May cause respiratory irritation.			
H372	Causes damage to organs through prolonged or repeated exposure.			
H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting effects.			
H412	Harmful to aquatic life with long lasting effects.			
	Full fourt of allocations			

#### Full text of classifications

## **SECTION 16: Other information**

Acute Tox. 3	ACUTE TOXICITY - Category 3	
Acute Tox. 4	ACUTE TOXICITY - Category 4	
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1	
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1	
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2	
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
Skin Sens. 1	SKIN SENSITISATION - Category 1	
Skin Sens. 1B	SKIN SENSITISATION - Category 1B	
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1	
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3	
Date of issue/ Date of	: 14/11/2023	
revision		
Date of previous issue	• : 04/10/2022	
Version	: 1.01	
	AQUAPRIMER 2900-02 TST 100739 BLACK TST 100739 BLACK	

#### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.