SAFETY DATA SHEET



AQUATOP 2600-21 - TS 14293 WEISS 114

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

: AQUATOP 2600-21 - TS 14293 WEISS 114 **Product name**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: Prod-safe@teknos.com

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable. Response : Not applicable. **Storage** : Not applicable. **Disposal** : Not applicable.

Supplemental label

elements

: Contains adipohydrazide. 1.2-benzisothiazol-3(2H)-one. 2-methyl-2H-isothiazol-3-one, 2-Octyl-2H-isothiazol-3-one, reaction mass of: 5-chloro-2-methyl-

4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1) and 2-Methyl-1,2-benzisothiazol-3(2H)-one. May produce an

allergic reaction.

Safety data sheet available on request.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and

DTBMA and Bronopol and MIT and OIT and MBIT.

Date of issue/Date of revision : 02/11/2023 . 26/07/2022 Version : 1.05 1/19 Date of previous issue Label No : 63135

SECTION 2: Hazards identification

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
itanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
2-methyl-2H-isothiazol- 3-one	EC: 220-239-6 CAS: 2682-20-4	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1	[1]
2-Octyl-2H-isothiazol-3-one	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 125 mg/kg ATE [Dermal] = 311 mg/kg ATE [Inhalation (dusts and mists)] = 0.27 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7]	CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50	[1]

Date of issue/Date of revision : 02/11/2023 Date of previous issue : 26/07/2022 Version : 1.05 2/19

Label No : 63135

SECTION 3: Composition/information on ingredients

<u></u>			9		
and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)			Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: C ≥ 0.6% Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: 0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	
2-Methyl-1,2-benzisothiazol-3(2H)-one	CAS: 2527-66-4 Index: 613-336-00-3	<0.0015	Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 175 mg/kg ATE [Dermal] = 1100 mg/kg Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact : Immediately flush e

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention if symptoms occur.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Ingestion : Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms

Label No : 63135

occur.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Date of issue/Date of revision : 02/11/2023 Date of previous issue : 26/07/2022 Version : 1.05 3/19

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

: None known.

media

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Label No : 63135

Date of issue/Date of revision . 26/07/2022 Version : 1.05 4/19 : 02/11/2023 Date of previous issue

SECTION 6: Accidental release measures

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
E thyldiglycol	Regulation on Limit Values - MAC (Austria, 4/2021). PEAK: 140 mg/m³, 4 times per shift, 15 minutes. PEAK: 24 ppm, 4 times per shift, 15 minutes.
	TWA: 35 mg/m³ 8 hours. TWA: 6 ppm 8 hours.
2-methyl-2H-isothiazol-3-one	Regulation on Limit Values - MAC (Austria, 4/2021). [] Skin sensitiser. TWA: 0.05 mg/m³ 8 hours.
2-Octyl-2H-isothiazol-3-one	Regulation on Limit Values - MAC (Austria, 4/2021). Absorbed through skin. Sensitization potential. TWA: 0.05 mg/m³ 8 hours. Form: Inhalable fraction CEIL: 0.05 mg/m³ 15 minutes. Form: Inhalable fraction
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Regulation on Limit Values - MAC (Austria, 4/2021). [] Skin sensitiser.
,	TWA: 0.05 mg/m³ 8 hours.
No exposure limit value known.	
No exposure limit value known.	
Propylene glycol	Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). ELV: 10 mg/m³ 8 hours. Form: only particles ELV: 474 mg/m³ 8 hours. Form: total vapour and particles ELV: 150 ppm 8 hours. Form: total vapour and particles

Date of issue/Date of revision : 02/11/2023 Date of previous issue : 26/07/2022 Version : 1.05 5/19

Label No : 63135

SECTION 8: Exposure controls/personal protection

No exposure limit value known.

Ethyldiglycol

1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazol-3-one 2-Octyl-2H-isothiazol-3-one

No exposure limit value known.

No exposure limit value known.

No exposure limit value known.

Propylene glycol

No exposure limit value known.

Propylene glycol

Propylene glycol

No exposure limit value known.

No exposure limit value known.

No exposure limit value known.

Propylene glycol

Propylene glycol

No exposure limit value known.

No exposure limit value known.

No exposure limit value known.

TRGS 900 OEL (Germany, 7/2021).

TWA: 35 mg/m³ 8 hours. PEAK: 70 mg/m³ 15 minutes.

TWA: 6 ppm 8 hours. PEAK: 12 ppm 15 minutes.

DFG MAC-values list (Germany, 10/2021).

PEAK: 100 mg/m³, 4 times per shift, 15 minutes. Form: inhalable

fraction

TWA: 50 mg/m³ 8 hours. Form: inhalable fraction

DFG MAC-values list (Germany, 10/2021). Skin sensitiser. DFG MAC-values list (Germany, 10/2021). Skin sensitiser. TRGS 900 OEL (Germany, 7/2021). Absorbed through skin.

TWA: $0.05~\text{mg/m}^3~8~\text{hours}$. Form: Inhalable fraction PEAK: $0.1~\text{mg/m}^3~15~\text{minutes}$. Form: Inhalable fraction

DFG MAC-values list (Germany, 10/2021). Absorbed through skin. Skin sensitiser.

TWA: 0.05 mg/m³ 8 hours. Form: inhalable fraction

PEAK: 0.1 mg/m³, 4 times per shift, 15 minutes. Form: inhalable

fraction

NAOSH (Ireland, 5/2021). Notes: Advisory Occupational Exposure Limit Values (OELVs)

OELV-8hr: 10 mg/m³ 8 hours. Form: particulate

OELV-8hr: 470 mg/m³ 8 hours. Form: vapour and particulates OELV-8hr: 150 ppm 8 hours. Form: vapour and particulates

Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021).

TWA: 7 mg/m³ 8 hours.

Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2021).

TWA: 7 mg/m³ 8 hours.

FOR-2011-12-06-1358 (Norway, 6/2021).

TWA: 79 mg/m³ 8 hours. TWA: 25 ppm 8 hours.

Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021).

TWA: 100 mg/m³ 8 hours. Form: vapor and inhalable fraction

Date of issue/Date of revision : 02/11/2023 Date of previous issue : 26/07/2022 Version : 1.05 6/19

AQUATOP 2600-21 - TS 14293 WEISS 114

Label No : 63135

SECTION 8: Exposure controls/personal protection

Ethyldiglycol Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). KTV: 12 ppm, 4 times per shift, 15 minutes. TWA: 6 ppm 8 hours. KTV: 70 mg/m³, 4 times per shift, 15 minutes. TWA: 35 mg/m³ 8 hours. 2-Octyl-2H-isothiazol-3-one Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). Absorbed through skin. TWA: 0.05 mg/m³ 8 hours. Form: Inhalable fraction KTV: 0.1 mg/m³, 4 times per shift, 15 minutes. Form: Inhalable fraction No exposure limit value known. **Ethyldiglycol** Work environment authority Regulation 2018:1 (Sweden, 9/2021). Absorbed through skin. TWA: 15 ppm 8 hours. TWA: 80 mg/m³ 8 hours. STEL: 30 ppm 15 minutes. STEL: 170 mg/m³ 15 minutes. **Ethyldiglycol** SUVA (Switzerland, 1/2021). STEL: 100 mg/m³ 15 minutes. Form: Inhalable fraction of Vapor and aerosols TWA: 50 mg/m³ 8 hours. Form: Inhalable fraction of Vapor and 2-Octyl-2H-isothiazol-3-one SUVA (Switzerland, 1/2021). Absorbed through skin. Skin sensitiser. TWA: 0.05 mg/m³ 8 hours. Form: Inhalable fraction STEL: 0.1 mg/m³ 15 minutes. Form: Inhalable fraction SUVA (Switzerland, 1/2021). Skin sensitiser. reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) STEL: 0.4 mg/m³ 15 minutes. Form: Inhalable fraction TWA: 0.2 mg/m³ 8 hours. Form: Inhalable fraction

No exposure limit value known.

Biological exposure indices

Product/ingredient name	Exposure indice
No exposure indices known.	

Date of issue/Date of revision . 26/07/2022 Version : 1.05 7/19 : 02/11/2023 Date of previous issue Label No : 63135

SECTION 8: Exposure controls/personal protection No exposure indices known. No exposure indices known.

Recommended monitoring procedures

No exposure indices known.

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
a dipohydrazide	DNEL	Long term	17.5 mg/m ³	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Inhalation Long term Dermal	0.345 mg/	General	Systemic
1,2-5611213011114201-3(211)-0116	DINCL	Long term berman	kg bw/day	population	Oysternic
	DNEL	Long term Dermal	0.966 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	1.2 mg/m ³	General	Systemic
	DNEL	Inhalation Long term	6.81 mg/m ³	population Workers	Systemic
	DIVLL	Inhalation	0.01 mg/m	VVOIKCIS	Oysternic
2-methyl-2H-isothiazol-3-one	DNEL	Long term	0.021 mg/	General	Local
		Inhalation	m³	population	
	DNEL	Long term	0.021 mg/	Workers	Local
	DNEL	Inhalation Long term Oral	m³ 0.027 mg/	General	Systemic
	DINCL	Long term Oral	kg bw/day	population	Oysternic
	DNEL	Short term	0.043 mg/	General	Local
		Inhalation	m³	population	
	DNEL	Short term	0.043 mg/ m ³	Workers	Local
	DNEL	Inhalation Short term Oral	0.053 mg/	General	Systemic
	DIVLL	Onort tomi Oral	kg bw/day	population	Cycloniic
reaction mass of: 5-chloro-2-methyl-	DNEL	Long term	0.02 mg/m ³		Local
4-isothiazolin-3-one [EC no.		Inhalation		population	
247-500-7] and 2-methyl-2H-					
	DNEL	Long term	0.02 mg/m ³	Workers	Local
		Inhalation			
isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL		0.02 mg/m³	Workers	Local

 Date of issue/Date of revision
 : 02/11/2023
 Date of previous issue
 : 26/07/2022
 Version
 : 1.05
 8/19

 AQUATOP 2600-21 - TS 14293 WEISS 114
 Label No : 3135

SECTION 8: Exposure controls/personal protection DNEL Short term 0.04 mg/m³ General Local Inhalation population **DNEL** Short term 0.04 mg/m³ Workers Local Inhalation **DNEL** Long term Oral General Systemic 0.09 mg/ kg bw/day population **DNEL** Short term Oral 0.11 mg/ General Systemic kg bw/day population

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering

 Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommendations: Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm Not recommended polyvinyl alcohol (PVA) gloves

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to

ensure they comply with the requirements of environmental protection legislation.

In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Label No : 63135

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state: Liquid.Colour: White.Odour: Slight

Odour threshold : Not available.

Date of issue/Date of revision : 02/11/2023 Date of previous issue : 26/07/2022 Version : 1.05 9/19

SECTION 9: Physical and chemical properties

Melting point/freezing point

: Not available.

Initial boiling point and boiling range

Ingredient name	°C	°F	Method
water	100	212	
Propylene glycol	188.2	370.8	

Flammability : Not available.

Lower and upper explosion : Lower: Not applicable. Upper: Not applicable. limit

: Closed cup: >100°C (>212°F) Flash point

Auto-ignition temperature

Ingredient name	°C	°F	Method
E thyldiglycol	204	399.2	
Propylene glycol	371	699.8	

Decomposition temperature : Not available. pН : 8 to 8.5 **Viscosity** : Not available.

Solubility(ies)

Not available.

: Not available. Solubility in water Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

	Va	Vapour Pressure at 20°C			apour pres	ssure at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
Propylene glycol	0.15	0.02	EU A.4			

Relative density : Not available. **Density** : 1.2 g/cm³ : Not available. Vapour density **Explosive properties** : Not available. **Oxidising properties** : Not available.

Particle characteristics

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Label No : 63135

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

Date of issue/Date of revision : 02/11/2023 Date of previous issue . 26/07/2022 Version : 1.05 10/19

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
7,2-benzisothiazol-3(2H)-	LD50 Oral	Rat	1020 mg/kg	-
one				
2-methyl-2H-isothiazol-	LC50 Inhalation Dusts and	Rat	0.11 mg/l	4 hours
3-one	mists			
2-Octyl-2H-isothiazol-3-one	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-
reaction mass of: 5-chloro-	LD50 Oral	Rat	53 mg/kg	-
2-methyl-4-isothiazolin-				
3-one [EC no. 247-500-7]				
and 2-methyl-2H-isothiazol-				
3-one [EC no. 220-239-6] (3:				
1)				

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

Route	ATE value
halation (vapours)	376.99 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
tranium dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug I	-
1,2-benzisothiazol-3(2H)-one	Skin - Mild irritant	Human	-	48 hours 5 %	-
2-Octyl-2H-isothiazol-3-one	Eyes - Severe irritant	Rabbit	-	100 mg	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Severe irritant	Human	-	0.01 %	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Sensitisation

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Date of issue/Date of revision : 26/07/2022 Version : 1.05 11/19 : 02/11/2023 Date of previous issue Label No : 63135

SECTION 11: Toxicological information

Not available.

Information on likely routes

of exposure

: Not available.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Manium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - <i>Daphnia pulex</i> - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.36 mg/l Marine water Acute EC50 3.7 mg/l Acute LC50 1.9 mg/l Fresh water Acute NOEC 0.15 mg/l Marine water	Algae - Skeletonema Costatum Daphnia - Daphnia Magna Fish - Onorhynchus Mykiss Algae - Skeletonema Costatum	72 hours 48 hours 96 hours 72 hours

Date of issue/Date of revision : 02/11/2023 Date of previous issue : 26/07/2022 Version : 1.05 12/19

Label No :63135

SECTION 12: Ecological information

2-methyl-2H-isothiazol-3-one	Acute EC50 0.18 ppm Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 0.07 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
2-Octyl-2H-isothiazol-3-one	Acute EC50 107 ppb Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 47 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 74 ppb Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 8.5 ppb	Fish - Pimephales promelas	35 days
2-Methyl-1,2-benzisothiazol-	Acute EC50 0.22 ppm Fresh water	Algae - Pseudokirchneriella	96 hours
3(2H)-one		subcapitata	
	Acute EC50 0.92 ppm Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 0.24 ppm Fresh water	Fish - Oncorhynchus mykiss -	96 hours
		Juvenile (Fledgling, Hatchling,	
		Weanling)	
	Chronic NOEC 0.16 ppm	Fish - <i>Pimephales promelas</i>	32 days

Conclusion/Summary

: Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
,2-benzisothiazol-3(2H)-one	EU	24 % - 28 days	-	-

Conclusion/Summary : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
7,2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
7,2-benzisothiazol-3(2H)-one	-	3.2	Low
2-Octyl-2H-isothiazol-3-one	2.45	-	Low

12.4 Mobility in soil

Soil/water partition

coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

Date of issue/Date of revision : 02/11/2023 Date of previous issue : 26/07/2022 Version : 1.05 13/19 Label No : 63135

SECTION 13: Disposal considerations

European waste catalogue (EWC) : 080112

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered

when recycling is not feasible.

Special precautions

This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Labelling

Other EU regulations

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Air

Date of issue/Date of revision . 26/07/2022 Version : 1.05 14/19 : 02/11/2023 Date of previous issue

Label No : 63135

SECTION 15: Regulatory information

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Explosive precursors : Mot applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

<u>Austria</u>

VbF class : Not regulated.

Limitation of the use of : Permitted.

organic solvents

Czech Republic

Storage code : IV

Denmark

Danish fire class : V-1
Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
Manium dioxide	Listed	-

MAL-code : 00-1

Protection based on MAL

: According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 00-1

Application: When spraying in existing* spray booths, if the operator is outside the spray zone.

- Arm protectors must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

Label No : 63135

- Full mask with combined filter, coveralls and hood must be worn.

Date of issue/Date of revision: 02/11/2023Date of previous issue: 26/07/2022Version: 1.0515/19

SECTION 15: Regulatory information

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

Restrictions on use : Not to be used by professional users below 18 years of age. See the National

Working Environment Authorities Executive Order regarding Young People At Work.

List of undesirable substances

Not listed

Carcinogenic waste : Waste containers must be labeled: Contains a substance or substances regulated

by Danish working environment legislation on cancer risks.

<u>Finland</u>

<u>France</u>

Reinforced medical surveillance

: Act of July 11, 1977 determining the list of activities which require reinforced

medical surveillance: not applicable

Germany

Storage class (TRGS 510) : 10 Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water : 1

Technical instruction on air quality control

: TA-Luft Number 5.2.5: 5.4%

AOX : The product contains organically bound halogens and can contribute to the AOX

value in waste water.

Italy

D.Lgs. 152/06 : Not determined.

Netherlands

Water Discharge Policy

(ABM)

: A(3) Hazardous for aquatic organisms, may have long-term hazardous effects in

aquatic environment. Decontamination effort: A

Norway
Sweden
Switzerland

VOC content : Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Date of issue/Date of revision : 02/11/2023 Date of previous issue : 26/07/2022 Version : 1.05 16/19

AQUATOP 2600-21 - TS 14293 WEISS 114

Label No :63135

SECTION 15: Regulatory information

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent. Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A

Date of issue/ Date of

: 02/11/2023

revision

Date of previous issue : 26/07/2022

Version : 1.05

Notice to reader

Date of issue/Date of revision . 26/07/2022 Version : 1.05 17/19 : 02/11/2023 Date of previous issue Label No : 63135

SECTION 16: Other information

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 02/11/2023 Date of previous issue : 26/07/2022 Version : 1.05 18/19

Version : 1.05 19/19 Date of issue/Date of revision : 02/11/2023 Date of previous issue : 26/07/2022 **Label No : 6**3135