## SAFETY DATA SHEET



AQUATOP 2600-22 - All variants

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

: AQUATOP 2600-22 - All variants **Product name** 

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: Prod-safe@teknos.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : In an emergency, call 112

#### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

: No signal word. Signal word

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

**Prevention** : Not applicable. Response : Not applicable. : Not applicable. **Storage Disposal** : Not applicable.

Supplemental label

elements

: Contains adipohydrazide, 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 2-Octyl-2H-isothiazol-

3-one. May produce an allergic reaction.

Safety data sheet available on request. Contains biocidal products for in-can preservation: BIT and DTBMA and Bronopol and MIT and OIT and MBIT.

**Annex XVII - Restrictions** on the manufacture. placing on the market and use of certain dangerous substances, mixtures and articles

2.3 Other hazards

Date of issue/Date of revision : 27/10/2025 : 14/04/2025 Version :3 1/24 Date of previous issue Label No : 1/34779

### **SECTION 2: Hazards identification**

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

### **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Dipropyleneglycolmethylether	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤3	Not classified.	-	[2]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C ≥ 0.036% M [Acute] = 1 M [Chronic] = 1	[1]
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
2-methyl-2H-isothiazol- 3-one	EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1	[1]
2-Octyl-2H-isothiazol-3-one	EC: 247-761-7 CAS: 26530-20-1	<0.001	Acute Tox. 3, H301 Acute Tox. 3, H311	ATE [Oral] = 125 mg/kg	[1]

Date of issue/Date of revision

: 27/10/2025

Date of previous issue

: 14/04/2025

Version :3

2/24

QUATOP 2600-22 - All variants

**Label No** : 1/34779

SECTION 3	SECTION 3: Composition/information on ingredients							
	Index: 613-112-00-5	Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Dermal] = 311 mg/kg ATE [Inhalation (dusts and mists)] = 0.27 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100					
		See Section 16 for the full text of the H statements declared above.						

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention if symptoms occur.

**Skin contact**: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

**Ingestion**: Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms

occur.

**Protection of first-aiders**: No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Date of issue/Date of revision : 27/10/2025 Date of previous issue : 14/04/2025 Version : 3 3/24

AQUATOP 2600-22 - All variants Label No : 1/34779

### SECTION 5: Firefighting measures

**Hazards from the** substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion** products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

#### 6.4 Reference to other sections

See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

### **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Date of issue/Date of revision • 27/10/2025 : 14/04/2025 Version:3 4/24 Date of previous issue Label No : 1/34779

### **SECTION 7: Handling and storage**

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
propyleneglycolmethylether	Regulation on Limit Values - MAC (Austria, 12/2024) [Dipropylenglykolmonomethylether (Isomerengemisch)] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 307 mg/m³. CEIL 5 minutes: 100 ppm 8 times per shift. CEIL 5 minutes: 614 mg/m³ 8 times per shift.
reaction mass of: 5-chloro-2-methyl-	Regulation on Limit Values - MAC (Austria, 12/2024) [5-Chlor-
4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-di- hydroisothiazol-3-on (Gemisch im Verhältnis 3:1)] Skin sensitiser. TWA 8 hours: 0.05 mg/m³.
2-methyl-2H-isothiazol-3-one	Regulation on Limit Values - MAC (Austria, 12/2024) [5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on (Gemisch im Verhältnis 3:1)] Skin sensitiser.  TWA 8 hours: 0.05 mg/m³.
2-Octyl-2H-isothiazol-3-one	Regulation on Limit Values - MAC (Austria, 12/2024) Absorbed through skin, Sensitiser.  TWA 8 hours: 0.05 mg/m³. Form: Inhalable fraction.  CEIL: 0.05 mg/m³. Form: Inhalable fraction.
Dipropyleneglycolmethylether	Limit values (Belgium, 12/2023) [Dipropyleenglycolmonomethylether] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m³.
Dipropyleneglycolmethylether	Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) [2-(Methoxymethyletoxy)propanol] Absorbed through skin. Limit value 8 hours: 308 mg/m³. Limit value 8 hours: 50 ppm.
Dipropyleneglycolmethylether	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) [(2-metoksimetiletoksi)-propanol] Absorbed through skin.  ELV 8 hours: 308 mg/m³.  ELV 8 hours: 50 ppm.
Dipropyleneglycolmethylether	Department of labour inspection (Cyprus, 7/2021) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m³.

Date of issue/Date of revision: 27/10/2025Date of previous issue: 14/04/2025Version: 35/24AQUATOP 2600-22 - All variantsLabel No : \$\frac{1}{3}4779\$

Dipropyleneglycolmethylether

Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) [(2-methoxymethylethoxy)propanol]

Absorbed through skin.
TWA 8 hours: 270 mg/m³.
TWA 8 hours: 43.8 ppm.
STEL 15 minutes: 550 mg/m³.
STEL 15 minutes: 89.3 ppm.

**D**ipropyleneglycolmethylether

Working Environment Authority (Denmark, 12/2024) [dipropylenglycolmethylether] Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 309 mg/m³. STEL 15 minutes: 618 mg/m³. STEL 15 minutes: 100 ppm.

Dipropyleneglycolmethylether

Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) [dipropüleenglükooli monometüüleeter] Absorbed

through skin.

TWA 8 hours: 308 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm.

Dipropyleneglycolmethylether

EU OEL (Europe, 1/2022) [(2-Methoxymethylethoxy)-propanol]

Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m³.

Dipropyleneglycolmethylether

Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) [(2-Metoksimetyylietoksi)-propanoli]

Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 310 mg/m³.

Dipropyleneglycolmethylether

Ministry of Labor (France, 6/2024) [(2-méthoxyméthyléthoxy)-

propanol] Absorbed through skin.

TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

TWA 8 hours: 308 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

**D**ipropyleneglycolmethylether

TRGS 900 OEL (Germany, 6/2024) [(2-Methoxymethylethoxy) propanol]

TWA 8 hours: 310 mg/m<sup>3</sup>. PEAK 15 minutes: 310 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. PEAK 15 minutes: 50 ppm.

DFG MAC-values list (Germany, 7/2024) [Dipropylene glycol monomethyl ether] Develop D.

TWA 8 hours: 50 ppm.

PEAK 15 minutes: 50 ppm 4 times per shift [Interval: 1 hour].

TWA 8 hours: 310 mg/m<sup>3</sup>.

PEAK 15 minutes: 310 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].

**DFG MAC-values list (Germany, 7/2024)** Skin sensitiser. **DFG MAC-values list (Germany, 7/2024)** Skin sensitiser. **TRGS 900 OEL (Germany, 6/2024)** Absorbed through skin. TWA 8 hours: 0.05 mg/m³. Form: Inhalable fraction.

PEAK 15 minutes: 0.1 mg/m³. Form: Inhalable fraction. **DFG MAC-values list (Germany, 7/2024)** Develop C. Absorbed through skin, Skin sensitiser.

TWA 8 hours: 0.05 mg/m<sup>3</sup>. Form: inhalable fraction.

PEAK 15 minutes: 0.1 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].

Label No : 1/34779

Form: inhalable fraction.

1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazol-3-one 2-Octyl-2H-isothiazol-3-one

Date of issue/Date of revision : 27/10/2025 Date of previous issue : 14/04/2025 Version : 3 6/24

**Dipropyleneglycolmethylether** Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) [μεθοξυμεθυλ-αιθοξυ-προπανόλη, 2-]

Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 600 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. STEL 15 minutes: 900 mg/m<sup>3</sup>.

**D**ipropyleneglycolmethylether 5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) [

> (2-metoximetiletoxi)-propanol] TWA 8 hours: 308 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm.

**D**ipropyleneglycolmethylether Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024)

[Díprópýlenglýkólmetýleter] Absorbed through skin.

TWA 8 hours: 300 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm.

NAOSH (Ireland, 4/2024) [(2-methoxymethylethoxy)-1-propanol] Dipropyleneglycolmethylether

Absorbed through skin. Notes: EU derived Occupational Exposure

Limit Values

OELV 8 hours: 50 ppm. OELV 8 hours: 308 mg/m3.

**Dipropyleneglycolmethylether** Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024)

> Absorbed through skin. Limit value 8 hours: 50 ppm. Limit value 8 hours: 308 mg/m<sup>3</sup>.

Dipropyleneglycolmethylether Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)

[Metoksipropoksi propanols] Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m<sup>3</sup>.

Dipropyleneglycolmethylether Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)

> Absorbed through skin. TWA 8 hours: 308 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. STEL 15 minutes: 450 mg/m<sup>3</sup>. STEL 15 minutes: 75 ppm.

Grand-Duchy Regulation 2016. Chemical agents. Annex I Dipropyleneglycolmethylether

(Luxembourg, 3/2021) [(2-méthoxyméthyléthoxy)-propanol]

Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m<sup>3</sup>.

EU OEL (Europe, 1/2022) [(2-Methoxymethylethoxy)-propanol] Dipropyleneglycolmethylether

> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m<sup>3</sup>.

Ministry of Social Affairs and Employment, Legal limit values Dipropyleneglycolmethylether

(Netherlands, 5/2024) [dipropyleenglycolmethylether]

TWA 8 hours: 300 mg/m<sup>3</sup>. TWA 8 hours: 48.7 ppm.

**D**ipropyleneglycolmethylether FOR-2011-12-06-1358 (Norway, 5/2024) [

(2-metoksymetyletoksy)-propanol] Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 300 mg/m<sup>3</sup>.

**D**ipropyleneglycolmethylether Regulation of the Minister of Family, Labor and Social Policy

of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) [dipropylene glycol methyl ether] Absorbed through skin.

TWA 8 hours: 240 mg/m<sup>3</sup>. STEL 15 minutes: 480 mg/m<sup>3</sup>.

reaction mass of: 5-chloro-2-methyl-Regulation of the Minister of Family, Labor and Social Policy

: 14/04/2025 Date of issue/Date of revision : 27/10/2025 Version:3 7/24 Date of previous issue Label No : 1/34779

4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) Absorbed through skin.

TWA 8 hours: 0.2 mg/m<sup>3</sup>. STEL 15 minutes: 0.4 mg/m<sup>3</sup>.

**D**ipropyleneglycolmethylether

Portuguese Institute of Quality (Portugal, 11/2014) [2-metoximetiletoxipropanol] Absorbed through skin.

TWA 8 hours: 100 ppm. STEL 15 minutes: 150 ppm.

Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) [2-metoximetiletoxi propanol] Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m³.

Dipropyleneglycolmethylether

HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) Absorbed through skin.

VLA 8 hours: 308 mg/m<sup>3</sup>. VLA 8 hours: 50 ppm.

**D**ipropyleneglycolmethylether

Government regulation SR c. 355/2006 (Slovakia, 6/2024) [2-metoxymetyl-etoxypropanol] Absorbed through skin, Inhalation sensitiser.

TWA 8 hours: 308 mg/m³ (2-methoxymetyl-ethoxypropanol). TWA 8 hours: 50 ppm (2-methoxymetyl-ethoxypropanol).

Dipropyleneglycolmethylether

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) [ (2-metoksimetiletoksi)propanol] Absorbed through skin.

TWA 8 hours: 308 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm.

KTV 15 minutes: 50 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 308 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

2-Octyl-2H-isothiazol-3-one

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)
Absorbed through skin.

TWA 8 hours: 0.05 mg/m³. Form: Inhalable fraction.

KTV 15 minutes: 0.1 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. Form: Inhalable fraction.

Dipropyleneglycolmethylether

National institute of occupational safety and health (Spain, 1/2024) [éter metílico de dipropilenglicol] Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m<sup>3</sup>.

Dipropyleneglycolmethylether

Work environment authority Regulation 2018:1 (Sweden, 11/2022) [dipropylene glycol monomethyl ether] Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 300 mg/m³. STEL 15 minutes: 75 ppm. STEL 15 minutes: 450 mg/m³.

**D**ipropyleneglycolmethylether

# SUVA (Switzerland, 1/2025) [Dipropylenglykolmethylether (Isomerengemisch)]

STEL 15 minutes: 50 ppm. Form: vapour and aerosols. STEL 15 minutes: 300 mg/m³. Form: vapour and aerosols. TWA 8 hours: 50 ppm. Form: vapour and aerosols. TWA 8 hours: 300 mg/m³. Form: vapour and aerosols.

SUVA (Switzerland, 1/2025) Sensitiser.

STEL 15 minutes: 0.4 mg/m³. Form: Inhalable fraction. TWA 8 hours: 0.2 mg/m³. Form: Inhalable fraction.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Date of issue/Date of revision : 27/10/2025 Date of previous issue : 14/04/2025 Version : 3 8/24

**AQUATOP 2600-22 - All variants** 

**Label No** : 1/34779

SUVA (Switzerland, 1/2025) Absorbed through skin, Sensitiser. 2-Octyl-2H-isothiazol-3-one TWA 8 hours: 0.05 mg/m<sup>3</sup>. Form: Inhalable fraction. STEL 15 minutes: 0.1 mg/m³. Form: Inhalable fraction.

#### **Biological exposure indices**

No exposure limit value known.

Product/ingredient name	Exposure indices
No exposure indices known.	

#### **Recommended monitoring** procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be

: 27/10/2025 Date of previous issue : 14/04/2025 Date of issue/Date of revision Version :3 9/24 **Label No** : 1/34779

required.

#### **DNELs/DMELs**

adipohydrazide

1,2-benzisothiazol-3(2H)-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and

2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

#### **Product/ingredient name**

Dipropyleneglycolmethylether

#### Result

#### DNEL - General population - Long term - Oral

36 mg/kg bw/day Effects: Systemic

### DNEL - General population - Long term - Inhalation

37.2 mg/m³
<u>Effects</u>: Systemic

#### **DNEL - General population - Long term - Dermal**

121 mg/kg bw/day Effects: Systemic

#### **DNEL - Workers - Long term - Dermal**

283 mg/kg bw/day Effects: Systemic

### **DNEL - Workers - Long term - Inhalation**

308 mg/m³ Effects: Systemic

#### **DNEL - Workers - Long term - Inhalation**

17.5 mg/m³ Effects: Systemic

#### DNEL - General population - Long term - Dermal

0.345 mg/kg bw/day Effects: Systemic

#### **DNEL - Workers - Long term - Dermal**

0.966 mg/kg bw/day Effects: Systemic

#### DNEL - General population - Long term - Inhalation

1.2 mg/m³ Effects: Systemic

#### **DNEL - Workers - Long term - Inhalation**

6.81 mg/m³ Effects: Systemic

#### DNEL - General population - Long term - Inhalation

0.02 mg/m³ Effects: Local

### **DNEL - Workers - Long term - Inhalation**

0.02 mg/m³ Effects: Local

#### DNEL - General population - Short term - Inhalation

0.04 mg/m³ Effects: Local

#### **DNEL - Workers - Short term - Inhalation**

0.04 mg/m³ Effects: Local

Date of previous issue

#### DNEL - General population - Long term - Oral

0.09 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral

Date of issue/Date of revision : 27/10/2025

**AQUATOP 2600-22 - All variants** 

: 14/04/2025

Version :3

10/24

Label No : 1/34779

0.11 mg/kg bw/day Effects: Systemic

2-methyl-2H-isothiazol-3-one

DNEL - General population - Long term - Inhalation

0.021 mg/m³ Effects: Local

**DNEL - Workers - Long term - Inhalation** 

0.021 mg/m³ Effects: Local

DNEL - General population - Long term - Oral

0.027 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Inhalation

0.043 mg/m³ Effects: Local

**DNEL - Workers - Short term - Inhalation** 

0.043 mg/m³ Effects: Local

DNEL - General population - Short term - Oral

0.053 mg/kg bw/day Effects: Systemic

#### **PNECs**

Not available.

#### 8.2 Exposure controls

Appropriate engineering controls

 Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommendations: Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm Not recommended polyvinyl alcohol (PVA) gloves

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Label No : 1/34779

Date of issue/Date of revision : 27/10/2025 Date of previous issue : 14/04/2025 Version : 3 11/24

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

#### **Appearance**

Physical state: Liquid.Colour: Clear.Odour: Slight

Odour threshold : Not available.

Melting point/freezing point : Not available.

Initial boiling point and

boiling range

Ingredient name	°C	°F	Method
water	100	212	
Dipropyleneglycolmethylether	189.6	373.3	EU A.2

Flammability : Not available.

Lower and upper explosion

limit

Lower: Not applicable.
Upper: Not applicable.

Flash point : Closed cup: >100°C (>212°F)

Auto-ignition temperature

Ingredient name	°C	°F	Method
Dipropyleneglycolmethylether	207	404.6	EU A.15

**Decomposition temperature**: Not available.

**pH** : 7.8 to 8.5 [Conc. (% w/w): 100%]

Viscosity : Not available.

Solubility(ies)

Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

	Vapour Pressure at 20°C			Var	oour pressu	re at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water value of the state of the	17.5	2.3				

Relative density : Not available.

Density : 1 g/cm³

Vapour density : Not available.

**Particle characteristics** 

Median particle size : Not applicable.

Date of issue/Date of revision : 27/10/2025 Date of previous issue : 14/04/2025 Version : 3 12/24

QUATOP 2600-22 - All variants Label No: \$\frac{1}{2}\frac{1}\frac{1}{2}\frac{1}{2}\frac{1}{2}\frac{1}{2}\frac{1}{2}\frac{1}{2}\frac{1}{2}\frac{1}{2}\frac{1}{2}\frac{1}{2}\frac{1}{2}\frac{

### SECTION 9: Physical and chemical properties

#### 9.2 Other information

9.2.1 Information with regard to physical hazard classes

: Not available. **Explosive properties** : Not available. **Oxidising properties** 

9.2.2 Other safety characteristics

Not applicable.

### SECTION 10: Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. 10.1 Reactivity

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Product/ingredient name Result

1,2-benzisothiazol-3(2H)-one Rat - Oral - LD50 1020 mg/kg

Rat - Oral - LD50 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 53 mg/kg

2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

Toxic effects: Behavioral - Somnolence (general depressed

activity) Behavioral - Ataxia Lung, Thorax, or Respiration -

Respiratory depression

2-methyl-2H-isothiazol-3-one Rat - Inhalation - LC50 Dusts and mists

0.11 mg/l [4 hours]

2-Octyl-2H-isothiazol-3-one Rat - Oral - LD50

550 mg/kg

Rabbit - Dermal - LD50

690 mg/kg

Conclusion/Summary [Product] : Not available.

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)

Date of issue/Date of revision : 27/10/2025 : 14/04/2025 Version:3 13/24 Date of previous issue Label No : 1/34779

### **SECTION 11: Toxicological information**

<b>AQUATOP 2600-22</b>	N/A	N/A	N/A	1765.6	N/A
1,2-benzisothiazol-3(2H)-one		N/A			0.21
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-	53	50	N/A	0.5	N/A
3-one [EC no. 247-500-7] and 2-methyl-2H-					
isothiazol-3-one [EC no. 220-239-6] (3:1)					
2-methyl-2H-isothiazol-3-one	100	300	N/A	N/A	0.11
2-Octyl-2H-isothiazol-3-one	125	311	N/A	N/A	0.27
isothiazol-3-one [EC no. 220-239-6] (3:1) 2-methyl-2H-isothiazol-3-one					

#### Skin corrosion/irritation

Product/ingredient name

Dipropyleneglycolmethylether

1,2-benzisothiazol-3(2H)-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

Result

Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

Human - Skin - Mild irritant

Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %

Human - Skin - Severe irritant Amount/concentration applied: 0.01 %

**Conclusion/Summary [Product]**: Not available.

Serious eye damage/eye irritation

Product/ingredient name

Dipropyleneglycolmethylether

Result

**Human - Eyes - Mild irritant** 

Amount/concentration applied: 8 mg

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours Amount/concentration applied: 500 mg

2-Octyl-2H-isothiazol-3-one Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]**: Not available.

Respiratory or skin sensitization

Not available.

Skin

**Conclusion/Summary [Product]**: Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

Date of issue/Date of revision : 27/10/2025 : 14/04/2025 Version :3 14/24 Date of previous issue Label No : 1/34779

### **SECTION 11: Toxicological information**

#### Carcinogenicity

Not available.

**Conclusion/Summary [Product]**: Not available.

#### Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

#### Information on likely routes of exposure

Not available.

#### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards. Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data. Inhalation : No specific data. **Skin contact** : No specific data. Ingestion : No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### **Short term exposure**

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

**Potential immediate** : Not available.

effects

Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : No known significant effects or critical hazards. : No known significant effects or critical hazards. Carcinogenicity Mutagenicity : No known significant effects or critical hazards. Reproductive toxicity : No known significant effects or critical hazards.

#### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

Date of issue/Date of revision : 27/10/2025 : 14/04/2025 Version :3 Date of previous issue Label No : 1/34779

15/24

### **SECTION 11: Toxicological information**

**Conclusion/Summary [Product]** 

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

### SECTION 12: Ecological information

#### 12.1 Toxicity

#### Product/ingredient name

1,2-benzisothiazol-3(2H)-one

#### Result

#### Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test] Fish - Trout - Onorhynchus Mykiss 1.9 mg/l [96 hours]

#### Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - Daphnia Magna 3.7 mg/l [48 hours]

#### Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - Skeletonema Costatum 0.36 mg/l [72 hours]

#### Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - Skeletonema Costatum 0.15 mg/l [72 hours]

#### 2-methyl-2H-isothiazol-3-one

#### Acute - EC50 - Fresh water

US EPA

Daphnia - Water flea - Daphnia magna

Age: <24 hours 0.18 ppm [48 hours] Effect: Intoxication

#### Acute - LC50 - Fresh water

**US EPA** 

Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss

Weight: 0.73 g 0.07 ppm [96 hours] Effect: Mortality

#### 2-Octyl-2H-isothiazol-3-one

#### Acute - EC50 - Fresh water

US EPA

Daphnia - Water flea - Daphnia magna

Age: <24 hours 107 ppb [48 hours] Effect: Intoxication

#### Acute - LC50 - Fresh water

**US EPA** 

Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss

Weight: 0.7 g 47 ppb [96 hours] Effect: Mortality

#### Chronic - NOEC - Fresh water

**US EPA** 

Daphnia - Water flea - Daphnia magna

74 ppb [21 days] Effect: No Effect Coded

Date of issue/Date of revision : 27/10/2025 : 14/04/2025 Version:3 Date of previous issue

**AQUATOP 2600-22 - All variants** 

16/24

**Label No**: 1/34779

### **SECTION 12: Ecological information**

**Chronic - NOEC** 

**US EPA** 

Fish - Fathead minnow - Pimephales promelas

8.5 ppb [35 days] Effect: Growth

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name **Result** 1,2-benzisothiazol-3(2H)-one EU

24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
<b>p</b> ipropyleneglycolmethylether	0.004	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low
2-Octyl-2H-isothiazol-3-one	2.45	-	Low

#### 12.4 Mobility in soil

#### Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
adipohydrazide	1.7	55.2165
1,2-benzisothiazol-3(2H)-one	1.9	73.142
2-methyl-2H-isothiazol-3-one	1.7	54.9187
2-Octyl-2H-isothiazol-3-one	2.8	706.605

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	M	Т	vPvM	νP	vM	
Dipropyleneglycolmethylether	No	No	No	No	No	No	No	
adipohydrazide	No	No	No	No	No	No	No	
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No	
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No	
2-methyl-2H-isothiazol-3-one		No	No	No	No	No	No	
2-Octyl-2H-isothiazol-3-one	No	No	No	No	No	No	No	

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

: 14/04/2025 Date of issue/Date of revision : 27/10/2025 Date of previous issue Version :3 17/24 Label No : 1/34779

### **SECTION 12: Ecological information**

Product/ingredient name	PBT	P	В	T	vPvB	vP	vB
<b>D</b> ipropyleneglycolmethylether	No	N/A	N/A	No	N/A	N/A	N/A
adipohydrazide	No	N/A	N/A	No	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	No	N/A	No	No	No	N/A	No
reaction mass of: 5-chloro-	No	N/A	N/A	No	N/A	N/A	N/A
2-methyl-4-isothiazolin-							
3-one [EC no. 247-500-7]							
and 2-methyl-2H-isothiazol-							
3-one [EC no. 220-239-6] (3:							
1)							
2-methyl-2H-isothiazol-3-one	No	N/A	N/A	No	N/A	N/A	N/A
2-Octyl-2H-isothiazol-3-one	N/A	N/A	N/A	Yes	N/A	N/A	N/A

#### **Regulation (EC) No. 1272/2008 [CLP]**

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB	
Dipropyleneglycolmethylether	No	No	No	No	No	No	No	
adipohydrazide	No	No	No	No	No	No	No	
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No	
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No	
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No	
2-Octyl-2H-isothiazol-3-one	No	No	No	No	No	No	No	

**Conclusion/Summary Regulation (EC) No. 1272/2008** [CLP]

: The product does not meet the criteria to be considered as a PBT or vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** 

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

: Avoid release to the environment. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous waste** 

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

**European waste** catalogue (EWC) : 080112

**Packaging** 

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 27/10/2025 Date of previous issue : 14/04/2025 Version :3 18/24 Label No : 1/34779

### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Maritime transport in

bulk according to IMO

instruments

: Not relevant/applicable due to nature of the product.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

**Substances of very high concern** 

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Labelling

**Synthetic polymer microparticles - Designation 78** 

Generic identity of

: 3901 - Polymers of ethylene., 3909 - Amino-resins, phenolic resins and

polyurethanes. polymer(s)

Total percentage of synthetic polymer microparticles

**2**.2%

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

Other EU regulations

**Industrial emissions** : Not listed

(integrated pollution prevention and control) -

: Not listed **Industrial emissions** 

(integrated pollution prevention and control) -

Water

**Explosive precursors** : Not applicable.

Date of issue/Date of revision : 27/10/2025 : 14/04/2025 Version :3 19/24 Date of previous issue AQUATOP 2600-22 - All variants Label No : 1/34779

### **SECTION 15: Regulatory information**

#### Ozone depleting substances (EU 2024/590)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### **Persistent Organic Pollutants**

Not listed.

#### **Seveso Directive**

This product is not controlled under the Seveso Directive.

#### **National regulations**

**Austria** 

Limitation of the use of

organic solvents

: Permitted.

**Belgium** 

**Czech Republic** 

: IV Storage code

**Denmark** 

: IV-1 Fire class **MAL-code** : 1-1

**Protection based on MAL** 

: According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, respiratory protection with air supply and arm protectors/apron/coveralls/protective clothing must be worn as appropriate or as instructed.

MAL-code: 1-1

**Application:** During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Air-supplied half mask must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Air-supplied half-mask and arm protectors must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spraycabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied half mask and eye protection must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied half mask, eye protection, coveralls and hood must be worn.

Version : 3 Date of issue/Date of revision : 27/10/2025 · 14/04/2025 20/24 Date of previous issue Label No : 1/34779

### **SECTION 15: Regulatory information**

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

Low-boiling liquids : This product contains low-boiling point liquids. Any respiratory protective equipment

should be air-fed.

Restrictions on use : Not to be used by professional users below 18 years of age. See the National

Working Environment Authorities Executive Order regarding Young People At Work.

List of undesirable substances

: Not listed

Finland France

Social Security Code,

Articles L 461-1 to L 461-7

: Dipropyleneglycolmethylether

RG 84

Reinforced medical

surveillance

: Act of July 11, 1977 determining the list of activities which require reinforced

medical surveillance: not applicable

**Germany** 

Storage class (TRGS 510) : 10 Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water : 1

Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
5.2.1	Total dust	35
5.2.4 [III]	Gaseous inorganic substances	0.09
5.2.5	Organic substances	3.8
5.2.5 [I]	Organic substances	2.8

AOX : The product contains organically bound halogens and can contribute to the AOX

value in waste water.

**Italy** 

D.Lgs. 152/06 : Not determined.

**Netherlands** 

**Water Discharge Policy** 

(ABM)

: A(4) Low hazard for aquatic organisms, may have long-term hazardous effects in

aquatic environment. Decontamination effort: A

Norway
Sweden
Switzerland

VOC content : Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Date of issue/Date of revision : 27/10/2025 Date of previous issue : 14/04/2025 Version : 3 21/24 AQUATOP 2600-22 - All variants Label No : 1/34779

### **SECTION 15: Regulatory information**

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

#### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

#### Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

#### Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A

Date of issue/ Date of

revision

: 27/10/2025

Date of previous issue : 14/04/2025

Version : 3

Date of issue/Date of revision : 27/10/2025 Date of previous issue : 14/04/2025 Version : 3 22/24

AQUATOP 2600-22 - All variants Label No: \$\frac{1}{12}\$34779

### **SECTION 16: Other information**

AQUATOP 2600-2

All variant

#### **Notice to reader**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 27/10/2025 Date of previous issue : 14/04/2025 Version : 3 23/24

Label No : 1/34779

Version :3 Date of issue/Date of revision : 27/10/2025 Date of previous issue : 14/04/2025 24/24 **Label No** : 1/34779