

# SAFETY DATA SHEET



AQUATOP 2600-22 - NCS S 4550-Y80R

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : AQUATOP 2600-22 - NCS S 4550-Y80R

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

#### National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : In an emergency, call 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Signal word** : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

#### Precautionary statements

**Prevention** : Not applicable.

**Response** : Not applicable.

**Storage** : Not applicable.

**Disposal** : Not applicable.

**Supplemental label elements** :  Contains adipohydrazide, 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one, 2-Octyl-2H-isothiazol-3-one and 2-Methyl-1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request. Contains biocidal products for in-can preservation: BIT and DTBMA and Bronopol and MIT and OIT and MBIT.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

**Date of issue/Date of revision** : 24/11/2023 **Date of previous issue** : 21/07/2022

**Version** : 1.03 1/20

AQUATOP 2600-22 - NCS S 4550-Y80R

**Label No** : 74353

## SECTION 2: Hazards identification

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Dipropyleneglycolmethylether	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤3	Not classified.	-	[2]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: C ≥ 0.6% Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: 0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	[1]
2-methyl-2H-isothiazol-3-one	EC: 220-239-6 CAS: 2682-20-4	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1	[1]
2-Octyl-2H-isothiazol-3-one	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318	ATE [Oral] = 125 mg/kg ATE [Dermal] = 311 mg/kg ATE [Inhalation	[1]

## SECTION 3: Composition/information on ingredients

2-Methyl-1,2-benzisothiazol-3(2H)-one	CAS: 2527-66-4 Index: 613-336-00-3	<0.0015	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071  Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH071 <b>See Section 16 for the full text of the H statements declared above.</b>	(dusts and mists)] = 0.27 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100  ATE [Oral] = 175 mg/kg ATE [Dermal] = 1100 mg/kg Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 1	[1]
---------------------------------------	---------------------------------------	---------	--	--	-----

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)


- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
Dipropyleneglycolmethylether	<b>Regulation on Limit Values - MAC (Austria, 4/2021). [] Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 307 mg/m <sup>3</sup> 8 hours. CEIL: 100 ppm, 8 times per shift, 5 minutes. CEIL: 614 mg/m <sup>3</sup> , 8 times per shift, 5 minutes.
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	<b>Regulation on Limit Values - MAC (Austria, 4/2021). [] Skin sensitiser.</b>  TWA: 0.05 mg/m <sup>3</sup> 8 hours.
2-methyl-2H-isothiazol-3-one	<b>Regulation on Limit Values - MAC (Austria, 4/2021). [] Skin sensitiser.</b> TWA: 0.05 mg/m <sup>3</sup> 8 hours.
2-Octyl-2H-isothiazol-3-one	<b>Regulation on Limit Values - MAC (Austria, 4/2021). Absorbed through skin. Sensitization potential.</b> TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction CEIL: 0.05 mg/m <sup>3</sup> 15 minutes. Form: Inhalable fraction
 Dipropyleneglycolmethylether	<b>Limit values (Belgium, 5/2021). [] Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 308 mg/m <sup>3</sup> 8 hours.
Dipropyleneglycolmethylether	<b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021). [2-(Methoxymethyletoxy)propanol] Absorbed through skin.</b> Limit value 8 hours: 308 mg/m <sup>3</sup> 8 hours. Limit value 8 hours: 50 ppm 8 hours.






## SECTION 8: Exposure controls/personal protection

Dipropyleneglycolmethylether	<b>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021).</b> [] Absorbed through skin. ELV: 308 mg/m <sup>3</sup> 8 hours. ELV: 50 ppm 8 hours.
Dipropyleneglycolmethylether	<b>EU OEL (Europe, 10/2019).</b> [(2-Methoxymethylethoxy)-propanol] Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. TWA: 308 mg/m <sup>3</sup> 8 hours.
Dipropyleneglycolmethylether	<b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 5/2021).</b> [] Absorbed through skin. TWA: 270 mg/m <sup>3</sup> 8 hours. TWA: 43.74 ppm 8 hours. STEL: 550 mg/m <sup>3</sup> 15 minutes. STEL: 89.1 ppm 15 minutes.
Dipropyleneglycolmethylether	<b>Working Environment Authority (Denmark, 6/2022).</b> [Dipropylenglycolmethylether] Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 309 mg/m <sup>3</sup> 8 hours. STEL: 618 mg/m <sup>3</sup> 15 minutes. STEL: 100 ppm 15 minutes.
Dipropyleneglycolmethylether	<b>Occupational exposure limits, Regulation No. 293 (Estonia, 10/2019).</b> [] Absorbed through skin. TWA: 308 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.
Dipropyleneglycolmethylether	<b>EU OEL (Europe, 1/2022).</b> [(2-Methoxymethylethoxy)-propanol] Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. TWA: 308 mg/m <sup>3</sup> 8 hours.
Dipropyleneglycolmethylether	<b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020).</b> [] Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 310 mg/m <sup>3</sup> 8 hours.
Dipropyleneglycolmethylether	<b>Ministry of Labor (France, 5/2021).</b> [] Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA: 50 ppm 8 hours. TWA: 308 mg/m <sup>3</sup> 8 hours.
Dipropyleneglycolmethylether	<b>TRGS 900 OEL (Germany, 7/2021).</b> [] TWA: 310 mg/m <sup>3</sup> 8 hours. PEAK: 310 mg/m <sup>3</sup> 15 minutes. TWA: 50 ppm 8 hours. PEAK: 50 ppm 15 minutes.
1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazol-3-one 2-Octyl-2H-isothiazol-3-one	<b>DFG MAC-values list (Germany, 10/2021).</b> [Dipropylene glycol monomethyl ether] TWA: 50 ppm 8 hours. PEAK: 50 ppm, 4 times per shift, 15 minutes. TWA: 310 mg/m <sup>3</sup> 8 hours. PEAK: 310 mg/m <sup>3</sup> , 4 times per shift, 15 minutes. <b>DFG MAC-values list (Germany, 10/2021).</b> Skin sensitiser. <b>DFG MAC-values list (Germany, 10/2021).</b> Skin sensitiser. <b>TRGS 900 OEL (Germany, 7/2021).</b> Absorbed through skin. TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction PEAK: 0.1 mg/m <sup>3</sup> 15 minutes. Form: Inhalable fraction <b>DFG MAC-values list (Germany, 10/2021).</b> Absorbed through skin. Skin sensitiser. TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form: inhalable fraction PEAK: 0.1 mg/m <sup>3</sup> , 4 times per shift, 15 minutes. Form: inhalable fraction

## SECTION 8: Exposure controls/personal protection

Dipropyleneglycolmethylether	<b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021).</b> <input type="checkbox"/> Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 600 mg/m <sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 900 mg/m <sup>3</sup> 15 minutes.
<input checked="" type="checkbox"/> Dipropyleneglycolmethylether	<b>5/2020. (II. 6.) ITM Decree (Hungary, 2/2020).</b> <input type="checkbox"/> TWA: 308 mg/m <sup>3</sup> 8 hours.
<input checked="" type="checkbox"/> Dipropyleneglycolmethylether	<b>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021).</b> <input type="checkbox"/> <b>Absorbed through skin.</b> TWA: 300 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.
<input checked="" type="checkbox"/> Dipropyleneglycolmethylether	<b>NAOSH (Ireland, 5/2021).</b> [(2-methoxymethylethoxy)-1-propanol] Absorbed through skin. Notes: EU derived <b>Occupational Exposure Limit Values</b> OELV-8hr: 50 ppm 8 hours. OELV-8hr: 308 mg/m <sup>3</sup> 8 hours.
Dipropyleneglycolmethylether	<b>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020).</b> <b>Absorbed through skin.</b> 8 hours: 50 ppm 8 hours. 8 hours: 308 mg/m <sup>3</sup> 8 hours.
<input checked="" type="checkbox"/> Dipropyleneglycolmethylether	<b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021).</b> <input type="checkbox"/> <b>Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 308 mg/m <sup>3</sup> 8 hours.
<input checked="" type="checkbox"/> Dipropyleneglycolmethylether	<b>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2021).</b> <b>Absorbed through skin.</b> TWA: 308 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. STEL: 450 mg/m <sup>3</sup> 15 minutes. STEL: 75 ppm 15 minutes.
Dipropyleneglycolmethylether	<b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021).</b> <input type="checkbox"/> Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 308 mg/m <sup>3</sup> 8 hours.
Dipropyleneglycolmethylether	<b>EU OEL (Europe, 10/2019).</b> [(2-Methoxymethylethoxy)-propanol] Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. TWA: 308 mg/m <sup>3</sup> 8 hours.
<input checked="" type="checkbox"/> Dipropyleneglycolmethylether	<b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 7/2021).</b> <input type="checkbox"/> OEL, 8-h TWA: 300 mg/m <sup>3</sup> 8 hours.
<input checked="" type="checkbox"/> Dipropyleneglycolmethylether	<b>FOR-2011-12-06-1358 (Norway, 6/2021).</b> <input type="checkbox"/> Absorbed through skin. Notes: indicative limit value TWA: 50 ppm 8 hours. TWA: 300 mg/m <sup>3</sup> 8 hours.
Dipropyleneglycolmethylether	<b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021).</b> [dipropylene glycol methyl ether] Absorbed through skin. TWA: 240 mg/m <sup>3</sup> 8 hours. STEL: 480 mg/m <sup>3</sup> 15 minutes.
<input checked="" type="checkbox"/> Dipropyleneglycolmethylether	<b>Portuguese Institute of Quality (Portugal, 11/2014).</b> <input type="checkbox"/> <b>Absorbed through skin.</b> TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes.

## SECTION 8: Exposure controls/personal protection

<p> Dipropylenglycolmethylether</p>	<p><b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). Absorbed through skin.</b> VLA: 308 mg/m<sup>3</sup> 8 hours. VLA: 50 ppm 8 hours.</p>
<p> Dipropylenglycolmethylether</p>	<p><b>Government regulation SR c. 355/2006 (Slovakia, 9/2020). [] Absorbed through skin.</b> TWA: 308 mg/m<sup>3</sup>, (2-methoxymetyl-ethoxypropanol) 8 hours. TWA: 50 ppm, (2-methoxymetyl-ethoxypropanol) 8 hours.</p>
<p>Dipropylenglycolmethylether</p>	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). [] Absorbed through skin.</b> TWA: 308 mg/m<sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. KTV: 50 ppm, 4 times per shift, 15 minutes. KTV: 308 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.</p>
<p>2-Octyl-2H-isothiazol-3-one</p>	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). Absorbed through skin.</b> TWA: 0.05 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction KTV: 0.1 mg/m<sup>3</sup>, 4 times per shift, 15 minutes. Form: Inhalable fraction</p>
<p>Dipropylenglycolmethylether</p>	<p><b>National institute of occupational safety and health (Spain, 4/2021). [] Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 308 mg/m<sup>3</sup> 8 hours.</p>
<p> Dipropylenglycolmethylether</p>	<p><b>Work environment authority Regulation 2018:1 (Sweden, 9/2021). [dipropylene glycol monomethyl ether] Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 300 mg/m<sup>3</sup> 8 hours. STEL: 75 ppm 15 minutes. STEL: 450 mg/m<sup>3</sup> 15 minutes.</p>
<p> Dipropylenglycolmethylether</p> <p>reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)</p>	<p><b>SUVA (Switzerland, 1/2021). []</b> STEL: 50 ppm 15 minutes. Form: vapour and aerosols STEL: 300 mg/m<sup>3</sup> 15 minutes. Form: vapour and aerosols TWA: 50 ppm 8 hours. Form: vapour and aerosols TWA: 300 mg/m<sup>3</sup> 8 hours. Form: vapour and aerosols <b>SUVA (Switzerland, 1/2021). Skin sensitiser.</b>  STEL: 0.4 mg/m<sup>3</sup> 15 minutes. Form: Inhalable fraction TWA: 0.2 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction</p>
<p>2-Octyl-2H-isothiazol-3-one</p>	<p><b>SUVA (Switzerland, 1/2021). Absorbed through skin. Skin sensitiser.</b> TWA: 0.05 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction STEL: 0.1 mg/m<sup>3</sup> 15 minutes. Form: Inhalable fraction</p>
<p> Dipropylenglycolmethylether</p>	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b> TWA: 308 mg/m<sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.</p>

### Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	



## SECTION 8: Exposure controls/personal protection

No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.  
 No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Dipropyleneglycolmethylether	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	37.2 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	121 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	283 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	308 mg/m <sup>3</sup>	Workers	Systemic
adipohydrazide	DNEL	Long term Inhalation	17.5 mg/m <sup>3</sup>	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/	General	Systemic

## SECTION 8: Exposure controls/personal protection

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL	Long term Dermal	kg bw/day 0.966 mg/ kg bw/day	population Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	0.02 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	0.02 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	0.04 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	0.04 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/ kg bw/day	General population	Systemic
	2-methyl-2H-isothiazol-3-one	DNEL	Long term Inhalation	0.021 mg/ m <sup>3</sup>	General population
DNEL		Long term Inhalation	0.021 mg/ m <sup>3</sup>	Workers	Local
DNEL		Long term Oral	0.027 mg/ kg bw/day	General population	Systemic
DNEL		Short term Inhalation	0.043 mg/ m <sup>3</sup>	General population	Local
DNEL		Short term Inhalation	0.043 mg/ m <sup>3</sup>	Workers	Local
DNEL		Short term Oral	0.053 mg/ kg bw/day	General population	Systemic

### PNECs

No PNECs available

### 8.2 Exposure controls

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommendations : Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Not recommended polyvinyl alcohol (PVA) gloves

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## SECTION 8: Exposure controls/personal protection

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.  
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Brownish-red.
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
Water	100	212	
Dipropyleneglycolmethylether	189.6	373.3	EU A.2

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: Not applicable.  
Upper: Not applicable.
- Flash point** : Closed cup: >100°C (>212°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Dipropyleneglycolmethylether	207	404.6	EU A.15

- Decomposition temperature** : Not available.
- pH** : 8 to 8.5
- Viscosity** : Not available.
- Solubility(ies)** :  
Not available.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	17.5	2.3				

- Relative density** : Not available.
- Density** : 1.1 g/cm<sup>3</sup>
- Vapour density** : Not available.

## SECTION 9: Physical and chemical properties

<b>Explosive properties</b>	: Not available.
<b>Oxidising properties</b>	: Not available.
<b>Particle characteristics</b>	
<b>Median particle size</b>	: Not applicable.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: The product is stable.
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: No specific data.
<b>10.5 Incompatible materials</b>	: No specific data.
<b>10.6 Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) 2-methyl-2H-isothiazol-3-one 2-Octyl-2H-isothiazol-3-one	LD50 Oral	Rat	1020 mg/kg	-
	LD50 Oral	Rat	53 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	0.11 mg/l	4 hours
	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Acute toxicity estimates

Route	ATE value
Inhalation (vapours)	1733 mg/l

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Dipropyleneglycolmethylether  1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) 2-Octyl-2H-isothiazol-3-one	Eyes - Mild irritant	Human	-	8 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Human	-	48 hours 5 %	-
	Skin - Severe irritant	Human	-	0.01 %	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-

## SECTION 11: Toxicological information

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Sensitisation

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Mutagenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Carcinogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Reproductive toxicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Teratogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.

**Inhalation** : No specific data.

**Skin contact** : No specific data.

**Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

## SECTION 11: Toxicological information

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2,2-benzisothiazol-3(2H)-one	Acute EC50 0.36 mg/l Marine water	Algae - <i>Skeletonema Costatum</i>	72 hours
	Acute EC50 3.7 mg/l	Daphnia - <i>Daphnia Magna</i>	48 hours
2-methyl-2H-isothiazol-3-one	Acute LC50 1.9 mg/l Fresh water	Fish - <i>Onorhynchus Mykiss</i>	96 hours
	Acute NOEC 0.15 mg/l Marine water	Algae - <i>Skeletonema Costatum</i>	72 hours
2-Octyl-2H-isothiazol-3-one	Acute EC50 0.18 ppm Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 0.07 ppm Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
	Acute EC50 107 ppb Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 47 ppb Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
2-Methyl-1,2-benzisothiazol-3(2H)-one	Chronic NOEC 74 ppb Fresh water	Daphnia - <i>Daphnia magna</i>	21 days
	Chronic NOEC 8.5 ppb	Fish - <i>Pimephales promelas</i>	35 days
	Acute EC50 0.22 ppm Fresh water	Algae - <i>Pseudokirchneriella subcapitata</i>	96 hours
	Acute EC50 0.92 ppm Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 0.24 ppm Fresh water	Fish - <i>Oncorhynchus mykiss</i> - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 0.16 ppm	Fish - <i>Pimephales promelas</i>	32 days

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2,2-benzisothiazol-3(2H)-one	EU	24 % - 28 days	-	-

**Conclusion/Summary** : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,2-benzisothiazol-3(2H)-one	-	-	Inherent

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Dipropylenglycolmethylether	0.004	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low
2-Octyl-2H-isothiazol-3-one	2.45	-	Low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

## SECTION 12: Ecological information

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

**European waste catalogue (EWC)** : 080112

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

#### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Labelling : 

#### Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors :  Not applicable.

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### Persistent Organic Pollutants

Not listed.

#### Seveso Directive

This product is not controlled under the Seveso Directive.

#### National regulations

##### Austria

VbF class : Not regulated.

Limitation of the use of organic solvents : Permitted.

##### Czech Republic


Storage code : IV

##### Denmark

Product registration number : 4367433

Danish fire class : IV-1

#### Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
 titanium dioxide	Listed	-

MAL-code : 00-1

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.



## SECTION 15: Regulatory information

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 00-1

**Application:** When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Arm protectors must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Full mask with combined filter, coveralls and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

- Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
- List of undesirable substances** : Not listed
- Carcinogenic waste** : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

### Finland

### France

**Social Security Code, Articles L 461-1 to L 461-7** : Dipropyleneglycolmethylether RG 84

**Reinforced medical surveillance** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

### Germany

**Storage class (TRGS 510)** : 10

### Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

**Hazard class for water** : 1

**Technical instruction on air quality control** : TA-Luft Number 5.2.5: 3.5%

**AOX** : The product contains organically bound halogens and can contribute to the AOX value in waste water.

### Italy

**D.Lgs. 152/06** : Not determined.

### Netherlands

**Water Discharge Policy (ABM)** : A(4) Low hazard for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A

### Norway

## SECTION 15: Regulatory information

### [Sweden](#)

### [Switzerland](#)

**VOC content** : Exempt.

### [International regulations](#)

#### [Chemical Weapon Convention List Schedules I, II & III Chemicals](#)

Not listed.

#### [Montreal Protocol](#)

Not listed.

#### [Stockholm Convention on Persistent Organic Pollutants](#)

Not listed.

#### [Rotterdam Convention on Prior Informed Consent \(PIC\)](#)

Not listed.

#### [UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### **Abbreviations and acronyms**

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

#### [Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Not classified.

#### [Full text of abbreviated H statements](#)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

#### [Full text of classifications \[CLP/GHS\]](#)

## SECTION 16: Other information

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A

**Date of issue/ Date of revision** : 24/11/2023

**Date of previous issue** : 21/07/2022

**Version** : 1.03

AQUATOP 2600-22\_NCS S 4550-Y80R

NCS S 4550-Y80R

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

