

SAFETY DATA SHEET



AQUATOP 2600-22 - RAL 9005

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : AQUATOP 2600-22 - RAL 9005

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label elements : Contains adipohydrazide, 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 2-Octyl-2H-isothiazol-3-one. May produce an allergic reaction.

Safety data sheet available on request. Contains biocidal products for in-can preservation: BIT and DTBMA and Bronopol and MIT and OIT and MBIT.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles :

SECTION 2: Hazards identification

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Dipropyleneglycolmethylether	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤3	Not classified.	-	[2]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C ≥ 0.036% M [Acute] = 1 M [Chronic] = 1	[1]
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: C ≥ 0.6% Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: 0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	[1]
2-methyl-2H-isothiazol-3-one	EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1	[1]
2-Octyl-2H-isothiazol-3-one	EC: 247-761-7	<0.001	Acute Tox. 3, H301	ATE [Oral] = 125	[1]

SECTION 3: Composition/information on ingredients

	CAS: 26530-20-1 Index: 613-112-00-5		Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 See Section 16 for the full text of the H statements declared above.	mg/kg ATE [Dermal] = 311 mg/kg ATE [Inhalation (dusts and mists)] = 0.27 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	
--	--	--	--	--	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

SECTION 5: Firefighting measures

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Dipropyleneglycolmethylether	Regulation on Limit Values - MAC (Austria, 12/2024) [Dipropylenglykolmonomethylether (Isomerengemisch)] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 307 mg/m ³ . CEIL 5 minutes: 100 ppm 8 times per shift. CEIL 5 minutes: 614 mg/m ³ 8 times per shift.
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Regulation on Limit Values - MAC (Austria, 12/2024) [5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on (Gemisch im Verhältnis 3:1)] Skin sensitiser. TWA 8 hours: 0.05 mg/m ³ .
2-methyl-2H-isothiazol-3-one	Regulation on Limit Values - MAC (Austria, 12/2024) [5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on (Gemisch im Verhältnis 3:1)] Skin sensitiser. TWA 8 hours: 0.05 mg/m ³ .
2-Octyl-2H-isothiazol-3-one	Regulation on Limit Values - MAC (Austria, 12/2024) Absorbed through skin , Sensitiser. TWA 8 hours: 0.05 mg/m ³ . Form: Inhalable fraction. CEIL: 0.05 mg/m ³ . Form: Inhalable fraction.
Dipropyleneglycolmethylether	Limit values (Belgium, 12/2023) [Dipropyleenglykolmonomethylether] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m ³ .
Dipropyleneglycolmethylether	Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) [2-(Methoxymethyletoxy)propanol] Absorbed through skin. Limit value 8 hours: 308 mg/m ³ . Limit value 8 hours: 50 ppm.
Dipropyleneglycolmethylether	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) [(2-metoksimetiletoksi)-propanol] Absorbed through skin. ELV 8 hours: 308 mg/m ³ . ELV 8 hours: 50 ppm.
Dipropyleneglycolmethylether	Department of labour inspection (Cyprus, 7/2021) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m ³ .

SECTION 8: Exposure controls/personal protection

Dipropyleneglycolmethylether	Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) [(2-methoxymethylethoxy)propanol] Absorbed through skin. TWA 8 hours: 270 mg/m ³ . TWA 8 hours: 43.8 ppm. STEL 15 minutes: 550 mg/m ³ . STEL 15 minutes: 89.3 ppm.
Dipropyleneglycolmethylether	Working Environment Authority (Denmark, 12/2024) [dipropylenglycolmethylether] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 309 mg/m ³ . STEL 15 minutes: 618 mg/m ³ . STEL 15 minutes: 100 ppm.
Dipropyleneglycolmethylether	Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) [dipropüleenglükooli monometüüleeter] Absorbed through skin. TWA 8 hours: 308 mg/m ³ . TWA 8 hours: 50 ppm.
Dipropyleneglycolmethylether	EU OEL (Europe, 1/2022) [(2-Methoxymethylethoxy)-propanol] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m ³ .
Dipropyleneglycolmethylether	Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) [(2-Metoksimetyylietoksi)-propanoli] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 310 mg/m ³ .
Dipropyleneglycolmethylether	Ministry of Labor (France, 6/2024) [(2-méthoxyméthyléthoxy)-propanol] Absorbed through skin. TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 308 mg/m ³ . Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)
Dipropyleneglycolmethylether	TRGS 900 OEL (Germany, 6/2024) [(2-Methoxymethylethoxy)propanol] TWA 8 hours: 310 mg/m ³ . PEAK 15 minutes: 310 mg/m ³ . TWA 8 hours: 50 ppm. PEAK 15 minutes: 50 ppm. DFG MAC-values list (Germany, 7/2024) [Dipropylene glycol monomethyl ether] Develop D. TWA 8 hours: 50 ppm. PEAK 15 minutes: 50 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 310 mg/m ³ . PEAK 15 minutes: 310 mg/m ³ 4 times per shift [Interval: 1 hour].
1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazol-3-one 2-Octyl-2H-isothiazol-3-one	DFG MAC-values list (Germany, 7/2024) Skin sensitiser. DFG MAC-values list (Germany, 7/2024) Skin sensitiser. TRGS 900 OEL (Germany, 6/2024) Absorbed through skin. TWA 8 hours: 0.05 mg/m ³ . Form: Inhalable fraction. PEAK 15 minutes: 0.1 mg/m ³ . Form: Inhalable fraction. DFG MAC-values list (Germany, 7/2024) Develop C. Absorbed through skin , Skin sensitiser. TWA 8 hours: 0.05 mg/m ³ . Form: inhalable fraction. PEAK 15 minutes: 0.1 mg/m ³ 4 times per shift [Interval: 1 hour]. Form: inhalable fraction.

SECTION 8: Exposure controls/personal protection

Dipropyleneglycolmethylether	Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) [μεθοξυμεθυλ-αιθοξυ-προπανόλη, 2-] Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 600 mg/m ³ . STEL 15 minutes: 150 ppm. STEL 15 minutes: 900 mg/m ³ .
Dipropyleneglycolmethylether	5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) [(2-metoximetiletoxi)-propanol] TWA 8 hours: 308 mg/m ³ . TWA 8 hours: 50 ppm.
Dipropyleneglycolmethylether	Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) [Díprópýlenglýkólmetyler] Absorbed through skin. TWA 8 hours: 300 mg/m ³ . TWA 8 hours: 50 ppm.
Dipropyleneglycolmethylether	NAOSH (Ireland, 4/2024) [(2-methoxymethylethoxy)-1-propanol] Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 50 ppm. OELV 8 hours: 308 mg/m ³ .
Dipropyleneglycolmethylether	Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024) Absorbed through skin. Limit value 8 hours: 50 ppm. Limit value 8 hours: 308 mg/m ³ .
Dipropyleneglycolmethylether	Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) [Metoksipropoksi propanols] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m ³ .
Dipropyleneglycolmethylether	Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) Absorbed through skin. TWA 8 hours: 308 mg/m ³ . TWA 8 hours: 50 ppm. STEL 15 minutes: 450 mg/m ³ . STEL 15 minutes: 75 ppm.
Dipropyleneglycolmethylether	Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) [(2-méthoxyméthyléthoxy)-propanol] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m ³ .
Dipropyleneglycolmethylether	EU OEL (Europe, 1/2022) [(2-Methoxymethylethoxy)-propanol] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m ³ .
Dipropyleneglycolmethylether	Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) [dipropyleenglycolmethylether] TWA 8 hours: 300 mg/m ³ . TWA 8 hours: 48.7 ppm.
Dipropyleneglycolmethylether	FOR-2011-12-06-1358 (Norway, 5/2024) [(2-metoksymetyletoksy)-propanol] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 300 mg/m ³ .
Dipropyleneglycolmethylether	Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) [dipropylene glycol methyl ether] Absorbed through skin. TWA 8 hours: 240 mg/m ³ . STEL 15 minutes: 480 mg/m ³ .
reaction mass of: 5-chloro-2-methyl-	Regulation of the Minister of Family, Labor and Social Policy

SECTION 8: Exposure controls/personal protection

4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) Absorbed through skin. TWA 8 hours: 0.2 mg/m ³ . STEL 15 minutes: 0.4 mg/m ³ .
Dipropyleneglycolmethylether	Portuguese Institute of Quality (Portugal, 11/2014) [2-metoximetiletoxipropanol] Absorbed through skin. TWA 8 hours: 100 ppm. STEL 15 minutes: 150 ppm. Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) [2-metoximetiletoxi propanol] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m ³ .
Dipropyleneglycolmethylether	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) Absorbed through skin. VLA 8 hours: 308 mg/m ³ . VLA 8 hours: 50 ppm.
Dipropyleneglycolmethylether	Government regulation SR c. 355/2006 (Slovakia, 6/2024) [2-metoxymetyl-etoxipropanol] Absorbed through skin , Inhalation sensitiser. TWA 8 hours: 308 mg/m ³ (2-methoxymetyl-ethoxypropanol). TWA 8 hours: 50 ppm (2-methoxymetyl-ethoxypropanol).
Dipropyleneglycolmethylether	Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) [(2-metoksimetiletoksi)propanol] Absorbed through skin. TWA 8 hours: 308 mg/m ³ . TWA 8 hours: 50 ppm. KTV 15 minutes: 50 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 308 mg/m ³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].
2-Octyl-2H-isothiazol-3-one	Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) Absorbed through skin. TWA 8 hours: 0.05 mg/m ³ . Form: Inhalable fraction. KTV 15 minutes: 0.1 mg/m ³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. Form: Inhalable fraction.
Dipropyleneglycolmethylether	National institute of occupational safety and health (Spain, 1/2024) [éter metílico de dipropilenglicol] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m ³ .
Dipropyleneglycolmethylether	Work environment authority Regulation 2018:1 (Sweden, 11/2022) [dipropylene glycol monomethyl ether] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 300 mg/m ³ . STEL 15 minutes: 75 ppm. STEL 15 minutes: 450 mg/m ³ .
Dipropyleneglycolmethylether	SUVA (Switzerland, 1/2025) [Dipropylenglykolmethylether (Isomerengemisch)] STEL 15 minutes: 50 ppm. Form: vapour and aerosols. STEL 15 minutes: 300 mg/m ³ . Form: vapour and aerosols. TWA 8 hours: 50 ppm. Form: vapour and aerosols. TWA 8 hours: 300 mg/m ³ . Form: vapour and aerosols.
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	SUVA (Switzerland, 1/2025) Sensitiser. STEL 15 minutes: 0.4 mg/m ³ . Form: Inhalable fraction. TWA 8 hours: 0.2 mg/m ³ . Form: Inhalable fraction.

SECTION 8: Exposure controls/personal protection

2-Octyl-2H-isothiazol-3-one	SUVA (Switzerland, 1/2025) Absorbed through skin , Sensitiser. TWA 8 hours: 0.05 mg/m³. Form: Inhalable fraction. STEL 15 minutes: 0.1 mg/m³. Form: Inhalable fraction.
No exposure limit value known.	

Biological exposure indices

[illegible]

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following:
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be

SECTION 8: Exposure controls/personal protection

required.

DNELs/DMELs

Product/ingredient name

Dipropyleneglycolmethylether

Result

DNEL - General population - Long term - Oral

36 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

37.2 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

121 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

283 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

308 mg/m³

Effects: Systemic

adipohydrazide

DNEL - Workers - Long term - Inhalation

17.5 mg/m³

Effects: Systemic

1,2-benzisothiazol-3(2H)-one

DNEL - General population - Long term - Dermal

0.345 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.966 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

1.2 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

6.81 mg/m³

Effects: Systemic

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

DNEL - General population - Long term - Inhalation

0.02 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

0.02 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

0.04 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

0.04 mg/m³

Effects: Local

DNEL - General population - Long term - Oral

0.09 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Oral

SECTION 8: Exposure controls/personal protection

0.11 mg/kg bw/day

Effects: Systemic

2-methyl-2H-isothiazol-3-one

DNEL - General population - Long term - Inhalation

0.021 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

0.021 mg/m³

Effects: Local

DNEL - General population - Long term - Oral

0.027 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Inhalation

0.043 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

0.043 mg/m³

Effects: Local

DNEL - General population - Short term - Oral

0.053 mg/kg bw/day

Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommendations : Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Not recommended polyvinyl alcohol (PVA) gloves

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Black.
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
water	100	212	
Dipropyleneglycolmethylether	189.6	373.3	EU A.2

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: Not applicable.
Upper: Not applicable.
- Flash point** : Closed cup: >100°C (>212°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Dipropyleneglycolmethylether	207	404.6	EU A.15

- Decomposition temperature** : Not available.
- pH** : 8 to 8.5 [Conc. (% w/w): 100%]
- Viscosity** : Not available.
- Solubility(ies)** :
Not available.

- Solubility in water** : Not available.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				

- Relative density** : Not available.
- Density** : 1 g/cm³
- Vapour density** : Not available.
- Particle characteristics**
- Median particle size** : Not applicable.

SECTION 9: Physical and chemical properties

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

Oxidising properties : Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

1,2-benzisothiazol-3(2H)-one

Result

Rat - Oral - LD50

1020 mg/kg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Rat - Oral - LD50

53 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

2-methyl-2H-isothiazol-3-one

Rat - Inhalation - LC50 Dusts and mists

0.11 mg/l [4 hours]

2-Octyl-2H-isothiazol-3-one

Rat - Oral - LD50

550 mg/kg

Rabbit - Dermal - LD50

690 mg/kg

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)

Date of issue/Date of revision

: 19/06/2025

Date of previous issue

: 19/06/2025

Version : 3

13/24

AQUATOP 2600-22 - RAL 9005

Label No : 120735

SECTION 11: Toxicological information

AQUATOP 2600-22	N/A	N/A	N/A	1826.2	N/A
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	53	50	N/A	0.5	N/A
2-methyl-2H-isothiazol-3-one	100	300	N/A	N/A	0.11
2-Octyl-2H-isothiazol-3-one	125	311	N/A	N/A	0.27

Skin corrosion/irritation

Product/ingredient name

Dipropyleneglycolmethylether

1,2-benzisothiazol-3(2H)-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Result

Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

Human - Skin - Mild irritant

Duration of treatment/exposure: 48 hours

Amount/concentration applied: 5 %

Human - Skin - Severe irritant

Amount/concentration applied: 0.01 %

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

Dipropyleneglycolmethylether

2-Octyl-2H-isothiazol-3-one

Result

Human - Eyes - Mild irritant

Amount/concentration applied: 8 mg

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

SECTION 11: Toxicological information

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : No known significant effects or critical hazards.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

SECTION 11: Toxicological information

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

1,2-benzisothiazol-3(2H)-one

Result

Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test]
Fish - Trout - *Onorhynchus Mykiss*
1.9 mg/l [96 hours]

Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test]
Daphnia - Daphnia - *Daphnia Magna*
3.7 mg/l [48 hours]

Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test]
Algae - Algae - *Skeletonema Costatum*
0.36 mg/l [72 hours]

Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test]
Algae - Algae - *Skeletonema Costatum*
0.15 mg/l [72 hours]

2-methyl-2H-isothiazol-3-one

Acute - EC50 - Fresh water

US EPA
Daphnia - Water flea - *Daphnia magna*
Age: <24 hours
0.18 ppm [48 hours]
Effect: Intoxication

Acute - LC50 - Fresh water

US EPA
Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss*
Weight: 0.73 g
0.07 ppm [96 hours]
Effect: Mortality

2-Octyl-2H-isothiazol-3-one

Acute - EC50 - Fresh water

US EPA
Daphnia - Water flea - *Daphnia magna*
Age: <24 hours
107 ppb [48 hours]
Effect: Intoxication

Acute - LC50 - Fresh water

US EPA
Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss*
Weight: 0.7 g
47 ppb [96 hours]
Effect: Mortality

Chronic - NOEC - Fresh water

US EPA
Daphnia - Water flea - *Daphnia magna*
74 ppb [21 days]
Effect: No Effect Coded

SECTION 12: Ecological information

Chronic - NOEC

US EPA

Fish - Fathead minnow - *Pimephales promelas*

8.5 ppb [35 days]

Effect: Growth

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name

1,2-benzisothiazol-3(2H)-one

Result

EU

24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Dipropyleneglycolmethylether	0.004	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low
2-Octyl-2H-isothiazol-3-one	2.45	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
adipohydrazide	1.7	55.2165
1,2-benzisothiazol-3(2H)-one	1.9	73.142
2-methyl-2H-isothiazol-3-one	1.7	54.9187
2-Octyl-2H-isothiazol-3-one	2.8	706.605

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Dipropyleneglycolmethylether	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No
2-Octyl-2H-isothiazol-3-one	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Dipropyleneglycolmethylether	No	N/A	N/A	No	N/A	N/A	N/A
adipohydrazide	No	N/A	N/A	No	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	No	N/A	No	No	No	N/A	No
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	No	N/A	N/A	No	N/A	N/A	N/A
2-methyl-2H-isothiazol-3-one	No	N/A	N/A	No	N/A	N/A	N/A
2-Octyl-2H-isothiazol-3-one	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Dipropyleneglycolmethylether	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No
2-Octyl-2H-isothiazol-3-one	No	No	No	No	No	No	No

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.
Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

European waste catalogue (EWC) : 080112

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Labelling :

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

SECTION 15: Regulatory information

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Austria

Limitation of the use of organic solvents : Permitted.

Belgium

Book VI carcinogenic agents annex VI.2-1 - VI.2-3

Ingredient name	Status
Noirs de charbon	Listed

Czech Republic

Storage code : IV

Denmark

Product registration number : 4366625

Fire class : IV-1

Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
carbon black respirable	Listed	-

MAL-code : 00-3

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, respiratory protection with air supply and arm protectors/apron/coveralls/protective clothing must be worn as appropriate or as instructed.

MAL-code: 00-3

Application: During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents. When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing* facility type, if the operator is inside the spray zone.

- Coveralls must be worn.

When spraying in existing* spray booths, if the operator is outside the spray zone.

- Arm protectors and apron must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, coveralls and hood must be worn.

SECTION 15: Regulatory information

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

- Low-boiling liquids** : This product contains low-boiling point liquids. Any respiratory protective equipment should be air-fed.
- Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
- List of undesirable substances** : Not listed
- Carcinogenic waste** : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

Finland

France

Social Security Code, Articles L 461-1 to L 461-7 : Dipropyleneglycolmethylether RG 84

Reinforced medical surveillance : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

Germany

Storage class (TRGS 510) : 10

Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water : 1

Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
5.2.1	Total dust	35.2
5.2.4 [III]	Gaseous inorganic substances	0.087
5.2.5	Organic substances	3.6
5.2.5 [I]	Organic substances	2.7

AOX : The product contains organically bound halogens and can contribute to the AOX value in waste water.

Italy

D.Lgs. 152/06 : Not determined.

Netherlands

Water Discharge Policy (ABM) : A(4) Low hazard for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A

Norway

Sweden

Switzerland

VOC content : Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

SECTION 15: Regulatory information

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

📌 Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A

Date of issue/ Date of revision : 19/06/2025

Date of previous issue : 19/06/2025

Date of issue/Date of revision : 19/06/2025 **Date of previous issue** : 19/06/2025

Version : 3 **22/24**

AQUATOP 2600-22 - RAL 9005

Label No : 120735

SECTION 16: Other information

Version

: 3

AQUATOP 2600-22_RAL 9005

RAL 9005

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

