# SAFETY DATA SHEET



AQUATOP 2600-60 - BASE T

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

: AQUATOP 2600-60 - BASE T **Product name** 

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: Prod-safe@teknos.com

**National contact** 

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

**National advisory body/Poison Centre** 

Telephone number : In an emergency, call 112

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

**Prevention** : Not applicable. Response : Not applicable. **Storage** : Not applicable. **Disposal** : Not applicable.

Supplemental label : Contains adipohydrazide, 1,2-benzisothiazol-3(2H)-one and 2-Methyl-

1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Safety data sheet available on request.

**Annex XVII - Restrictions** on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

2.3 Other hazards

elements

Date of issue/Date of revision : 13/11/2023 Version:1 1/17 Date of previous issue : No previous validation Label No: 73924

### **SECTION 2: Hazards identification**

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

| Product/ingredient name                   | Identifiers   | %       | Classification   | Specific Conc.<br>Limits, M-factors<br>and ATEs  | Туре    |
|---|---|---------|--|--|---------|
| 2-(2-butoxyethoxy)ethanol                 | REACH #:<br>01-2119475104-44<br>EC: 203-961-6<br>CAS: 112-34-5<br>Index: 603-096-00-8 | ≤3      | Eye Irrit. 2, H319   | -  | [1] [2] |
| adipohydrazide                            | REACH #:<br>01-2119962900-36<br>EC: 213-999-5<br>CAS: 1071-93-8                       | <1      | Skin Sens. 1, H317<br>Aquatic Chronic 2,<br>H411   | -  | [1]     |
| 1,2-benzisothiazol-3(2H)-<br>one          | EC: 220-120-9<br>CAS: 2634-33-5<br>Index: 613-088-00-6                                | <0.05   | Acute Tox. 4, H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Acute 1, H400   | ATE [Oral] = 1020<br>mg/kg<br>Skin Sens. 1, H317:<br>C ≥ 0.05%<br>M [Acute] = 1                                  | [1]     |
| 2-Methyl-1,2-benzisothiazol-<br>3(2H)-one | CAS: 2527-66-4<br>Index: 613-336-00-3   | <0.0015 | Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH071 See Section 16 for the full text of the H statements declared above. | ATE [Oral] = 175<br>mg/kg<br>ATE [Dermal] =<br>1100 mg/kg<br>Skin Sens. 1, H317:<br>C ≥ 0.0015%<br>M [Acute] = 1 | [1]     |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### <u>Type</u>

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

Eye contact : Im

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Skin contact** 

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Date of issue/Date of revision: 13/11/2023Date of previous issue: No previous validationVersion: 12/17AQUATOP 2600-60 - BASE TLabel No :73924

### **SECTION 4: First aid measures**

Ingestion

: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### **Over-exposure signs/symptoms**

**Eve contact** : No specific data. Inhalation : No specific data. Skin contact : No specific data. Ingestion : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

# SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

**Hazards from the** substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion** 

products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

#### 5.3 Advice for firefighters

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Date of issue/Date of revision : 13/11/2023 Version :1 3/17 Date of previous issue : No previous validation Label No: 73924

### **SECTION 6: Accidental release measures**

# **6.2 Environmental precautions**

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

# SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

Protective measures
Advice on general
occupational hygiene

- : Put on appropriate personal protective equipment (see Section 8).
- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

# SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

| Product/ingredient name   | Exposure limit values  |
|---------------------------|--|
| 2-(2-butoxyethoxy)ethanol | Regulation on Limit Values - MAC (Austria, 4/2021).  TWA: 10 ppm 8 hours.  TWA: 67.5 mg/m³ 8 hours.  PEAK: 15 ppm, 4 times per shift, 15 minutes.  PEAK: 101.2 mg/m³, 4 times per shift, 15 minutes. |

Date of issue/Date of revision: 13/11/2023Date of previous issue: No previous validationVersion: 14/17AQUATOP 2600-60 - BASE TLabel No :73924

2-(2-butoxyethoxy)ethanol Limit values (Belgium, 5/2021). STEL: 15 ppm 15 minutes. TWA: 10 ppm 8 hours. TWA: 67.5 mg/m<sup>3</sup> 8 hours. STEL: 101.2 mg/m<sup>3</sup> 15 minutes. Ministry of Labour and Social Policy and the Ministry of 2-(2-butoxyethoxy)ethanol Health - Ordinance No 13/2003. (Bulgaria, 6/2021). Limit value 8 hours: 67.5 mg/m<sup>3</sup> 8 hours. Limit value 15 min: 101.2 mg/m<sup>3</sup> 15 minutes. Limit value 15 min: 15 ppm 15 minutes. Limit value 8 hours: 10 ppm 8 hours. 2-(2-butoxyethoxy)ethanol Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). STELV: 101.2 mg/m<sup>3</sup> 15 minutes. STELV: 15 ppm 15 minutes. ELV: 67.5 mg/m<sup>3</sup> 8 hours. ELV: 10 ppm 8 hours. 2-(2-butoxyethoxy)ethanol Department of labour inspection (Cyprus, 7/2021). STEL: 15 ppm 15 minutes. STEL: 101.2 mg/m3 15 minutes. TWA: 10 ppm 8 hours. TWA: 67.5 mg/m<sup>3</sup> 8 hours. Government regulation of Czech Republic PEL/NPK-P (Czech 2-(2-butoxyethoxy)ethanol Republic, 10/2022). TWA: 70 mg/m<sup>3</sup> 8 hours. TWA: 10.36 ppm 8 hours. STEL: 100 mg/m<sup>3</sup> 15 minutes. STEL: 14.8 ppm 15 minutes. 2-(2-butoxyethoxy)ethanol Working Environment Authority (Denmark, 6/2022). TWA: 68 mg/m<sup>3</sup> 8 hours. TWA: 10 ppm 8 hours. STEL: 15 ppm 15 minutes. STEL: 101 mg/m<sup>3</sup> 15 minutes. Occupational exposure limits, Regulation No. 293 (Estonia, 2-(2-butoxyethoxy)ethanol 12/2022). TWA: 10 ppm 8 hours. TWA: 67.5 mg/m<sup>3</sup> 8 hours. 2-(2-butoxyethoxy)ethanol EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values TWA: 67.5 mg/m<sup>3</sup> 8 hours. TWA: 10 ppm 8 hours. STEL: 101.2 mg/m<sup>3</sup> 15 minutes. STEL: 15 ppm 15 minutes. Institute of Occupational Health, Ministry of Social Affairs 2-(2-butoxyethoxy)ethanol (Finland, 10/2021).

TWA: 10 ppm 8 hours. TWA: 68 mg/m<sup>3</sup> 8 hours.

Ministry of Labor (France, 10/2022). Notes: Indicative 2-(2-butoxyethoxy)ethanol regulatory limit values (decree of 30-06-2004 modified)

> STEL: 101.2 mg/m3 15 minutes. STEL: 15 ppm 15 minutes. TWA: 67.5 mg/m<sup>3</sup> 8 hours. TWA: 10 ppm 8 hours.

No exposure limit value known.

Presidential Decree 307/1986: Occupational exposure limit 2-(2-butoxyethoxy)ethanol values (Greece, 9/2021).

> STEL: 101.2 mg/m<sup>3</sup> 15 minutes. STEL: 15 ppm 15 minutes. TWA: 67.5 mg/m<sup>3</sup> 8 hours. TWA: 10 ppm 8 hours.

Date of issue/Date of revision : 13/11/2023 5/17 Date of previous issue : No previous validation Version: 1

AQUATOP 2600-60 - BASE T Label No: 73924

2-(2-butoxyethoxy)ethanol 5/2020. (II. 6.) ITM Decree (Hungary, 12/2022).

TWA: 67.5 mg/m³ 8 hours. PEAK: 101.2 mg/m³ 15 minutes. PEAK: 15 ppm 15 minutes. TWA: 10 ppm 8 hours.

2-(2-butoxyethoxy)ethanol Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021).

STEL: 101.2 mg/m³ 15 minutes. STEL: 15 ppm 15 minutes. TWA: 67.5 mg/m³ 8 hours. TWA: 10 ppm 8 hours.

2-(2-butoxyethoxy)ethanol NAOSH (Ireland, 5/2021). Notes: EU derived Occupational

Exposure Limit Values
OELV-8hr: 10 ppm 8 hours.

OELV-15min: 101.2 mg/m³ 15 minutes. OELV-8hr: 67.5 mg/m³ 8 hours. OELV-15min: 15 ppm 15 minutes.

2-(2-butoxyethoxy)ethanol Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020).

8 hours: 10 ppm 8 hours. 8 hours: 67.5 mg/m³ 8 hours. Short Term: 15 ppm 15 minutes. Short Term: 101.2 mg/m³ 15 minutes.

No exposure limit value known.

2-(2-butoxyethoxy)ethanol Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022).

TWA: 67.5 mg/m<sup>3</sup> 8 hours. TWA: 10 ppm 8 hours.

STEL: 101.2 mg/m³ 15 minutes. STEL: 15 ppm 15 minutes.

2-(2-butoxyethoxy)ethanol Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). Absorbed through skin.

STEL: 15 ppm 15 minutes. STEL: 101.2 mg/m³ 15 minutes.

TWA: 10 ppm 8 hours. TWA: 67.5 mg/m³ 8 hours.

2-(2-butoxyethoxy)ethanol EU OEL (Europe, 1/2022). Notes: list of indicative

occupational exposure limit values

TWA: 67.5 mg/m<sup>3</sup> 8 hours. TWA: 10 ppm 8 hours. STEL: 101.2 mg/m<sup>3</sup> 15 minutes.

STEL: 15 ppm 15 minutes.

No exposure limit value known.

2-(2-butoxyethoxy)ethanol FOR-2011-12-06-1358 (Norway, 12/2022). Notes: indicative

limit value

TWA: 10 ppm 8 hours. TWA: 68 mg/m³ 8 hours.

No exposure limit value known.

No exposure limit value known.

2-(2-butoxyethoxy)ethanol HG 1218/2006, Annex 1, with subsequent modifications and

additions (Romania, 3/2021).

VLA: 67.5 mg/m<sup>3</sup> 8 hours.

Short term: 101.2 mg/m³ 15 minutes. Short term: 15 ppm 15 minutes.

VLA: 10 ppm 8 hours.

2-(2-butoxyethoxy)ethanol Government regulation SR c. 355/2006 (Slovakia, 9/2020).

TWA: 67.5 mg/m³ 8 hours. STEL: 101.2 mg/m³ 15 minutes. TWA: 10 ppm 8 hours.

TWA: 10 ppm 8 hours. STEL: 15 ppm 15 minutes.

Date of issue/Date of revision: 13/11/2023Date of previous issue: No previous validationVersion: 16/17

AQUATOP 2600-60 - BASE T Label No :73924

2-(2-butoxyethoxy)ethanol Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). TWA: 67.5 mg/m<sup>3</sup> 8 hours. TWA: 10 ppm 8 hours. KTV: 101.2 mg/m³, 4 times per shift, 15 minutes. KTV: 15 ppm, 4 times per shift, 15 minutes. National institute of occupational safety and health (Spain, 2-(2-butoxyethoxy)ethanol 4/2022). TWA: 67.5 mg/m<sup>3</sup> 8 hours. TWA: 10 ppm 8 hours. STEL: 15 ppm 15 minutes. STEL: 101.2 mg/m<sup>3</sup> 15 minutes. Work environment authority Regulation 2018:1 (Sweden, 2-(2-butoxyethoxy)ethanol 9/2021). TWA: 10 ppm 8 hours. TWA: 68 mg/m<sup>3</sup> 8 hours. STEL: 15 ppm 15 minutes. STEL: 101 mg/m<sup>3</sup> 15 minutes. 2-(2-butoxyethoxy)ethanol SUVA (Switzerland, 1/2023). TWA: 67 mg/m<sup>3</sup> 8 hours. Form: vapour and aerosols STEL: 101 mg/m³ 15 minutes. Form: vapour and aerosols STEL: 15 ppm 15 minutes. Form: vapour and aerosols TWA: 10 ppm 8 hours. Form: vapour and aerosols No exposure limit value known.

# Riological exposure indices

| Product/ingredient name    | Exposure indices |
|----------------------------|------------------|
| No exposure indices known. |                  |

Date of issue/Date of revision: 13/11/2023Date of previous issue: No previous validationVersion: 17/17AQUATOP 2600-60 - BASE TLabel No :73924

No exposure indices known.

### **Recommended monitoring** procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

| Product/ingredient name      | Type | Exposure                 | Value                  | Population            | Effects  |
|------------------------------|------|--------------------------|------------------------|-----------------------|----------|
| 2-(2-butoxyethoxy)ethanol    | DNEL | Long term Oral           | 6.25 mg/               | General               | Systemic |
|                              |      |                          | kg bw/day              | population            |          |
|                              | DNEL | Long term<br>Inhalation  | 67.5 mg/m³             | Workers               | Local    |
|                              | DNEL | Short term<br>Inhalation | 101.2 mg/<br>m³        | Workers               | Local    |
| adipohydrazide               | DNEL | Long term                | 17.5 mg/m³             | Workers               | Systemic |
| 1,2-benzisothiazol-3(2H)-one | DNEL | Long term Dermal         | 0.345 mg/<br>kg bw/day | General<br>population | Systemic |
|                              | DNEL | Long term Dermal         | 0.966 mg/<br>kg bw/day | Workers               | Systemic |
|                              | DNEL | Long term<br>Inhalation  | 1.2 mg/m <sup>3</sup>  | General population    | Systemic |
|                              | DNEL | Long term<br>Inhalation  | 6.81 mg/m <sup>3</sup> | Workers               | Systemic |

### **PNECs**

No PNECs available

#### 8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### **Skin protection**

Date of issue/Date of revision : 13/11/2023 Version:1 8/17 Date of previous issue : No previous validation Label No: 73924

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommendations: Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm Not recommended polyvinyl alcohol (PVA) gloves

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

**Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Colour Colourless. **Odour** Slight

Not available. **Odour threshold** Melting point/freezing point Not available.

Initial boiling point and

boiling range

| Ingredient name               | °C  | °F  | Method |
|-------------------------------|-----|-----|--------|
| water                         | 100 | 212 |        |
| Dipropylenglycoldimethylether | 175 | 347 |        |

**Flammability** : Not available.

Lower and upper explosion

limit

: Lower: Not applicable. Upper: Not applicable.

Flash point Closed cup: >100°C (>212°F)

**Auto-ignition temperature** 

| Ingredient name               | °C  | °F  | Method    |
|-------------------------------|-----|-----|-----------|
| Dipropylenglycoldimethylether | 165 | 329 |           |
| 2-(2-butoxyethoxy)ethanol     | 210 | 410 | DIN 51794 |

**Decomposition temperature** : Not available. 8.7 to 9.1

pН Not available. **Viscosity** 

Solubility(ies)

Not available.

Solubility in water : Not available.

Date of issue/Date of revision · 13/11/2023 9/17 Date of previous issue : No previous validation Version :1 AQUATOP 2600-60 - BASE T Label No: 73924

# SECTION 9: Physical and chemical properties

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

|                               | Vap   | Vapour Pressure at 20°C |        |       | Vapour pressure at 50°C |        |
|-------------------------------|-------|-------------------------|--------|-------|-------------------------|--------|
| Ingredient name               | mm Hg | kPa                     | Method | mm Hg | kPa                     | Method |
| water                         | 17.5  | 2.3                     |        |       |                         |        |
| Dipropylenglycoldimethylether | 0.52  | 0.069                   |        |       |                         |        |

Relative density : Not available.

Density : 1.1 g/cm³
Vapour density : Not available.

Explosive properties : Not available.

Oxidising properties : Not available.

**Particle characteristics** 

Median particle size : Not applicable.

# **SECTION 10: Stability and reactivity**

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

# **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

| Product/ingredient name                 | Result      | Species | Dose       | Exposure |
|---|-------------|---------|------------|----------|
| , | LD50 Dermal |         | 2700 mg/kg | -        |
|   | LD50 Oral   | Rat     | 4500 mg/kg | -        |
| 1,2-benzisothiazol-3(2H)-               | LD50 Oral   | Rat     | 1020 mg/kg | -        |
| one                                     |             |         |            |          |

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

**Acute toxicity estimates** 

| Route                | ATE value  |
|----------------------|------------|
| Inhalation (vapours) | 732.6 mg/l |

#### **Irritation/Corrosion**

| Product/ingredient name      | Result   | Species         | Score | Exposure              | Observation |
|------------------------------|--|-----------------|-------|-----------------------|-------------|
| 2-(2-butoxyethoxy)ethanol    | Eyes - Moderate irritant                       | Rabbit          | -     | 24 hours 20<br>mg     | -           |
| 1,2-benzisothiazol-3(2H)-one | Eyes - Severe irritant<br>Skin - Mild irritant | Rabbit<br>Human | -     | 20 mg<br>48 hours 5 % | -           |

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

Date of issue/Date of revision: 13/11/2023Date of previous issue: No previous validationVersion: 110/17AQUATOP 2600-60 - BASE TLabel No :73924

# SECTION 11: Toxicological information

**Sensitisation** 

Conclusion/Summary : Based on available data, the classification criteria are not met.

Mutagenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Carcinogenicity** 

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Reproductive toxicity** 

Conclusion/Summary : Based on available data, the classification criteria are not met.

**Teratogenicity** 

: Based on available data, the classification criteria are not met. **Conclusion/Summary** 

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes

of exposure

: Not available.

Potential acute health effects

**Eye contact** : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Skin contact** Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data. Inhalation : No specific data. **Skin contact** : No specific data. : No specific data. Ingestion

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

**Potential immediate** : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

**Potential immediate** : Not available.

effects

: Not available. Potential delayed effects

Potential chronic health effects

Not available.

: Not available. **Conclusion/Summary** 

**General** : No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

Date of issue/Date of revision : 13/11/2023 Date of previous issue Version:1 11/17

AQUATOP 2600-60 - BASE T

: No previous validation

Label No: 73924

# **SECTION 11: Toxicological information**

### 11.2.1 Endocrine disrupting properties

Not available.

### 11.2.2 Other information

Not available.

# **SECTION 12: Ecological information**

### 12.1 Toxicity

| Product/ingredient name               | Result                              | Species  | Exposure |
|---------------------------------------|-------------------------------------|--|----------|
| 2-(2-butoxyethoxy)ethanol             | Acute LC50 1300000 μg/l Fresh water | Fish - Lepomis macrochirus   | 96 hours |
| 1,2-benzisothiazol-3(2H)-one          | Acute EC50 0.36 mg/l Marine water   | Algae - Skeletonema Costatum   | 72 hours |
|                                       | Acute EC50 3.7 mg/l                 | Daphnia - Daphnia Magna  | 48 hours |
|                                       | Acute LC50 1.9 mg/l Fresh water     | Fish - Onorhynchus Mykiss  | 96 hours |
|                                       | Acute NOEC 0.15 mg/l Marine water   | Algae - Skeletonema Costatum   | 72 hours |
| 2-Methyl-1,2-benzisothiazol-3(2H)-one | Acute EC50 0.22 ppm Fresh water     | Algae - Pseudokirchneriella subcapitata                                      | 96 hours |
|                                       | Acute EC50 0.92 ppm Fresh water     | Daphnia - Daphnia magna  | 48 hours |
|                                       | Acute LC50 0.24 ppm Fresh water     | Fish - Oncorhynchus mykiss -<br>Juvenile (Fledgling, Hatchling,<br>Weanling) | 96 hours |
|                                       | Chronic NOEC 0.16 ppm               | Fish - Pimephales promelas   | 32 days  |

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

| Product/ingredient name      | Test | Result         | Dose | Inoculum |
|------------------------------|------|----------------|------|----------|
| 1,2-benzisothiazol-3(2H)-one | EU   | 24 % - 28 days | -    | -        |

**Conclusion/Summary**: This product has not been tested for biodegradation.

| Product/ingredient name      | Aquatic half-life | Photolysis | Biodegradability |
|------------------------------|-------------------|------------|------------------|
| 1,2-benzisothiazol-3(2H)-one | -                 | -          | Inherent         |

#### 12.3 Bioaccumulative potential

| Product/ingredient name                                | LogPow | BCF | Potential  |
|--|--------|-----|------------|
| 2-(2-butoxyethoxy)ethanol 1,2-benzisothiazol-3(2H)-one | 1 -    | 3.2 | Low<br>Low |

#### **12.4 Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

Date of issue/Date of revision: 13/11/2023Date of previous issue: No previous validationVersion: 112/17

**Label No: 73924** 

# SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

**European waste** catalogue (EWC) : 080112

**Packaging** 

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

|                                    | ADR/RID        | ADN            | IMDG           | IATA           |
|------------------------------------|----------------|----------------|----------------|----------------|
| 14.1 UN number or ID number        | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name       | -              | -              | -              | -              |
| 14.3 Transport<br>hazard class(es) | -              | -              | -              | -              |
| 14.4 Packing group                 | -              | -              | -              | -              |
| 14.5<br>Environmental<br>hazards   | No.            | No.            | No.            | No.            |

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

**Annex XIV - List of substances subject to authorisation** 

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

Date of issue/Date of revision : 13/11/2023 13/17 Date of previous issue : No previous validation Version :1 Label No: 73924

# **SECTION 15: Regulatory information**

ŧ

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Product/ingredient name   | %  | Designation [Usage] |
|---------------------------|----|---------------------|
| 2-(2-butoxyethoxy)ethanol | ≤3 | 55 [Consumer paint] |

Labelling

Other EU regulations

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Persistent Organic Pollutants** 

Not listed.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

**National regulations** 

**Austria** 

VbF class : Not regulated.

Limitation of the use of : Permitted.

organic solvents

Czech Republic
Storage code : IV

Denmark

Danish fire class : IV-1 MAL-code : 00-1

**Protection based on MAL** 

: According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 00-1

**Application:** When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Arm protectors must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the

Date of issue/Date of revision: 13/11/2023Date of previous issue: No previous validationVersion: 114/17AQUATOP 2600-60 - BASE TLabel No :73924

# **SECTION 15: Regulatory information**

operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Full mask with combined filter, coveralls and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

List of undesirable substances

: Not listed

**Finland France** 

**Social Security Code,** Articles L 461-1 to L 461-7

: 2-(2-butoxyethoxy)ethanol

**RG 84** 

Reinforced medical

surveillance

: Act of July 11, 1977 determining the list of activities which require reinforced

medical surveillance: not applicable

**Germany** 

**Hazardous incident ordinance** 

<u>Italy</u>

D.Lqs. 152/06 : Not determined.

**Netherlands** 

**Norway Sweden** 

**Switzerland** 

**VOC** content : Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still required.

Date of issue/Date of revision : 13/11/2023 Version:1 15/17 Date of previous issue : No previous validation Label No: 73924

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

#### Full text of abbreviated H statements

| H301   | Toxic if swallowed.                              |
|--------|--|
| H302   | Harmful if swallowed.                            |
| H312   | Harmful in contact with skin.                    |
| H314   | Causes severe skin burns and eye damage.         |
| H315   | Causes skin irritation.                          |
| H317   | May cause an allergic skin reaction.             |
| H318   | Causes serious eye damage.                       |
| H319   | Causes serious eye irritation.                   |
| H400   | Very toxic to aquatic life.                      |
| H411   | Toxic to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract.              |

### Full text of classifications [CLP/GHS]

| Acute Tox. 3      | ACUTE TOXICITY - Category 3                     |
|-------------------|---|
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                     |
| Aquatic Acute 1   | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1  |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 |
| Eye Dam. 1        | SERIOUS EYÈ DAMAGE/EYE IRRITATION - Category 1  |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2  |
| Skin Corr. 1C     | SKIN CORROSION/IRRITATION - Category 1C         |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2          |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                 |
| Skin Sens. 1A     | SKIN SENSITISATION - Category 1A                |
|                   | <b>5</b> ,                                      |

Date of issue/ Date of

revision

: 13/11/2023

Date of previous issue : No previous validation

Version : 1

AQUATOP 2600-60 BASE T BASE 1

#### **Notice to reader**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 13/11/2023 Date of previous issue : No previous validation Version : 1 16/17

Label No: 73924

Date of issue/Date of revision : 13/11/2023 Date of previous issue : No previous validation Version :1 17/17 **Label No** :73924