Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET



AQUATOP 2600-82 - BASE 2

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier Product name

: AQUATOP 2600-82 - BASE 2

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com

responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number: In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

| 2.2 Label elements | | |
|--------------------------------|---|---|
| Signal word | : | No signal word. |
| Hazard statements | : | No known significant effects or critical hazards. |
| Precautionary statements | | |
| Prevention | : | Not applicable. |
| Response | : | Not applicable. |
| Storage | : | Not applicable. |
| Disposal | : | Not applicable. |
| Supplemental label elements | : | Contains adipohydrazide, 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol- 3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-Octyl-2H-isothiazol- 3-one and 2-Methyl-1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and |

breathe spray or mist. Contains biocidal products for in-can preservation: BIT and DTBMA and Bronopol and MIT and OIT and MBIT.

: 24/10/2023 Date of previous issue

: 23/11/2022

SECTION 2: Hazards identification

Annex XVII - Restrictions : on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

2.3 Other hazards

Product meets the criteria : for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do :

not result in classification

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

: None known.

SECTION 3: Composition/information on ingredients

| 3.2 Mixtures Product/ingredient name | : Mixture | % | Classification | Specific Conc. Limits, M-factors and ATEs | Туре |
|---|--|---------|---|---|---------|
| titanium dioxide | REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 | ≤10 | Carc. 2, H351 (inhalation) | - | [1] [*] |
| 1,2-benzisothiazol-3(2H)- one | EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6 | <0.05 | Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 | ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1 | [1] |
| 2-methyl-2H-isothiazol- 3-one | EC: 220-239-6 CAS: 2682-20-4 | <0.0015 | Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 | ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C $\geq 0.0015\%$ M [Acute] = 10 M [Chronic] = 1 | [1] |
| reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1) | CAS: 55965-84-9 Index: 613-167-00-5 | <0.001 | Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 | ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100 | [1] |
| 2-Octyl-2H-isothiazol-3-one | EC: 247-761-7 CAS: 26530-20-1 | <0.001 | Acute Tox. 3, H301 Acute Tox. 3, H311 | ATE [Oral] = 125 mg/kg | [1] |

| | Index: 613-112-00-5 | | Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 | ATE [Dermal] = 311 mg/kg ATE [Inhalation (dusts and mists)] = 0.27 mg/I Skin Sens. 1, H317: C $\geq 0.0015\%$ M [Acute] = 100 M [Chronic] = 100 | |
|---|---------------------------------------|---------|--|--|-----|
| 2-Methyl-1,2-benzisothiazol- 3(2H)-one | CAS: 2527-66-4 Index: 613-336-00-3 | <0.0015 | Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH071 See Section 16 for the full text of the H statements declared above. | ATE [Oral] = 175 mg/kg ATE [Dermal] = 1100 mg/kg Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 1 | [1] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

| 4.1 Description of first aid m | neasures |
|--------------------------------|--|
| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs. |
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. |
| Skin contact | Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. |
| Ingestion | : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. |

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

| Eye contact | : No specific data. |
|--------------|---------------------|
| Inhalation | : No specific data. |
| Skin contact | : No specific data. |
| Ingestion | : No specific data. |

| 4.3 Indication of any immediate medical attention and special treatment needed | | |
|--|---|--|
| Notes to physician | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. | |
| Specific treatments | : No specific treatment. | |

| Date of issue/Date of revision | : 24/10/2023 | Date of previous issue | : 23/11/2022 | Version : 1.01 3/18 |
|--------------------------------|--------------|------------------------|--------------|---------------------|
| AQUATOP 2600-82 - BASE 2 | | | | Label No :51993 |

SECTION 5: Firefighting measures

| 5.1 Extinguishing media | |
|---|---|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |
| 5.2 Special hazards arising | rom the substance or mixture |
| Hazards from the substance or mixture | : In a fire or if heated, a pressure increase will occur and the container may burst. |
| Hazardous combustion products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides |
| 5.3 Advice for firefighters | |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |

SECTION 6: Accidental release measures

| 6.1 Personal precautions, pro | te | ctive equipment and emergency procedures |
|---------------------------------|----|--|
| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. |
| For emergency responders | : | If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| 6.2 Environmental precautions | : | Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
| 6.3 Methods and material for | со | ntainment and cleaning up |
| Small spill | : | Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : | Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. |
| 6.4 Reference to other sections | : | See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information. |

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). |
|--|---|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s) Recommendations

: Not available.

Industrial sector specific solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|---|--|
| Ethyldiglycol | Regulation on Limit Values - MAC (Austria, 4/2021). PEAK: 140 mg/m ³ , 4 times per shift, 15 minutes. PEAK: 24 ppm, 4 times per shift, 15 minutes. TWA: 35 mg/m ³ 8 hours. TWA: 6 ppm 8 hours. |
| 2-methyl-2H-isothiazol-3-one | Regulation on Limit Values - MAC (Austria, 4/2021). [] Skin sensitiser. TWA: 0.05 mg/m ³ 8 hours. |
| reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | Regulation on Limit Values - MAC (Austria, 4/2021). [] Skin sensitiser. |
| 2-Octyl-2H-isothiazol-3-one | TWA: 0.05 mg/m ³ 8 hours. Regulation on Limit Values - MAC (Austria, 4/2021). Absorbed through skin. Sensitization potential. TWA: 0.05 mg/m ³ 8 hours. Form: Inhalable fraction CEIL: 0.05 mg/m ³ 15 minutes. Form: Inhalable fraction |
| No exposure limit value known. | |
| No exposure limit value known. | |
| Propylene glycol | Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). ELV: 10 mg/m ³ 8 hours. Form: only particles ELV: 474 mg/m ³ 8 hours. Form: total vapour and particles ELV: 150 ppm 8 hours. Form: total vapour and particles |
| No exposure limit value known. | |
| No exposure limit value known. | |
| No exposure limit value known. | |
| Date of issue/Date of revision : 24/10/2023 | Date of previous issue : 23/11/2022 Version : 1.01 5/18 |

| No exposure limit value known. | |
|---|--|
| No exposure limit value known. | |
| No exposure limit value known. | |
| No exposure limit value known. | |
| Ethyldiglycol | TRGS 900 OEL (Germany, 7/2021). TWA: 35 mg/m ³ 8 hours. PEAK: 70 mg/m ³ 15 minutes. TWA: 6 ppm 8 hours. PEAK: 12 ppm 15 minutes. DFG MAC-values list (Germany, 10/2021). |
| 1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazol-3-one 2-Octyl-2H-isothiazol-3-one | PEAK: 100 mg/m³, 4 times per shift, 15 minutes. Form: inhalable fraction TWA: 50 mg/m³ 8 hours. Form: inhalable fraction DFG MAC-values list (Germany, 10/2021). Skin sensitiser. DFG MAC-values list (Germany, 10/2021). Skin sensitiser. TRGS 900 OEL (Germany, 7/2021). Absorbed through skin. TWA: 0.05 mg/m³ 8 hours. Form: Inhalable fraction DFG MAC-values list (Germany, 10/2021). Absorbed through skin. TWA: 0.05 mg/m³ 8 hours. Form: Inhalable fraction DFG MAC-values list (Germany, 10/2021). Absorbed through skin. TWA: 0.05 mg/m³ 8 hours. Form: Inhalable fraction DFG MAC-values list (Germany, 10/2021). Absorbed through skin. Skin sensitiser. TWA: 0.05 mg/m³ 8 hours. Form: inhalable fraction PEAK: 0.1 mg/m³, 4 times per shift, 15 minutes. Form: inhalable fraction |
| No exposure limit value known. | |
| No exposure limit value known. | |
| No exposure limit value known. | |
| Propylene glycol | NAOSH (Ireland, 5/2021). Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV-8hr: 10 mg/m ³ 8 hours. Form: particulate OELV-8hr: 470 mg/m ³ 8 hours. Form: vapour and particulates OELV-8hr: 150 ppm 8 hours. Form: vapour and particulates |
| No exposure limit value known. | |
| Propylene glycol | Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021). TWA: 7 mg/m³ 8 hours. |
| Propylene glycol | Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2021). TWA: 7 mg/m³ 8 hours. |
| No exposure limit value known. | |
| No exposure limit value known. | |
| No exposure limit value known. | |
| Propylene glycol | FOR-2011-12-06-1358 (Norway, 6/2021). TWA: 79 mg/m ³ 8 hours. TWA: 25 ppm 8 hours. |
| Propylene glycol | Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). TWA: 100 mg/m ³ 8 hours. Form: vapor and inhalable fraction |
| No exposure limit value known. | |
| ' No exposure limit value known. | |
| • | |
| No exposure limit value known. | |

Date of issue/Date of revision AQUATOP 2600-82 - BASE 2

SECTION 8: Exposure controls/personal protection

| Ethyldiglycol | Regulation on protection of workers from the risks related to |
|---|---|
| | exposure to chemical substances at work (Slovenia, 5/2021). |
| | KTV: 12 ppm, 4 times per shift, 15 minutes. |
| | TWA: 6 ppm 8 hours. |
| | KTV: 70 mg/m ³ , 4 times per shift, 15 minutes. |
| | TWA: 35 mg/m ³ 8 hours. |
| 2-Octyl-2H-isothiazol-3-one | Regulation on protection of workers from the risks related to |
| | exposure to chemical substances at work (Slovenia, 5/2021). |
| | Absorbed through skin. |
| | TWA: 0.05 mg/m ³ 8 hours. Form: Inhalable fraction |
| | KTV: 0.1 mg/m³, 4 times per shift, 15 minutes. Form: Inhalable |
| | fraction |
| No exposure limit value known. | |
| Ethyldiglycol | Work environment authority Regulation 2018:1 (Sweden, |
| | 9/2021). Absorbed through skin. |
| | TWA: 15 ppm 8 hours. |
| | TWA: 80 mg/m ³ 8 hours. |
| | STEL: 30 ppm 15 minutes. |
| | STEL: 170 mg/m ³ 15 minutes. |
| Ethyldiglycol | SUVA (Switzerland, 1/2021). |
| | STEL: 100 mg/m ³ 15 minutes. Form: Inhalable fraction of Vapor |
| | and aerosols |
| | TWA: 50 mg/m ³ 8 hours. Form: Inhalable fraction of Vapor and |
| | aerosols |
| reaction mass of: 5-chloro-2-methyl- | SUVA (Switzerland, 1/2021). Skin sensitiser. |
| 4-isothiazolin-3-one [EC no. 247-500-7] and | |
| 2-methyl-2H-isothiazol-3-one [EC no. | |
| 220-239-6] (3:1) | |
| | STEL: 0.4 mg/m ³ 15 minutes. Form: Inhalable fraction |
| 2 Octul 24 inorthiazol 2 ono | TWA: 0.2 mg/m ³ 8 hours. Form: Inhalable fraction |
| 2-Octyl-2H-isothiazol-3-one | SUVA (Switzerland, 1/2021). Absorbed through skin. Skin sensitiser. |
| | |
| | TWA: 0.05 mg/m ³ 8 hours. Form: Inhalable fraction STEL: 0.1 mg/m ³ 15 minutes. Form: Inhalable fraction |
| | |
| No exposure limit value known. | |

Biological exposure indices

| Product/ingredient name | Exposure indices |
|--|--|
| No exposure indices known. | |
| ate of issue/Date of revision : 24/10/2023 Date of p | revious issue : 23/11/2022 Version : 1.01 7/18 |

| SECTION 8: Exposure controls/pe | rsonal protection |
|---------------------------------|-------------------|
| No exposure indices known. | |

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Туре | Exposure | Value | Population | Effects |
|---|--------|--------------------------|-----------------------------|-----------------------|--|
| adipohydrazide | DNEL | Long term Inhalation | 17.5 mg/m ³ | Workers | Systemic |
| 1,2-benzisothiazol-3(2H)-one | DNEL | Long term Dermal | 0.345 mg/ kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 0.966 mg/ kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 1.2 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 6.81 mg/m³ | Workers | Systemic |
| 2-methyl-2H-isothiazol-3-one | DNEL | Long term Inhalation | 0.021 mg/ m³ | General population | Local |
| | DNEL | Long term Inhalation | 0.021 mg/ m ³ | Workers | Local |
| | DNEL | Long term Oral | 0.027 mg/ kg bw/day | General population | Systemic |
| | DNEL | Short term Inhalation | 0.043 mg/ | General population | Local |
| | DNEL | Short term Inhalation | 0.043 mg/ m ³ | Workers | Local |
| | DNEL | Short term Oral | 0.053 mg/ kg bw/day | General population | Systemic |
| reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1) | DNEL | Long term Inhalation | 0.02 mg/m ³ | | Local |
| () | DNEL | Long term Inhalation | 0.02 mg/m ³ | Workers | Local |
| | DNEL | Short term | 0.04 mg/m ³ | General | Local |
| e of issue/Date of revision : 24/1 | 0/2023 | Date of previous issue | : 23/11/20 | 022 | Version : 1.01 8/18 |
| te of issue/Date of revision : 24/1 QUATOP 2600-82 - BASE 2 | 0/2023 | Date of previous issue | : 23/11/20 | | Version : 1.01 bel No : <mark>5</mark> 1993 |

| SECTION 8: Exposure controls/personal protection | | | | | | | |
|--|-----------------|------------------------|--------------------|----------|--|--|--|
| | Inhalation | | population | | | | |
| DNEL | Short term | 0.04 mg/m ³ | Workers | Local | | | |
| | Inhalation | _ | | | | | |
| DNEL | Long term Oral | 0.09 mg/ | General | Systemic | | | |
| | | kg bw/day | population | | | | |
| DNEL | Short term Oral | 0.11 mg/ kg bw/day | General population | Systemic | | | |

PNECs

No PNECs available

| 8.2 Exposure controls | | |
|-------------------------------------|--|-------------------|
| Appropriate engineering controls | Good general ventilation should be sufficient to control worker exposure to air contaminants. | borne |
| Individual protection measu | <u>s</u> | |
| Hygiene measures | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working p Appropriate techniques should be used to remove potentially contaminated cle Wash contaminated clothing before reusing. Ensure that eyewash stations ar safety showers are close to the workstation location. | eriod. othing. |
| Eye/face protection | Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, r gases or dusts. If contact is possible, the following protection should be worn unless the assessment indicates a higher degree of protection: safety glasse side-shields. | mists, ı, |
| Skin protection | | |
| Hand protection | Chemical-resistant, impervious gloves complying with an approved standard s be worn at all times when handling chemical products if a risk assessment inc this is necessary. | |
| | Recommendations : Wear suitable gloves tested to EN374. | |
| | > 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm | |
| | Not recommended polyvinyl alcohol (PVA) gloves | |
| Body protection | Personal protective equipment for the body should be selected based on the t being performed and the risks involved and should be approved by a specialis before handling this product. | |
| Other skin protection | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should approved by a specialist before handling this product. | d be |
| Respiratory protection | Based on the hazard and potential for exposure, select a respirator that meets appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other imp aspects of use. | а |
| | Filter type (spray application): A P | |
| Environmental exposure controls | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislat In some cases, fume scrubbers, filters or engineering modifications to the pro equipment will be necessary to reduce emissions to acceptable levels. | |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties **Appearance Physical state** : Liquid. : White. Colour Odour : Slight : Not available. **Odour threshold** Melting point/freezing point : Not available. Date of issue/Date of revision Version : 1.01 9/18 : 24/10/2023 Date of previous issue : 23/11/2022 Label No :51993 AQUATOP 2600-82 - BASE 2

SECTION 9: Physical and chemical properties

2

Initial boiling point and boiling range

| Ingredient name | °C | °F | Method |
|------------------|-------|-------|--------|
| Water | 100 | 212 | |
| Propylene glycol | 188.2 | 370.8 | |

Lower and upper explosion : Lower: Not applicable. Upper: Not applicable.

2

: Not applicable.

Flash point

limit

: Closed cup: >100°C (>212°F) ż

Auto-ignition temperature

| Ingredient name | | | °C | °F | | Method | |
|----------------------------------|------------------|----------|----------|-------|--|--------|--|
| ⊑ thyldiglycol | 204 | | | 399.2 | | | |
| Propylene glycol | Propylene glycol | | 371 | 699.8 | | | |
| Decomposition temperature | : | Not ava | ilable. | | | | |
| рН | : | 8 to 8.5 | | | | | |
| Viscosity | 1 | Not ava | ilable. | | | | |
| Solubility(ies) | 1 | | | | | | |
| Not available. | | | | | | | |
| Solubility in water | : | Not ava | ilable. | | | | |
| Partition coefficient: n-octanol | : | Not app | licable. | | | | |

Vapour pressure

Median particle size

water

| | Va | apour Pres | sure at 20°C | Vapour pressure at 50°C | | | |
|--------------------------|-------|------------|--------------|-------------------------|-----|--------|--|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method | |
| water | 17.5 | 2.3 | | | | | |
| Propylene glycol | 0.15 | 0.02 | EU A.4 | | | | |
| Relative density | : Not | available. | | · | | | |
| Density | : 1.1 | g/cm³ | | | | | |
| /apour density | : Not | available. | | | | | |
| Explosive properties | : Not | available. | | | | | |
| Dxidising properties | : Not | available. | | | | | |
| Particle characteristics | | | | | | | |

SECTION 10: Stability and reactivity

| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients |
|--|--|
| 10.2 Chemical stability | : The product is stable. |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : No specific data. |
| 10.5 Incompatible materials | : No specific data. |
| 10.6 Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |
| Date of issue/Date of revision AQUATOP 2600-82 - BASE 2 | : 24/10/2023 Date of previous issue : 23/11/2022 Version : 1.01 10/1 Label No : 51993 |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|---------------------------------|----------------------|------------------------|----------|
| ✓,2-benzisothiazol-3(2H)- one | LD50 Oral | Rat | 1020 mg/kg | - |
| 2-methyl-2H-isothiazol- 3-one | LC50 Inhalation Dusts and mists | Rat | 0.11 mg/l | 4 hours |
| reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1) | LD50 Oral | Rat | 53 mg/kg | - |
| 2-Octyl-2H-isothiazol-3-one | LD50 Dermal LD50 Oral | Rabbit Rat | 690 mg/kg 550 mg/kg | - |
| Conclusion/Summary | : Based on available data, the | classification crite | eria are not met. | · |

Acute toxicity estimates

| Route | ATE value |
|--------------------|-------------|
| halation (vapours) | 366.86 mg/l |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|------------------------|---------|-------|----------------------|-------------|
| titanium dioxide | Skin - Mild irritant | Human | | 72 hours 300 ug l | - |
| 1,2-benzisothiazol-3(2H)-one | Skin - Mild irritant | Human | - | 48 hours 5 % | - |
| reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1) | Skin - Severe irritant | Human | - | 0.01 % | - |
| 2-Octyl-2H-isothiazol-3-one | Eyes - Severe irritant | Rabbit | - | 100 mg | - |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Sensitisation

Conclusion/Summary : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

| Conclusion/Summary | : Based on available data, the classification criteria are not met. |
|-----------------------------|---|
| Reproductive toxicity | |
| Conclusion/Summary | : Based on available data, the classification criteria are not met. |
| Teratogenicity | |
| Conclusion/Summary | : Based on available data, the classification criteria are not met. |
| Specific target organ toxic | <u>city (single exposure)</u> |
| Not available. | |
| Specific target organ toxic | city (repeated exposure) |

Not available.

Aspiration hazard

Not available.

| Information on likely routes of exposure | : Not available. |
|---|--|
| Potential acute health effects | |
| Eye contact | : No known significant effects or critical hazards. |
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : No known significant effects or critical hazards. |
| Ingestion | : No known significant effects or critical hazards. |
| Symptoms related to the phy | sical, chemical and toxicological characteristics |
| Eye contact | : No specific data. |
| Inhalation | : No specific data. |
| Skin contact | : No specific data. |
| Ingestion | : No specific data. |
| Short term exposure Potential immediate effects | ts as well as chronic effects from short and long-term exposure : Not available. |
| Potential delayed effects | : Not available. |
| Long term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Potential chronic health effe | ects |
| Not available. | |
| Conclusion/Summary | : Not available. |
| General | : No known significant effects or critical hazards. |
| Carcinogenicity | : No known significant effects or critical hazards. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Reproductive toxicity | : No known significant effects or critical hazards. |

11.2 Information on other hazards

- 11.2.1 Endocrine disrupting properties
- Not available.
- **11.2.2 Other information**

Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------------|--|---|--------------------|
| inanium dioxide | Acute LC50 3 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 6.5 mg/l Fresh water | Daphnia - <i>Daphnia pulex -</i> Neonate | 48 hours |
| | Acute LC50 >1000000 μg/l Marine water | Fish - Fundulus heteroclitus | 96 hours |
| 1,2-benzisothiazol-3(2H)-one | Acute EC50 0.36 mg/l Marine water | Algae - Skeletonema Costatum | 72 hours |
| | Acute EC50 3.7 mg/l | Daphnia - Daphnia Magna | 48 hours |
| | Acute LC50 1.9 mg/l Fresh water | Fish - Onorhynchus Mykiss | 96 hours |
| | Acute NOEC 0.15 mg/l Marine water | Algae - Skeletonema Costatum | 72 hours |
| 2-methyl-2H-isothiazol-3-one | Acute EC50 0.18 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| - | Acute LC50 0.07 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| 2-Octyl-2H-isothiazol-3-one | Acute EC50 107 ppb Fresh water | Daphnia - Daphnia magna | 48 hours |
| ate of issue/Date of revision | : 24/10/2023 Date of previous issue | : 23/11/2022 Version | :1.01 12/18 |
| QUATOP 2600-82 - BASE 2 | | Label No | :5 1993 |

| SECTION 12: Ecological information | | | | | |
|---|--|---|--------------------------------|--|--|
| | Acute LC50 47 ppb Fresh water Chronic NOEC 74 ppb Fresh water Chronic NOEC 8.5 ppb | Fish - Oncorhynchus mykiss Daphnia - Daphnia magna Fish - Pimephales promelas | 96 hours 21 days 35 days | | |
| 2-Methyl-1,2-benzisothiazol- 3(2H)-one | Acute EC50 0.22 ppm Fresh water | Algae - Pseudokirchneriella subcapitata | 96 hours | | |
| | Acute EC50 0.92 ppm Fresh water Acute LC50 0.24 ppm Fresh water | Daphnia - <i>Daphnia magna</i> Fish - <i>Oncorhynchus mykiss</i> - Juvenile (Fledgling, Hatchling, Weanling) | 48 hours 96 hours | | |
| | Chronic NOEC 0.16 ppm | Fish - Pimephales promelas | 32 days | | |

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | | Dose | Inoculum |
|---|---------------------|----------------|------------|------|------------------|
| 7,2-benzisothiazol-3(2H)-one | EU | 24 % - 28 days | | - | - |
| Conclusion/Summary : This product has not been tested for biodegradation. | | | | | |
| Product/ingredient name | Aquatic half-life F | | Photolysis | 5 | Biodegradability |
| 7,2-benzisothiazol-3(2H)-one | - | | - | | Inherent |

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|------------------------------|--------|-----|-----------|
| 7,2-benzisothiazol-3(2H)-one | - | 3.2 | Low |
| 2-Octyl-2H-isothiazol-3-one | 2.45 | | Low |

| 12.4 Mobility in soil | |
|---|------------------|
| Soil/water partition coefficient (Koc) | : Not available. |
| Mobility | : Not available. |

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

| 13.1 Waste treatment method | ds | | | |
|-----------------------------------|---|--|--|--|
| Product | | | | |
| Methods of disposal | Disposal o with the red any region products vi | quirements of environmer al local authority requirem a a licensed waste dispos o the sewer unless fully c | nd any by-products ntal protection and v ients. Dispose of su sal contractor. Was | d wherever possible. should at all times comply vaste disposal legislation and urplus and non-recyclable te should not be disposed of quirements of all authorities |
| Hazardous waste | | present knowledge of the waste, as defined by EU | | |
| European waste catalogue (EWC) | : 080112 | | | |
| Packaging | | | | |
| Date of issue/Date of revision | : 24/10/2023 | Date of previous issue | : 23/11/2022 | Version : 1.01 13/18 |
| AQUATOP 2600-82 - BASE 2 | | | | Label No :51993 |

Label No :51993

SECTION 13: Disposal considerations

| Methods of disposal | : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. |
|---------------------|---|
| Special precautions | : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. |

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | ΙΑΤΑ |
|------------------------------------|----------------|----------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - | - |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. | No. |

: Not relevant/applicable due to nature of the product.

user

14.6 Special precautions for : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Labelling | : | |
|---|----|-----------------------|
| Other EU regulations | | |
| Industrial emissions (integrated pollution prevention and control) - Air | : | Not listed |
| Industrial emissions (integrated pollution prevention and control) - Water | : | Not listed |
| Explosive precursors | : | Not applicable. |
| Ozone depleting substanc | es | <u>(1005/2009/EU)</u> |

SECTION 15: Regulatory information

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

| National regulations | | |
|---|---|----------------|
| <u>Austria</u> | | |
| VbF class | : | Not regulated. |
| Limitation of the use of organic solvents | : | Permitted. |
| Czech Republic | | |
| Storage code | : | IV |
| <u>Denmark</u> | | |
| Danish fire class | : | IV-1 |
| Executive Order No. 1795/2015 | | |
| Ingredient name | | |

| Ingredient name | Annex I Section A | Annex I Section B |
|-----------------|-------------------|-------------------|
| Manium dioxide | Listed | - |

| MAL-code | : 00-1 |
|-------------------------|--|
| Protection based on MAL | : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment: |

General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 00-1 **Application:** When spraying in existing* spray booths, if the operator is outside the spray zone.

- Arm protectors must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Full mask with combined filter, coveralls and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

| Date of issue/Date of revision | : 24/10/2023 | Date of previous issue | : 23/11/2022 | Version : 1.01 15/18 |
|--------------------------------|--------------|------------------------|--------------|--------------------------------|
| AQUATOP 2600-82 - BASE 2 | | | | Label No : <mark>5</mark> 1993 |

SECTION 15: Regulatory information

| | *See Regulations. |
|---|--|
| Restrictions on use | Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work |
| List of undesirable substances | Not listed |
| Carcinogenic waste | Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks. |
| <u>Finland</u> France | |
| Reinforced medical surveillance | Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable |
| Germany | |
| Storage class (TRGS 510) | 10 |
| Hazardous incident ordina | |
| This product is not controlle | der the Germany Hazardous Incident Ordinance. |
| Hazard class for water | 1 |
| Technical instruction on air quality control | TA-Luft Number 5.2.5: 5.1% |
| ΑΟΧ | The product contains organically bound halogens and can contribute to the AOX value in waste water. |
| <u>Italy</u> | |
| D.Lgs. 152/06 | Not determined. |
| <u>Netherlands</u> | |
| Water Discharge Policy (ABM) | A(3) Hazardous for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A |
| <u>Norway</u> | |
| <u>Sweden</u> | |
| Switzerland | |
| VOC content | Exempt. |
| International regulations | |
| Chemical Weapon Convent Not listed. | List Schedules I, II & III Chemicals |
| Montreal Protocol Not listed. | |
| Stockholm Convention on | istant Organic Pollutants |
| Not listed. | istent organic Politiants |
| Rotterdam Convention on F Not listed. | <u>Informed Consent (PIC)</u> |
| UNECE Aarhus Protocol on | <u>Ps and Heavy Metals</u> |
| Not listed. | |
| 15.2 Chemical safety assessment | This product contains substances for which Chemical Safety Assessments are still required. |

SECTION 16: Other information

Indicates information that has changed from previously issued version.

| | as onlyinged norm previously issued version. |
|---------------------------------|---|
| Abbreviations and acronyms | ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level |
| | EUH statement = CLP-specific Hazard statement |
| | N/A = Not available |
| | PBT = Persistent, Bioaccumulative and Toxic |
| | PNEC = Predicted No Effect Concentration |
| | RRN = REACH Registration Number |
| | SGG = Segregation Group |
| | vPvB = Very Persistent and Very Bioaccumulative |
| Due and the trend to device the | electricities according to Description (EC) No. 4272/2000 [CLD/CUS] |

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Not classified.

Full text of abbreviated H statements

| H301 | Toxic if swallowed. |
|--------|---|
| H302 | Harmful if swallowed. |
| H310 | Fatal in contact with skin. |
| H311 | Toxic in contact with skin. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H330 | Fatal if inhaled. |
| H351 | Suspected of causing cancer. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

Full text of classifications [CLP/GHS]

| Acute Tox. 2 | ACUTE TOXICITY - Category 2 |
|------------------------|---|
| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Aquatic Acute 1 | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 |
| Carc. 2 | CARCINOGENICITY - Category 2 |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| Skin Corr. 1 | SKIN CORROSION/IRRITATION - Category 1 |
| Skin Corr. 1B | SKIN CORROSION/IRRITATION - Category 1B |
| Skin Corr. 1C | SKIN CORROSION/IRRITATION - Category 1C |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITISATION - Category 1 |
| Skin Sens. 1A | SKIN SENSITISATION - Category 1A |
| Date of issue/ Date of | : 24/10/2023 |

| revision | |
|------------------------|------------------------|
| Date of previous issue | : 23/11/2022 |
| Version | : 1.01 |
| | AQUATOP 2600-82_BASE 2 |

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

: 24/10/2023 Date of previous issue

: 23/11/2022

Date of issue/Date of revision AQUATOP 2600-82 - BASE 2