# Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

# **SAFETY DATA SHEET**

AQUATOP 2600-82 - CLEAR T070



### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier Product name

: AQUATOP 2600-82 - CLEAR T070

**1.2 Relevant identified uses of the substance or mixture and uses advised against Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

# responsible for this SDS

### National contact

Teknos (UK) Limited, 7 Longlands Rd, Bicester, Oxfordshire OX26 5AH, United Kingdom. Tel. +44 (0) 1869 208005.

### 1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS Skin Sens. 1, H317

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Hazard pictograms



Signal word Hazard statements <u>Precautionary statements</u>	: Warning : H317 - May cause an allergic skin reaction.	
Prevention	: P280 - Wear protective gloves. P261 - Avoid breathing vapour.	
Response	<ul> <li>P362 + P364 - Take off contaminated clothing and wash it before reuse.</li> <li>P302 + P352 - IF ON SKIN: Wash with plenty of water.</li> <li>P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.</li> </ul>	
Storage	Not applicable.	
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.	
Supplemental label elements	: Contains biocidal products for dry film and in-can preservation: IPBC and BIT ar DTBMA and Bronopol and MIT and MBIT and OIT. Risk of skin sensitisation.	٦d

SECTION 2: Hazards identification		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

# **SECTION 3: Composition/information on ingredients**

B.2 Mixtures : N	1			
Product/ingredient name	Identifiers	%	Classification	Туре
Dipropyleneglycolmethylether	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤3	Not classified.	[2]
EO bis(benztriazolyl) phenylpropionat	REACH #: 01-0000015075-76 EC: 400-830-7 CAS: 104810-48-2 Index: 607-176-00-3	<1	Skin Sens. 1A, H317 Aquatic Chronic 2, H411	[1]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤0.1	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
Ammonia	REACH #: 01-2119488876-14 EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	<0.1	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1)	[1] [2]
Propylene glycol	REACH #: 01-2119456809-23 EC: 200-338-0 CAS: 57-55-6	≤0.1	Not classified.	[2]
Formaldehyde	REACH #: 01-2119488953-20 EC: 200-001-8 CAS: 50-00-0 Index: 605-001-00-5	<0.01	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1)	[1] [2]

SECTION 3: Composition/information on ingredients		
		Aquatic Chronic 1, H410 (M=10)
		See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

# SECTION 4: First aid measures

### 4.1 Description of first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms				
Eye contact	: No specific data.			
Inhalation	: No specific data.			
Skin contact	: Adverse symptoms may include the following: irritation redness			
Ingestion	: No specific data.			

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Date of issue/Date of revision	: 20/07/2022	Date of previous issue	: No previous validation	Version	:1	3/17
AQUATOP 2600-82 - CLEAR T070	)			Label No	:3836	1

#### SECTION 4: First aid measures **Specific treatments** : No specific treatment. SECTION 5: Firefighting measures 5.1 Extinguishing media Suitable extinguishing : Use an extinguishing agent suitable for the surrounding fire. media Unsuitable extinguishing : None known. media 5.2 Special hazards arising from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. Hazards from the substance or mixture **Hazardous combustion** : Decomposition products may include the following materials: carbon dioxide products carbon monoxide nitrogen oxides 5.3 Advice for firefighters **Special protective actions** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without for fire-fighters suitable training. Fire-fighters should wear appropriate protective equipment and self-contained **Special protective** 2

breathing apparatus (SCBA) with a full face-piece operated in positive pressure

### **SECTION 6: Accidental release measures**

equipment for fire-fighters

mode.

erri ereenan preesaanene, pre			
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
6.3 Methods and material for	со	ntainment and cleaning up	
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	:	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazar as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.	
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.	
Date of issue/Date of revision		: 20/07/2022 Date of previous issue : No previous validation Version : 1 4/17	

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Occupational exposure limits	
Dipropyleneglycolmethylether	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
	through skin.
	TWA: 308 mg/m <sup>3</sup> 8 hours.
	TWA: 50 ppm 8 hours.
2-Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
	through skin.
	STEL: 50 ppm 15 minutes.
	TWA: 25 ppm 8 hours.
	STEL: 246 mg/m <sup>3</sup> 15 minutes.
	TWA: 123 mg/m <sup>3</sup> 8 hours.
Ammonia	EH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia]
	STEL: 25 mg/m <sup>3</sup> 15 minutes. Form: anhydrous
	STEL: 35 ppm 15 minutes. Form: anhydrous
	TWA: 25 ppm 8 hours. Form: anhydrous
	TWA: 18 mg/m <sup>3</sup> 8 hours. Form: anhydrous
Propylene glycol	EH40/2005 WELs (United Kingdom (UK), 1/2020).
	TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Particulate
	TWA: 474 mg/m <sup>3</sup> 8 hours. Form: total vapour and particulates
	TWA: 150 ppm 8 hours. Form: total vapour and particulates
Formaldehyde	EH40/2005 WELs (United Kingdom (UK), 1/2020).
	STEL: 2.5 mg/m <sup>3</sup> 15 minutes.
	STEL: 2 ppm 15 minutes.
	TWA: 2 ppm 8 hours.
	TWA: 2.5 mg/m³ 8 hours.

### **SECTION 8: Exposure controls/personal protection**

procedures

**Recommended monitoring** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Dipropyleneglycolmethylether	DNEL	Long term Oral	0.33 mg/	General	Systemic
		-	kg bw/day	population	
	DNEL	Long term	37.2 mg/m <sup>3</sup>	General	Systemic
		Inhalation	•··	population	- ) - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1
	DNEL	Long term Dermal	121 mg/kg	General	Systemic
	DINLL	Long term Derma			Systemic
			bw/day	population	0
	DNEL	Long term Dermal	283 mg/kg	Workers	Systemic
			bw/day		
	DNEL	Long term	308 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			
3-iodo-2-propynyl-butyl carbamate	DNEL	Long term	0.023 mg/	Workers	Systemic
		Inhalation	m³		
	DNEL	Short term	0.07 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	J. J		-
	DNEL	Short term	1.16 mg/m <sup>3</sup>	Workers	Local
		Inhalation	g,		
	DNEL	Long term	1.16 mg/m <sup>3</sup>	Workers	Local
		Inhalation	1.10 mg/m	WOINCIS	Local
	DNEL		2 mg/kg	Workers	Svotomio
	DNEL	Long term Dermal	2 mg/kg	VIOINEIS	Systemic
			bw/day	<b>A</b>	
2-Butoxyethanol	DNEL	Long term Oral	6.3 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Short term Oral	26.7 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term	59 mg/m³	General	Systemic
		Inhalation	_	population	
	DNEL	Long term Dermal	75 mg/kg	General	Systemic
		5	bw/day	population	,
	DNEL	Short term Dermal	89 mg/kg	General	Systemic
		onort term Derma	bw/day	population	Oysternie
	DNEL	Short torm Dormal		Workers	Sustamia
	DNEL	Short term Dermal	89 mg/kg	WOIKEIS	Systemic
		1	bw/day	\ <b>\</b> /	0
	DNEL	Long term	98 mg/m³	Workers	Systemic
		Inhalation			
	DNEL	Long term Dermal	125 mg/kg	Workers	Systemic
			bw/day		
	DNEL	Short term	147 mg/m³	General	Local
		Inhalation		population	
	DNEL	Short term	246 mg/m <sup>3</sup>	Workers	Local
		Inhalation	_		
	DNEL	Short term	426 mg/m <sup>3</sup>	General	Systemic
		Inhalation	<u> </u>	population	
	DNEL	Short term	1091 mg/	Workers	Systemic
		Inhalation	m <sup>3</sup>		- , - , - , - , - , - , - , - , - , - ,
Propylene glycol	DNEL	Long term	10 mg/m <sup>3</sup>	General	Local
		Inhalation	i o mg/m	population	Looal
	DNEL		10 mg/m <sup>3</sup>	Workers	
	DINEL	Long term	io mg/m	VVUINCIS	Local
		Inhalation	50	0	Ct
	DNEL	Long term	50 mg/m³	General	Systemic
		Inhalation		population	
	DNEL	Long term	168 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			
Formaldehyde	DNEL	Long term Dermal	0.012 mg/	General	Local
			cm <sup>2</sup>	population	
	DNEL	Long term Dermal	0.037 mg/	Workers	Local
			cm <sup>2</sup>		
					1

Label No :38361

DNEL	Long term	0.1 mg/m <sup>3</sup>	General	Local
	Inhalation		population	
DNEL	Long term	3.2 mg/m <sup>3</sup>	General	Systemic
	Inhalation		population	
DNEL	Long term Oral	4.1 mg/kg	General	Systemic
		bw/day	population	
DNEL	Long term	9 mg/m³	Workers	Systemic
	Inhalation			
DNEL	Long term Dermal	102 mg/kg	General	Systemic
		bw/day	population	
DNEL	Long term Dermal	240 mg/kg	Workers	Systemic
		bw/day		
DNEL	Long term	0.375 mg/	Workers	Local
	Inhalation	m³		
DNEL	Short term	0.75 mg/m <sup>3</sup>	Workers	Local
	Inhalation	_		

#### **PNECs**

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	<ul> <li>Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.</li> <li>Filter type (spray application): A P</li> </ul>

: 20/07/2022 Date of previous issue

### **SECTION 8: Exposure controls/personal protection**

Environmental	exposure
controls	

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Clear.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name		°C	°F	Method
water		100	212	
Dipropyleneglycolmethylether		189.6	373.3	EU A.2
Flammability (solid, gas) : Not ava		ilable.		
Upper/lower flammability or : Lower: N		Not applicable.		

#### Upper: Not applicable. explosive limits **Flash point** : Closed cup: >100°C (>212°F)

Α	Auto-ignition temperature :					
	Ingredient name	°C	°F	Method		
	Dipropyleneglycolmethylether	207	404.6	EU A.15		

Decomposition temperature	: Not available.
---------------------------	------------------

рН	: 7.7 to 8.1 [Conc. (% w/w): 100%]
Viscosity	: Not available.

ŝ

ŝ

### Solubility(ies) Not available.

Solubility in water	;	Not available.
Partition coefficient: n-octanol/	÷	Not applicable.

#### water

Upp

### Vapour pressure

	Va	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	23.8	3.2					
Relative density	: Not	available.					
Density	: 1 g/	/cm³					
/apour density	: Not	available.					
Explosive properties	: Not	available.					

**Oxidising properties** : Not available.

### : Not applicable.

Date of issue/Date of revision AQUATOP 2600-82 - CLEAR T070

**Particle characteristics** Median particle size

> : 20/07/2022 Date of previous issue

<b>SECTION 10: Stabilit</b>	and reactivity	
10.1 Reactivity	No specific test data related to reactivity available for this product or its ing	redients.
10.2 Chemical stability	The product is stable.	
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not o	occur.
10.4 Conditions to avoid	No specific data.	
10.5 Incompatible materials	No specific data.	
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition pro should not be produced.	oducts

# **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl-butyl	LC50 Inhalation Dusts and	Rat	0.67 g/m³	4 hours
carbamate	mists			
	LC50 Inhalation Dusts and	Rat	0.763 mg/l	4 hours
	mists			
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	400 mg/kg	-
Ammonia	LD50 Oral	Rat	350 mg/kg	-
Propylene glycol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
Formaldehyde	LC50 Inhalation Gas.	Rat	250 ppm	4 hours
,	LD50 Dermal	Rabbit	270 mg/kg	-
	LD50 Oral	Rat	100 mg/kg	-

### Conclusion/Summary

: Based on available data, the classification criteria are not met.

### Acute toxicity estimates

Route	ATE value
Not available.	

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Dipropyleneglycolmethylether	Eyes - Mild irritant	Human	-	8 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Rabbit	-	500 mg	-
3-iodo-2-propynyl-butyl carbamate	Eyes - Severe irritant	Rabbit	-	-	-
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
Ammonia	Eyes - Severe irritant	Rabbit	-	0.5 minutes	-
				1 mg	
	Eyes - Severe irritant	Rabbit	-	250 ug	-
Propylene glycol	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Human	-	168 hours	-
				500 mg	
	Skin - Mild irritant	Woman	-	96 hours 30 %	-
ate of issue/Date of revision	: 20/07/2022 Date of previous	<b>issue</b> : No	previous val	idation Versio	on:1 9/17

	Skin - Moderate irritant	Child	-	96 hours 30 -	
				% C	
	Skin - Moderate irritant	Human	-	72 hours 104 - mg I	
Formaldehyde	Eyes - Mild irritant	Human	-	6 minutes 1 -	
				ppm	
	Eyes - Severe irritant	Rabbit	-	24 hours 750 -	
				ug	
	Eyes - Severe irritant	Rabbit	-	750 ug -	
	Skin - Mild irritant	Human	-	72 hours 150 - ug l	
	Skin - Mild irritant	Rabbit	-	540 mg -	
	Skin - Moderate irritant	Rabbit	-	24 hours 50 -	
				mg	
	Skin - Severe irritant	Human	-	0.01 % -	
	Skin - Severe irritant	Rabbit	-	0.8 % -	
	Skin - Severe irritant	Rabbit	-	24 hours 2 -	
				mg	

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
3-iodo-2-propynyl-butyl carbamate	skin	Guinea pig	Not sensitizing

**Conclusion/Summary** : May cause an allergic skin reaction.

### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
3-iodo-2-propynyl-butyl carbamate	-	Experiment: In vitro Subject: Bacteria	Negative

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### **Carcinogenicity**

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
3-iodo-2-propynyl-butyl carbamate	Negative	-	Negative	Rabbit - Female	Oral: 20 mg/kg	13 days; 7 days per week
	Positive	-	Negative	Rabbit - Female		13 days; 7 days per week

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Teratogenicity** 

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl-butyl carbamate	Negative - Oral	Rabbit - Female	50 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Ammonia	Category 3	-	Respiratory tract irritation
Formaldehyde	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

: 20/07/2022 Date of previous issue

sue : No previous validation

AQUATOP 2600-82 - CLEAR T070

Date of issue/Date of revision

Product/ingredient name			Category	Route of exposure	Target organs
3-iodo-2-propynyl-butyl carba	ama	ate	Category 1	-	larynx
Aspiration hazard Not available.					
nformation on likely routes f exposure	:	Not available.			
otential acute health effects	2				
Eye contact	:	No known significant effect	ts or critical hazards	6.	
Inhalation	:	No known significant effect	ts or critical hazards	6.	
Skin contact	:	May cause an allergic skin	reaction.		
Ingestion	:	: No known significant effects or critical hazards.			
symptoms related to the phy	<u>/sic</u>	cal, chemical and toxicolo	gical characteristic	<u>25</u>	
Eye contact	:	No specific data.			
Inhalation	:	No specific data.			
Skin contact	:	Adverse symptoms may in irritation redness	clude the following:		
Ingestion	:	No specific data.			
elayed and immediate effect	ts	as well as chronic effects	from short and lor	ng-term exposur	e
Short term exposure					_
Potential immediate effects	:	Not available.			
Potential delayed effects	:	Not available.			
-					
Long term exposure	1	Not available.			
-	1				
Long term exposure Potential immediate effects Potential delayed effects	:	Not available.			
Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effe	:				
Long term exposure Potential immediate effects Potential delayed effects	:				
Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effe	: ect				
Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effects Not available.	: <u>ect</u> :	<u>s</u>	allergic reaction ma	y occur when sub	sequently exposed
Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effects Not available. Conclusion/Summary	: ect :	<b>s</b> Not available. Once sensitized, a severe	-	-	sequently exposed
Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effe Not available. Conclusion/Summary General	: ect : :	<ul> <li>Not available.</li> <li>Once sensitized, a severe to very low levels.</li> </ul>	ts or critical hazards	5.	sequently exposed
Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effe Not available. Conclusion/Summary General Carcinogenicity	: ect : : :	<b>S</b> Not available. Once sensitized, a severe to very low levels. No known significant effect	ts or critical hazards ts or critical hazards	). ).	esequently exposed

# **SECTION 12: Ecological information**

12.1 Toxicity

# **SECTION 12: Ecological information**

Product/ingredient name	Result	Species	Exposure
3-iodo-2-propynyl-butyl	Acute EC50 0.022 mg/l Fresh water	Algae - Algae - Scenedemus	72 hours
carbamate	_	subspicatus	
	Acute EC50 0.16 mg/l Fresh water	Daphnia - Daphnia - Daphnia	48 hours
		magna	
	Acute LC50 0.067 mg/l Fresh water	Fish - Trout - Oncorhynchus	96 hours
		mykiss	
	Acute NOEC 0.049 mg/l Fresh water	Fish - Trout - Oncorhynchus	96 hours
	Chronic NOEC 0.05 mg/l Fresh water	mykiss Daphnia - Daphnia - Daphnia	21 days
	Chronic NOEC 0.05 mg/r Fresh water	Magna	ZTuays
2-Butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - Water flea - Daphnia	48 hours
	Acute 2000 - 1000 mg/11 resh water	magna	40 110013
	Acute LC50 800000 µg/l Marine water	Crustaceans - Common shrimp,	48 hours
		sand shrimp - Crangon crangon	
	Acute LC50 1250000 µg/l Marine water	Fish - Inland silverside -	96 hours
		Menidia beryllina	
Ammonia	Acute LC50 37 ppm Fresh water	Fish - Western mosquitofish -	96 hours
		Gambusia affinis - Adult	
Propylene glycol	Acute EC50 19300 mg/l Fresh water	Algae - Algae	96 hours
	Acute EC50 43500 mg/l Fresh water	Daphnia - Daphnia - Daphnia	48 hours
		magna	401
	Acute LC50 18340000 µg/l Fresh water	Crustaceans - Water flea -	48 hours
	Acute LC50 40613 mg/l Fresh water	Ceriodaphnia dubia Fish - Trout - Oncorhynchus	96 hours
	Acute LC50 40015 mg/l Flesh water	mykiss	90 Hours
Formaldehyde	Acute EC50 3.48 mg/l Fresh water	Algae - Green algae -	72 hours
ronnaldenyde		Desmodesmus subspicatus	
	Acute EC50 0.788 mg/l Marine water	Algae - Green algae - Ulva	96 hours
	3	pertusa	
	Acute EC50 12.98 mg/l Fresh water	Crustaceans - Water flea -	48 hours
		Ceriodaphnia dubia - Neonate	
	Acute EC50 5800 µg/l Fresh water	Daphnia - Water flea - Daphnia	48 hours
		pulex - Neonate	
	Acute LC50 1.41 ppm Fresh water	Fish - Rainbow trout,donaldson	96 hours
		trout - Oncorhynchus mykiss	
	Chronic NOEC 0.005 mg/l Marine	Algae - Haptophyte - Isochrysis	96 hours
	water	galbana - Exponential growth	
	Chronic NOEC 052 0 ppm Freeh water	phase Fish Chinack colmon	12 dovo
	Chronic NOEC 953.9 ppm Fresh water	Fish - Chinook salmon - Oncorhynchus tshawytscha -	43 days
		Egg	
		-39	

Conclusion/Summary

: Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

<b>Conclusion/Summary</b>	: This product has not been tested fo	r biodegradation.	
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-iodo-2-propynyl-butyl carbamate	-	-	Not readily

#### **12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Dipropyleneglycolmethylether 3-iodo-2-propynyl-butyl carbamate	0.004 >1	-	low low

### 12.4 Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

### **SECTION 12: Ecological information**

**Mobility** 

: Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

13.1 Waste treatment method	s	
Product		
Methods of disposal	:	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	1	The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	:	080112
Packaging		
Methods of disposal	:	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	:	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

# **SECTION 15: Regulatory information**

oconton 15. Regulatory mormation
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
UK (GB) /REACH
Annex XIV - List of substances subject to authorisation
Annex XIV
None of the components are listed.
Substances of very high concern
None of the components are listed.
Ozone depleting substances
Not listed.
Prior Informed Consent (PIC)
Not listed.
Persistent Organic Pollutants Not listed.
Annex XVII - Restrictions : Not applicable.
on the manufacture,
placing on the market
and use of certain
dangerous substances, mixtures and articles
<u>Seveso Directive</u>
This product is not controlled under the Seveso Directive.
EU regulations
Industrial emissions : Not listed
(integrated pollution
prevention and control) -
Air Industrial emissions : Not listed
Industrial emissions : Not listed (integrated pollution
prevention and control) -
Water
International regulations
Chemical Weapon Convention List Schedules I, II & III Chemicals
Not listed.
Montreal Protocol
Not listed.
Stockholm Convention on Persistent Organic Pollutants
Not listed.
Rotterdam Convention on Prior Informed Consent (PIC)
Not listed.
UNECE Aarhus Protocol on POPs and Heavy Metals
Not listed.
<b>15.2 Chemical safety</b> : This product contains substances for which Chemical Safety Assessments are still
assessment required.

# **SECTION 16: Other information**

Indicates informatio	n that has changed from previously issued version.
Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative</li> </ul>
Procedure used to de	rive the classification

#### Procedure used to derive the classification

Classification	Justification	
Skin Sens. 1, H317	Calculation method	

### Full text of abbreviated H statements

11004	
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

### Full text of classifications

AQUATOP 2600-82 - CLEAR T070			Label No :38361		
Date of issue/Date of revisior	20/07/2022 Date of previous issue : No previous validation	Version	1 <b>15/17</b>		
Notice to reader					
Version	: 1				
Date of previous issue	: No previous validation				
Date of issue/ Date of revision	: 20/07/2022				
Acute Tox. 4AAquatic Acute 1SAquatic Chronic 1IAquatic Chronic 2ICarc. 1BSEye Dam. 1SEye Irrit. 2SMuta. 2SSkin Corr. 1BSSkin Sens. 1SSkin Sens. 1SStort RE 1SSTOT SE 3S	ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 CARCINOGENICITY - Category 1B SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 GERM CELL MUTAGENICITY - Category 2 SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Cat	• •			
	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3				

# **SECTION 16: Other information**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision AQUATOP 2600-82 - CLEAR T070

: 20/07/2022 Date of previous issue