Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - United Kingdom: Northern Ireland

# **SAFETY DATA SHEET**



AQUATOP 2600-83 - NCS S 0502-Y

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1	Product identifier	
Pr	roduct name	

: AQUATOP 2600-83 - NCS S 0502-Y

**1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use**: Paint.

#### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com responsible for this SDS

### National contact

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

### **1.4 Emergency telephone number**

National advisory body/Poison Centre

Telephone number : NHS: 111

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Hazard pictograms



Signal word	: Warning	
Hazard statements	: H317 - May cause an allergic skin reaction.	
Precautionary statements		
Prevention	: P280 - Wear protective gloves. P261 - Avoid breathing vapour.	
Response	: P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention	ı.
Storage	: Not applicable.	
Disposal	: P501 - Dispose of contents and container in accordance with all local, regiona national and international regulations.	al,
Hazardous ingredients	: Contains: adipohydrazide; 1,2-benzisothiazol-3(2H)-one; 2-methyl-2H-isothiaz 3-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	zol-

Date of issue/Date of revision	: 21/11/2023	Date of previous issue	: 30/06/2022	Version	:1.01	1/16
AQUATOP 2600-83 - NCS S 0502	-Y			Label No	50127	,

### **SECTION 2: Hazards identification**

Supplemental label elements	:	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and DTBMA and MIT and Bronopol and MBIT and OIT.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do	:	None known.

not result in classification

# SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture	1	T	1	1
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Manium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	<1	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	≤0.3	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
Ammonia	REACH #: 01-2119488876-14 EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	<0.1	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400	STOT SE 3, H335: C ≥ 5% M [Acute] = 1	[1] [2]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
2-Ethoxyethanol	EC: 203-804-1 CAS: 110-80-5 Index: 603-012-00-X	<0.1	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 3, H331 Repr. 1B, H360FD	ATE [Oral] = 500 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
2-methyl-2H-isothiazol- 3-one	EC: 220-239-6 CAS: 2682-20-4	<0.01	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l	[1]
Date of issue/Date of revision		e of previous is	sue : 30/06/2022	Version :1.0	
AQUATOP 2600-83 - NCS S	0502-Y			Label No :5012	27

SECTION 3: Compo	sition/informat	ion on in	greaients		
			Aquatic Chronic 1, H410 EUH071	Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1	
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: 0.06% $\le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
2-Methyl-1,2-benzisothiazol- 3(2H)-one	CAS: 2527-66-4 Index: 613-336-00-3	<0.0015	Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 175 mg/kg ATE [Dermal] = 1100 mg/kg Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq$  10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First a	d measures
4.1 Description of first aid	neasures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing befor reuse. Clean shoes thoroughly before reuse.
Date of issue/Date of revision	: 21/11/2023 Date of previous issue : 30/06/2022 Version : 1.01 3/16
AQUATOP 2600-83 - NCS S	0502-Y Label No :50127

### SECTION 4: First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symportant symportant symportant symposities and strain symposities and sym	otoms and effects, both acute and delayed <u>ymptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.

# SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing	: Use an extinguishing agent suitable for the surrounding fire.
media	
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	m the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

: 21/11/2023 Date of previous issue

### **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

### **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Recommendations: Not available.Industrial sector specific: Not available.solutions: Not available.	7.3 Specific end use(s)	
	Recommendations	: Not available.
		: Not available.

Date of issue/Date of revision : 2 AQUATOP 2600-83 - NCS S 0502-Y

: 21/11/2023 Date of previous issue

: 30/06/2022

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

**Occupational exposure limits** 

Product/ingredient name	Exposure limit values
2-Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
	through skin.
	STEL: 50 ppm 15 minutes.
	TWA: 25 ppm 8 hours.
	STEL: 246 mg/m <sup>3</sup> 15 minutes.
	TWA: 123 mg/m <sup>3</sup> 8 hours.
Ammonia	EH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia
	anhydrous]
	STEL: 25 mg/m <sup>3</sup> 15 minutes. Form: anhydrous
	STEL: 35 ppm 15 minutes. Form: anhydrous
	TWA: 25 ppm 8 hours. Form: anhydrous
	TWA: 18 mg/m <sup>3</sup> 8 hours. Form: anhydrous
2-Ethoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
	through skin.
	TWA: 2 ppm 8 hours.
	TWA: 8 mg/m <sup>3</sup> 8 hours.

### **Biological exposure indices**

Product/ingredient name	Exposure indices
₽-Butoxyethanol	EH40/2005 BMGVs (United Kingdom (UK), 8/2018) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.
procedures European S assessmen values and atmosphere of exposure (Workplace for the mea	should be made to monitoring standards, such as the following: Standard EN 689 (Workplace atmospheres - Guidance for the t of exposure by inhalation to chemical agents for comparison with limit measurement strategy) European Standard EN 14042 (Workplace es - Guide for the application and use of procedures for the assessment to chemical and biological agents) European Standard EN 482 e atmospheres - General requirements for the performance of procedures surement of chemical agents) Reference to national guidance for methods for the determination of hazardous substances will also be

#### **DNELs/DMELs**

-		1	Population	Effects
DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
DNEL	Short term Oral	26.7 mg/ kg bw/day	General population	Systemic
DNEL	Long term Inhalation	59 mg/m <sup>3</sup>	General population	Systemic
DNEL	Long term Inhalation	98 mg/m³	Workers	Systemic
DNEL	Short term Inhalation	147 mg/m³	General population	Local
DNEL	Short term Inhalation	246 mg/m <sup>3</sup>	Workers	Local
DNEL	Short term Inhalation	426 mg/m <sup>3</sup>	General population	Systemic
DNEL	Short term Inhalation	1091 mg/ m³	Workers	Systemic
DNEL	Long term Inhalation	17.5 mg/m³	Workers	Systemic
DNEL	Long term Dermal	0.345 mg/ kg bw/day	General population	Systemic
DNEL	Long term Dermal	0.966 mg/	Workers	Systemic
	DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL	DNELShort term OralDNELLong term InhalationDNELLong term InhalationDNELShort term InhalationDNELShort term InhalationDNELShort term InhalationDNELShort term InhalationDNELShort term InhalationDNELShort term InhalationDNELLong term InhalationDNELLong term Long term DermalDNELLong term Dermal	DNELShort term Oralbw/dayDNELShort term Oral26.7 mg/ kg bw/dayDNELLong term Inhalation59 mg/m³DNELLong term Inhalation98 mg/m³DNELShort term Inhalation147 mg/m³DNELShort term Inhalation246 mg/m³DNELShort term Inhalation246 mg/m³DNELShort term Inhalation1091 mg/ m³DNELShort term Inhalation1091 mg/ m³DNELLong term Inhalation17.5 mg/m³DNELLong term Dermal0.345 mg/ kg bw/dayDNELLong term Dermal0.966 mg/	DNELShort term Oralbw/daypopulationDNELShort term Oral26.7 mg/ kg bw/dayGeneral populationDNELLong term59 mg/m³General populationDNELLong term98 mg/m³WorkersInhalation147 mg/m³General populationDNELShort term147 mg/m³General populationDNELShort term246 mg/m³WorkersInhalation1091 mg/ m³WorkersDNELShort term1091 mg/ m³WorkersDNELShort term1091 mg/ m³WorkersDNELLong term0.345 mg/ kg bw/dayGeneral populationDNELLong term Dermal0.966 mg/Workers

			kg bw/day		
	DNEL	Long term Inhalation	1.2 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m <sup>3</sup>		Systemic
2-methyl-2H-isothiazol-3-one	DNEL	Long term Inhalation	0.021 mg/ m³	General population	Local
	DNEL	Long term Inhalation	0.021 mg/ m³	Workers	Local
	DNEL	Long term Oral	0.027 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.043 mg/ m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	0.043 mg/ m³	Workers	Local
	DNEL	Short term Oral	0.053 mg/ kg bw/day	General population	Systemic
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL	Long term Inhalation	0.02 mg/m <sup>3</sup>	General population	Local
(3.1)	DNEL	Long term Inhalation	0.02 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	0.04 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	0.04 mg/m <sup>3</sup>		Local
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/ kg bw/day	General population	Systemic

#### **PNECs**

ſ

No PNECs available

8.2 Exposure controls Appropriate engineering	: Good general ventilation should be sufficient to control worker exposure to airborne
controls	contaminants.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
Date of issue/Date of revision	: 21/11/2023 Date of previous issue : 30/06/2022 Version : 1.01 7/16

 Date of issue/Date of revision
 : 21/11/2023
 Date of previous issue
 : 30/06/2022
 Version
 : 1.01
 //16

 AQUATOP 2600-83 - NCS S 0502-Y
 Label No : 50127
 Label No : 50127
 Label No : 50127

### **SECTION 8: Exposure controls/personal protection**

	Not recommended polyvinyl alcohol (PVA) gloves	
Body protection	: Personal protective equipment for the body should be selected based on t being performed and the risks involved and should be approved by a spec before handling this product.	
Other skin protection	: Appropriate footwear and any additional skin protection measures should selected based on the task being performed and the risks involved and sh approved by a specialist before handling this product.	
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that m appropriate standard or certification. Respirators must be used according respiratory protection program to ensure proper fitting, training, and other aspects of use.	l to a
	Filter type (spray application): A P	
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked ensure they comply with the requirements of environmental protection legi In some cases, fume scrubbers, filters or engineering modifications to the equipment will be necessary to reduce emissions to acceptable levels.	islation.

### **SECTION 9: Physical and chemical properties**

ŝ

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>							
Physical state	: Liquid.						
Colour	: White to yellowish.						
Odour	: Slight						
Odour threshold	: Not available.						
Melting point/freezing point	: Not available.						
Initial boiling point and	:						
boiling range							
Ingredient name		°C	°F	Method			
water		100	212				
Ethyldiglycol		196	384.8				
Flammability	: Not a	available.					
Lower and upper explosion limit		er: Not applicable er: Not applicable					

### **Flash point Auto-ignition temperature**

Ingredient name		°C	°F	Method	
<b>F</b> thyldiglycol		204	399.2		
Decomposition temperature	: Not av	ailable.		1	
pH	: 8 to 8.	5 [Conc. (%	w/w): 100%]		
Viscosity	: Not av	ailable.			
Solubility(ies)	:				
Not available.					
Solubility in water	: Not av	ailable.			
Partition coefficient: n-octanol/ water	: Not ap	plicable.			
Vapour pressure	:				

: Closed cup: >100°C (>212°F)

	Va	apour Press	sure at 20°C	V	Vapour pressure at 50°0		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
Ethyldiglycol	0.14	0.019					
elative density	: Not	available.		·			
ensity	: 1.2	g/cm³					
apour density	: Not	available.					
xplosive properties	: Not	available.					
xidising properties	: Not	available.					
article characteristics							
Median particle size	: Not	applicable.					

SECTION 10: Stability and reactivity					
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
10.2 Chemical stability	: The product is stable.				
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.				
10.4 Conditions to avoid	: No specific data.				
10.5 Incompatible materials	: No specific data.				
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.				

## **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	
7,2-benzisothiazol-3(2H)-	LD50 Oral	Rat	1020 mg/kg	-	
one					
2-methyl-2H-isothiazol-	LC50 Inhalation Dusts and	Rat	0.11 mg/l	4 hours	
3-one	mists				
reaction mass of: 5-chloro-	LD50 Oral	Rat	53 mg/kg	-	
2-methyl-4-isothiazolin-					
3-one [EC no. 247-500-7]					
and 2-methyl-2H-isothiazol-					
3-one [EC no. 220-239-6] (3:					
1)					
<b>Conclusion/Summary</b> : Based on available data, the classification criteria are not met.					

### Acute toxicity estimates

Route	ATE value
Malation (vapours)	443.45 mg/l

Irritation/Corrosion

: 21/11/2023 Date of previous issue

: 30/06/2022

Product/ingredient name	Result	Species	Score	Exposure	Observation
titanium dioxide	Skin - Mild irritant	Human		72 hours 300	
	Skill - Milu Illiant	Tuman	-	ug l	-
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Mild irritant Skin - Severe irritant	Human Human	-	48 hours 5 % 0.01 %	-
Conclusion/Summary	: Based on available data, the	he classification o	riteria are	not met.	
Sensitisation					
Conclusion/Summary	: May cause an allergic skin	reaction.			
Mutagenicity	, ,				
Conclusion/Summary	: Based on available data, the	he classification c	riteria are	not met.	
Carcinogenicity					
It has been observed that the leading to significant impairme				le dust is inhale	ed in quantities
Conclusion/Summary	: Based on available data, the	he classification c	riteria are	e not met.	
Reproductive toxicity					
Conclusion/Summary	: Based on available data, the	he classification c	riteria are	e not met.	
<u>Teratogenicity</u>					
Conclusion/Summary	: Based on available data, the	he classification c	riteria are	not met.	
<u>Specific target organ toxicit</u> Not available.	<u>y (single exposure)</u>				
Specific target organ toxicit	<u>y (repeated exposure)</u>				
Not available.					
Aspiration hazard Not available.					
nformation on likely routes of exposure	: Not available.				
Potential acute health effects					
Eye contact	: No known significant effec	ts or critical haza	rds.		
Inhalation	: No known significant effect	ts or critical haza	rds.		
Skin contact	: May cause an allergic skin	reaction.			
Ingestion	: No known significant effec	ts or critical haza	rds.		
Symptoms related to the physic		gical characteris	<u>stics</u>		
Eye contact	: No specific data.				
Inhalation	: No specific data.				
Skin contact	: Adverse symptoms may in irritation redness	iciude the followin	ıg:		
Ingestion	: No specific data.				
	ts as well as chronic effects				

Date of issue/Date of revision AQUATOP 2600-83 - NCS S 0502-Y

: 21/11/2023 Date of previous issue

: 30/06/2022

Version : 1.01 10/16 Label No : 50127

### **SECTION 11: Toxicological information**

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	<u>ects</u>
Not available.	
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

### **11.2 Information on other hazards**

## 11.2.1 Endocrine disrupting properties

Not available.

### 11.2.2 Other information

Not available.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia	48 hours
		dubia - Neonate	
	Acute LC50 6.5 mg/l Fresh water	Daphnia - <i>Daphnia pulex</i> -	48 hours
		Neonate	
	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
2-Butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
-	Acute LC50 800000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1250000 µg/l Marine water	Fish - Menidia beryllina	96 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.36 mg/l Marine water	Algae - Skeletonema Costatum	72 hours
	Acute EC50 3.7 mg/l	Daphnia - Daphnia Magna	48 hours
	Acute LC50 1.9 mg/l Fresh water	Fish - Onorhynchus Mykiss	96 hours
	Acute NOEC 0.15 mg/l Marine water	Algae - Skeletonema Costatum	72 hours
2-methyl-2H-isothiazol-3-one	Acute EC50 0.18 ppm Fresh water	Daphnia - Daphnia magna	48 hours
-	Acute LC50 0.07 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
2-Methyl-1,2-benzisothiazol- 3(2H)-one	Acute EC50 0.22 ppm Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
( ),	Acute EC50 0.92 ppm Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 0.24 ppm Fresh water	Fish - Oncorhynchus mykiss -	96 hours
		Juvenile (Fledgling, Hatchling, Weanling)	
	Chronic NOEC 0.16 ppm	Fish - Pimephales promelas	32 days

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

Ī	Product/ingredient name	Test	Result	Dose	Inoculum
	2-benzisothiazol-3(2H)-one	EU	24 % - 28 days	-	-

Conclusion/Summary

: This product has not been tested for biodegradation.

 Date of issue/Date of revision
 : 21/11/2023
 Date of previous issue

# SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
P-Butoxyethanol	0.81	-	Low
1,2-benzisothiazol-3(2H)-one		3.2	Low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

#### **13.1 Waste treatment methods**

#### **Product**

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	: 080112
Packaging	
Methods of disposal	<ul> <li>The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.</li> </ul>
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
Date of issue/Date of rev	vision : 21/11/2023	Date of previous issue	: 30/06/2022	Version : 1.01 12/16
AQUATOP 2600-83		Label No :50127		

SECTION 14: Transport information				
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

# user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

# : Not relevant/applicable due to nature of the product.

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### EU Regulation (EC) No. 1907/2006 (REACH)

### Annex XIV - List of substances subject to authorisation

#### **Annex XIV**

None of the components are listed.

### Substances of very high concern

None of the components are listed.

### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous

### substances, mixtures and articles

Product/ingredient name		%	Designation [Usage]	
AQUATOP 2600-83		≥90	3	
Labelling	: 🖊			
Other EU regulations				
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed			
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed			
Explosive precursors	: Not applica	ble.		
Ozone depleting substanc	<u>es (1005/2009/</u>	<u>EU)</u>		
Not listed.				
Prior Informed Consent (P	IC) (649/2012/E	<u>EU)</u>		
Not listed.				
Persistent Organic Polluta Not listed.	<u>ints</u>			
Seveso Directive				
This product is not controlled	d under the Sev	eso Directi	ve.	
nternational regulations				
Chemical Weapon Convent	ion List Sched	<u>ules I, II &amp;</u>	III Chemicals	
te of issue/Date of revision	: 21/11/2023	Date of pre	evious issue : 30/06/2022	Version : 1.01 13/1
	500 V			

AQUATOP 2600-83 - NCS S 0502-Y

### **SECTION 15: Regulatory information**

Not listed.

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

15.2 Chemical safety	1	This product contains substances for which Chemical Safety Assessments are still
assessment		required.

### **SECTION 16: Other information**

Indicates information	n that has changed from previously issued version.
Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group</li> </ul>
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method

### Full text of abbreviated H statements

<b>⊮</b> 226	Elemmehle liquid and veneur
•	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H360FD	May damage fertility. May damage the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

: 21/11/2023 Date of previous issue

: 30/06/2022

### **SECTION 16: Other information**

320110N 10. 01	
Cute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of issue/ Date of	: 21/11/2023
revision	
Date of previous issue	: 30/06/2022
Version	: 1.01

#### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 21.AQUATOP 2600-83 - NCS S 0502-Y

: 21/11/2023 Date of previous issue

: 30/06/2022

Version : 1.01 16/16 Label No :50127