Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - United Kingdom: Northern Ireland

SAFETY DATA SHEET



Label No :96320

AQUATOP 2600-83 - RAL 9010

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1	Product identifier	
P	roduct name	

: AQUATOP 2600-83 - RAL 9010

1.2 Relevant identified uses of the substance or mixture and uses advised against **Product use** : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms

AQUATOP 2600-83 - RAL 9010



Signal word Hazard statements		Warning H317 - May cause an allergic skin reaction.		
Precautionary statements	1	TIST/ - May cause an allergic skill reaction.		
Prevention	:	P280 - Wear protective gloves. P261 - Avoid breathing vapour.		
Response	:	▶302 + P352 - IF ON SKIN: Wash with pler P333 + P313 - If skin irritation or rash occur P362 + P364 - Take off contaminated cloth	rs: Get medical advice or attention.	
Storage	:	Not applicable.		
Disposal	:	P501 - Dispose of contents and container in national and international regulations.	n accordance with all local, regional,	
Hazardous ingredients	:	Contains: adipohydrazide; 1,2-benzisothiaz 3-one and reaction mass of: 5-chloro-2-me 247-500-7] and 2-methyl-2H-isothiazol-3-or	thyl-4-isothiazolin-3-one [EC no.	1-
Date of issue/Date of revision		: 10/07/2025 Date of previous issue : 23	3/11/2023 Version : 2 1	1/19

SECTION 2: Hazards identification

Supplemental label elements	:	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and DTBMA and MIT and Bronopol and MBIT and OIT.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do	:	None known.

not result in classification

SECTION 3: Composition/information on ingredients

Image: Second state Constraints Constraints <thconstraints< t<="" th=""><th>3.2 Mixtures Product/ingredient name</th><th>: Mixture</th><th>%</th><th>Classification</th><th>Specific Conc.</th><th>Туре</th></thconstraints<>	3.2 Mixtures Product/ingredient name	: Mixture	%	Classification	Specific Conc.	Туре	
$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	g.		~		Limits, M-factors and ATEs	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
101-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0Acute Tox. 3, H331 	Manium dioxide	01-2119489379-17 EC: 236-675-5	≥10 - ≤25		-	[1] [*]	
$\begin{array}{c c c c c c c c c c c c c c c c c c c $	2-Butoxyethanol	01-2119475108-36 EC: 203-905-0 CAS: 111-76-2	<1	Acute Tox. 3, H331 Skin Irrit. 2, H315	mg/kg ATE [Inhalation	[1] [2]	
one CAS: 2634-33-5 Index: 613-088-00-6 Acute Tox. 2, H330 mg/kg Acute Tox. 2, H330 Mg/kg ATE [Inhalation (dusts and mists)] 2-methyl-2H-isothiazol- 3-one EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9 <0.01	adipohydrazide	01-2119962900-36 EC: 213-999-5	≤0.3	Aquatic Chronic 2,	-	[1]	
3-one CAS: 2682-20-4 Index: 613-326-00-9 Acute Tox. 3, H311 $Acute Tox. 2, H330$ ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] Skin Corr. 1B, H314 Bye Dam. 1, H318 ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 $EUH071$ M [Acute] = 10 M [Chronic] = 1 M [Chronic] = 1 M [Chronic] = 1 $Acute Tox. 3, H301$ ATE [Oral] = 53 mg/ [1] $Acute Tox. 2, H310$ ATE [Oral] = 53 mg/ [1]		CAS: 2634-33-5	<0.036	Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1,	mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C $\ge 0.036\%$ M [Acute] = 1	[1]	
2-methyl-4-isothiazolin- CAS: 55965-84-9 Acute Tox. 2, H310 kg		CAS: 2682-20-4	<0.01	Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C $\geq 0.0015\%$ M [Acute] = 10	[1]	
Date of issue/Date of revision : 10/07/2025 Date of previous issue : 23/11/2023 Version : 2 2/			<0.001			[1]	
AQUATOP 2600-83 - RAL 9010 Label No :96320			e of previous is	sue : 23/11/2023		2/19	

SECTION 3: Composition/information on ingredients

SECTION 5. Compo	SECTION 5. Composition/information on ingredients					
3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	Index: 613-167-00-5	Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 See Section 16 for	ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100			
		the full text of the H statements declared above.				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid n	neasures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Date of issue/Date of revision	: 10/07/2025	Date of previous issue	: 23/11/2023	Version	:2	3/19
AQUATOP 2600-83 - RAL 9010				Label No	: <mark>9</mark> 6320	0

SECTION 4: First aid measures

Over-exposure signs/sy	mptoms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
4.3 Indication of any imm	ediate medical attention and special treatment needed
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

5.1 Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	g : None known.	

5.2 Special hazards arising from the substance or mixture

or obcour unarras anomy u	
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

		The second se
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

: 10/07/2025 Date of previous issue

SECTION 6: Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 50 ppm. TWA 8 hours: 25 ppm. STEL 15 minutes: 246 mg/m ³ . TWA 8 hours: 123 mg/m ³ .

SECTION 8: Exposure controls/personal protection

Biological exposure indices		
Product/ingredient	name	Exposure indices
2-Butoxyethanol		EH40/2005 BMGVs (United Kingdom (UK), 1/2020) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.
Recommended monitoring procedures	European Stand assessment of e values and mea atmospheres - C of exposure to c (Workplace atm for the measure	Id be made to monitoring standards, such as the following: lard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit surement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessmen themical and biological agents) European Standard EN 482 ospheres - General requirements for the performance of procedure ment of chemical agents) Reference to national guidance nethods for the determination of hazardous substances will also be
DNELs/DMELs		
Product/ingredient name		Result
manium dioxide		DNEL - General population - Long term - Inhalation 28 μg/m³ <u>Effects</u> : Local
		DNEL - Workers - Long term - Inhalation 170 μg/m³ <u>Effects</u> : Local
2-Butoxyethanol		DNEL - General population - Long term - Oral 6.3 mg/kg bw/day <u>Effects</u> : Systemic
		DNEL - General population - Short term - Oral 26.7 mg/kg bw/day <u>Effects</u> : Systemic
		DNEL - General population - Long term - Inhalation 59 mg/m ³ <u>Effects</u> : Systemic
		DNEL - Workers - Long term - Inhalation 98 mg/m ³ <u>Effects</u> : Systemic
		DNEL - General population - Short term - Inhalation 147 mg/m³ <u>Effects</u> : Local
		DNEL - Workers - Short term - Inhalation 246 mg/m³ <u>Effects</u> : Local
		DNEL - General population - Short term - Inhalation 426 mg/m ³ <u>Effects</u> : Systemic
		DNEL - Workers - Short term - Inhalation 1091 mg/m³ <u>Effects</u> : Systemic
adipohydrazide		DNEL - Workers - Long term - Inhalation 17.5 mg/m³ <u>Effects</u> : Systemic
1,2-benzisothiazol-3(2H)-one		DNEL - General population - Long term - Dermal 0.345 mg/kg bw/day

AQUATOP 2600-83 - RAL 9010

SECTION 8: Exposure controls/personal protection

Effects: Systemic

DNEL - Workers - Long term - Dermal 0.966 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation 1.2 mg/m³ <u>Effects</u>: Systemic

DNEL - Workers - Long term - Inhalation 6.81 mg/m³ <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation 0.021 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation 0.021 mg/m³ Effects: Local

DNEL - General population - Long term - Oral 0.027 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Inhalation 0.043 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation 0.043 mg/m³ Effects: Local

DNEL - General population - Short term - Oral 0.053 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation 0.02 mg/m³ <u>Effects</u>: Local

DNEL - Workers - Long term - Inhalation 0.02 mg/m³ Effects: Local

DNEL - General population - Short term - Inhalation 0.04 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation 0.04 mg/m³ <u>Effects</u>: Local

DNEL - General population - Long term - Oral 0.09 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Oral 0.11 mg/kg bw/day <u>Effects</u>: Systemic

2-methyl-2H-isothiazol-3-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

PNECs

SECTION 8: Exposure controls/personal protection

Not available.

8.2 Exposure controls		
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborn contaminants.	ne
Individual protection meas	<u>ires</u>	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working perio Appropriate techniques should be used to remove potentially contaminated clothin Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.	
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mist gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses wi side-shields.	S,
Skin protection		
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard shou be worn at all times when handling chemical products if a risk assessment indicat this is necessary. Considering the parameters specified by the glove manufacture check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.	tes
	Recommendations : Wear suitable gloves tested to EN374.	
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm	
	Not recommended polyvinyl alcohol (PVA) gloves	
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	;
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other importa aspects of use.	
	Filter type (spray application): A P	
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the proces equipment will be necessary to reduce emissions to acceptable levels.	

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: White.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.

: 10/07/2025 Date of previous issue

SECTION 9: Physical and chemical properties

2

Initial boiling point and

boiling range

Ingredient name		°C	°F	Method
water		100	212	
Ethyldiglycol		196	384.8	
Flammability	: Not	available.		
Lower and upper explosion imit		er: Not applicat er: Not applicat		
Flash point	: Clos	ed cup: >100°C	C (>212°F)	
Auto-ignition temperature	:			
Ingredient name		°C	°F	Method
Ethyldiglycol		204	399.2	
Decomposition temperature	: Not	available.		
рН	: 8 to	8.5 [Conc. (% v	v/w): 100%]	
Viscosity	: Not a	available.		
Solubility(ies)	:			
Not available				

Not available.

Solubility in water

: Not available.

÷

Partition	coefficient: n-octanol/	:	Not applicable.

water

Vapour pressure

	Va	apour Pres	sure at 20°C	Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
Ethyldiglycol	0.14	0.019				
Relative density	: Not	available.				
Density	: 1.2	g/cm³				
Vapour density	: Not	available.				
Particle characteristics						
Median particle size	: Not	applicable.				

9.2 Other information

9.2.1 Information with regard to physical hazard classes					
Explosive properties	: Not available.				
Oxidising properties	: Not available.				
9.2.2 Other safety characteristics					

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	1	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	No specific data.

Date of issue/Date of revision	: 10/07/2025	Date of previous issue	: 23/11/2023	
AQUATOP 2600-83 - RAL 9010				L

SECTION 10: Stability and reactivity

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined i	n Regulation (EC) No 1272/2008
Acute toxicity	
Product/ingredient name	Result
✓,2-benzisothiazol-3(2H)-one	Rat - Oral - LD50 1020 mg/kg
2-methyl-2H-isothiazol-3-one	Rat - Inhalation - LC50 Dusts and mists 0.11 mg/l [4 hours]
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Rat - Oral - LD50 53 mg/kg <u>Toxic effects</u> : Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
AQUATOP 2600-83 2-Butoxyethanol 1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazol-3-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	N/A 1200 450 100 53	N/A N/A 300 50	N/A N/A N/A N/A N/A	452.3 3 N/A N/A 0.5	N/A N/A 0.21 0.11 N/A

Skin corrosion/irritation

Product/ingredient name Result titanium dioxide Human - Skin - Mild irritant Duration of treatment/exposure: 72 hours Amount/concentration applied: 300 ug I 2-Butoxyethanol Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg 1,2-benzisothiazol-3(2H)-one Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 % reaction mass of: 5-chloro-2-methyl-Human - Skin - Severe irritant 4-isothiazolin-3-one [EC no. 247-500-7] and Amount/concentration applied: 0.01 % 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) **Conclusion/Summary [Product]** : Not available. Serious eye damage/eye irritation **Product/ingredient name** Result

Date of previous issue

: 10/07/2025

SECTION 11: Toxicological informat	ion
2-Butoxyethanol	Rabbit - Eyes - Moderate irritant <u>Duration of treatment/exposure</u> : 24 hours <u>Amount/concentration applied</u> : 100 mg
	Rabbit - Eyes - Severe irritant Amount/concentration applied: 100 mg
Conclusion/Summary [Product] : Not available	9.
Respiratory corrosion/irritation Not available.	
Conclusion/Summary [Product] : Not available	Э.
Respiratory or skin sensitization Not available.	
Skin Conclusion/Summary [Product] : Not available	Э.
Respiratory Conclusion/Summary [Product] : Not available	Э.
Germ cell mutagenicity Not available.	
Conclusion/Summary [Product] : Not available	e.
<u>Carcinogenicity</u> It has been observed that the carcinogenic hazard of leading to significant impairment of particle clearance Not available.	this product arises when respirable dust is inhaled in quantities e mechanisms in the lung.
Conclusion/Summary [Product] : Not available	9.
Reproductive toxicity Not available.	
Conclusion/Summary [Product] : Not available	9.
Specific target organ toxicity (single exposure) Not available.	
Specific target organ toxicity (repeated exposure) Not available.	
Aspiration hazard Not available.	
Information on likely routes of exposure Not available.	
Potential acute health effects	
	nt effects or critical hazards. nt effects or critical hazards.
Date of issue/Date of revision : 10/07/2025 Date of	previous issue : 23/11/2023 Version : 2 11/19
AQUATOP 2600-83 - RAL 9010	Label No :96320

Skin contact	:	May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the ph	iysi	cal, chemical and toxicological characteristics
Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Delayed and immediate effe	ects	as well as chronic effects from short and long-term exposure
Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health eff	ects	
Not available.		
Conclusion/Summary [Pr	odu	ct] : Not available.
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	1	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	1	No known significant effects or critical hazards.

11.2 Information on other hazards

Not available.

Conclusion/Summary [Product]	:
------------------------------	---

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity	
Product/ingredient name	Result
<mark>I</mark> tanium dioxide	Acute - LC50 - Marine water Fish - Mummichog - <i>Fundulus heteroclitus</i> >1000000 μg/l [96 hours] <u>Effect</u> : Mortality
	Acute - LC50 - Fresh water Crustaceans - Water flea - <i>Ceriodaphnia dubia</i> - Neonate <u>Age</u> : <24 hours 3 mg/l [48 hours] <u>Effect</u> : Mortality
2-Butoxyethanol	Acute - LC50 - Marine water Fish - Inland silverside - <i>Menidia beryllina</i> <u>Size</u> : 40 to 100 mm 1250000 μg/l [96 hours] <u>Effect</u> : Mortality

: 10/07/2025 Date of previous issue

SECTION 12: Ecological inform	ation
	Acute - LC50 - Marine water Crustaceans - Common shrimp, sand shrimp - <i>Crangon</i> <i>crangon</i> 800000 μg/l [48 hours] <u>Effect</u> : Mortality
1,2-benzisothiazol-3(2H)-one	Acute - LC50 - Fresh water OECD [Fish, Acute Toxicity Test] Fish - Trout - <i>Onorhynchus Mykiss</i> 1.9 mg/l [96 hours]
	Acute - EC50 OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - <i>Daphnia Magna</i> 3.7 mg/l [48 hours]
	Acute - EC50 - Marine water OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.36 mg/l [72 hours]
	Acute - NOEC - Marine water OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.15 mg/l [72 hours]
2-methyl-2H-isothiazol-3-one	Acute - EC50 - Fresh water US EPA Daphnia - Water flea - <i>Daphnia magna</i> <u>Age</u> : <24 hours 0.18 ppm [48 hours] <u>Effect</u> : Intoxication
	Acute - LC50 - Fresh water US EPA Fish - Rainbow trout,donaldson trout - <i>Oncorhynchus mykiss</i> <u>Weight</u> : 0.73 g 0.07 ppm [96 hours] <u>Effect</u> : Mortality
Conclusion/Summary [Product] : Not a	available.
12.2 Paraistance and degradability	

12.2 Persistence and degradability

Product/ingredient name	Result
7,2-benzisothiazol-3(2H)-one	EU
	24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
7,2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-Butoxyethanol	0.81	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

12.4 Mobility in soil

Soil/water partition coefficient

SECTION 12: Ecological information

Product/ingredient name	logKoc	Кос	
2-Butoxyethanol	1.8	67.3685	
adipohydrazide	1.7	55.2165	
1,2-benzisothiazol-3(2H)-one	1.9	73.142	
2-methyl-2H-isothiazol-3-one	1.7	54.9187	

Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	М	Т	vPvM	vP	vM
titanium dioxide	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one		No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No
Mobility	: Not av	ailable.			1		

Mobility

Conclusion/Summary

: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
2-Butoxyethanol	No	N/A	N/A	No	N/A	N/A	N/A
adipohydrazide	No	N/A	N/A	No	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	No	N/A	No	No	No	N/A	No
2-methyl-2H-isothiazol-3-one		N/A	N/A	No	N/A	N/A	N/A
reaction mass of: 5-chloro-	No	N/A	N/A	No	N/A	N/A	N/A
2-methyl-4-isothiazolin-							
3-one [EC no. 247-500-7]							
and 2-methyl-2H-isothiazol-							
3-one [EC no. 220-239-6] (3:							
1)							

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
Manium dioxide 2-Butoxyethanol adipohydrazide 1,2-benzisothiazol-3(2H)-one	No No No	No No No No	No No No No	No No No No	No No No No	No No No No	No No No No
2-methyl-2H-isothiazol-3-one reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)		No No	No No	No No	No No	No No	No No

Conclusion/Summary Regulation (EC) No. 1272/2008 : The product does not meet the criteria to be considered as a PBT or vPvB.

[CLP]

12.6 Endocrine disrupting properties

Not available.

: 10/07/2025 Date of previous issue

SECTION 12: Ecological information

Conclusion/Summary [Product] : The product do disrupting prop

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment metho	ds
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	: 080112
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
AQUATOP 2600-83	≥90	3
Labelling :		
Other EU regulations		
Industrial emissions : Not listed (integrated pollution prevention and control) - Air		
Industrial emissions : Not listed (integrated pollution prevention and control) - Water		
Explosive precursors : Not applicable	le.	
Ozone depleting substances (EU 2024/590	<u>))</u>	
Not listed.		
Prior Informed Consent (PIC) (649/2012/EL	J)	
Not listed.	_	
Persistent Organic Pollutants Not listed.		
<u>Seveso Directive</u>		
This product is not controlled under the Seve	so Directive.	
International regulations		
Chemical Weapon Convention List Schedu	<u>ies I, II & III</u>	Chemicals
Not listed.		
Montreal Protocol		
Not listed.		
Stockholm Convention on Persistent Organ	nic Pollutan	<u>ts</u>
Not listed.		
Rotterdam Convention on Prior Informed C	onsent (PIC	2)
Not listed.		
UNECE Aarhus Protocol on POPs and Heaven Not listed.	/y Metals	
15.2 Chemical safety: This productassessmentrequired.	contains su	bstances for which Chemical Safety Assessments are still

SECTION 16: Other information

Indicates information that has changed from previously issued version.

	has onanged norm previously issued version.
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
Barris and the second state of the state of the	

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Skin Sens. 1, H317	Calculation method	

Full text of abbreviated H statements

H 301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Date of issue/ Date of	of : 10/07/2025

revision	: 10/07/2025
Date of previous issue	: 23/11/2023
Version	: 2

Notice to reader

SECTION 16: Other information

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision AQUATOP 2600-83 - RAL 9010 : 10/07/2025 Date of previous issue