

SAFETY DATA SHEET



DRYWOOD OPTIFINISH TR SG - BASE T

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : DRYWOOD OPTIFINISH TR SG - BASE T

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

National contact

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 - May cause an allergic skin reaction.

Precautionary statements

Prevention : P280 - Wear protective gloves.
P261 - Avoid breathing vapour.

Response : P362 + P364 - Take off contaminated clothing and wash it before reuse.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : Contains: EO bis(benzotriazolyl)phenylpropionat; adipohydrazide; 1,2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one

Date of issue/Date of revision : 12/10/2023 Date of previous issue : 09/03/2023

Version : 1 1/16

DRYWOOD OPTIFINISH TR SG - BASE T

Label No : 47463

SECTION 2: Hazards identification

Supplemental label elements : Contains biocidal products for in-can preservation: BIT and DTBMA and Bronopol and MIT and OIT and MBIT.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles :

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤3	Eye Irrit. 2, H319	-	[1] [2]
EO bis(benzotriazolyl) phenylpropionat	REACH #: 01-0000015075-76 EC: 400-830-7 CAS: 104810-48-2 Index: 607-176-00-3	<1	Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	<1	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
Ammonia	REACH #: 01-2119488876-14 EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	<0.1	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400	STOT SE 3, H335: C ≥ 5% M [Acute] = 1	[1] [2]
2-methyl-2H-isothiazol-3-one	EC: 220-239-6 CAS: 2682-20-4	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation	[1]

SECTION 3: Composition/information on ingredients

2-Octyl-2H-isothiazol-3-one	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.001	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	(dusts and mists) = 0.11 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1	[1]
2-Methyl-1,2-benzisothiazol-3(2H)-one	CAS: 2527-66-4 Index: 613-336-00-3	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 125 mg/kg ATE [Dermal] = 311 mg/kg ATE [Inhalation (dusts and mists)] = 0.27 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	[1]
			Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 175 mg/kg ATE [Dermal] = 1100 mg/kg Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

SECTION 4: First aid measures

- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-(2-butoxyethoxy)ethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 ppm 8 hours. STEL: 15 ppm 15 minutes.
2-Butoxyethanol	TWA: 67.5 mg/m ³ 8 hours. STEL: 101.2 mg/m ³ 15 minutes. EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours.
Ammonia	STEL: 246 mg/m ³ 15 minutes. TWA: 123 mg/m ³ 8 hours. EH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia anhydrous] STEL: 25 mg/m ³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m ³ 8 hours. Form: anhydrous

Biological exposure indices

Product/ingredient name	Exposure indices
2-Butoxyethanol	EH40/2005 BMGVs (United Kingdom (UK), 8/2018) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
2-(2-butoxyethoxy)ethanol	DNEL	Long term Oral	6.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	67.5 mg/m ³	Workers	Local
2-Butoxyethanol	DNEL	Short term Inhalation	101.2 mg/m ³	Workers	Local
	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	59 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	98 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	147 mg/m ³	General population	Local
	DNEL	Short term Inhalation	246 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	426 mg/m ³	General population	Systemic

SECTION 8: Exposure controls/personal protection

adipohydrazide	DNEL	Short term Inhalation	1091 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	17.5 mg/m ³	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/kg bw/day	Workers	Systemic
2-methyl-2H-isothiazol-3-one	DNEL	Long term Inhalation	1.2 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	0.021 mg/m ³	General population	Local
	DNEL	Long term Inhalation	0.021 mg/m ³	Workers	Local
	DNEL	Long term Oral	0.027 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.043 mg/m ³	General population	Local
	DNEL	Short term Inhalation	0.043 mg/m ³	Workers	Local
	DNEL	Short term Oral	0.053 mg/kg bw/day	General population	Systemic

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Not recommended polyvinyl alcohol (PVA) gloves

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Colourless.
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
Water	100	212	
Dipropylenglycoldimethylether	175	347	

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: Not applicable.
Upper: Not applicable.
- Flash point** : Closed cup: >100°C (>212°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Dipropylenglycoldimethylether	165	329	
2-(2-butoxyethoxy)ethanol	210	410	DIN 51794

- Decomposition temperature** : Not available.
- pH** : 8 to 8.5 [Conc. (% w/w): 100%]
- Viscosity** : Not available.
- Solubility(ies)** :
Not available.

- Solubility in water** : Not available.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	17.5	2.3				
Dipropylenglycoldimethylether	0.52	0.069				

- Relative density** : Not available.
- Density** : 1 g/cm³
- Vapour density** : Not available.
- Explosive properties** : Not available.

SECTION 9: Physical and chemical properties

Oxidising properties : Not available.

Particle characteristics

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-
1,2-benzisothiazol-3(2H)-one	LD50 Oral	Rat	1020 mg/kg	-
2-methyl-2H-isothiazol-3-one	LC50 Inhalation Dusts and mists	Rat	0.11 mg/l	4 hours
2-Octyl-2H-isothiazol-3-one	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Route	ATE value
Inhalation (vapours)	666.67 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-(2-butoxyethoxy)ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Severe irritant	Rabbit	-	20 mg	-
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
1,2-benzisothiazol-3(2H)-one	Skin - Mild irritant	Human	-	48 hours 5 %	-
2-Octyl-2H-isothiazol-3-one	Eyes - Severe irritant	Rabbit	-	100 mg	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Sensitisation

Conclusion/Summary : May cause an allergic skin reaction.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Date of issue/Date of revision : 12/10/2023 **Date of previous issue** : 09/03/2023

Version : 1 9/16

DRYWOOD OPTIFINISH TR SG - BASE T

Label No : 47463

SECTION 11: Toxicological information

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

SECTION 11: Toxicological information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-(2-butoxyethoxy)ethanol	Acute LC50 1300000 µg/l Fresh water	Fish - <i>Lepomis macrochirus</i>	96 hours
2-Butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 800000 µg/l Marine water	Crustaceans - <i>Crangon crangon</i>	48 hours
1,2-benzisothiazol-3(2H)-one	Acute LC50 1250000 µg/l Marine water	Fish - <i>Menidia beryllina</i>	96 hours
	Acute EC50 0.36 mg/l Marine water	Algae - <i>Skeletonema Costatum</i>	72 hours
	Acute EC50 3.7 mg/l	Daphnia - <i>Daphnia Magna</i>	48 hours
	Acute LC50 1.9 mg/l Fresh water	Fish - <i>Onorhynchus Mykiss</i>	96 hours
2-methyl-2H-isothiazol-3-one	Acute NOEC 0.15 mg/l Marine water	Algae - <i>Skeletonema Costatum</i>	72 hours
	Acute EC50 0.18 ppm Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
2-Octyl-2H-isothiazol-3-one	Acute LC50 0.07 ppm Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
	Acute EC50 107 ppb Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 47 ppb Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
	Chronic NOEC 74 ppb Fresh water	Daphnia - <i>Daphnia magna</i>	21 days
	Chronic NOEC 8.5 ppb	Fish - <i>Pimephales promelas</i>	35 days
2-Methyl-1,2-benzisothiazol-3(2H)-one	Acute EC50 0.22 ppm Fresh water	Algae - <i>Pseudokirchneriella subcapitata</i>	96 hours
	Acute EC50 0.92 ppm Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 0.24 ppm Fresh water	Fish - <i>Oncorhynchus mykiss</i> - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 0.16 ppm	Fish - <i>Pimephales promelas</i>	32 days

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
1,2-benzisothiazol-3(2H)-one	EU	24 % - 28 days	-	-

Conclusion/Summary : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-(2-butoxyethoxy)ethanol	1	-	Low
2-Butoxyethanol	0.81	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low
2-Octyl-2H-isothiazol-3-one	2.45	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

SECTION 12: Ecological information

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC) : 080112

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
AQUATOP 2600-24 2-(2-butoxyethoxy)ethanol	≥90 ≤3	3 55 [Consumer paint]

Labelling :

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment : Not applicable.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 12/10/2023

Date of previous issue : 09/03/2023

Version : 1

DRYWOOD OPTIFINISH TR SG_BASE T BASE T

Notice to reader

Date of issue/Date of revision : 12/10/2023 Date of previous issue : 09/03/2023 Version : 1 14/16

DRYWOOD OPTIFINISH TR SG - BASE T

Label No : 47463

SECTION 16: Other information

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

