Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

SAFETY DATA SHEET



DRYWOOD OPTIPRIMER LG - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product	identifier
-------------	------------

Product name : DRYWOOD OPTIPRIMER LG - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

- Telephone number
- Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.
 Members of the public Number (8 am-10 pm): +353 (0)1 809 2166 Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms

Signal word	:	Warning
Hazard statements	:	H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements		
General	:	P103 - Read carefully and follow all instructions. P102 - Keep out of reach of children.

SECTION 2: Hazards identification

Brovention	 D290 Wear protective gloves Wear eve or face protection
Prevention	 P280 - Wear protective gloves. Wear eye or face protection. P273 - Avoid release to the environment.
Response	: P391 - Collect spillage.
Storage	: Not applicable.
Disposal	 P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	: Contains: adipohydrazide; 4,5-dichloro-2-octyl-2H-isothiazol-3-one; 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
Supplemental label elements	: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:
2.3 Other hazards	

2.5 Other nazarus		
Product meets the criteria for PBT or vPvB according	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
to Regulation (EC) No. 1907/2006, Annex XIII		
Other hazards which do	÷	None known.

not result in classification

SECTION 3: Composition/information on ingredients

$\begin{array}{c c c c c c c c c c c c c c c c c c c $	3.2 Mixtures Product/ingredient name	: Mixture	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
$01-2119475108-36$ EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 mg/kg ATE [Inhalation 	<mark>u</mark> tanium dioxide	01-2119489379-17 EC: 236-675-5	≥10 - ≤25		-	[1] [*]
101-2119962900-36 EC: 213-999-5 CAS: 1071-93-8Aquatic Chronic 2, H411ATE [Oral] = 567 	2-Butoxyethanol	01-2119475108-36 EC: 203-905-0 CAS: 111-76-2	≤0.3	Acute Tox. 3, H331 Skin Irrit. 2, H315	mg/kg ATE [Inhalation	[1] [2]
isothiazol-3-one CAS: 64359-81-5 Index: 613-335-00-8 Acute Tox. 2, H330 mg/kg ATE [Inhalation Eye Dam. 1, H318 $(dusts and mists)$] Skin Sens. 1A, H317 $= 0.16 mg/l$ Aquatic Acute 1, H400 Aquatic Chronic 1, H410 $C \ge 5\%$ EUH071 Skin Irrit. 2, H315: $0.025\% \le C < 5\%$ Eye Dam. 1, H318: $C \ge 3\%$ Eye Irrit. 2, H319: $0.025\% \le C < 3\%$	adipohydrazide	01-2119962900-36 EC: 213-999-5	≤0.3	Aquatic Chronic 2,	-	[1]
	4,5-dichloro-2-octyl-2H- isothiazol-3-one	CAS: 64359-81-5	<0.1	Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	mg/kg ATE [Inhalation (dusts and mists)] = 0.16 mg/l Skin Corr. 1, H314: $C \ge 5\%$ Skin Irrit. 2, H315: 0.025% $\le C < 5\%$ Eye Dam. 1, H318: $C \ge 3\%$ Eye Irrit. 2, H319: 0.025% $\le C < 3\%$	

SECTION 3: Compo	sition/informat	ion on in	aredients		
				C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C $\geq 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]
Bronopol	EC: 200-143-0 CAS: 52-51-7 Index: 603-085-00-8	≤0.096	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400	ATE [Oral] = 307 mg/kg ATE [Dermal] = 1100 mg/kg M [Acute] = 10	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: 0.06% $\le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
2-methyl-2H-isothiazol- 3-one	EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 10 M [Chronic] = 1	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

2025 Date of previous issue

: 25/10/2023

SECTION 4: First aid measures

4.1 Description of first aid n	4.1 Description of first aid measures					
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.					
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.					
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.					
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.					
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.					

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

5.2 Special hazards arising from the substance or mixture

SECTION 5: Firefighting measures

Ŭ		•
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, prot	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for o	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

SECTION 7: Handling and storage

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Dan	ger criteria		
Cat	egory	Notification and MAPP threshold	Safety report threshold
E 2		200 tonnes	500 tonnes

7.3 Specific end use(s)

Recommendations Industrial sector specific solutions

: Not available.

: Not available.

3010110113

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Butoxyethanol	NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU
	derived Occupational Exposure Limit Values OELV 8 hours: 20 ppm. OELV 8 hours: 98 mg/m ³ . OELV 15 minutes: 50 ppm.
	OELV 15 minutes: 246 mg/m ³ .

Biological exposure indices

		Exposure indices		
		NAOSH (Ireland, 1/2011) BMGV: 200 mg/g creatinine, BAA [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.		
Recommended monitoring : procedures	European Stand assessment of values and mea atmospheres - of of exposure to of (Workplace atm	uld be made to monitoring standards, such as the following: dard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit asurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedures ement of chemical agents) Reference to national guidance		

Date of issue/Date of revision	: 28/05/2025	Date of previous issue	: 25/10/2023	Version	:2	6/23
DRYWOOD OPTIPRIMER LG - A	Il variants			Label No	1205	89

documents for methods for the determination of hazardous substances will also be required.

required.	
DNELs/DMELs	
Product/ingredient name	Result DNEL - General population - Long term - Inhalation 28 µg/m ³ Effects: Local
	DNEL - Workers - Long term - Inhalation 170 μg/m³ <u>Effects</u> : Local
2-Butoxyethanol	DNEL - General population - Long term - Oral 6.3 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Short term - Oral 26.7 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 59 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 98 mg/m³ <u>Effects</u> : Systemic
	DNEL - General population - Short term - Inhalation 147 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Short term - Inhalation 246 mg/m³ <u>Effects</u> : Local
	DNEL - General population - Short term - Inhalation 426 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Short term - Inhalation 1091 mg/m ³ <u>Effects</u> : Systemic
adipohydrazide	DNEL - Workers - Long term - Inhalation 17.5 mg/m ³ <u>Effects</u> : Systemic
1,2-benzisothiazol-3(2H)-one	DNEL - General population - Long term - Dermal 0.345 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 0.966 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 1.2 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 6.81 mg/m ³ <u>Effects</u> : Systemic
Bronopol	DNEL - General population - Short term - Oral
te of issue/Date of revision : 28/05/2025 RYWOOD OPTIPRIMER LG - All variants	Date of previous issue : 25/10/2023 Version : 2 Label No : 1/20589

0.5 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Inhalation 1.8 mg/m³ Effects: Systemic

DNEL - General population - Short term - Dermal 2.1 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Short term - Dermal 6 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Short term - Inhalation 10.5 mg/m³ Effects: Systemic

DNEL - General population - Short term - Dermal 4 µg/cm² Effects: Local

DNEL - General population - Long term - Dermal 4 µg/cm² Effects: Local

DNEL - Workers - Short term - Dermal 8 µg/cm² <u>Effects</u>: Local

DNEL - Workers - Long term - Dermal 8 µg/cm² <u>Effects</u>: Local

DNEL - General population - Long term - Oral 0.18 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Inhalation 0.6 mg/m³ Effects: Local

DNEL - General population - Long term - Inhalation 0.6 mg/m³ Effects: Local

DNEL - General population - Long term - Inhalation 0.6 mg/m³ <u>Effects</u>: Systemic

DNEL - General population - Long term - Dermal 0.7 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Long term - Dermal 2 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Short term - Inhalation 2.5 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation 2.5 mg/m³

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

2-methyl-2H-isothiazol-3-one

Effects: Local

DNEL - Workers - Long term - Inhalation 3.5 mg/m³ Effects: Systemic

DNEL - General population - Long term - Inhalation 0.02 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation 0.02 mg/m³ <u>Effects</u>: Local

DNEL - General population - Short term - Inhalation 0.04 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation 0.04 mg/m³ Effects: Local

DNEL - General population - Long term - Oral 0.09 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Oral 0.11 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation 0.021 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation 0.021 mg/m³ Effects: Local

DNEL - General population - Long term - Oral 0.027 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Inhalation 0.043 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation 0.043 mg/m³ Effects: Local

DNEL - General population - Short term - Oral 0.053 mg/kg bw/day <u>Effects</u>: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Date of issue/Date of revision: 28/05/2025DRYWOOD OPTIPRIMER LG - All variants

Date of previous issue

: 25/10/2023

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

b. I information on basic physic	sal anu chen	nical prope	rues			
<u>Appearance</u>						
Physical state	: Liquid.					
Colour	: Various					
Odour	: Slight	: Slight				
Odour threshold	: Not ava	ailable.				
Melting point/freezing point	: Not ava	: Not available.				
Initial boiling point and boiling range	:					
Ingredient name		°C	°F	Method		
water		100	212			
Ethyldiglycol		196	384.8			
Flammability	: Not ava	ilable.		·		
Lower and upper explosion limit			ethoxyethoxy)ethan 2-ethoxyethoxy)etha			
Date of issue/Date of revision	: 28/05/2025	Date of pre	vious issue : 2	5/10/2023	Version : 2	10/23

SECTION 9: Physical and chemical properties

Flash point

: Closed cup: 100°C (212°F)

Auto-ignition temperature :				
Ingredient name	°C	°F	Method	
<mark>,</mark> €t hyldiglycol	204	399.2		

Decomposition temperature	:	Not available.
рН	1	8.6 to 9
Viscosity	÷	Not available.
Solubility(ies)	÷	
Not available.		
Solubility in water	:	Not available.
Partition coefficient: n-octanol/ water	:	Not applicable.

ŝ

Vapour pressure

	Vapour Pressure at 20°C		V	Vapour pressure at 5		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
Ethyldiglycol	0.14	0.019				
Relative density	: Not	available.		4		I
Density	: 1.2	g/cm³				

Vapour density	: Not available.
Particle characteristics	

Median particle size	: Not applicable.
----------------------	-------------------

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties	: Not available.
Oxidising properties	: Not available.
9.2.2 Other safety characterist	ics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	;	No specific data.
10.5 Incompatible materials	;	No specific data.
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

4,5-dichloro-2-octyl-2H-isothiazol-3-one

Result

Rat - Oral - LD50 1585 mg/kg OECD [Acute Oral Toxicity]

Rabbit - Dermal - LD50 >652 mg/kg OECD [Acute Dermal Toxicity]

Rat - Male, Female - Inhalation - LC50 Dusts and mists 0.26 mg/l [4 hours] OECD [Acute Inhalation Toxicity]

1,2-benzisothiazol-3(2H)-one

Bronopol

Rat - Oral - LD50 1020 mg/kg

Rat - Dermal - LD50 4750 mg/kg

Rat - Oral - LD50 307 mg/kg

Rat - Inhalation - LC50 Dusts and mists >0.588 mg/l [4 hours]

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Rat - Oral - LD50 53 mg/kg <u>Toxic effects</u>: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration -Respiratory depression

2-methyl-2H-isothiazol-3-one

Rat - Inhalation - LC50 Dusts and mists

0.11 mg/l [4 hours]

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
P RYWOOD OPTIPRIMER LG	N/A	N/A	N/A	1250	N/A
2-Butoxyethanol	1200	N/A	N/A	3	N/A
4,5-dichloro-2-octyl-2H-isothiazol-3-one	567	N/A	N/A	N/A	0.16
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
Bronopol	307	1100	N/A	N/A	N/A
reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	53	50	N/A	0.5	N/A
2-methyl-2H-isothiazol-3-one	100	300	N/A	N/A	0.11

Skin corrosion/irritation

Product/ingredient name

Result

2025 Date of previous issue

: 25/10/2023

SECTION 11: Toxicological inform	nation
inanium dioxide	Human - Skin - Mild irritant Duration of treatment/exposure: 72 hours Amount/concentration applied: 300 ug l
2-Butoxyethanol	Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg
1,2-benzisothiazol-3(2H)-one	Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours
Bronopol	Amount/concentration applied: 5 % Human - Skin - Moderate irritant Amount/concentration applied: 10 mg
	Rabbit - Skin - Mild irritant <u>Duration of treatment/exposure</u> : 24 hours <u>Amount/concentration applied</u> : 500 mg
	Rabbit - Skin - Moderate irritant Amount/concentration applied: 80 mg
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Human - Skin - Severe irritant Amount/concentration applied: 0.01 %
Conclusion/Summary [Product] : Not available	ilable.
Serious eye damage/eye irritation	
Product/ingredient name 2-Butoxyethanol	Result Rabbit - Eyes - Moderate irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 100 mg
	Rabbit - Eyes - Severe irritant Amount/concentration applied: 100 mg
Conclusion/Summary [Product] : Not available	ilable.
Respiratory corrosion/irritation Not available.	
Conclusion/Summary [Product] : Not avai	ilable.
Respiratory or skin sensitization Not available.	
Skin Conclusion/Summary [Product] : Not avai	ilable.
Respiratory Conclusion/Summary [Product] : Not avail	ilable.
<u>Germ cell mutagenicity</u> Not available.	
Conclusion/Summary [Product] : Not avai	9. T. T.

SECTION 11: Toxicological information

DRYWOOD OPTIPRIMER LG - All variants

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. Not available.

Reproductive toxicity	
Not available.	
Conclusion/Summary [Pro	oduct] : Not available.
Specific target organ toxicit	y (single exposure)
Product/ingredient name	Result
Bronopol	STOT SE 3, H335 (Respiratory tract irritation)
Specific target organ toxicit	y (repeated exposure)
Not available.	
Aspiration hazard	
Not available.	
Information on likely routes	of exposure
Not available. Potential acute health effect	S
Eye contact	Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
	ysical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation
Ingestion	redness : No specific data.
	cts as well as chronic effects from short and long-term exposure
Short term exposure	cts as well as chronic effects from short and long-term exposure
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Not available. Conclusion/Summary [Pro	oduct] : Not available.
	 bduct] : Not available. : Once sensitized, a severe allergic reaction may occur when subsequently expose to very low levels.

Label No : 1/20589

SECTION 11: Toxicological information

Mutagenicity

- : No known significant effects or critical hazards.
- **Reproductive toxicity**
- : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity	
Product/ingredient name	Result Acute - LC50 - Marine water Fish - Mummichog - <i>Fundulus heteroclitus</i> >1000000 μg/l [96 hours] <u>Effect</u> : Mortality
	Acute - LC50 - Fresh water Crustaceans - Water flea - <i>Ceriodaphnia dubia</i> - Neonate <u>Age</u> : <24 hours 3 mg/l [48 hours] <u>Effect</u> : Mortality
2-Butoxyethanol	Acute - LC50 - Marine water Fish - Inland silverside - <i>Menidia beryllina</i> <u>Size</u> : 40 to 100 mm 1250000 μg/l [96 hours] <u>Effect</u> : Mortality
	Acute - LC50 - Marine water Crustaceans - Common shrimp, sand shrimp - <i>Crangon</i> <i>crangon</i> 800000 μg/l [48 hours] <u>Effect</u> : Mortality
4,5-dichloro-2-octyl-2H-isothiazol-3-one	Acute - EC50 - Fresh water Algae - Green algae - <i>Pseudokirchneriella subcapitata</i> 0.003 mg/l [72 hours] <u>Effect</u> : Population
	Acute - EC50 - Fresh water Daphnia - Water flea - <i>Daphnia magna</i> 0.001 mg/l [48 hours] <u>Effect</u> : Intoxication
	Acute - LC50 - Fresh water US EPA Fish - Rainbow trout,donaldson trout - <i>Oncorhynchus mykiss</i> <u>Weight</u> : 1.2 g 2.7 ppb [96 hours] <u>Effect</u> : Mortality
	Chronic - NOEC US EPA Fish - Rainbow trout,donaldson trout - <i>Oncorhynchus mykiss</i> 0.56 ppb [97 days] <u>Effect</u> : Growth
	Chronic - NOEC - Marine water

Date of issue/Date of revision : 28/05/2025 Date of previous issue : 25/10/2023 Version :2 15/23 Label No :1/20589 **DRYWOOD OPTIPRIMER LG - All variants**

SECTION 12: Ecological	information
-------------------------------	-------------

OECD

Algae - Diatom - *Nitzschia pungens* 19.789 μg/l [96 hours] Effect: Population

1,2-benzisothiazol-3(2H)-one

Bronopol

2-methyl-2H-isothiazol-3-one

Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test] Fish - Trout - *Onorhynchus Mykiss* 1.9 mg/l [96 hours]

Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - *Daphnia Magna* 3.7 mg/l [48 hours]

Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.36 mg/l [72 hours]

Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.15 mg/l [72 hours]

Acute - EC50

Daphnia 1.4 mg/l [48 hours]

Acute - LC50 Fish 41.2 mg/l [96 hours]

Chronic - NOEC

US EPA Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss* 1.94 ppm [49 days] <u>Effect</u>: Growth

Acute - EC50 - Fresh water

US EPA Algae - Green algae - *Scenedesmus subspicatus* 0.02 ppm [96 hours]

Acute - LC50 - Fresh water

US EPA Fish - Bluegill - *Lepomis macrochirus* <u>Weight</u>: 0.34 g 11.17 ppm [96 hours] <u>Effect</u>: Mortality

Acute - EC50 - Fresh water

US EPA Daphnia - Water flea - *Daphnia magna* <u>Age</u>: <24 hours 0.18 ppm [48 hours] <u>Effect</u>: Intoxication

Acute - LC50 - Fresh water

US EPA Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss* <u>Weight</u>: 0.73 g 0.07 ppm [96 hours] <u>Effect</u>: Mortality

: 28/05/2025 Date of previous issue

: 25/10/2023

SECTION 12: Ecological information

: Not available. Conclusion/Summary [Product]

12.2 Persistence and degradability

Product/ingredient name

2-benzisothiazol-3(2H)-one

Result

EU 24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
7,2-benzisothiazol-3(2H)-one	-	-	Inherent
Bronopol	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
· · · · · · · · · · · · · · · · · · ·	0.81	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low
Bronopol	0.18	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
2-Butoxyethanol	1.83	67.3685
adipohydrazide	1.74	55.2165
4,5-dichloro-2-octyl-2H-isothiazol-3-one	3.41	2562.01
1,2-benzisothiazol-3(2H)-one	1.86	73.142
Bronopol	1.02	10.3771
2-methyl-2H-isothiazol-3-one	1.74	54.9187

Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	Μ	т	vPvM	vP	vM
titanium dioxide	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
4,5-dichloro-2-octyl-2H- isothiazol-3-one	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
Bronopol	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No
Nobility	: Not av	ailable.					

Mobility

Conclusion/Summary

: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
4,5-dichloro-2-octyl-2H- isothiazol-3-one	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
Bronopol	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No
Regulation (EC) No. 1272/20	08 [CLP]						
Regulation (EC) No. 1272/20 Product/ingredient name	08 [CLP] PBT	Р	В	т	vPvB	vP	vB
• • •		P No	B	T No	vPvB No	vP No	vB No
Product/ingredient name	PBT						
Product/ingredient name Ittanium dioxide 2-Butoxyethanol	PBT No	No	No	No	No	No	No
Product/ingredient name	PBT No No	No No	No No	No No	No No	No No	No No
Product/ingredient name titanium dioxide 2-Butoxyethanol adipohydrazide 4,5-dichloro-2-octyl-2H- isothiazol-3-one	PBT No No No	No No No	No No No	No No No	No No No	No No No	No No No
Product/ingredient name Itanium dioxide 2-Butoxyethanol adipohydrazide 4,5-dichloro-2-octyl-2H-	PBT No No No No	No No No	No No No	No No No	No No No No	No No No No	No No No No
Product/ingredient name tranium dioxide 2-Butoxyethanol adipohydrazide 4,5-dichloro-2-octyl-2H- isothiazol-3-one 1,2-benzisothiazol-3(2H)-one	PBT No No No No	No No No No	No No No No	No No No No	No No No No	No No No No	No No No No

Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment method	S
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
European waste catalogue (EWC)	: 080112
Packaging	

SECTION 13: Disposal considerations

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (adipohydrazide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (adipohydrazide)	NVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (adipohydrazide)	NVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (adipohydrazide)
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group		111	111	111
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

Additional information

ADR/RID	:	This product is not regulated as a dangerous good when transported in sizes of \leq 5 L or \leq 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Tunnel code (-)
ADN	:	This product is not regulated as a dangerous good when transported in sizes of \leq 5 L or \leq 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	:	This product is not regulated as a dangerous good when transported in sizes of \leq 5 L or \leq 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	-	This product is not regulated as a dangerous good when transported in sizes of \leq 5 L or \leq 5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
14.6 Special precautions for user	:	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Maritime transport in bulk according to IMO instruments	:	Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

substances, mixtures and articles		
Product/ingredient name	%	Designation [Usage]
DRYWOOD OPTIPRIMER LG	≥90	3
Labelling :		
Other EU regulations		
Industrial emissions : Not listed (integrated pollution prevention and control) - Air		
Industrial emissions : Not listed (integrated pollution prevention and control) - Water		
Explosive precursors : Not applicab	e.	
Ozone depleting substances (EU 2024/590	1	
Not listed.		
Prior Informed Consent (PIC) (649/2012/EU	<u>J)</u>	
Not listed.		
Persistent Organic Pollutants Not listed.		
Seveso Directive		
This product is controlled under the Seveso I	Directive.	
Danger criteria		
Category		
₽2		
International regulations		
Chemical Weapon Convention List Schedu	les I, II & III (<u>Chemicals</u>
Not listed.		
Montreal Protocol		
Not listed.		
Stockholm Convention on Persistent Organ	nic Pollutant	'S
Not listed.		_
Rotterdam Convention on Prior Informed C	onsent (PIC)
Not listed.		-
UNECE Aarhus Protocol on POPs and Heav	vy Metals	
Not listed.		
15.2 Chemical safety assessment: This product required.	contains sub	ostances for which Chemical Safety Assessments are still

Date of issue/Date of revision	: 28/05/2025	Date of previous issue	: 25/10/2023	Version : 2	20/23
DRYWOOD OPTIPRIMER LG - A	All variants			Label No :120	589

SECTION 16: Other information

Indicates information that has changed from previously issued version.

	at has shanged norm providely located version.
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
Broodure used to derive	the electricities according to Regulation (EC) No. 1272/2008 [CL R/CHS]

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Date of issue/Date of revision	on : 28/05/2025 Date of previous issue : 25/10/2023 Vers	sion :2	21/23
Version	: 2		
Date of previous issue	: 25/10/2023		
Date of issue/ Date of revision	: 28/05/2025		
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3		
Skin Sens. 1A	SKIN SENSITISATION - Category 1A		
Skin Sens. 1	SKIN SENSITISATION - Category 1		
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2		
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C		
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B		
Eye Irrit. 2 Skin Corr. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 1		
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1		
Carc. 2	CARCINOGENICITY - Category 2		
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2		
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1		
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1		
Acute Tox. 4	ACUTE TOXICITY - Category 4		
Acute Tox. 3	ACUTE TOXICITY - Category 3		
Acute Tox. 2	ACUTE TOXICITY - Category 2		

SECTION 16: Other information

DRYWOOD OPTIPRIMER LG

All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 28/05/2025DRYWOOD OPTIPRIMER LG - All variants

: 28/05/2025 Date of previous issue