

# SAFETY DATA SHEET



DRYWOOD UV PRIMER UV RC - All variants

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : DRYWOOD UV PRIMER UV RC - All variants

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

#### National contact

Teknos (UK) Limited, 7 Longlands Rd, Bicester, Oxfordshire OX26 5AH, United Kingdom. Tel. +44 (0) 1869 208005.

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : NHS: 111

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to UK CLP/GHS

Eye Dam. 1, H318

Skin Sens. 1, H317

Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H412 - Harmful to aquatic life with long lasting effects.

#### Precautionary statements

**General** : P103 - Read carefully and follow all instructions.  
P102 - Keep out of reach of children.  
P101 - If medical advice is needed, have product container or label at hand.

**Prevention** : P280 - Wear protective gloves. Wear eye or face protection.  
P273 - Avoid release to the environment.  
P261 - Avoid breathing vapour.

## SECTION 2: Hazards identification

<b>Response</b>	: P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
<b>Storage</b>	: Not applicable.
<b>Disposal</b>	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Supplemental label elements</b>	: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	: Not applicable.

### 2.3 Other hazards

<b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b>	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
<b>Other hazards which do not result in classification</b>	: None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	REACH #: 01-2119489900-30 EC: 500-066-5 CAS: 28961-43-5	≥10 - ≤25	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
Vinylester resin	REACH #: 01-2119490020-53 EC: 500-130-2 CAS: 55818-57-0	≥10 - <25	Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
Dipropylenglycol diacrylate	REACH #: 01-2119484629-21 EC: 260-754-3 CAS: 57472-68-1	<10	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317	[1]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤5	Carc. 2, H351 (inhalation)	[1] [*]
Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide	REACH #: 01-2119972295-29 EC: 278-355-8 CAS: 75980-60-8 Index: 015-203-00-X	<1	Skin Sens. 1B, H317 Repr. 2, H361f (causing atrophy of the testes) Aquatic Chronic 2, H411	[1]
2-Methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	<1	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]
4-morpholinecarbaldehyde	REACH #: 01-2119987993-12 CAS: 4394-85-8	<1	Skin Sens. 1, H317	[1]
n-Butyl acetate	REACH #: 01-2119485493-29	≤0.3	Flam. Liq. 3, H226 Acute Tox. 2, H330	[1] [2]

**Date of issue/Date of revision** : 02/08/2022 **Date of previous issue** : 28/07/2022 **Version** : 1.01 2/16

DRYWOOD UV PRIMER UV RC - All variants

**Label No** :38454

## SECTION 3: Composition/information on ingredients

	EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1		Eye Irrit. 2, H319 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066 <b>See Section 16 for the full text of the H statements declared above.</b>
--	---	--	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq 10 \mu\text{m}$  not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

## SECTION 4: First aid measures

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
halogenated compounds  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

## SECTION 6: Accidental release measures

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

## SECTION 8: Exposure controls/personal protection

2-Methoxy-1-methylethyl acetate

**EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.**

STEL: 548 mg/m<sup>3</sup> 15 minutes.

TWA: 50 ppm 8 hours.

TWA: 274 mg/m<sup>3</sup> 8 hours.

STEL: 100 ppm 15 minutes.

n-Butyl acetate

**EH40/2005 WELs (United Kingdom (UK), 1/2020).**

STEL: 966 mg/m<sup>3</sup> 15 minutes.

STEL: 200 ppm 15 minutes.

TWA: 724 mg/m<sup>3</sup> 8 hours.

TWA: 150 ppm 8 hours.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	DNEL	Long term Dermal	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.8 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	1.4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	4.9 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	16.2 mg/m <sup>3</sup>	Workers	Systemic
Vinylester resin	DNEL	Long term Dermal	17.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.17 mg/m <sup>3</sup>	Workers	Systemic
Dipropylenglycol diacrylate	DNEL	Long term Dermal	1.66 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	2.08 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.77 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	7.24 mg/m <sup>3</sup>	General population	Systemic
titanium dioxide	DNEL	Long term Inhalation	24.48 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	10 mg/m <sup>3</sup>	Workers	Local
Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide	DNEL	Long term Oral	700 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	83.3 µg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	83.3 µg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.145 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0.233 mg/kg bw/day	Workers	Systemic
2-Methoxy-1-methylethyl acetate	DNEL	Long term Inhalation	0.822 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	1.67 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	33 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	33 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	54.8 mg/	General	Systemic

## SECTION 8: Exposure controls/personal protection

n-Butyl acetate	DNEL	Long term Dermal	kg bw/day 153.5 mg/ kg bw/day	population Workers	Systemic
	DNEL	Long term Inhalation	275 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	550 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Dermal	3.4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	7 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	12 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	48 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	6 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	11 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	35.7 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	300 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Systemic

### PNECs

No PNECs available

### 8.2 Exposure controls

#### Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### Individual protection measures

##### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

##### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

##### Skin protection

## SECTION 8: Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Recommendations : Wear suitable gloves tested to EN374.
- < 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
- 1 - 4 hours (breakthrough time): polyvinyl alcohol (PVA) thickness > 0.3 mm or 4H / Silver Shield® gloves.
- > 8 hours (breakthrough time): Viton® thickness > 0.3 mm gloves
- Wash hands before breaks and immediately after handling the product.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
hydroxycyclohexyl phenyl ketone	316.1	601	OECD 103
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	>391	>735.8	OECD 103

- Flammability (solid, gas)** : Not available.
- Upper/lower flammability or explosive limits** : Lower: Not applicable.  
Upper: Not applicable.
- Flash point** :

Ingredient name	Closed cup			Open cup		
	°C	°F	Method	°C	°F	Method
Dipropylenglycol diacrylate	137	278.6	DIN 51758			
hydroxycyclohexyl phenyl ketone	164	327.2	EU A.9			

- Auto-ignition temperature** :



## SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
Dipropylenglycol diacrylate	240	464	DIN 51794
Vinylester resin	465	869	EU A.15

**Decomposition temperature** : Not available.

**pH** : Not available.

**Viscosity** : Not available.

**Solubility(ies)** :  
Not available.

**Solubility in water** : Not available.

**Partition coefficient: n-octanol/ water** : Not applicable.

**Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	0	0	OECD 104			
Vinylester resin	0	0	OECD 104	0	0	OECD 104

**Relative density** : Not available.

**Density** : 1.6 g/cm<sup>3</sup>

**Vapour density** : Not available.

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

### Particle characteristics

**Median particle size** : Not applicable.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

**10.5 Incompatible materials** : No specific data.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

## SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	LD50 Dermal	Rabbit	>13 g/kg	-
Dipropylenglycol diacrylate	LD50 Oral	Rat	4600 mg/kg	-
2-Methoxy-1-methylethyl acetate	LD50 Dermal	Rabbit	>5 g/kg	-
n-Butyl acetate	LD50 Oral	Rat	8532 mg/kg	-
	LC50 Inhalation Vapour	Rat	0.74 mg/l	4 hours
	LD50 Dermal	Rabbit	14112 mg/kg	-
	LD50 Oral	Rat	10760 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Acute toxicity estimates

Route	ATE value
Inhalation (vapours)	474.36 mg/l

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Eyes - Moderate irritant	Rabbit	-	100 mg	-
Dipropylenglycol diacrylate	Skin - Moderate irritant	Rabbit	-	500 mg	-
titanium dioxide	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Severe irritant	Rabbit	-	500 mg	-
n-Butyl acetate	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Sensitisation

**Conclusion/Summary** : May cause an allergic skin reaction.

### Mutagenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Reproductive toxicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Teratogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-Methoxy-1-methylethyl acetate	Category 3	-	Narcotic effects
n-Butyl acetate	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

**Information on likely routes of exposure** : Not available.

## SECTION 11: Toxicological information

### Potential acute health effects

- Eye contact** : Causes serious eye damage.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : May cause an allergic skin reaction.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.  
**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Water flea - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Water flea - Daphnia pulex - Neonate	48 hours
n-Butyl acetate	Acute LC50 >1000000 µg/l Marine water	Fish - Mummichog - Fundulus heteroclitus	96 hours
	Acute LC50 32 mg/l Marine water	Crustaceans - Brine shrimp - Artemia salina	48 hours
	Acute LC50 18000 µg/l Fresh water	Fish - Fathead minnow - Pimephales promelas	96 hours

**Conclusion/Summary** : Harmful to aquatic life with long lasting effects.

## SECTION 12: Ecological information

### 12.2 Persistence and degradability

**Conclusion/Summary** : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2.89	-	low
Vinylester resin	1.6 to 3	-	low
Dipropylenglycol diacrylate	0.01 to 0.39	-	low
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide	-	53 to 72	low
n-Butyl acetate	2.3	-	low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**European waste catalogue (EWC)** : 080111\*

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB) /REACH

#### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

##### Ozone depleting substances

Not listed.

##### Prior Informed Consent (PIC)

Not listed.

##### Persistent Organic Pollutants

Not listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

##### Seveso Directive

This product is not controlled under the Seveso Directive.

##### EU regulations

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

## SECTION 15: Regulatory information

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = GB CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification

Classification	Justification
Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	Calculation method Calculation method Calculation method

### Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361f	Suspected of damaging fertility.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### Full text of classifications

## SECTION 16: Other information

Acute Tox. 2	ACUTE TOXICITY - Category 2
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of issue/ Date of revision** : 02/08/2022

**Date of previous issue** : 28/07/2022

**Version** : 1.01

DRYWOOD UV PRIMER UV RC

All variants

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

