

# SAFETY DATA SHEET



EPINOX 21 - TO-950 METALLIC GREY

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : EPINOX 21 - TO-950 METALLIC GREY

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

#### National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Fam. Liq. 3, H226

Eye Irrit. 2, H319

Skin Sens. 1, H317

Aquatic Acute 1, H400

Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

#### **Hazard pictograms**



**Signal word** : Warning

#### **Hazard statements**

H226 - Flammable liquid and vapour.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H410 - Very toxic to aquatic life with long lasting effects.

#### Precautionary statements

##### **Prevention**

P280 - Wear protective gloves. Wear eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P273 - Avoid release to the environment.  
P261 - Avoid breathing vapour.

## SECTION 2: Hazards identification

<b>Response</b>	: P391 - Collect spillage.
<b>Storage</b>	: Not applicable.
<b>Disposal</b>	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Hazardous ingredients</b>	: Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]
<b>Supplemental label elements</b>	:
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	:

### 2.3 Other hazards

<b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b>	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
<b>Other hazards which do not result in classification</b>	: None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Zinc powder - zinc dust (stabilized)	REACH #: 01-2119467174-37 EC: 231-175-3 CAS: 7440-66-6	≥75 - ≤90	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
n-Butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≤10	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]	CAS: 25036-25-3	≤6	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
iso-butanol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≤2.2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	-	[1]
Xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≤1.6	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (oral, inhalation) Asp. Tox. 1, H304	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]

## SECTION 3: Composition/information on ingredients

Solvent naphtha (petroleum), light aromatic	REACH #: 01-2119455851-35 EC: 265-199-0 CAS: 64742-95-6 Index: 649-356-00-4	≤2.4	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066 <b>See Section 16 for the full text of the H statements declared above.</b>	-	[1]
---	---	------	---	---	-----

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness

## SECTION 4: First aid measures

**Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
halogenated compounds  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

## SECTION 6: Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c E1	5000 tonne 100 tonne	50000 tonne 200 tonne

### 7.3 Specific end use(s)


- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.


### 8.1 Control parameters

#### Occupational exposure limits


Product/ingredient name	Exposure limit values
 Butyl acetate	<b>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values</b> STEL: 150 ppm 15 minutes. STEL: 723 mg/m <sup>3</sup> 15 minutes. TWA: 241 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.
Xylene	<b>EU OEL (Europe, 1/2022). [xylene, mixed isomers pure] Absorbed through skin. Notes: list of indicative occupational exposure limit values</b> TWA: 50 ppm 8 hours. TWA: 221 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m <sup>3</sup> 15 minutes.

#### Biological exposure indices

No exposure indices known.

**Recommended monitoring procedures** :  Reference should be made to monitoring standards, such as the following:  
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
 Zinc powder - zinc dust (stabilized)	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	2.5 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	5 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	6 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	11 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	35.7 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	300 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Local
n-Butyl acetate					



## SECTION 8: Exposure controls/personal protection

iso-butanol	DNEL	Inhalation Short term	600 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Inhalation Long term	3.4 mg/kg bw/day	General population	Systemic
	DNEL	Dermal Long term	7 mg/kg bw/day	Workers	Systemic
	DNEL	Inhalation Long term	12 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Inhalation Long term	48 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Inhalation Long term	55 mg/m <sup>3</sup>	General population	Local
Xylene	DNEL	Inhalation Long term	310 mg/m <sup>3</sup>	Workers	Local
	DNEL	Inhalation Long term	65.3 mg/m <sup>3</sup>	General population	Local
	DNEL	Inhalation Short term	260 mg/m <sup>3</sup>	General population	Local
	DNEL	Inhalation Short term	260 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Inhalation Long term	221 mg/m <sup>3</sup>	Workers	Local
	DNEL	Inhalation Long term	12.5 mg/kg bw/day	General population	Systemic
Solvent naphtha (petroleum), light aromatic	DNEL	Inhalation Long term	65.3 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Dermal Long term	125 mg/kg bw/day	General population	Systemic
	DNEL	Dermal Long term	212 mg/kg bw/day	Workers	Systemic
	DNEL	Inhalation Long term	221 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Inhalation Short term	442 mg/m <sup>3</sup>	Workers	Local
	DNEL	Inhalation Short term	442 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Inhalation Long term	0.41 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Inhalation Long term	1.9 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Inhalation Long term	178.57 mg/m <sup>3</sup>	General population	Local
	DNEL	Inhalation Short term	640 mg/m <sup>3</sup>	General population	Local
	DNEL	Inhalation Long term	837.5 mg/m <sup>3</sup>	Workers	Local
	DNEL	Inhalation Short term	1066.67 mg/m <sup>3</sup>	Workers	Local
	DNEL	Inhalation Short term	1152 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Inhalation Short term	1286.4 mg/m <sup>3</sup>	Workers	Systemic

### PNECs

No PNECs available

### 8.2 Exposure controls

#### Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Individual protection measures

## SECTION 8: Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Recommendations : Wear suitable gloves tested to EN374.
- < 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
- > 8 hours (breakthrough time): 4H / Silver Shield® gloves.
- Wash hands before breaks and immediately after handling the product.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Filter type: A
- Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Grey.
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :



## SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
iso-butanol	108	226.4	OECD 103
n-Butyl acetate	126	258.8	OECD 103

**Flammability** : Not available.

**Lower and upper explosion limit** : Lower: 0.8%  
Upper: 7.6%

**Flash point** : Closed cup: 23°C (73.4°F)

**Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Solvent naphtha (petroleum), light aromatic	280 to 470	536 to 878	
n-Butyl acetate	415	779	EU A.15

**Decomposition temperature** : Not available.

**pH** : Not applicable.

**Viscosity** : Not available.

**Solubility(ies)** :  
Not available.

**Solubility in water** : Not available.

**Partition coefficient: n-octanol/ water** : Not applicable.

**Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
n-Butyl acetate	11.25	1.5	DIN EN 13016-2			
iso-butanol	<12	<1.6	DIN EN 13016-2			

**Relative density** : Not available.

**Density** : 3.1 g/cm<sup>3</sup>

**Vapour density** : Not available.

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

**Particle characteristics**

**Median particle size** : Not applicable.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
oxidising materials

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-Butyl acetate	LC50 Inhalation Vapour	Rat	0.74 mg/l	4 hours
	LD50 Dermal	Rabbit	14112 mg/kg	-
	LD50 Oral	Rat	10760 mg/kg	-
iso-butanol	LC50 Inhalation Vapour	Rat	19200 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	3400 mg/kg	-
	LD50 Oral	Rat	2460 mg/kg	-
Xylene	LC50 Inhalation Vapour	Rat	21.7 mg/l	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
Solvent naphtha (petroleum), light aromatic	LD50 Oral	Rat	8400 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Acute toxicity estimates

Route	ATE value
Dermal	66618.69 mg/kg
Inhalation (vapours)	666.19 mg/l

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Zinc powder - zinc dust (stabilized)	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
n-Butyl acetate	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Xylene	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 uL	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Solvent naphtha (petroleum), light aromatic	Eyes - Mild irritant	Rabbit	-	24 hours 100 uL	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Sensitisation

**Conclusion/Summary** : May cause an allergic skin reaction.

#### Mutagenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Carcinogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Reproductive toxicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Teratogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
n-Butyl acetate	Category 3	-	Narcotic effects
iso-butanol	Category 3	-	Respiratory tract irritation
Xylene	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
Solvent naphtha (petroleum), light aromatic	Category 3	-	Respiratory tract

## SECTION 11: Toxicological information

	Category 3		irritation Narcotic effects
--	------------	--	--------------------------------

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Xylene	Category 2	oral, inhalation	-

### Aspiration hazard

Product/ingredient name	Result
Xylene Solvent naphtha (petroleum), light aromatic	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : May cause an allergic skin reaction.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness  
**Inhalation** : No specific data.  
**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
**Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.  
**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

## SECTION 11: Toxicological information

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Zinc powder - zinc dust (stabilized)	Acute EC50 106 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
	Acute EC50 10000 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute IC50 65 µg/l Marine water	Algae - Nitzschia closterium - Exponential growth phase	4 days
	Acute LC50 65 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 68 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 12.21 µg/l Marine water	Fish - Periophthalmus waltoni - Adult	96 hours
	Chronic EC10 27.3 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
	Chronic EC10 59.2 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 9 mg/l Fresh water	Aquatic plants - Ceratophyllum demersum	3 days
	Chronic NOEC 178 µg/l Marine water	Crustaceans - Palaemon elegans	21 days
	Chronic NOEC 2.6 µg/l Fresh water	Fish - Cyprinus carpio	4 weeks
	Acute LC50 32 mg/l Marine water	Crustaceans - Artemia salina	48 hours
	Acute LC50 18000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 600 mg/l Marine water	Crustaceans - Artemia salina	48 hours
n-Butyl acetate	Acute LC50 1030000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
iso-butanol	Acute LC50 1330000 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
Solvent naphtha (petroleum), light aromatic	Acute EC50 3.2 mg/l	Daphnia	48 hours
	Acute LC50 9.2 mg/l	Fish	96 hours

**Conclusion/Summary** : Very toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
iso-butanol	-	74 % - Readily - 28 days	-	-

**Conclusion/Summary** : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
iso-butanol	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
n-Butyl acetate	2.3	-	low
iso-butanol	1	-	low
Xylene	3.12	8.1 to 25.9	low
Solvent naphtha (petroleum), light aromatic	-	10 to 2500	high

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

## SECTION 12: Ecological information

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.








**European waste catalogue (EWC)** : 080111\*, 200127\*

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT (zinc, Solvent naphtha (petroleum), light arom.)	PAINT
14.3 Transport hazard class(es)	3  	3  	3  	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

#### Additional information

## SECTION 14: Transport information

<b>ADR/RID</b>	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Tunnel code</b> (D/E)
<b>ADN</b>	: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
<b>IMDG</b>	: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
<b>IATA</b>	: The environmentally hazardous substance mark may appear if required by other transportation regulations.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions** :  
on the manufacture,  
placing on the market  
and use of certain  
dangerous substances,  
mixtures and articles

#### Other EU regulations

**Industrial emissions** : Listed  
(integrated pollution  
prevention and control) -  
Air

**Industrial emissions** : Listed  
(integrated pollution  
prevention and control) -  
Water

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### Persistent Organic Pollutants

Not listed.

#### Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

##### **Category**

P5c  
E1



## SECTION 15: Regulatory information

### [International regulations](#)

#### [Chemical Weapon Convention List Schedules I, II & III Chemicals](#)

Not listed.

#### [Montreal Protocol](#)

Not listed.

#### [Stockholm Convention on Persistent Organic Pollutants](#)

Not listed.

#### [Rotterdam Convention on Prior Informed Consent \(PIC\)](#)

Not listed.

#### [UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

### 15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

### [Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Classification	Justification
Flam. Liq. 3, H226 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	On basis of test data Calculation method Calculation method Calculation method Calculation method

### [Full text of abbreviated H statements](#)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### [Full text of classifications \[CLP/GHS\]](#)

## SECTION 16: Other information

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of issue/ Date of revision** : 07/06/2023

**Date of previous issue** : 23/09/2022

**Version** : 2

EPINOX 21\_TO-950 METALLIC GREY

TO-950 METALLIC GREY

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

