

SAFETY DATA SHEET



FEIDOPUR ZD55 - All variants

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : FEIDOPUR ZD55 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Eye Irrit. 2, H319

Skin Sens. 1, H317

STOT SE 3, H336

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 - Flammable liquid and vapour.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P280 - Wear protective gloves. Wear eye or face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.

Response : P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Storage : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Date of issue/Date of revision : 09/02/2026 **Date of previous issue** : 27/05/2025

Version : 4.01 1/42

FEIDOPUR ZD55 - All variants

Label No : 41863

SECTION 2: Hazards identification

- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazardous ingredients** : Contains: n-Butyl acetate; Acrylic polymer; Solvent naphtha (petroleum), light aromatic and Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
- Supplemental label elements** : Repeated exposure may cause skin dryness or cracking.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

2.3 Other hazards

- Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
- Other hazards which do not result in classification** : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
n-Butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥10 - ≤25	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
Acrylic polymer	-	≤10	Eye Irrit. 2, H319 Skin Sens. 1B, H317	-	[1]
Solvent naphtha (petroleum), light aromatic	REACH #: 01-2119455851-35 EC: 265-199-0 CAS: 64742-95-6 Index: 649-356-00-4	≤10	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	-	[1]
2-Methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≤5	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
Xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≤3	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (oral, inhalation) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]

SECTION 3: Composition/information on ingredients

2-butoxyethyl acetate	REACH #: 01-2119475112-47 EC: 203-933-3 CAS: 112-07-2	≤3	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1500 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≤0.62	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
propylidynetrimethanol	REACH #: 01-2119486799-10 EC: 201-074-9 CAS: 77-99-6	≤0.3	Repr. 2, H361fd	-	[1]
Fatty acids, tall-oil, compds. with oleylamine	REACH #: 01-2120101675-63	<0.1	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1A, H317 STOT RE 2, H373 (digestive system, immune system, liver) Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/kg	[1]
2,3-epoxypropyl neodecanoat	REACH #: 01-2119431597-33 EC: 247-979-2 CAS: 26761-45-5 Index: 607-770-00-2	≤0.01	Skin Sens. 1A, H317 Muta. 2, H341 Repr. 2, H361d Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.	Skin Sens. 1, H317: C ≥ 0.001%	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

- : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

- : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SECTION 4: First aid measures

- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

SECTION 5: Firefighting measures

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

SECTION 7: Handling and storage

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
 Butyl acetate	Regulation on Limit Values - MAC (Austria, 12/2024) [Butylacetat alle Isomeren außer tert-Butylacet] CEIL: 480 mg/m ³ . CEIL: 100 ppm. TWA 8 hours: 241 mg/m ³ . TWA 8 hours: 50 ppm.
2-Methoxy-1-methylethyl acetate	Regulation on Limit Values - MAC (Austria, 12/2024) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . CEIL 5 minutes: 100 ppm 8 times per shift. CEIL 5 minutes: 550 mg/m ³ 8 times per shift.
Xylene	Regulation on Limit Values - MAC (Austria, 12/2024) [Xylol (alle Isomeren, rein)] PEAK 15 minutes: 442 mg/m ³ 4 times per shift.

SECTION 8: Exposure controls/personal protection

2-butoxyethyl acetate	<p>TWA 8 hours: 50 ppm. PEAK 15 minutes: 100 ppm 4 times per shift. TWA 8 hours: 221 mg/m³.</p> <p>Regulation on Limit Values - MAC (Austria, 12/2024) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 133 mg/m³. PEAK 30 minutes: 40 ppm 4 times per shift. PEAK 30 minutes: 270 mg/m³ 4 times per shift.</p>
2,3-epoxypropyl neodecanoat	<p>Regulation on Limit Values - MAC (Austria, 12/2024) [1,2-Epoxy-3-(tolylxy)propan (alle Isomeren)] Carc B. TWA 8 hours: 10 ppm. TWA 8 hours: 70 mg/m³. PEAK 15 minutes: 20 ppm 4 times per shift. PEAK 15 minutes: 140 mg/m³ 4 times per shift.</p>
n-Butyl acetate	<p>Limit values (Belgium, 12/2023) [butylacetaat] STEL 15 minutes: 712 mg/m³. STEL 15 minutes: 150 ppm. TWA 8 hours: 238 mg/m³. TWA 8 hours: 50 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>Limit values (Belgium, 12/2023) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³.</p>
Xylene	<p>Limit values (Belgium, 12/2023) [Xyleen] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.</p>
2-butoxyethyl acetate	<p>Limit values (Belgium, 12/2023) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 133 mg/m³. STEL 15 minutes: 50 ppm. STEL 15 minutes: 333 mg/m³.</p>
n-Butyl acetate	<p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Limit value 8 hours: 241 mg/m³. Limit value 15 minutes: 723 mg/m³. Limit value 15 minutes: 150 ppm. Limit value 8 hours: 50 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Absorbed through skin. Limit value 8 hours: 275 mg/m³. Limit value 15 minutes: 550 mg/m³. Limit value 15 minutes: 100 ppm. Limit value 8 hours: 50 ppm.</p>
Xylene	<p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) [Xylene] Absorbed through skin. Limit value 8 hours: 221 mg/m³. Limit value 15 minutes: 442 mg/m³. Limit value 15 minutes: 100 ppm. Limit value 8 hours: 50 ppm.</p>
2-butoxyethyl acetate	<p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Absorbed through skin. Limit value 8 hours: 133 mg/m³. Limit value 15 minutes: 333 mg/m³. Limit value 8 hours: 20 ppm. Limit value 15 minutes: 50 ppm.</p>

SECTION 8: Exposure controls/personal protection

propylidynetrimethanol	Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Limit value 8 hours: 50 mg/m ³ .
<input checked="" type="checkbox"/> Butyl acetate	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) STELV 15 minutes: 723 mg/m ³ . STELV 15 minutes: 150 ppm. ELV 8 hours: 241 mg/m ³ . ELV 8 hours: 50 ppm.
Solvent naphtha (petroleum), light aromatic	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia) ELV: 100 ppm. ELV: 400 mg/m ³ .
2-Methoxy-1-methylethyl acetate	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) Absorbed through skin. STELV 15 minutes: 550 mg/m ³ . STELV 15 minutes: 100 ppm. ELV 8 hours: 275 mg/m ³ . ELV 8 hours: 50 ppm.
Xylene	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) [ksilen] Absorbed through skin. STELV 15 minutes: 442 mg/m ³ . STELV 15 minutes: 100 ppm. ELV 8 hours: 221 mg/m ³ . ELV 8 hours: 50 ppm.
2-butoxyethyl acetate	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) Absorbed through skin. STELV 15 minutes: 333 mg/m ³ . STELV 15 minutes: 50 ppm. ELV 8 hours: 133 mg/m ³ . ELV 8 hours: 20 ppm.
<input checked="" type="checkbox"/> Butyl acetate	Department of labour inspection (Cyprus, 7/2021) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m ³ .
2-Methoxy-1-methylethyl acetate	Department of labour inspection (Cyprus, 7/2021) Absorbed through skin. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ .
Xylene	Department of labour inspection (Cyprus, 7/2021) [Ξυλένιο, μικτά ισομερή, καθαρά] Absorbed through skin. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m ³ .
2-butoxyethyl acetate	Department of labour inspection (Cyprus, 7/2021) Absorbed through skin. STEL 15 minutes: 50 ppm. STEL 15 minutes: 333 mg/m ³ . TWA 8 hours: 20 ppm. TWA 8 hours: 133 mg/m ³ .

SECTION 8: Exposure controls/personal protection

<p> Butyl acetate</p>	<p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) TWA 8 hours: 241 mg/m³. STEL 15 minutes: 723 mg/m³. STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm.</p>
<p>Solvent naphtha (petroleum), light aromatic</p>	<p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) [nafta solventní] TWA 8 hours: 200 mg/m³. STEL 15 minutes: 1000 mg/m³.</p>
<p>2-Methoxy-1-methylethyl acetate</p>	<p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) Absorbed through skin. TWA 8 hours: 275 mg/m³. TWA 8 hours: 50 ppm. STEL 15 minutes: 550 mg/m³. STEL 15 minutes: 100 ppm.</p>
<p>Xylene</p>	<p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) [xylen] Absorbed through skin. TWA 8 hours: 200 mg/m³. TWA 8 hours: 45.33 ppm. STEL 15 minutes: 400 mg/m³. STEL 15 minutes: 90.66 ppm.</p>
<p>2-butoxyethyl acetate</p>	<p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) Absorbed through skin. TWA 8 hours: 130 mg/m³. TWA 8 hours: 19.5 ppm. STEL 15 minutes: 300 mg/m³. STEL 15 minutes: 45 ppm.</p>
<p> Butyl acetate</p>	<p>Working Environment Authority (Denmark, 12/2024) [butylacetat, alle isomerer] TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m³. STEL 15 minutes: 723 mg/m³. STEL 15 minutes: 150 ppm.</p>
<p>2-Methoxy-1-methylethyl acetate</p>	<p>Working Environment Authority (Denmark, 12/2024) [2-methoxy-1-methylethylacetat] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³. STEL 15 minutes: 550 mg/m³. STEL 15 minutes: 100 ppm.</p>
<p>Xylene</p>	<p>Working Environment Authority (Denmark, 12/2024) [xylen, alle isomere] Absorbed through skin. TWA 8 hours: 25 ppm. TWA 8 hours: 109 mg/m³. STEL 15 minutes: 442 mg/m³. STEL 15 minutes: 100 ppm.</p>
<p>2-butoxyethyl acetate</p>	<p>Working Environment Authority (Denmark, 12/2024) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 134 mg/m³. STEL 15 minutes: 333 mg/m³. STEL 15 minutes: 50 ppm.</p>
<p> Butyl acetate</p>	<p>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m³.</p>
<p>2-Methoxy-1-methylethyl acetate</p>	<p>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) Absorbed through skin , Sensitiser. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³.</p>

SECTION 8: Exposure controls/personal protection

Xylene	<p>TWA 8 hours: 275 mg/m³. TWA 8 hours: 50 ppm.</p> <p>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) [ksüleen] Absorbed through skin. TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm. STEL 15 minutes: 450 mg/m³. TWA 8 hours: 200 mg/m³.</p>
2-butoxyethyl acetate	<p>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) Absorbed through skin , Sensitiser. TWA 8 hours: 133 mg/m³. TWA 8 hours: 20 ppm. STEL 15 minutes: 333 mg/m³. STEL 15 minutes: 50 ppm.</p>
<input checked="" type="checkbox"/> Butyl acetate	<p>EU OEL (Europe, 1/2022) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³. TWA 8 hours: 241 mg/m³. TWA 8 hours: 50 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³.</p>
Xylene	<p>EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.</p>
2-butoxyethyl acetate	<p>EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 133 mg/m³. STEL 15 minutes: 50 ppm. STEL 15 minutes: 333 mg/m³.</p>
<input checked="" type="checkbox"/> Butyl acetate	<p>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) TWA 8 hours: 150 ppm. TWA 8 hours: 720 mg/m³. STEL 15 minutes: 200 ppm. STEL 15 minutes: 960 mg/m³.</p>
Solvent naphtha (petroleum), light aromatic	<p>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2020) TWA 8 hours: 100 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 270 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³.</p>
Xylene	<p>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) [Ksyleeni] Absorbed through skin. STEL 15 minutes: 440 mg/m³. TWA 8 hours: 220 mg/m³. TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm.</p>
2-butoxyethyl acetate	<p>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 130 mg/m³. STEL 15 minutes: 50 ppm. STEL 15 minutes: 330 mg/m³.</p>

SECTION 8: Exposure controls/personal protection

<p> n-Butyl acetate</p>	<p>Ministry of Labor (France, 6/2024) TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 241 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 150 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 723 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p>
<p>Solvent naphtha (petroleum), light aromatic</p>	<p>Ministry of Labor (France, 6/2024) [hydrocarbures en C6-C12] TWA 8 hours: 1000 mg/m³. Form: Vapour. Notes: Permissible limit values (circulars) STEL 15 minutes: 1500 mg/m³. Form: Vapour. Notes: Permissible limit values (circulars)</p>
<p>2-Methoxy-1-methylethyl acetate</p>	<p>Ministry of Labor (France, 6/2024) Absorbed through skin. STEL 15 minutes: 550 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 100 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 275 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p>
<p>Xylene</p>	<p>Ministry of Labor (France, 6/2024) [xylènes, isomères mixtes, purs] Absorbed through skin. STEL 15 minutes: 442 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 100 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 221 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p>
<p>2-butoxyethyl acetate</p>	<p>Ministry of Labor (France, 6/2024) Absorbed through skin. STEL 15 minutes: 333 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 66.5 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 10 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p>
<p> n-Butyl acetate</p>	<p>TRGS 900 OEL (Germany, 6/2024) TWA 8 hours: 300 mg/m³. TWA 8 hours: 62 ppm. PEAK 15 minutes: 600 mg/m³. PEAK 15 minutes: 124 ppm. DFG MAC-values list (Germany, 7/2024) Develop C. TWA 8 hours: 100 ppm. PEAK 15 minutes: 200 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 480 mg/m³. PEAK 15 minutes: 960 mg/m³ 4 times per shift [Interval: 1 hour].</p>
<p>2-Methoxy-1-methylethyl acetate</p>	<p>TRGS 900 OEL (Germany, 6/2024) TWA 8 hours: 270 mg/m³. PEAK 15 minutes: 270 mg/m³. TWA 8 hours: 50 ppm. PEAK 15 minutes: 50 ppm. DFG MAC-values list (Germany, 7/2024) Develop C. TWA 8 hours: 50 ppm. PEAK 15 minutes: 50 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 270 mg/m³. PEAK 15 minutes: 270 mg/m³ 4 times per shift [Interval: 1 hour].</p>

SECTION 8: Exposure controls/personal protection

Xylene	<p>TRGS 900 OEL (Germany, 6/2024) [Xylol] Absorbed through skin. TWA 8 hours: 220 mg/m³. PEAK 15 minutes: 440 mg/m³. TWA 8 hours: 50 ppm. PEAK 15 minutes: 100 ppm.</p> <p>DFG MAC-values list (Germany, 7/2024) [Xylene] Develop D. Absorbed through skin. TWA 8 hours: 50 ppm. PEAK 15 minutes: 100 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 220 mg/m³. PEAK 15 minutes: 440 mg/m³ 4 times per shift [Interval: 1 hour].</p>
2-butoxyethyl acetate	<p>TRGS 900 OEL (Germany, 6/2024) Absorbed through skin. TWA 8 hours: 65 mg/m³. PEAK 15 minutes: 130 mg/m³. TWA 8 hours: 10 ppm. PEAK 15 minutes: 20 ppm.</p> <p>DFG MAC-values list (Germany, 7/2024) Develop C. Absorbed through skin. TWA 8 hours: 10 ppm. PEAK 15 minutes: 20 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 66 mg/m³. PEAK 15 minutes: 132 mg/m³ 4 times per shift [Interval: 1 hour].</p>
Butyl acetate	<p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³.</p>
Xylene	<p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) [ξυλόλια (όλα τα ισομερή)] Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 435 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 650 mg/m³.</p>
2-butoxyethyl acetate	<p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) TWA 8 hours: 20 ppm. TWA 8 hours: 135 mg/m³. STEL 15 minutes: 40 ppm. STEL 15 minutes: 270 mg/m³.</p>
Butyl acetate	<p>5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) Sensitiser. TWA 8 hours: 241 mg/m³. PEAK 15 minutes: 723 mg/m³. PEAK 15 minutes: 150 ppm. TWA 8 hours: 50 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) TWA 8 hours: 275 mg/m³. PEAK 15 minutes: 550 mg/m³. PEAK 15 minutes: 100 ppm. TWA 8 hours: 50 ppm.</p>
Xylene	<p>5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) [xilol izomerek keveréke] Absorbed through skin. TWA 8 hours: 221 mg/m³. PEAK 15 minutes: 442 mg/m³. PEAK 15 minutes: 100 ppm.</p>

SECTION 8: Exposure controls/personal protection

2-butoxyethyl acetate	TWA 8 hours: 50 ppm. 5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) Absorbed through skin. TWA 8 hours: 133 mg/m ³ . PEAK 15 minutes: 333 mg/m ³ . PEAK 15 minutes: 50 ppm. TWA 8 hours: 20 ppm.
<input checked="" type="checkbox"/> Butyl acetate	Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) [bútýlasetat, allir ísómerar] TWA 8 hours: 241 mg/m ³ . TWA 8 hours: 50 ppm. STEL 15 minutes: 723 mg/m ³ . STEL 15 minutes: 150 ppm.
2-Methoxy-1-methylethyl acetate	Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) Absorbed through skin. STEL 15 minutes: 550 mg/m ³ . STEL 15 minutes: 100 ppm. TWA 8 hours: 275 mg/m ³ . TWA 8 hours: 50 ppm.
Xylene	Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) [Xýlen, allir ísómerar] Absorbed through skin. STEL 15 minutes: 442 mg/m ³ . STEL 15 minutes: 100 ppm. TWA 8 hours: 109 mg/m ³ . TWA 8 hours: 25 ppm.
2-butoxyethyl acetate	Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) Absorbed through skin. STEL 15 minutes: 333 mg/m ³ . STEL 15 minutes: 50 ppm. TWA 8 hours: 133 mg/m ³ . TWA 8 hours: 20 ppm.
<input checked="" type="checkbox"/> Butyl acetate	NAOSH (Ireland, 4/2024) Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 50 ppm. OELV 8 hours: 241 mg/m ³ . OELV 15 minutes: 150 ppm. OELV 15 minutes: 723 mg/m ³ .
2-Methoxy-1-methylethyl acetate	NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 50 ppm. OELV 8 hours: 275 mg/m ³ . OELV 15 minutes: 100 ppm. OELV 15 minutes: 550 mg/m ³ .
Xylene	NAOSH (Ireland, 4/2024) [xylene] Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 50 ppm. OELV 8 hours: 221 mg/m ³ . OELV 15 minutes: 100 ppm. OELV 15 minutes: 442 mg/m ³ .
2-butoxyethyl acetate	NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 20 ppm. OELV 8 hours: 133 mg/m ³ . OELV 15 minutes: 50 ppm. OELV 15 minutes: 333 mg/m ³ .
<input checked="" type="checkbox"/> Butyl acetate	Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024) Short Term 15 minutes: 150 ppm. Short Term 15 minutes: 723 mg/m ³ . Limit value 8 hours: 50 ppm. Limit value 8 hours: 241 mg/m ³ .
2-Methoxy-1-methylethyl acetate	Legislative Decree No. 81/2008. Title IX. Protection from

SECTION 8: Exposure controls/personal protection

Xylene	<p>chemical agents, carcinogens and mutagens (Italy, 9/2024) Absorbed through skin. Limit value 8 hours: 50 ppm. Limit value 8 hours: 275 mg/m³. Short Term 15 minutes: 100 ppm. Short Term 15 minutes: 550 mg/m³.</p>
2-butoxyethyl acetate	<p>Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024) [xilene, isomeri misti, puro] Absorbed through skin. Limit value 8 hours: 50 ppm. Limit value 8 hours: 221 mg/m³. Short Term 15 minutes: 100 ppm. Short Term 15 minutes: 442 mg/m³.</p>
n-Butyl acetate	<p>Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024) Absorbed through skin. Limit value 8 hours: 20 ppm. Limit value 8 hours: 133 mg/m³. Short Term 15 minutes: 50 ppm. Short Term 15 minutes: 333 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) TWA 8 hours: 241 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³. TWA 8 hours: 50 ppm.</p>
Xylene	<p>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³.</p>
2-butoxyethyl acetate	<p>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) [Ksilols] Absorbed through skin. TWA 8 hours: 221 mg/m³. TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.</p>
n-Butyl acetate	<p>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) Absorbed through skin. STEL 15 minutes: 50 ppm. TWA 8 hours: 133 mg/m³. TWA 8 hours: 20 ppm. STEL 15 minutes: 333 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) TWA 8 hours: 241 mg/m³. TWA 8 hours: 50 ppm. STEL 15 minutes: 723 mg/m³. STEL 15 minutes: 150 ppm.</p>
Xylene	<p>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) Absorbed through skin. TWA 8 hours: 250 mg/m³. TWA 8 hours: 50 ppm. STEL 15 minutes: 400 mg/m³. STEL 15 minutes: 75 ppm.</p>
2-butoxyethyl acetate	<p>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) [ksilenas, mišrūs izomerai, grynas] Absorbed through skin. STEL 15 minutes: 442 mg/m³. TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm. TWA 8 hours: 221 mg/m³.</p>

SECTION 8: Exposure controls/personal protection

propylidynetrimethanol	TWA 8 hours: 70 mg/m ³ . TWA 8 hours: 10 ppm. STEL 15 minutes: 140 mg/m ³ . STEL 15 minutes: 20 ppm.
 n-Butyl acetate	Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) CEIL: 5 ppm. Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m ³ .
2-Methoxy-1-methylethyl acetate	Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ .
Xylene	Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) [xylène Isomères mixtes, pures] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m ³ .
2-butoxyethyl acetate	Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 133 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 333 mg/m ³ .
 n-Butyl acetate	EU OEL (Europe, 1/2022) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ . TWA 8 hours: 241 mg/m ³ . TWA 8 hours: 50 ppm.
2-Methoxy-1-methylethyl acetate	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ .
Xylene	EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m ³ .
2-butoxyethyl acetate	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 133 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 333 mg/m ³ .
 n-Butyl acetate	Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) TWA 8 hours: 241 mg/m ³ . STEL 15 minutes: 723 mg/m ³ . STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm.
2-Methoxy-1-methylethyl acetate	Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) TWA 8 hours: 550 mg/m ³ . TWA 8 hours: 100 ppm.

SECTION 8: Exposure controls/personal protection

Xylene	<p>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) [xyleen, o-, m-, p-isomeren] Absorbed through skin.</p> <p>TWA 8 hours: 210 mg/m³. STEL 15 minutes: 442 mg/m³. STEL 15 minutes: 100 ppm. TWA 8 hours: 47.5 ppm.</p>
2-butoxyethyl acetate	<p>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) Absorbed through skin.</p> <p>TWA 8 hours: 135 mg/m³. STEL 15 minutes: 333 mg/m³. TWA 8 hours: 20.3 ppm. STEL 15 minutes: 50 ppm.</p>
<input checked="" type="checkbox"/> Butyl acetate	<p>FOR-2011-12-06-1358 (Norway, 5/2024)</p> <p>STEL 15 minutes: 723 mg/m³. STEL 15 minutes: 150 ppm. TWA 8 hours: 241 mg/m³. TWA 8 hours: 50 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p>FOR-2011-12-06-1358 (Norway, 5/2024) Absorbed through skin.</p> <p>TWA 8 hours: 50 ppm. TWA 8 hours: 270 mg/m³.</p>
Xylene	<p>FOR-2011-12-06-1358 (Norway, 5/2024) [xylen] Absorbed through skin.</p> <p>TWA 8 hours: 25 ppm. TWA 8 hours: 108 mg/m³.</p>
2-butoxyethyl acetate	<p>FOR-2011-12-06-1358 (Norway, 5/2024) Absorbed through skin.</p> <p>TWA 8 hours: 10 ppm. TWA 8 hours: 65 mg/m³.</p>
<input checked="" type="checkbox"/> Butyl acetate	<p>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024)</p> <p>TWA 8 hours: 240 mg/m³. STEL 15 minutes: 720 mg/m³.</p>
2-Methoxy-1-methylethyl acetate	<p>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) Absorbed through skin.</p> <p>TWA 8 hours: 260 mg/m³. STEL 15 minutes: 520 mg/m³.</p>
Xylene	<p>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) [xylene – mixed isomers (1,2-, 1,3-, 1,4-)] Absorbed through skin.</p> <p>TWA 8 hours: 100 mg/m³. STEL 15 minutes: 200 mg/m³.</p>
2-butoxyethyl acetate	<p>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) Absorbed through skin.</p> <p>TWA 8 hours: 100 mg/m³. STEL 15 minutes: 300 mg/m³.</p>

SECTION 8: Exposure controls/personal protection

<p>n-Butyl acetate</p>	<p>Portuguese Institute of Quality (Portugal, 11/2014) TWA 8 hours: 150 ppm. STEL 15 minutes: 200 ppm. Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m³.</p>
<p>2-Methoxy-1-methylethyl acetate</p>	<p>Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) Absorbed through skin. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m³.</p>
<p>Xylene</p>	<p>Portuguese Institute of Quality (Portugal, 11/2014) [xileno (isómeros o, m & p)] A4. TWA 8 hours: 100 ppm. STEL 15 minutes: 150 ppm. Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) [xilenos] Absorbed through skin. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³.</p>
<p>2-butoxyethyl acetate</p>	<p>Portuguese Institute of Quality (Portugal, 11/2014) A3. TWA 8 hours: 20 ppm. Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) Absorbed through skin. STEL 15 minutes: 50 ppm. STEL 15 minutes: 333 mg/m³. TWA 8 hours: 20 ppm. TWA 8 hours: 133 mg/m³.</p>
<p>n-Butyl acetate</p>	<p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) VLA 8 hours: 241 mg/m³. VLA 8 hours: 50 ppm. Short term 15 minutes: 723 mg/m³. Short term 15 minutes: 150 ppm.</p>
<p>Solvent naphtha (petroleum), light aromatic</p>	<p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) [Solvent nafta] Absorbed through skin. VLA 8 hours: 100 mg/m³. Short term 15 minutes: 200 mg/m³.</p>
<p>2-Methoxy-1-methylethyl acetate</p>	<p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) Absorbed through skin. VLA 8 hours: 275 mg/m³. VLA 8 hours: 50 ppm. Short term 15 minutes: 550 mg/m³. Short term 15 minutes: 100 ppm.</p>
<p>Xylene</p>	<p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) [xilen] Absorbed through skin. VLA 8 hours: 221 mg/m³. VLA 8 hours: 50 ppm. Short term 15 minutes: 442 mg/m³. Short term 15 minutes: 100 ppm.</p>
<p>2-butoxyethyl acetate</p>	<p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) Absorbed through skin. VLA 8 hours: 133 mg/m³. VLA 8 hours: 20 ppm. Short term 15 minutes: 333 mg/m³. Short term 15 minutes: 50 ppm.</p>

SECTION 8: Exposure controls/personal protection

n-Butyl acetate

Government regulation SR c. 355/2006 (Slovakia, 6/2024)

[butylacetáty] Inhalation sensitiser.

TWA 8 hours: 241 mg/m³ (Butyl acetates).

TWA 8 hours: 50 ppm (Butyl acetates).

STEL 15 minutes: 723 mg/m³ (Butyl acetates).

STEL 15 minutes: 150 ppm (Butyl acetates).

2-Methoxy-1-methylethyl acetate

Government regulation SR c. 355/2006 (Slovakia, 6/2024)

Absorbed through skin , Inhalation sensitiser.

TWA 8 hours: 275 mg/m³.

TWA 8 hours: 50 ppm.

STEL 15 minutes: 550 mg/m³.

STEL 15 minutes: 100 ppm.

Xylene

Government regulation SR c. 355/2006 (Slovakia, 6/2024)

[xylén, zmiešané izoméry] Absorbed through skin , Inhalation sensitiser.

TWA 8 hours: 221 mg/m³ (xylene, mixed isomers).

TWA 8 hours: 50 ppm (xylene, mixed isomers).

STEL 15 minutes: 442 mg/m³ (xylene, mixed isomers).

STEL 15 minutes: 100 ppm (xylene, mixed isomers).

2-butoxyethyl acetate

Government regulation SR c. 355/2006 (Slovakia, 6/2024)

Absorbed through skin , Inhalation sensitiser.

TWA 8 hours: 133 mg/m³.

TWA 8 hours: 20 ppm.

STEL 15 minutes: 333 mg/m³.

STEL 15 minutes: 50 ppm.

n-Butyl acetate

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

TWA 8 hours: 241 mg/m³.

TWA 8 hours: 50 ppm.

KTV 15 minutes: 723 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

KTV 15 minutes: 150 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

2-Methoxy-1-methylethyl acetate

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

Absorbed through skin.

TWA 8 hours: 275 mg/m³.

TWA 8 hours: 50 ppm.

KTV 15 minutes: 550 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

KTV 15 minutes: 100 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

Xylene

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

[ksilen] Absorbed through skin.

TWA 8 hours: 221 mg/m³.

TWA 8 hours: 50 ppm.

KTV 15 minutes: 442 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

KTV 15 minutes: 100 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

2-butoxyethyl acetate

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

Absorbed through skin.

TWA 8 hours: 133 mg/m³.

TWA 8 hours: 20 ppm.

KTV 15 minutes: 333 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

KTV 15 minutes: 50 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

SECTION 8: Exposure controls/personal protection

n-Butyl acetate	National institute of occupational safety and health (Spain, 1/2024) TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m ³ . STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ .
2-Methoxy-1-methylethyl acetate	National institute of occupational safety and health (Spain, 1/2024) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ .
Xylene	National institute of occupational safety and health (Spain, 1/2024) [xileno, mezcla isómeros] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m ³ .
2-butoxyethyl acetate	National institute of occupational safety and health (Spain, 1/2024) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 133 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 333 mg/m ³ .
n-Butyl acetate	Work environment authority Regulation 2018:1 (Sweden, 11/2022) [butyl acetate] TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m ³ . STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ .
2-Methoxy-1-methylethyl acetate	Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ .
Xylene	Work environment authority Regulation 2018:1 (Sweden, 11/2022) [xylene] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m ³ .
2-butoxyethyl acetate	Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. TWA 8 hours: 10 ppm. TWA 8 hours: 70 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 333 mg/m ³ .
propylidynetrimethanol	Work environment authority Regulation 2018:1 (Sweden, 11/2022) TWA 8 hours: 5 mg/m ³ .
n-Butyl acetate	SUVA (Switzerland, 1/2025) TWA 8 hours: 50 ppm. TWA 8 hours: 240 mg/m ³ . STEL 15 minutes: 150 ppm. STEL 15 minutes: 720 mg/m ³ .
2-Methoxy-1-methylethyl acetate	SUVA (Switzerland, 1/2025) TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 275 mg/m ³ .
Xylene	SUVA (Switzerland, 1/2025) [Xylo] Absorbed through skin.

SECTION 8: Exposure controls/personal protection

2-butoxyethyl acetate	TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 440 mg/m ³ .
<input checked="" type="checkbox"/> Butyl acetate	SUVA (Switzerland, 1/2025) Absorbed through skin. TWA 8 hours: 10 ppm. Form: vapour and aerosols. TWA 8 hours: 66 mg/m ³ . Form: vapour and aerosols. STEL 15 minutes: 20 ppm. Form: vapour and aerosols. STEL 15 minutes: 132 mg/m ³ . Form: vapour and aerosols.
2-Methoxy-1-methylethyl acetate	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 966 mg/m ³ . STEL 15 minutes: 200 ppm. TWA 8 hours: 724 mg/m ³ . TWA 8 hours: 150 ppm.
Xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 548 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 274 mg/m ³ . STEL 15 minutes: 100 ppm.
2-butoxyethyl acetate	EH40/2005 WELs (United Kingdom (UK), 1/2020) [xylene, o-,m-, p- or mixed isomers] Absorbed through skin. STEL 15 minutes: 441 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m ³ . STEL 15 minutes: 100 ppm.
2-butoxyethyl acetate	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. TWA 8 hours: 20 ppm. STEL 15 minutes: 50 ppm. STEL 15 minutes: 332 mg/m ³ . TWA 8 hours: 133 mg/m ³ .

Biological exposure indices

Product/ingredient name	Exposure indices
<input checked="" type="checkbox"/> Xylene	VGU BEI (Austria, 9/2020) [Xylole] BEI Fitness: 1000 µg/l, xylene [in blood]. Sampling time: one year. BEI Fitness: 1.5 g/l, methylhippuricacid [in urine]. Sampling time: one year.
No exposure indices known.	
No exposure indices known.	
<input checked="" type="checkbox"/> Xylene	Ordinance on the protection of workers from exposure to hazardous chemicals at work, biological limit values (Annex IV) (Croatia, 12/2023) [ksilen] BEI: 1.5 mg/l, xylene [in blood]. Sampling time: at the end of the work shift. BEI: 14.13 µmol/l, xylene [in blood]. Sampling time: at the end of the work shift. BEI: 0.88 mol/mol creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the work shift. BEI: 1.5 g/g creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the work shift.
No exposure indices known.	
<input checked="" type="checkbox"/> Xylene	Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015) [Xyleny] Biological limit values: 820 µmol/mmol creatinine, methylhippuric acid [in urine]. Sampling time: end of the shift. Biological limit values: 1400 mg/g creatinine, methylhippuric acid [in urine]. Sampling time: end of the shift.

SECTION 8: Exposure controls/personal protection

2-butoxyethyl acetate

Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015)

Biological limit values: 0.17 mmol/mmol creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week.

Biological limit values: 200 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week.

No exposure indices known.

No exposure indices known.

No exposure indices known.

Xylene

Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020) [Ksyleeni]

BEI: 5 mmol/l, methylhippuric acid [in urine]. Sampling time: at the end of the work shift.

2-butoxyethyl acetate

Biological limit values (BLV) - Labour Code / ANSES (France, 4/2023) [2- butoxyéthanol et son acétate]

BLV: 100 mg/g Cr, 2-butoxyacetic acid [in urine]. Sampling time: end of shift (regardless of the day of the week).

Xylene

DFG BEI-values list (Germany, 7/2024) [Xylene (all isomers)]

Notes: danger from percutaneous absorption (see p. 211 and p. 228).

BEI: 1800 mg/g creatinine, Methylhippuric acids (=toluric acids) (all isomers) [in urine]. Sampling time: end of exposure or end of shift.

TRGS 903 - BEI Values (Germany, 10/2024) [Xylol alle Isomeren]

BEI: 2000 mg/l, methylhippuric acid [in urine]. Sampling time: end of exposure or end of shift.

2-butoxyethyl acetate

DFG BEI-values list (Germany, 7/2024) Notes: danger from percutaneous absorption (see p. 211 and p. 228).

BEI: 150 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the shift, for long-term exposures after several previous shifts.

TRGS 903 - BEI Values (Germany, 10/2024)

BEI: 150 mg/g, butoxy acetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the shift, for long-term exposure after several previous shifts.

No exposure indices known.

Xylene

5/2020. (II. 6.) ITM Decree (Hungary, 12/2023) [xilol]

BEI: 1500 mg/g creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the shift.

BEI: 860 µmol/mmol creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the shift.

No exposure indices known.

Xylene

NAOSH BGVs (Ireland, 1/2011) [Xylene]

BMGV: 1.5 g/g creatinine, methylhippuric acids [in urine].

Sampling time: end of shift - As soon as possible after exposure ceases.

No exposure indices known.

Xylene

Minister Cabinet Regulations No.325 - BEI (Latvia, 3/2024) [ksiloli (visi izomēri)]

BEI: 2000 mg/l, methylhippuric (toluric) acid (all isomers) [in urine]. Sampling time: at the end of the exposure or at the end of the shift.

No exposure indices known.

No exposure indices known.

SECTION 8: Exposure controls/personal protection

No exposure indices known.	
Xylene	Portuguese Institute of Quality (Portugal, 11/2014) [Xilenos (graus técnico e comercial)] BEI: 1.5 g/g creatinine, (o, m, p) -methyl-boronic acids [in urine]. Sampling time: end of shift.
Xylene	HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2024) [xilén] OBLV: 3 g/l, methylhippuric acid [in urine]. Sampling time: end of shift.
Xylene	Government regulation SR c. 355/2006 (Slovakia, 6/2024) [xylén (všetky izoméry)] BLV: 781 µmol/mmol creatinine, as sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift. BLV: 1334 mg/g creatinine, as sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift. BLV: 10355 µmol/l, as sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift. BLV: 14.6 µmol/l, as xylene [in blood]. Sampling time: at the end of exposure or work shift. BLV: 2000 mg/l, as sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift. BLV: 1.5 mg/l, as xylene [in blood]. Sampling time: at the end of exposure or work shift.
Xylene	Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) [ksilen (vse izomere)] BAT: 2 g/l, methylhippuric acid (all isomers) [in urine]. Sampling time: at the end of the work shift.
2-butoxyethyl acetate	Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) BAT: 150 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the work shift, at long-term exposure: at the end of the work shift after several consecutive workdays.
Xylene	National institute of occupational safety and health (Spain, 1/2024) [Xilenos] VLB: 1 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.
No exposure indices known.	
Xylene	SUVA (Switzerland, 1/2025) [Xylol (alle Isomere)] BEI: 2 g/l, methyl hippuric acid [in urine]. Sampling time: immediately after exposure or after working hours.
2-butoxyethyl acetate	SUVA (Switzerland, 1/2025) BEI: 150 mg/g creatinine, 2-butoxy acetic acid (after hydrolysis) [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift.
Xylene	EH40/2005 BMGVs (United Kingdom (UK), 1/2020) [Xylene, o-, m-, p- or mixed isomers] BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift.

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

Butyl acetate

Result

DNEL - General population - Long term - Oral

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Oral

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

3.4 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

6 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

7 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Dermal

11 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

12 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

35.7 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

48 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

300 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

300 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

300 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

600 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

SECTION 8: Exposure controls/personal protection

	600 mg/m ³ <u>Effects</u> : Systemic
Solvent naphtha (petroleum), light aromatic	DNEL - General population - Long term - Inhalation 0.41 mg/m ³ <u>Effects</u> : Systemic DNEL - Workers - Long term - Inhalation 1.9 mg/m ³ <u>Effects</u> : Systemic DNEL - General population - Long term - Inhalation 178.57 mg/m ³ <u>Effects</u> : Local DNEL - General population - Short term - Inhalation 640 mg/m ³ <u>Effects</u> : Local DNEL - Workers - Long term - Inhalation 837.5 mg/m ³ <u>Effects</u> : Local DNEL - Workers - Short term - Inhalation 1066.67 mg/m ³ <u>Effects</u> : Local DNEL - General population - Short term - Inhalation 1152 mg/m ³ <u>Effects</u> : Systemic DNEL - Workers - Short term - Inhalation 1286.4 mg/m ³ <u>Effects</u> : Systemic
2-Methoxy-1-methylethyl acetate	DNEL - General population - Long term - Inhalation 33 mg/m ³ <u>Effects</u> : Local DNEL - General population - Long term - Inhalation 33 mg/m ³ <u>Effects</u> : Systemic DNEL - General population - Long term - Oral 36 mg/kg bw/day <u>Effects</u> : Systemic DNEL - Workers - Long term - Inhalation 275 mg/m ³ <u>Effects</u> : Systemic DNEL - General population - Long term - Dermal 320 mg/kg bw/day <u>Effects</u> : Systemic DNEL - Workers - Short term - Inhalation 550 mg/m ³ <u>Effects</u> : Local DNEL - Workers - Long term - Dermal 796 mg/kg bw/day <u>Effects</u> : Systemic
Xylene	DNEL - General population - Long term - Oral 5 mg/kg bw/day <u>Effects</u> : Systemic

SECTION 8: Exposure controls/personal protection

DNEL - General population - Long term - Inhalation

65.3 mg/m³

Effects: Local

DNEL - General population - Long term - Inhalation

65.3 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

125 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

212 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

221 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

221 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

260 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

260 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

442 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

442 mg/m³

Effects: Systemic

2-butoxyethyl acetate

DNEL - General population - Long term - Inhalation

80 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

133 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

200 mg/m³

Effects: Local

DNEL - General population - Long term - Oral

8.6 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Oral

36 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

72 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

SECTION 8: Exposure controls/personal protection

102 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Dermal

120 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

169 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Inhalation

333 mg/m³

Effects: Local

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

DNEL - General population - Long term - Oral

0.18 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.31 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

0.9 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

1.27 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

1.8 mg/kg bw/day

Effects: Systemic

propylidynetrimethanol

DNEL - General population - Long term - Oral

0.34 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

0.34 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.58 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.94 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

3.3 mg/m³

Effects: Systemic

2,3-epoxypropyl neodecanoat

DNEL - General population - Long term - Oral

2.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

2.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

4 mg/m³

Effects: Systemic

SECTION 8: Exposure controls/personal protection

DNEL - Workers - Long term - Dermal

4.2 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

5.88 mg/m³

Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.

Body protection

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection

- : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

- : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type: A

Filter type (spray application): A P

SECTION 8: Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Colour : Various
Odour : Slight
Odour threshold : Not available.
Melting point/freezing point : Not available.
Initial boiling point and boiling range :

Ingredient name	°C	°F	Method
Butyl acetate	126	258.8	OECD 103
Solvent naphtha (petroleum), light aromatic	135 to 210	275 to 410	

Flammability : Not available.
Lower and upper explosion limit : Lower: 0.8% (xylene)
Upper: 7.6% (n-butyl acetate)
Flash point : Closed cup: 24°C (75.2°F)
Auto-ignition temperature :

Ingredient name	°C	°F	Method
Solvent naphtha (petroleum), light aromatic	280 to 470	536 to 878	
2-Methoxy-1-methylethyl acetate	333	631.4	DIN 51794

Decomposition temperature : Not available.
pH : Not applicable.
Viscosity : Not available.
Solubility(ies) :
Not available.
Solubility in water : Not available.
Partition coefficient: n-octanol/ water : Not applicable.
Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Butyl acetate	11.25096	1.5	DIN EN 13016-2			
Xylene	6.7	0.89				

Relative density : Not available.
Density : 0.73 g/cm³
Vapour density : Not available.
Particle characteristics
Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

SECTION 9: Physical and chemical properties

Explosive properties : Not available.

Oxidising properties : Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials : Reactive or incompatible with the following materials:
oxidising materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

Butyl acetate

Result

Rat - Oral - LD50

10760 mg/kg
EU

Rabbit - Dermal - LD50

14112 mg/kg

Rat - Inhalation - LC50 Vapour

0.74 mg/l [4 hours]

Solvent naphtha (petroleum), light aromatic

Rat - Oral - LD50

8400 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Tremor Lung, Thorax, or Respiration - Other changes

2-Methoxy-1-methylethyl acetate

Rat - Oral - LD50

8532 mg/kg

Rabbit - Dermal - LD50

>5 g/kg

Xylene

Rat - Oral - LD50

4300 mg/kg

Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other changes

Rat - Inhalation - LC50 Vapour

21.7 mg/l [4 hours]

2-butoxyethyl acetate

Rat - Oral - LD50

2400 mg/kg

Toxic effects: Kidney, Ureter, and Bladder - Hematuria Kidney, Ureter, and Bladder - Other changes in urine composition

Date of issue/Date of revision

: 09/02/2026

Date of previous issue

: 27/05/2025

Version : 4.01 29/42

FEIDOPUR ZD55 - All variants

Label No : 1863

SECTION 11: Toxicological information

Rabbit - Dermal - LD50

1500 mg/kg

Toxic effects: Kidney, Ureter, and Bladder - Hematuria Kidney, Ureter, and Bladder - Other changes in urine composition
Blood - Normocytic anemia

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Rat - Oral - LD50

3230 mg/kg

propylidynetrimethanol

Rat - Dermal - LD50

>3170 mg/kg

Rat - Oral - LD50

14000 mg/kg

2,3-epoxypropyl neodecanoat

Rat - Oral - LD50

>10 g/kg

Toxic effects: Behavioral - Ataxia Gross Metabolite Changes - Weight loss or decreased weight gain

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
FEIDOPUR ZD55	23255.8	25070.3	N/A	221.7	N/A
n-Butyl acetate	10760	14112	N/A	N/A	N/A
Solvent naphtha (petroleum), light aromatic	8400	N/A	N/A	N/A	N/A
2-Methoxy-1-methylethyl acetate	8532	N/A	N/A	N/A	N/A
Xylene	4300	1100	N/A	11	N/A
2-butoxyethyl acetate	500	1500	N/A	11	N/A
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3230	N/A	N/A	N/A	N/A
propylidynetrimethanol	14000	N/A	N/A	N/A	N/A
Fatty acids, tall-oil, compds. with oleylamine	500	N/A	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name

n-Butyl acetate

Result

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Xylene

Rat - Skin - Mild irritant

Duration of treatment/exposure: 8 hours

Amount/concentration applied: 60 uL

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

2-butoxyethyl acetate

Rabbit - Skin - Moderate irritant

Amount/concentration applied: 100 %

2,3-epoxypropyl neodecanoat

Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

Rabbit - Skin - Moderate irritant

Amount/concentration applied: 0.5 MI

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

 Butyl acetate

Solvent naphtha (petroleum), light aromatic

Xylene

2-butoxyethyl acetate

Result

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 mg

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 uL

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 87 mg

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

SECTION 11: Toxicological information

Product/ingredient name	Result
n-Butyl acetate	STOT SE 3, H336 (Narcotic effects)
Solvent naphtha (petroleum), light aromatic	STOT SE 3, H335 (Respiratory tract irritation)
	STOT SE 3, H336 (Narcotic effects)
2-Methoxy-1-methylethyl acetate	STOT SE 3, H336 (Narcotic effects)
Xylene	STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
Xylene	STOT RE 2, H373 (oral, inhalation)
Fatty acids, tall-oil, compds. with oleylamine	STOT RE 2, H373 (digestive system, immune system, liver)

Aspiration hazard

Product/ingredient name	Result
Solvent naphtha (petroleum), light aromatic	ASPIRATION HAZARD - Category 1
Xylene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
Ingestion	: Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

SECTION 11: Toxicological information

- Carcinogenicity** : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

Butyl acetate

Result

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*
Age: 31 to 32 days; Size: 21.6 mm; Weight: 0.175 g
18000 µg/l [96 hours]
Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Brine shrimp - *Artemia salina*
32 mg/l [48 hours]
Effect: Mortality

Solvent naphtha (petroleum), light aromatic

Acute - LC50

Fish
9.2 mg/l [96 hours]

Acute - EC50

Daphnia
3.2 mg/l [48 hours]

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Acute - LC50

OECD [Fish, Acute Toxicity Test]
Fish - *Brachydanio rerio*
0.9 mg/l [96 hours]

EC50

OECD [Alga, Growth Inhibition Test]
Aquatic plants - *Desmodesmodus subspicatus*
1.68 mg/l [72 hours]

Chronic - NOEC

OECD [Daphnia Magna Reproduction Test]
Daphnia - Daphnia
1 mg/l [21 days]

propylidynetrimethanol

Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*
Age: 1 to 3 days
13000000 µg/l [48 hours]
Effect: Intoxication

Acute - LC50 - Marine water

Fish - Sheepshead minnow - *Cyprinodon variegatus*
14400000 µg/l [96 hours]
Effect: Mortality

Conclusion/Summary [Product] : Not available.

SECTION 12: Ecological information

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Butyl acetate	2.3	-	Low
Solvent naphtha (petroleum), light aromatic	-	10 to 2500	High
2-Methoxy-1-methylethyl acetate	1.2	-	Low
Xylene	3.12	8.1 to 25.9	Low
2-butoxyethyl acetate	1.51	-	Low
propylidynetrimethanol	-0.47	<1 [OECD 305 C]	Low
2,3-epoxypropyl neodecanoat	4.4	-	High

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
Butyl acetate	1.5	33.2139
2-Methoxy-1-methylethyl acetate	0.36	2.31363
2-butoxyethyl acetate	2.1	112.842
propylidynetrimethanol	1.2	16.5101

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Butyl acetate	No	No	No	No	No	No	No
Acrylic polymer	No	No	No	No	No	No	No
Solvent naphtha (petroleum), light aromatic	No	No	No	No	No	No	No
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Xylene	No	No	No	No	No	No	No
2-butoxyethyl acetate	No	No	No	No	No	No	No
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	No	No	No	No	No	No	No
propylidynetrimethanol	No	No	No	No	No	No	No
Fatty acids, tall-oil, compds. with oleylamine	No	No	No	No	No	No	No
2,3-epoxypropyl neodecanoat	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
<input checked="" type="checkbox"/> Butyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
Acrylic polymer	No	N/A	N/A	No	N/A	N/A	N/A
Solvent naphtha (petroleum), light aromatic	No	N/A	No	No	No	N/A	No
2-Methoxy-1-methylethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
Xylene	No	N/A	No	Yes	No	N/A	No
2-butoxyethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A
propylidynetrimethanol	No	N/A	No	Yes	No	N/A	No
Fatty acids, tall-oil, compds. with oleylamine	N/A	N/A	N/A	Yes	N/A	N/A	N/A
2,3-epoxypropyl neodecanoat	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
<input checked="" type="checkbox"/> Butyl acetate	No	No	No	No	No	No	No
Acrylic polymer	No	No	No	No	No	No	No
Solvent naphtha (petroleum), light aromatic	No	No	No	No	No	No	No
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Xylene	No	No	No	No	No	No	No
2-butoxyethyl acetate	No	No	No	No	No	No	No
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	No	No	No	No	No	No	No
propylidynetrimethanol	No	No	No	No	No	No	No
Fatty acids, tall-oil, compds. with oleylamine	No	No	No	No	No	No	No
2,3-epoxypropyl neodecanoat	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC) : 08 01 11*

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADR/RID : **Tunnel code** (D/E)

ADN : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
FEIDOPUR ZD55	≥90	3

Labelling :

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c

National regulations

Austria

VbF class : Category 3

Limitation of the use of organic solvents : Permitted.

Belgium

Czech Republic

Storage code : II

Denmark

Fire class : II-1

Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
Titanium dioxide	Listed	-
Ethylbenzene	Listed	-

MAL-code : 4-5

SECTION 15: Regulatory information

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 4-5

Application: When using scraper or knife, brush, roller etc. for pre- and post-treatments in a spray booth where the operator is outside the spray zone and when working in similar new* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in new* booths and cabins with non-atomizing guns.

- Protective clothing must be worn.

When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Air-supplied half mask, protective clothing and eye protection must be worn.

When spraying in new* booths if the operator is outside the spray zone.

- Air-supplied half mask and eye protection must be worn.

When spraying in existing* spray booths, if the operator is outside the spray zone. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Air-supplied full mask and protective clothing must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, protective clothing and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc. must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

Restrictions on use : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

SECTION 15: Regulatory information

List of undesirable substances : Not listed

Carcinogenic waste : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

Finland

France

Social Security Code, Articles L 461-1 to L 461-7 : Butyl acetate RG 84
Solvent naphtha (petroleum), light aromatic RG 84
2-Methoxy-1-methylethyl acetate RG 84
Xylene RG 4bis, RG 84
2-butoxyethyl acetate RG 84

Reinforced medical surveillance : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

Germany

Storage class (TRGS 510) : 3

Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

Danger criteria

Category	Reference number
P5c	1.2.5.3

Hazard class for water : 2

Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
<input checked="" type="checkbox"/> 5.2.1	Total dust	63.7
5.2.2 [III]	Dusty inorganic substances	0.01
5.2.5	Organic substances	36.2
5.2.5 [I]	Organic substances	23
5.2.7.2	Poorly degradable, easily accumulating and highly toxic organic substances	0.084

AOX : The product contains organically bound halogens and can contribute to the AOX value in waste water.

Italy

D.Lgs. 152/06 : Not determined.

Netherlands

Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development	Harmful via breastfeeding
<input checked="" type="checkbox"/> Solvent naphtha (petroleum), light arom.	Listed	Listed	-	-	-
xyleen	-	-	-	Development 2	-
hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, containing <2% of aromatics, < 0,1% of benzene, < 1% of n-hexane and < 0,5 % of aromatic hydrocarbons	Listed	Listed	-	-	-

Water Discharge Policy (ABM) : Z(1) Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioacumulative potential/ toxicity or persistence). Decontamination effort: Z

Norway

SECTION 15: Regulatory information

Sweden

Flammable liquid class : 2a
(SRVFS 2005:10)

Switzerland

VOC content : VOC (w/w): 31.5%

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H336 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

✔H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.

Date of issue/Date of revision : 09/02/2026 **Date of previous issue** : 27/05/2025

Version : 4.01 40/42

FEIDOPUR ZD55 - All variants

Label No : 41863

SECTION 16: Other information

H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Muta. 2	GERM CELL MUTAGENICITY - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 09/02/2026

Date of previous issue : 27/05/2025

Version : 4.01

FEIDOPUR ZD55

All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

