SAFETY DATA SHEET



INFRALIT EP 8024-21 - All variants

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : INFRALIT EP 8024-21 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person :

responsible for this SDS

: Prod-safe@teknos.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360FD Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms









Signal word : Danger

Hazard statements : H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H360FD - May damage fertility. May damage the unborn child. H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention: P201 - Obtain special instructions before use.

P280 - Wear protective gloves, protective clothing, eye protection, face protection,

Label No : 1/29558

or hearing protection.

P273 - Avoid release to the environment.

Response : P391 - Collect spillage.

P308 + P313 - IF exposed or concerned: Get medical advice or attention.

Storage : Not applicable.

Date of issue/Date of revision: 26/09/2025Date of previous issue: 13/06/2023Version: 51/22

SECTION 2: Hazards identification

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients

Supplemental label

contains: bisphenol A and 2-methylimidazole

elements

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

: Restricted to professional users.

2.3 Other hazards

articles

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.

: Contains bisphenol A. May cause endocrine disruption.

Other hazards which do not result in classification : May form explosible dust-air mixture if dispersed.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
prsphenol A	REACH #: 01-2119457856-23 EC: 201-245-8 CAS: 80-05-7 Index: 604-030-00-0	≤10	Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 1B, H360F STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 10	[1] [2] [3] [4]
2-methylimidazole	REACH #: 01-2119980041-46 EC: 211-765-7 CAS: 693-98-1 Index: 613-330-00-0	<1	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Carc. 2, H351 Repr. 1B, H360Df See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 500 mg/kg	[1] [4]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

Substance classified with a health or environmental hazard

- [2] Substance with a workplace exposure limit
- [3] Substance of equivalent concern Endocrine disrupting properties
- [4] Substance with carcinogenic, mutagenic or reproductive toxicity properties

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 26/09/2025 · 13/06/2023 Version :5 2/22 Date of previous issue Label No : 1/29558

SECTION 4: First aid measures

4.1 Description of first aid measures

Eve contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eves with plenty of water, occasionally lifting the upper and lower evelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

· 13/06/2023

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

> pain watering redness

Inhalation : Adverse symptoms may include the following:

> reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

Date of issue/Date of revision

• 26/09/2025 Date of previous issue Version :5

3/22

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

5.2 Special hazards arising from the substance or mixture

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Hazards from the substance or mixture

: This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill

: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 13/06/2023 Version:5 4/22 : 26/09/2025 Date of previous issue Label No : 1/29558

SECTION 6: Accidental release measures

Large spill

: Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

	Notification and MAPP threshold	Safety report threshold
E 1	100 tonnes	200 tonnes

7.3 Specific end use(s)

: Not available. Recommendations **Industrial sector specific** : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Date of issue/Date of revision : 26/09/2025 : 13/06/2023 Version:5 5/22 Date of previous issue Label No : 1/29558

Product/ingredient name	Exposure limit values
bisphenol A	Regulation on Limit Values - MAC (Austria, 12/2024) F. Sensitiser. TWA 8 hours: 2 mg/m³. Form: Inhalable fraction. CEIL: 5 mg/m³. Form: Inhalable fraction.
bisphenol A	Limit values (Belgium, 12/2023) TWA 8 hours: 2 mg/m³.
b ísphenol A	Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 10/2003 (OEL). (Bulgaria, 4/2024) Limit value 8 hours: 2 mg/m³. Form: inhalable fraction
b ísphenol A	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) Repr 1B. Skin sensitiser. ELV 8 hours: 2 mg/m³. Form: Inhalable fraction.
písphenol A	Department of labour inspection (Cyprus, 7/2021) TWA 8 hours: 2 mg/m³. Form: Inhalable fraction
písphenol A	Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) Repr. Sensitiser. TWA 8 hours: 2 mg/m³. Form: dust, aerosol, inhalable fraction. STEL 15 minutes: 5 mg/m³. Form: dust, aerosol, inhalable fraction.
Ørganic dust	Working Environment Authority (Denmark) TWA 8 hours: 3 mg/m³.
bisphenol A	Working Environment Authority (Denmark, 12/2024) TWA 8 hours: 2 mg/m³. Form: suspended dust. STEL 15 minutes: 4 mg/m³. Form: suspended dust.
Ørganic dust	Occupational exposure limits, Regulation No. 293 (Estonia) TWA 8 hours: 5 mg/m ³ .
bisphenol A	Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) TWA 8 hours: 2 mg/m³. Form: Inhalable fraction.
písphenol A	EU OEL (Europe, 1/2022) TWA 8 hours: 2 mg/m³. Form: Inhalable fraction.
Ørganic dust	Institute of Occupational Health, Ministry of Social Affairs (Finland) TWA 8 hours: 5 mg/m³. STEL 15 minutes: 10 mg/m³.
bisphenol A	Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) TWA 8 hours: 2 mg/m³.
bisphenol A	Ministry of Labor (France, 6/2024) Repr 1B. TWA 8 hours: 2 mg/m³. Form: Dust. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)
Ørganic dust	DFG MAC-values list (Germany) TWA 8 hours: 5 mg/m³.
bisphenol A	TRGS 900 OEL (Germany, 6/2024) Skin sensitiser. TWA 8 hours: 2 mg/m³. Form: Inhalable fraction. PEAK 15 minutes: 5 mg/m³. Form: Inhalable fraction. DFG MAC-values list (Germany, 7/2024) Develop C. Phototoxic. TWA 8 hours: 5 mg/m³. Form: inhalable fraction. PEAK 15 minutes: 5 mg/m³ 4 times per shift [Interval: 1 hour]. Form: inhalable fraction.
b ísphenol A	Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) TWA 8 hours: 2 mg/m³. Form: Inhalable fraction.
prisphenol A	5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) Repr.(1B). TWA 8 hours: 2 mg/m³.
prsphenol A	Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) TWA 8 hours: 2 mg/m ³ .

 Date of issue/Date of revision
 : 26/09/2025
 Date of previous issue
 : 13/06/2023
 Version
 : 5
 6/22

 INFRALIT EP 8024-21 - All variants
 Label No : ₹29558

bisphenol A NAOSH (Ireland, 4/2024) Repr 1B. Sensitiser. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 2 mg/m³. Form: Inhalable fraction. bisphenol A Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024) Absorbed through skin. Limit value 8 hours: 2 mg/m³. Form: inhalable fraction. **b**ísphenol A **EU OEL (Europe, 1/2022)** TWA 8 hours: 2 mg/m³. Form: Inhalable fraction. bisphenol A Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) Repr. Sensitiser. TWA 8 hours: 2 mg/m³. Form: Inhalable fraction. bisphenol A Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) TWA 8 hours: 2 mg/m³. Form: inhalable fraction. bisphenol A EU OEL (Europe, 1/2022) TWA 8 hours: 2 mg/m³. Form: Inhalable fraction. bisphenol A Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) Repr B3. TWA 8 hours: 2 mg/m³. Form: inhalable dust. **Organic** dust FOR-2011-12-06-1358 (Norway) TWA 8 hours: 5 mg/m³. bisphenol A FOR-2011-12-06-1358 (Norway, 5/2024) Repr. Sensitiser. TWA 8 hours: 2 mg/m³. Form: inhalable. Ørganic dust Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland) TWA 8 hours: 10 mg/m³. bisphenol A Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) TWA 8 hours: 2 mg/m³. Form: Inhalable fraction. bisphenol A Decree-Law 301/2000 - Occupational exposure limits for carcinogenic and mutagenic agents (Portugal, 12/2024) TWA 8 hours: 2 mg/m³. Form: inhalable fration. Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) TWA 8 hours: 2 mg/m³. Form: inhalable fraction. bisphenol A HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) R1B. VLA 8 hours: 2 mg/m³. Form: Inhalable fraction. bisphenol A **EU OEL (Europe, 1/2022)** TWA 8 hours: 2 mg/m³. Form: Inhalable fraction. bisphenol A Regulation on the protection of workers from the risks related to exposure to carcinogens, mutagens or reprotoxic substances at work (Slovenia, 4/2024) Repr Fer 1B. Peak 15 minutes: 2 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. Form: Inhalable fraction. TWA 8 hours: 2 mg/m³. Form: Inhalable fraction. bisphenol A National institute of occupational safety and health (Spain, 1/2024) TR1B. Skin sensitiser. TWA 8 hours: 2 mg/m³.

 Date of issue/Date of revision
 : 26/09/2025
 Date of previous issue
 : 13/06/2023
 Version
 : 5
 7/22

 INFRALIT EP 8024-21 - All variants
 Label No : ₹29558

Work environment authority Regulation 2018:1 (Sweden) Ørganic dust TWA 8 hours: 5 mg/m³. bisphenol A Work environment authority Regulation 2018:1 (Sweden, 11/2022) Repr. TWA 8 hours: 2 mg/m³. Form: inhalable fraction. **b**isphenol A SUVA (Switzerland, 1/2025) Repr 1B. Sensitiser. TWA 8 hours: 3 mg/m³. Form: Inhalable fraction. **b**isphenol A EH40/2005 WELs (United Kingdom (UK), 1/2020) TWA 8 hours: 2 mg/m³.

Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	
sphenol A	DFG BEI-values list (Germany, 7/2024) BGV: 80 mg/l, bisphenol A (after hydrolysis) [in urine]. Sampling time: end of exposure or end of shift.
No exposure indices known.	

: 13/06/2023 Date of issue/Date of revision : 26/09/2025 Date of previous issue Version:5 8/22 Label No : 1/29558

procedures

Recommended monitoring: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

bisphenol A

Result

DNEL - General population - Short term - Dermal

24 µg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Dermal

24 µg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral

53 µg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Oral

53 ug/kg bw/dav Effects: Systemic

DNEL - Workers - Short term - Dermal

66 µg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Dermal

66 µg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Inhalation

1 mg/m³ Effects: Local

DNEL - General population - Long term - Inhalation

1 mg/m³ Effects: Local

DNEL - General population - Short term - Inhalation

1 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

1 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

2 ma/m³ Effects: Local

DNEL - Workers - Long term - Inhalation

2 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation

2 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

Date of issue/Date of revision : 26/09/2025 : 13/06/2023 Version :5 9/22 Date of previous issue Label No : 1/29558

2 mg/m³

Effects: Systemic

2-methylimidazole

DNEL - General population - Long term - Oral

0.02 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Dermal

0.04 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Inhalation

0.3 mg/m³ Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations: Wear gloves according to EN374 to protect against skin effects from powders.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Label No : 1/29558

Filter type: P 2

Date of issue/Date of revision: 26/09/2025Date of previous issue: 13/06/2023Version: 510/22

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Solid.
Colour : Various
Odour : Slight

Odour threshold : Not available.

Melting point/freezing point : Not available.

Initial boiling point and

Ingredient name

boiling range

bisphenol A

°C	°F	Method
360	680	

Flammability : Not available.

Lower and upper explosion

limit

Lower: Not applicable. Upper: Not applicable.

Flash point : Not applicable.

Auto-ignition temperature : Not applicable.

Decomposition temperature : Not available.

pH : Mot available.

Viscosity : Mot available.

Solubility(ies)

Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/ : Not applicable.

water

 Vapour pressure
 : Not available.

 Relative density
 : Not available.

 Density
 : ₹.6 g/cm³

 Vapour density
 : Not applicable.

Particle characteristics

Median particle size : 40 μm

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

Oxidising properties : Not available.

9.2.2 Other safety characteristics

Not applicable.

Date of issue/Date of revision: 26/09/2025Date of previous issue: 13/06/2023Version: 511/22

INFRALIT EP 8024-21 - All variants

Label No :1/29558

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name Result

1200 mg/kg

<u>Toxic effects</u>: Effects on Fertility - Female fertility index (e.g., number of females pregnant per number of sperm-positive females; number of females pregnant per number of females

mated)

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Z -methylimidazole	500	N/A	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name Result

> <u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 500 mg

Rabbit - Skin - Mild irritant

Amount/concentration applied: 250 mg

Conclusion/Summary [Product]: Not available.

Serious eye damage/eye irritation

Product/ingredient name Result

▶ Sphenol A Rabbit - Eyes - Severe irritant

<u>Duration of treatment/exposure</u>: 24 hours Amount/concentration applied: 250 ug

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Date of issue/Date of revision: 26/09/2025Date of previous issue: 13/06/2023Version: 512/22

INFRALIT EP 8024-21 - All variants

Label No : 1/29558

SECTION 11: Toxicological information

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product]: Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product]: Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product]: Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product]: Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name Result

bisphenol A STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure

Not available.

Ingestion

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact: May cause an allergic skin reaction.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

Date of issue/Date of revision : 26/09/2025 Date of previous issue : 13/06/2023 Version : 5 13/22

Label No : 1/29558

: No known significant effects or critical hazards.

SECTION 11: Toxicological information

Skin contact: Adverse symptoms may include the following:

pain or irritation redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product]: Not available.

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : May damage fertility. May damage the unborn child.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]: May cause endocrine disruption.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

sphenol A

Result

Acute - EC50 - Marine water

Algae - Diatom - Skeletonema costatum

1000 µg/l [96 hours] Effect: Growth

Chronic - NOEC - Fresh water

Fish - Goldfish - Carassius auratus - Adult

Age: 2 to 3 years 0.2 µg/l [90 days] Effect: Reproduction

Chronic - NOEC - Fresh water

Algae - Algae - Chlorolobion braunii - Exponential growth phase

Label No : 1/29558

2 mg/l [4 days] Effect: Population

Acute - LC50 - Marine water

Fish - Rivulus - Rivulus marmoratus - Embryo

Date of issue/Date of revision : 26/09/2025 Date of previous issue : 13/06/2023 Version : 5 14/22

SECTION 12: Ecological information

3.5 mg/l [96 hours] Effect: Mortality

Chronic - NOEC - Marine water

Crustaceans - Harpacticoid copepod - Tigriopus japonicus -

Nauplii

Age: <24 hours 10 µg/l [21 days] Effect: Reproduction

Acute - LC50 - Marine water

Crustaceans - Brine shrimp - Artemia sinica

Age: 15 days 50.4 µg/l [48 hours] Effect: Mortality

2-methylimidazole

Acute - LC50 - Fresh water

Fish - Fathead minnow - Pimephales promelas Age: 30 days; Size: 22.8 mm; Weight: 0.206 g

286000 µg/l [96 hours] Effect: Mortality

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
'	3.4 0.24	20 to 67	Low Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
isphenol A	3.2	1436.23
2-methylimidazole	1.2	14.3075

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
sphenol A	No	No	No	No	No	No	No
2-methylimidazole	No	No	No	No	No	No	No

: Not available. **Mobility**

: The product does not meet the criteria to be considered as a PMT or vPvM. **Conclusion/Summary**

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	В	T	vPvB	vP	vB
sphenol A	No	N/A	No	Yes	No	N/A	No
2-methylimidazole	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
pisphenol A	No	No	No	No	No	No	No
2-methylimidazole	No	No	No	No	No	No	No

Version :5 Date of issue/Date of revision : 26/09/2025 : 13/06/2023 15/22 Date of previous issue INFRALIT EP 8024-21 - All variants Label No : 1/29558

SECTION 12: Ecological information

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]: May cause endocrine disruption.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: Noid release to the environment. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous waste

: The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

: 080111*, 200127*

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3077	UN3077	UN3077	UN3077
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (PAINT)
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

Additional information

ADR/RID

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Tunnel code (-)

 Date of issue/Date of revision
 : 26/09/2025
 Date of previous issue
 : 13/06/2023
 Version
 : 5
 16/22

 INFRALIT EP 8024-21 - All variants
 Label No : ₹29558

SECTION 14: Transport information

ADN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG

This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA

This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
Poxic to reproduction	4,4'-isopropylidenediphenol	Recommended	9th recommendation	10/1/2019
	2-methylimidazole	Candidate	D(2020) 4578-DC	6/25/2020
Endocrine disrupting properties for human health	4,4'-isopropylidenediphenol	Recommended	9th recommendation	10/1/2019
Endocrine disrupting properties for environment	4,4'-isopropylidenediphenol	Recommended	9th recommendation	10/1/2019

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
FRALIT EP 8024-21	≥90	30
bisphenol A	≤10	30
		66
2-methylimidazole	<1	30

Labelling : Restricted to professional users.

Synthetic polymer microparticles - Designation 78

Generic identity of polymer(s)

: 3907 - Polyacetals, other polyethers and epoxide resins; polycarbonates, alkyd resins, polyallyl esters and other polyesters.

Total percentage of synthetic polymer microparticles

54.7%

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

Other EU regulations

Date of issue/Date of revision : 13/06/2023 Version :5 17/22 : 26/09/2025 Date of previous issue INFRALIT EP 8024-21 - All variants Label No : 1/29558

SECTION 15: Regulatory information

: Not listed **Industrial emissions** (integrated pollution

prevention and control) -

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

: Not applicable. **Explosive precursors** Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

E1

National regulations

Austria

Limitation of the use of

: Permitted.

organic solvents

Belgium

Book VI carcinogenic agents annex VI.2-1 - VI.2-3

Ingredient name	Status
M oirs de charbon	Listed

Czech Republic

Denmark

Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
Manium dioxide	Listed	-
carbon black respirable	Listed	-

MAL-code : 00-6

Protection based on MAL

According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

Date of issue/Date of revision : 26/09/2025 : 13/06/2023 Version:5 18/22 Date of previous issue Label No : 1/29558

SECTION 15: Regulatory information

MAL-code: 00-6

Application: When using scraper or knife, brush, roller etc. for pre- and post-treatments in a spray booth where the operator is outside the spray zone and when working in similar new* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in new* booths and cabins with non-atomizing guns. During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents. During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Protective clothing must be worn.

When spraying in existing* spray booths, if the operator is outside the spray zone.

- Air-supplied full mask and protective clothing must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, protective clothing and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

Restrictions on use

: Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

List of undesirable substances

Listed

Carcinogenic waste

: Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

Finland

France

Reinforced medical surveillance

: Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

Germany

Storage class (TRGS 510) : 6.1D Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

Danger criteria

Category	Reference number
₹ 1	1.3.1

Hazard class for water : 3

Technical instruction on air quality control (TA Luft)

 Date of issue/Date of revision
 : 26/09/2025
 Date of previous issue
 : 13/06/2023
 Version
 : 5
 19/22

 INFRALIT EP 8024-21 - All variants
 Label No : ₹29558

SECTION 15: Regulatory information

Number [Class]	Description	%
5 .2.1 5.2.2 [III] 5.2.7.1.3	Total dust Dusty inorganic substances Reproductive toxic substances	92.5 1.5 6

AOX

: The product contains organically bound halogens and can contribute to the AOX

value in waste water.

<u>Italy</u>

D.Lgs. 152/06 : Not determined.

Netherlands

Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development	Harmful via breastfeeding
sfenol A	-	-	Fertility 1B	-	-
2-methylimidazool	-	-	Fertility 2	Development 1B	-

Water Discharge Policy

(ABM)

: Z(1) Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioacumulative potential/

toxicity or persistence). Decontamination effort: Z

Norway

<u>Sweden</u>

Switzerland

VOC content : Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Date of issue/Date of revision: 26/09/2025Date of previous issue: 13/06/2023Version: 520/22INFRALIT EP 8024-21 - All variantsLabel No : 1/29558

SECTION 16: Other information

Classification	Justification
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 1B, H360FD	Calculation method
Aquatic Chronic 1, H410	Calculation method

Full text of abbreviated H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H360Df	May damage the unborn child. Suspected of damaging fertility.
H360F	May damage fertility.
H360FD	May damage fertility. May damage the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
	5 ,

Date of issue/ Date of

revision

Date of previous issue : 13/06/2023

: 26/09/2025

Version : 5

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 26/09/2025 Date of previous issue : 13/06/2023 Version :5 21/22 Label No : 1/29558

Version :5 Date of issue/Date of revision : 26/09/2025 Date of previous issue : 13/06/2023 22/22 **Label No** : 1/29558