

3895110

Reviewed on: 18/12/2019

Printing date: 18/12/2019

01 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- *Trade name:*
ISO FILL 1070-00
- Article number / Safety Data Sheet:
107000
- **Details of the supplier of the safety data sheet**
- *Manufacturer/Supplier:*
Teknos Feyco AG
Industriestrasse 3
LI-9487 Gamprin-Bendern
T +423 375 94 00
F +423 375 94 99
- *Further information obtainable from:*
Product safety department. e-mail address: li-sdb@teknos.com
- *Emergency telephone number:*
Swiss Toxicological Information Centre Emergency telephone: +41 (0)44 251 51 51

02 Hazards identification

- *Classification of the substance or mixture*



GHS02

Flam. Liq. 3 - H226 Flammable liquid and vapour.



GHS07

STOT SE 3 - H336 May cause drowsiness or dizziness.

Acute Tox. 5 - H333 May be harmful if inhaled.
H316 Causes mild skin irritation.

- *Label elements*
- GHS label elements
- Hazard pictograms



GHS02 GHS07

- Signal word
Warning

- * Hazard-determining components of labelling:
titanium dioxide / xylene / ethylbenzene
- * Hazard statements
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H333 May be harmful if inhaled.
H316 Causes mild skin irritation.
- * Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
- * P240 Ground and bond container and receiving equipment.
- * P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

RUS

(continued on page 2)

3895110

Reviewed on: 18/12/2019

Printing date: 18/12/2019

PRODUCT : ISOFILL 1070-00

(continued of page 1)

03 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:**

Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

* CAS Number		%
80-62-6	methyl methacrylate EC number: 201-297-1 Record number 01-2119452498-28 ⚠ Flam. Liq. 2 - H225; ⚠ Skin Irrit. 2 - H315, Skin Sens. 1 - H317, STOT SE 3 - H335	0,00- 0,50
123-86-4	n-butyl acetate EC number: 204-658-1 Record number 01-2119485493-29 ⚠ Flam. Liq. 3 - H226; ⚠ STOT SE 3 - H336	15,00- 25,00
108-65-6	2-methoxy-1-methylethyl acetate EC number: 203-603-9 Record number 01-2119475791-29 ⚠ Flam. Liq. 3 - H226	1,00- 5,00
* 64742-95-6	Solvent naphtha (petroleum), light arom. EC number: 265-199-0 Record number 01-2119455851-35 ⚠ Asp. Tox. 1 - H304; ⚠ Acute Tox. 4 - H332, STOT SE 3 - H335; H227, Acute Tox. 5 - H313; ⚠ Aquatic Chronic 2 - H411; H401	0,00- 0,50
* 9004-34-6	Cellulose EC number: 232-674-9	1,00- 5,00
* 13463-67-7	titanium dioxide EC number: 236-675-5 Record number 01-2119489379-17 Acute Tox. 5 - H333	5,00- 10,00
* 1330-20-7	xylene EC number: 215-535-7 Record number 01-2119488216-32 ⚠ Flam. Liq. 3 - H226; ⚠ Acute Tox. 4 - H312, Acute Tox. 4 - H332, Skin Irrit. 2 - H315	5,00- 10,00
* 100-41-4	ethylbenzene EC number: 202-849-4 Record number 01-2119489370-35 ⚠ Flam. Liq. 2 - H225; ⚠ STOT RE 2 - H373, Asp. Tox. 1 - H304; ⚠ Acute Tox. 4 - H332	1,00- 5,00
* 141-78-6	ethyl acetate EC number: 205-500-4 Record number 01-2119475103-46 ⚠ Flam. Liq. 2 - H225; ⚠ Eye Irrit.	1,00- 5,00

(continued on page 3)

3895110

Reviewed on: 18/12/2019

Printing date: 18/12/2019

PRODUCT : ISOFILL 1070-00

(continued of page 2)

*	2A - H319, STOT SE 3 - H336	
*	BENZOTRIAZOL DERIVATIVES Index no. 607-176-	0,00- 0,50
*	00-3	
*	EC number: 400-830-7	
*	Record number 01-0000015075-76	
*	⚠ Skin Sens. 1 - H317; ⚠ Aquatic	
*	Chronic 2 - H411	

04 First aid measures

- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water.
- **After swallowing:**
Do not induce vomiting; call for medical help immediately.

05 Firefighting measures

- **Suitable extinguishing agents:**
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:**
Water with full jet
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Protective equipment:**
Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

06 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

07 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Take note of emission threshold.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- **Information about fire - and explosion protection:**

(continued on page 4)

3895110

Reviewed on: 18/12/2019

Printing date: 18/12/2019

PRODUCT : ISOFILL 1070-00

(continued of page 3)

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

- **Storage:**
- *Requirements to be met by storerooms and receptacles:*
Store only in the original receptacle.
- *Information about storage in one common storage facility:*
Not required.
- *Further information about storage conditions:*
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Specific end use(s)**
No further relevant information available.

08 Exposure controls/personal protection

- * **Ingredients with limit values that require monitoring at the workplace:**
- 80-62-6 methyl methacrylate
PDK

Short-term value	20	mg/m3
Long-term value	10	mg/m3
a _i # ±/± ^o ± ýa¥#		
- 123-86-4 n-butyl acetate
PDK

Short-term value	200	mg/m3
Long-term value	50	mg/m3
a _i # ±/± ^o ± ýa¥#		
- 108-65-6 2-methoxy-1-methylethyl acetate
PDK

Short-term value	10	mg/m3
a _i # ±/± ^o ± ýa¥#		
- * 9004-34-6 Cellulose
PDK

Short-term value	10	mg/m3
a© _i ÆÝÆ ^o ¢		
- * 1330-20-7 xylene
PDK

Short-term value	150	mg/m3
Long-term value	50	mg/m3
a _i # ±/± ^o ± ýa¥#		
- * 100-41-4 ethylbenzene
PDK

Short-term value	150	mg/m3
Long-term value	50	mg/m3
a _i # ±/± ^o ± ýa¥#		
- * 141-78-6 ethyl acetate
PDK

Short-term value	200	mg/m3
Long-term value	50	mg/m3
a _i # ±/± ^o ± ýa¥#		
- *Additional information:*
The lists valid during the making were used as basis.
- **Personal protective equipment:**
- *General protective and hygienic measures:*

(continued on page 5)

according to 2001/58 EC

3895110

Reviewed on: 18/12/2019

Printing date: 18/12/2019

PRODUCT : ISOFILL 1070-00

(continued of page 4)

- The usual precautionary measures are to be adhered to when handling chemicals.
Do not eat or drink while working.
Be sure to clean skin thoroughly after work and before breaks.
- *Respiratory protection: Suitable respiratory protective device recommended.*
 - *Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Impervious gloves*
 - *Material of gloves*
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
 - *Penetration time of glove material*
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.
 - *Eye protection: Safety glasses Tightly sealed goggles*
 - *Body protection: Protective work clothing*

09 Physical and chemical properties**Appearance****Appearance:**

Form:	Liquid
Colour:	According to product specifica
Odour:	Characteristic Characteristic
Odour threshold:	Not determined.

Change in condition

Initial boiling point and boiling range:	124 °C
---	--------

Flash point:	27 °C
---------------------	-------

Flammability (solid, gas):	Not applicable.
-----------------------------------	-----------------

Ignition temperature:	425 °C
------------------------------	--------

Decomposition temperature:	Not determined.
-----------------------------------	-----------------

Auto-ignition temperature:	Not determined.
-----------------------------------	-----------------

Explosive properties:	Not determined.
------------------------------	-----------------

Explosion limits:

Lower:	1 Vol %
---------------	---------

Upper:	7 Vol %
---------------	---------

Vapour pressure:	at 20 °C	10,7000 mbar at 50 °C	55,0000 mbar
-------------------------	----------	-----------------------	--------------

Density:	1,3200 g/cm3
-----------------	--------------

Solubility in / Miscibility with

water:	Not determined.
---------------	-----------------

Viscosity:

•	Not determined.
---	-----------------

•	at 23 °C	110 - 120 s DIN 4 mm
---	----------	----------------------

Other information

	No further relevant information available.
--	--

RUS

(continued on page 6)

3895110

Reviewed on: 18/12/2019

Printing date: 18/12/2019

PRODUCT : ISOFILL 1070-00

(continued of page 5)

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Incompatible materials:**
No further relevant information available.
- **Hazardous decomposition products:**
No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity**
- **LD/LC50 values relevant for classification:**

80-62-6 methyl methacrylate

Oral, LD50: 7872 mg/kg (rat) Oral, LD50: 13100 mg/kg (rat) Dermal, LD50: >5000 mg/kg (Rabbit) Inhalative, LC50/4h: >21 mg/l (rat) Oral, LD50: 5050 mg/kg (rat) Oral, LD50: 8532 mg/kg (rat) Inhalative, LC50/4h: 35,7 mg/l (rat) Oral, LD50: 5750 mg/kg (rat) Dermal, LD50: 16000 mg/kg (Rabbit) Oral, LD50: >6800 mg/kg (rat) Dermal, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: 10000 mg/kg (rat) Oral, LD50: >20000 mg/kg (rat) Dermal, LD50: >10000 mg/kg (Rabbit) Inhalative, LC50/4h: >6,82 mg/l (rat) Oral, LD50: 4300 mg/kg (rat) Dermal, LD50: 2000 mg/kg (Rabbit) Oral, LD50: 3500 mg/kg (rat) Dermal, LD50: 17800 mg/kg (Rabbit) Oral, LD50: 2460 mg/kg (rat) Dermal, LD50: 3400 mg/kg (Rabbit) Oral, LD50: 5620 mg/kg (Rabbit) Inhalative, LC50/4h: 1600 mg/l (rat) Dermal, LD50: 20000 mg/kg (Rabbit) Oral, LD50: 175 mg/kg (rat)

123-86-4 n-butyl acetate**868-77-9 2-hydroxyethyl methacrylate****108-65-6 2-methoxy-1-methylethyl acetate*** **108-83-8 2,6-dimethylheptan-4-one*** **64742-95-6 Solvent naphtha (petroleum), light arom.*** **7631-86-9 silicon dioxide, chemically prepared*** **13463-67-7 titanium dioxide*** **1330-20-7 xylene*** **100-41-4 ethylbenzene****78-83-1 butanol****141-78-6 ethyl acetate****122-51-0 triethyl orthoformate****77-58-7 dibutyltin dilaurate**

- **Primary irritant effect:**
- Skin corrosion/irritation
No irritant effect.
- Serious eye damage/irritation
No irritating effect.
- **Respiratory or skin sensitisation**
No sensitising effects known.

12 Ecological information

- **Aquatic toxicity:**
No further relevant information available.
- **Persistence and degradability**
No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential**
No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

RUS

(continued on page 7)

3895110

Reviewed on: 18/12/2019

Printing date: 18/12/2019

PRODUCT : ISOFILL 1070-00

(continued of page 6)

13 Disposal considerations• **Waste treatment methods**• **European and swiss waste code**

08

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01

wastes from MFSU and removal of paint and varnish

08 01 11

waste paint and varnish containing organic solvents or other hazardous substances

• **Uncleaned packaging:**• **Recommendation:**

Disposal must be made according to official regulations.

14 Transport information• **UN-Number**

ADR UN1263

IMDG UN1263

IATA UN1263

• **UN proper shipping name**

ADR 1263 PAINT

IMDG PAINT

IATA PAINT

• **Transport hazard class(es)**

ADR

Class 3 Flammable liquids.

Label

3



IMDG

Class 3 Flammable liquids.

Label

3



IATA

Class 3 Flammable liquids.

Label

3

• **Packing group**

ADR III

(continued on page 8)

3895110

Reviewed on: 18/12/2019

Printing date: 18/12/2019

PRODUCT : ISOFILL 1070-00

(continued of page 7)

IMDG III
IATA III
 • **Environmental hazards:**
 Not applicable.
 • **Special precautions for user**
 Warning: Flammable liquids.
Danger code (Kemler): 30
EMS Number: F-E,S-E
 • **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**
 Not applicable.
 • **Transport/Additional information:**
 Not applicable.
Excepted quantities (EQ): E1
Limited quantities (LQ) 5L
Transport category 3
Tunnel restriction code D/E
Remarks: ADR/RID 2.2.3.1.5 (<= 450 l)
IMDG
Limited quantities (LQ) 5L
Excepted quantities (EQ) E1
Remarks: IMDG 2.3.2.5 (<= 30 l)
 • **UN "Model Regulation":**
 UN 1263 PAINT, 3, III

15 Regulatory information

- **National regulations:**
- **Classification according to VbF:**
—
- **Technical instructions (air):**
- **Class Share in %**

III	23, 55
II	9, 99
I	
- **Waterhazard class:**
 Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H333	May be harmful if inhaled.
H335	May cause respiratory irritation.

(continued on page 9)

3895110

Reviewed on: 18/12/2019

Printing date: 18/12/2019

PRODUCT : ISOFILL 1070-00*(continued of page 8)*

H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

- **Department issuing MSDS:**

Environment protection department.

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids, Austria)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

- * Data compared to the previous version altered.