# **TEKNOS**

#### according to 1907/2006/EC, Article 31

4050613

Reviewed on: 31/05/2022 Printing date: 31/05/2022

# SECTION 01: Identification of the substance/mixture and of the company undertaking

- 1.1 Product identifier
- · Trade name:

**MOTIVO COLORATO 2070** 

- Article number / Safety Data Sheet:
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the preparation

Coating material

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Teknos AG

Industriestrasse 7

LI-9487 Gamprin-Bendern

T +423 375 94 00

F +423 375 94 99

- · Further information obtainable from:
  - Product safety department. e-mail address: li-sdb@teknos.com
- 1.4 Emergency telephone number:

Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

## SECTION 02: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008 Void
- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms
- Void
- Signal word

Void

- Hazard statements
  - EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol- 3-one, reaction mass of: 5-chloro-2-methyl -4- isothiazolin-3-one [EC no. 247-500-7] and 2- methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1). May produce an allergic reaction.
- EUH210 Safety data sheet available on request.
- EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 2.3 Other hazards
- - Results of PBT and vPvB assessment
- PBT:

Not applicable.

vPvB:

Not applicable.

# SECTION 03: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- Description:

**CAS Number** 

Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

108-01-0 2-dimethylaminoethanol

0.0015- 0.50

EC number: 203-542-8

01-2119492298-24 Record number Skin Corr. 1B - H314; 🚸 Flam. Lig.

(continued on page 2)

# Page: 2/9 MATERIAL SAFETY DATA SHEET



# according to 1907/2006/EC, Article 31

4050613

Reviewed on: 31/05/2022 Printing date: 31/05/2022

		(continued of page 1)
	Tox. 4 - H312, Acute Tox. 4 - H332;	(commune or page 1)
	STOT SE 3; H335: C >= 5 %	
2634-33-5	1,2-benzisothiazol-3(2H)-one	0,0015- 0,50
	EC number: 220-120-9	
	🥎 Eye Dam. 1 - H318; 💠 Acute Tox. 4	
	- H302, Skin Irrit. 2 - H315, Skin Sens. 1 -	
	H317; 🥸 Aquatic Acute 1 - H400;	
	Skin Sens. 1; H317: C >= 0,05 %	
55965-84-9	reaction mass of: 5-chloro-2-methyl-4-	0,00-0,0015
	isothiazolin-3-one [EC no. 247-500-7] and 2-	
	methyl-2H-isothiazol-3-one [EC no. 220-239-	
	6] (3: 1)	
	Skin Corr. 1C - H314, Eye Dam. 1 -	
	H318; 🧇 Acute Tox. 3 - H301, Acute Tox.	
	2 - H310, Acute Tox. 2 - H330; 💠 Skin	
	Sens. 1A - H317; 🕸 Aquatic Acute 1 -	
	H400 (M=100), Aquatic Chronic 1 - H410	
	(M=100);	
	Skin Corr. 1C; H314: C >= 0,6 %, Skin Irrit.	
	2; H315: 0,06 <= C < 0,6 %, Eye Dam. 1;	
	H318: C >= 0,6 %, Eye Irrit. 2; H319: 0,06	
	<= C < 0,6 %, Skin Sens. 1A; H317: C >= 0,	
444.70.0	0015 %	100 500
111-76-2	<b>2-butoxyethanol</b> EC number: 203-905-0	1,00- 5,00
	Record number 01-2119475108-36	
	Acute Tox. 3 - H311; Acute Tox.	
	4 - H302, Acute Tox. 4 - H332, Skin Irrit. 2	
	- H315, Eye Irrit. 2 - H319	
112-34-5	2-(2-butoxyethoxy)ethanol	1,00- 5,00
	EC number: 203-961-6	,,
	Record number 01-2119475104-44	
	Eye Irrit. 2 - H319	
34590-94-8	Dipropylene glycol monomethyl ether	0,0015- 0,50
	EC number: 252-104-2	
	Record number 01-2119450011-60	
	substance with a Community workplace	
0000 00 4	exposure limit.	0.00.0.0045
2682-20-4	<b>2-methyl-2H-isothiazol-3-one</b> EC number: 220-239-6	0,00-0,0015
	Skin Corr. 1B - H314, Eye Dam. 1 -	
	H318; Acute Tox. 3 - H301, Acute Tox.	
	•	
	3 - H311, Acute Tox. 2 - H330; 🚯 Skin	
	Sens. 1A - H317; 🔖 Aquatic Acute 1 -	
	H400 (M=10), Aquatic Chronic 1 - H410;	
40.00 5= =	Skin Sens. 1A; H317: C >= 0,0015 %	
13463-67-7	titanium dioxide	10,00- 25,00
	EC number: 236-675-5	
	Record number 01-2119489379-17	(continued on page 3)



#### according to 1907/2006/EC, Article 31

4050613

Reviewed on: 31/05/2022 Printing date: 31/05/2022

> PRODUCT: **MOTIVO COLORATO 2070**

> > (continued of page 2)

Carc. 2 - H351

Additional information:

For the wording of the listed risk phrases refer to section 16.

# SECTION 04: First aid measures

- · 4.1 Description of first aid measures
- After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water.

After swallowing:

Do not induce vomiting; call for medical help immediately.

- Information for doctor:
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

# **SECTION 05:** Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

## SECTION 06: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

In case of seepage into the ground inform responsible authorities.

Dilute with plenty of water.

In case of gas release or seepage into the ground inform responsible authorities.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB



# according to 1907/2006/EC, Article 31

4050613

Reviewed on: 31/05/2022 Printing date: 31/05/2022

> PRODUCT: **MOTIVO COLORATO 2070**

> > (continued of page 3)

#### SECTION 07: Handling and storage

- · Handling:
- 7.1 Precautions for safe handling Open and handle receptacle with care.
- Information about fire and explosion protection: Prevent impact and friction.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:
- Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Protect from frost.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s)

No further relevant information available.

# SECTION 08: Exposure controls/personal protection

· 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace:

108-01-0 2-dimethylaminoethanol

WEL

Short-term value	22	mg/m3
	6	ppm
Long-term value	7.4	mg/m3
	2	maa

111-76-2 2-butoxyethanol

WEL

Short-term value 246 mg/m3 50 ppm Long-term value 123 mg/m3 25 ppm

Sk, BMGV

112-34-5 2-(2-butoxyethoxy)ethanol

WEL

101.2 Short-term value mg/m3 15 ppm Long-term value 67.5 mg/m3 10 ppm

34590-94-8 Dipropylene glycol monomethyl ether

WEL

308 Long-term value mg/m3 50 ppm

Sk

· Ingredients with biological limit values: 111-76-2 2-butoxyethanol

**BMGV** 

240 mmol/mol creatinine

Medium: urine

(continued on page 5)



# according to 1907/2006/EC, Article 31

4050613

Reviewed on: 31/05/2022 Printing date: 31/05/2022

PRODUCT: MOTIVO COLORATO 2070

(continued of page 4)

Sampling time: post shift Parameter: butoxyacetic acid

· Additional information:

The lists valid during the making were used as basis.

- 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

- · Respiratory protection: Suitable respiratory protective device recommended.
- Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the
  preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the
  preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates
  of diffusion and the degradation Impervious gloves
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- · Eye protection: Safety glasses
- · Body protection: Protective work clothing

# SECTION 09: Physical and chemical properties

9.1 Information on basic physical and che	emical properties
Appearance	
Appearance:	
Form:	Liquid
Colour:	According to product specifica
Odour:	Characteristic Characteristic
Odour threshold:	Not determined.
pH-value:	at 20 °C 8,0 - 9,0
Change in condition	
Melting point/freezing point:	0 °C
Initial boiling point and boiling range:	100 °C
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	Undetermined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	at 20 °C 23,0000 mbar
Density:	1,1900 g/cm3
Solubility in / Miscibility with	
water:	Not determined.
Viscosity:	



#### according to 1907/2006/EC, Article 31

4050613

Reviewed on: 31/05/2022 Printing date: 31/05/2022

PRODUCT: MOTIVO COLORATO 2070

	(continued of page 5)	
	Not determined.	
	20 - 30 s DIN 6 mm	
9.2 Other information	No further relevant information available.	

# SECTION 10: Stability and reactivity

• 10.1 Reactivity

No further relevant information available.

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions
- No dangerous reactions known.
- 10.4 Conditions to avoid
- No further relevant information available.
- 10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:

No dangerous decomposition products known.

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity
- LD/LC50 values relevant for classification:

#### 108-01-0 2-dimethylaminoethanol

Oral, LD50: 2000 mg/kg (rat)
Dermal, LD50: 1370 mg/kg (Rabbit)
Inhalative, LC50/4h: 3,25 mg/l (mouse)

111-76-2 2-butoxyethanol

Oral, LD50: 1746 mg/kg (rat) Oral, LD50: 1414 mg/kg (guinea Pig) Dermal, LD50: 2000 mg/kg (rat) Dermal, LD50: 1000 mg/kg (Rabbit) Dermal, LD50: 2000 mg/kg (guinea Pig)

112-34-5 2-(2-butoxyethoxy)ethanol

Oral, LD50: 5660 mg/kg (rat) Dermal, LD50: 4000 mg/kg (Rabbit) **50-00-0 formaldehyde** 

Oral, LD50: >200 mg/kg (rat)

34590-94-8 Dipropylene glycol monomethyl ether

Oral, LD50: 5135 mg/kg (rat)

Dermal, LD50: >19000 mg/kg (Rabbit)

13463-67-7 titanium dioxide

Oral, LD50: >20000 mg/kg (rat) Dermal, LD50: >10000 mg/kg (Rabbit)

- Inhalative, LC50/4h: >6,82 mg/l (rat)
   Primary irritant effect:
- Skin corrosion/irritation
- No irritant effect.
- Serious eye damage/irritation
- No irritating effect.
- Respiratory or skin sensitisation
  - No sensitising effects known.
- Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

- 11.2 Information on other hazards
- Endocrine disrupting properties
- None of the ingredients is listed.

GB

# according to 1907/2006/EC, Article 31



4050613

Reviewed on: 31/05/2022 Printing date: 31/05/2022

PRODUCT: MOTIVO COLORATO 2070

(continued of page 6)

# SECTION 12: Ecological information

- 12.1 Toxicity
- · Aquatic toxicity:

No further relevant information available.

· 12.2 Persistence and degradability

No further relevant information available.

- · Behaviour in environmental systems:
- 12.3 Bioaccumulative potential
- No further relevant information available.
- 12.4 Mobility in soil

No further relevant information available.

- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- PRT

Not applicable.

- vPvB:
- Not applicable.
- · 12.6 Other adverse effects

No further relevant information available.

# SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- European and swiss waste code

08

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01

wastes from MFSU and removal of paint and varnish

Void

08 01 19

aqueous suspensions containing paint or varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

• Recommended cleansing agents:

Water, if necessary together with cleansing agents.

# **SECTION 14: Transport information**

• 14.1 UN-Number ADR

IMDG Void
IATA Void

• 14.2 UN proper shipping name
ADR Void
IMDG Void
IATA Void

• 14.3 Transport hazard class(es)

ADR

**Class** Void

IMDG

**Class** Void

IATA

(continued on page 8)



#### according to 1907/2006/EC, Article 31

4050613

Reviewed on: 31/05/2022 Printing date: 31/05/2022

PRODUCT: MOTIVO COLORATO 2070

(continued of page 7)

Class

14.4 Packing group

ADR Void IMDG Void IATA Void

- 14.5 Environmental hazards:
- Not applicable.
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
  Not applicable.

Void

· Transport/Additional information:

Not applicable.

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II
- None of the ingredients is listed.
- REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
- None of the ingredients is listed.
- Annex II REPORTABLE EXPLOSIVES PRECURSORS
- None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 55
- National regulations:
- Technical instructions (air):
- Class Share in %
- I 2,98
- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H310 Fatal in contact with skin.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.

H332 Harmful if inhaled.

\* H351 Suspected of causing cancer.
 \* H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### Department issuing MSDS:

(continued on page 9)

Page: 9/9

# MATERIAL SAFETY DATA SHEET



# according to 1907/2006/EC, Article 31

4050613

Reviewed on: 31/05/2022 Printing date: 31/05/2022

#### PRODUCT: MOTIVO COLORATO 2070

(continued of page 8)

Environment protection department.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative \* Data compared to the previous version altered.