

SAFETY DATA SHEET



MOTIVO COLORATO 2070-15 - All variants

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : MOTIVO COLORATO 2070-15 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P273 - Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles :

2.3 Other hazards

SECTION 2: Hazards identification

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤5	Eye Irrit. 2, H319	-	[1] [2]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤3	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
2-Propenoic acid, 2-methyl-, polymer with ethyl 2-propenoate	CAS: 1431957-88-8	≤1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
2-Dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	≤0.3	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	ATE [Oral] = 2000 mg/kg ATE [Dermal] = 1100 mg/kg ATE [Inhalation (gases)] = 1641 ppm STOT SE 3, H335: C ≥ 5%	[1]
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C ≥ 0.036% M [Acute] = 1 M [Chronic] = 1	[1]
pyrithione zinc	REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7 Index: 613-333-00-7	<0.01	Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 221 mg/kg ATE [Inhalation (dusts and mists)] = 0.14 mg/l M [Acute] = 1000 M [Chronic] = 10	[1]
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400	ATE [Oral] = 53 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l	[1]

Date of issue/Date of revision : 05/12/2025 **Date of previous issue** : 06/05/2025 **Version** : 1.02 2/29

MOTIVO COLORATO 2070-15 - All variants

Label No :38826

SECTION 3: Composition/information on ingredients

			Aquatic Chronic 1, H410 EUH071 See Section 16 for the full text of the H statements declared above.	Skin Corr. 1C, H314: C ≥ 0.6% Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: 0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	
--	--	--	--	--	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

☒ Substance classified with a health or environmental hazard

☐ Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

SECTION 5: Firefighting measures

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations

: Not available.
- Industrial sector specific solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-(2-butoxyethoxy)ethanol	Regulation on Limit Values - MAC (Austria, 12/2024) TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m³. PEAK 15 minutes: 15 ppm 4 times per shift. PEAK 15 minutes: 101.2 mg/m³ 4 times per shift.
2-Butoxyethanol	Regulation on Limit Values - MAC (Austria, 12/2024) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m³. PEAK 30 minutes: 40 ppm 4 times per shift. PEAK 30 minutes: 200 mg/m³ 4 times per shift.
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Regulation on Limit Values - MAC (Austria, 12/2024) [5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on (Gemisch im Verhältnis 3:1)] Skin sensitiser. TWA 8 hours: 0.05 mg/m³.
2-(2-butoxyethoxy)ethanol	Limit values (Belgium, 12/2023) STEL 15 minutes: 15 ppm. TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m³. STEL 15 minutes: 101.2 mg/m³.
2-Butoxyethanol	Limit values (Belgium, 12/2023) Absorbed through skin. TWA 8 hours: 20 ppm.

SECTION 8: Exposure controls/personal protection

2-(2-butoxyethoxy)ethanol	TWA 8 hours: 98 mg/m³. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m³. Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Limit value 8 hours: 67.5 mg/m³. Limit value 15 minutes: 101.2 mg/m³. Limit value 15 minutes: 15 ppm. Limit value 8 hours: 10 ppm.
2-Butoxyethanol	Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Absorbed through skin. Limit value 8 hours: 98 mg/m³. Limit value 15 minutes: 246 mg/m³. Limit value 15 minutes: 50 ppm. Limit value 8 hours: 20 ppm.
2-(2-butoxyethoxy)ethanol	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) STELV 15 minutes: 101.2 mg/m³. STELV 15 minutes: 15 ppm. ELV 8 hours: 67.5 mg/m³. ELV 8 hours: 10 ppm.
2-Butoxyethanol	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) Absorbed through skin. STELV 15 minutes: 246 mg/m³. STELV 15 minutes: 50 ppm. ELV 8 hours: 98 mg/m³. ELV 8 hours: 20 ppm.
2-Dimethylaminoethanol	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) STELV 15 minutes: 22 mg/m³. STELV 15 minutes: 6 ppm. ELV 8 hours: 7.4 mg/m³. ELV 8 hours: 2 ppm.
2-(2-butoxyethoxy)ethanol	Department of labour inspection (Cyprus, 7/2021) STEL 15 minutes: 15 ppm. STEL 15 minutes: 101.2 mg/m³. TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m³.
2-Butoxyethanol	Department of labour inspection (Cyprus, 7/2021) Absorbed through skin. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m³. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m³.
2-(2-butoxyethoxy)ethanol	Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) TWA 8 hours: 67.5 mg/m³. TWA 8 hours: 10 ppm. STEL 15 minutes: 101.2 mg/m³. STEL 15 minutes: 15 ppm.
2-Butoxyethanol	Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) Absorbed through skin. TWA 8 hours: 98 mg/m³. TWA 8 hours: 20 ppm. STEL 15 minutes: 200 mg/m³. STEL 15 minutes: 40.7 ppm.

SECTION 8: Exposure controls/personal protection

2-(2-butoxyethoxy)ethanol	Working Environment Authority (Denmark, 12/2024) TWA 8 hours: 68 mg/m ³ . TWA 8 hours: 10 ppm. STEL 15 minutes: 15 ppm. STEL 15 minutes: 101 mg/m ³ .
2-Butoxyethanol	Working Environment Authority (Denmark, 12/2024) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m ³ . STEL 15 minutes: 246 mg/m ³ . STEL 15 minutes: 50 ppm.
2-(2-butoxyethoxy)ethanol	Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m ³ .
2-Butoxyethanol	Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) Absorbed through skin , Sensitiser. TWA 8 hours: 98 mg/m ³ . TWA 8 hours: 20 ppm. STEL 15 minutes: 246 mg/m ³ . STEL 15 minutes: 50 ppm.
2-(2-butoxyethoxy)ethanol	EU OEL (Europe, 1/2022) TWA 8 hours: 67.5 mg/m ³ . TWA 8 hours: 10 ppm. STEL 15 minutes: 101.2 mg/m ³ . STEL 15 minutes: 15 ppm.
2-Butoxyethanol	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m ³ .
2-(2-butoxyethoxy)ethanol	Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) TWA 8 hours: 10 ppm. TWA 8 hours: 68 mg/m ³ .
2-Butoxyethanol	Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 250 mg/m ³ .
2-(2-butoxyethoxy)ethanol	Ministry of Labor (France, 6/2024) STEL 15 minutes: 101.2 mg/m ³ . Notes: Indicative regulatory limit values (decree of 30-06-2004 modified) STEL 15 minutes: 15 ppm. Notes: Indicative regulatory limit values (decree of 30-06-2004 modified) TWA 8 hours: 67.5 mg/m ³ . Notes: Indicative regulatory limit values (decree of 30-06-2004 modified) TWA 8 hours: 10 ppm. Notes: Indicative regulatory limit values (decree of 30-06-2004 modified)
2-Butoxyethanol	Ministry of Labor (France, 6/2024) Absorbed through skin. TWA 8 hours: 10 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 49 mg/m ³ . Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 246 mg/m ³ . Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

SECTION 8: Exposure controls/personal protection

2-(2-butoxyethoxy)ethanol	TRGS 900 OEL (Germany, 6/2024) TWA 8 hours: 67 mg/m³. PEAK 15 minutes: 100.5 mg/m³. TWA 8 hours: 10 ppm. PEAK 15 minutes: 15 ppm. DFG MAC-values list (Germany, 7/2024) Develop C. TWA 8 hours: 67 mg/m³. PEAK 15 minutes: 100.5 mg/m³ 4 times per shift [Interval: 1 hour]. TWA 8 hours: 10 ppm. PEAK 15 minutes: 15 ppm 4 times per shift [Interval: 1 hour]. TRGS 900 OEL (Germany, 6/2024) Absorbed through skin. TWA 8 hours: 49 mg/m³. PEAK 15 minutes: 98 mg/m³. TWA 8 hours: 10 ppm. PEAK 15 minutes: 20 ppm. DFG MAC-values list (Germany, 7/2024) Develop C. Absorbed through skin. TWA 8 hours: 10 ppm. PEAK 15 minutes: 20 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 49 mg/m³. PEAK 15 minutes: 98 mg/m³ 4 times per shift [Interval: 1 hour]. DFG MAC-values list (Germany, 7/2024) Skin sensitiser. DFG MAC-values list (Germany, 7/2024) Absorbed through skin.
2-Butoxyethanol	
1,2-benzisothiazol-3(2H)-one pyrithione zinc	
2-(2-butoxyethoxy)ethanol	Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) STEL 15 minutes: 101.2 mg/m³. STEL 15 minutes: 15 ppm. TWA 8 hours: 67.5 mg/m³. TWA 8 hours: 10 ppm. Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) Absorbed through skin. TWA 8 hours: 25 ppm. TWA 8 hours: 120 mg/m³.
2-Butoxyethanol	
2-(2-butoxyethoxy)ethanol	5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) TWA 8 hours: 67.5 mg/m³. PEAK 15 minutes: 101.2 mg/m³. PEAK 15 minutes: 15 ppm. TWA 8 hours: 10 ppm. 5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) Absorbed through skin. TWA 8 hours: 98 mg/m³. PEAK 15 minutes: 246 mg/m³. PEAK 15 minutes: 50 ppm. TWA 8 hours: 20 ppm.
2-Butoxyethanol	
2-(2-butoxyethoxy)ethanol	Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) STEL 15 minutes: 101.2 mg/m³. STEL 15 minutes: 15 ppm. TWA 8 hours: 67.5 mg/m³. TWA 8 hours: 10 ppm. Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) Absorbed through skin. STEL 15 minutes: 246 mg/m³. STEL 15 minutes: 50 ppm. TWA 8 hours: 100 mg/m³. TWA 8 hours: 20 ppm.
2-Butoxyethanol	
2-(2-butoxyethoxy)ethanol	NAOSH (Ireland, 4/2024) Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 10 ppm. OELV 15 minutes: 101.2 mg/m³. OELV 8 hours: 67.5 mg/m³. OELV 15 minutes: 15 ppm.
2-Butoxyethanol	NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU

SECTION 8: Exposure controls/personal protection

	derived Occupational Exposure Limit Values OELV 8 hours: 20 ppm. OELV 8 hours: 98 mg/m³. OELV 15 minutes: 50 ppm. OELV 15 minutes: 246 mg/m³.
 2-(2-butoxyethoxy)ethanol	Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024) Limit value 8 hours: 10 ppm. Limit value 8 hours: 67.5 mg/m³. Short Term 15 minutes: 15 ppm. Short Term 15 minutes: 101.2 mg/m³.
2-Butoxyethanol	Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024) Absorbed through skin. Limit value 8 hours: 20 ppm. Limit value 8 hours: 98 mg/m³. Short Term 15 minutes: 50 ppm. Short Term 15 minutes: 246 mg/m³.
 2-(2-butoxyethoxy)ethanol	Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) STEL 15 minutes: 101.2 mg/m³. TWA 8 hours: 10 ppm. STEL 15 minutes: 15 ppm. TWA 8 hours: 67.5 mg/m³.
2-Butoxyethanol	Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) Absorbed through skin. TWA 8 hours: 98 mg/m³. TWA 8 hours: 20 ppm. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m³.
2-Dimethylaminoethanol	Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) TWA 8 hours: 5 mg/m³.
2-(2-butoxyethoxy)ethanol	Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) TWA 8 hours: 67.5 mg/m³. TWA 8 hours: 10 ppm. STEL 15 minutes: 101.2 mg/m³. STEL 15 minutes: 15 ppm.
2-Butoxyethanol	Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) Absorbed through skin. TWA 8 hours: 50 mg/m³. TWA 8 hours: 10 ppm. STEL 15 minutes: 100 mg/m³. STEL 15 minutes: 20 ppm.
2-(2-butoxyethoxy)ethanol	Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) STEL 15 minutes: 15 ppm. STEL 15 minutes: 101.2 mg/m³. TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m³.
2-Butoxyethanol	Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m³. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m³.
2-(2-butoxyethoxy)ethanol	EU OEL (Europe, 1/2022) TWA 8 hours: 67.5 mg/m³. TWA 8 hours: 10 ppm. STEL 15 minutes: 101.2 mg/m³. STEL 15 minutes: 15 ppm.
2-Butoxyethanol	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m³.

SECTION 8: Exposure controls/personal protection

	STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m³.
2-(2-butoxyethoxy)ethanol	Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) Absorbed through skin. TWA 8 hours: 50 mg/m³. STEL 15 minutes: 100 mg/m³. TWA 8 hours: 7.4 ppm. STEL 15 minutes: 14.8 ppm.
2-Butoxyethanol	Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) Absorbed through skin. TWA 8 hours: 100 mg/m³. STEL 15 minutes: 246 mg/m³. TWA 8 hours: 20.4 ppm. STEL 15 minutes: 50 ppm.
 2-(2-butoxyethoxy)ethanol	FOR-2011-12-06-1358 (Norway, 5/2024) TWA 8 hours: 10 ppm. TWA 8 hours: 68 mg/m³.
2-Butoxyethanol	FOR-2011-12-06-1358 (Norway, 5/2024) Absorbed through skin. TWA 8 hours: 10 ppm. TWA 8 hours: 50 mg/m³.
 2-(2-butoxyethoxy)ethanol	Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) TWA 8 hours: 67 mg/m³. STEL 15 minutes: 100 mg/m³.
2-Butoxyethanol	Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) Absorbed through skin. TWA 8 hours: 98 mg/m³. STEL 15 minutes: 200 mg/m³.
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) Absorbed through skin. TWA 8 hours: 0.2 mg/m³. STEL 15 minutes: 0.4 mg/m³.
 2-(2-butoxyethoxy)ethanol	Portuguese Institute of Quality (Portugal, 11/2014) TWA 8 hours: 10 ppm. Form: Inhalable fraction and vapor. Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) STEL 15 minutes: 15 ppm. STEL 15 minutes: 101.2 mg/m³. TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m³.
2-Butoxyethanol	Portuguese Institute of Quality (Portugal, 11/2014) A3. TWA 8 hours: 20 ppm. Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) Absorbed through skin. STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m³. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m³.

SECTION 8: Exposure controls/personal protection

2-(2-butoxyethoxy)ethanol	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) VLA 8 hours: 67.5 mg/m³. Short term 15 minutes: 101.2 mg/m³. Short term 15 minutes: 15 ppm. VLA 8 hours: 10 ppm.
2-Butoxyethanol	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) Absorbed through skin. VLA 8 hours: 98 mg/m³. VLA 8 hours: 20 ppm. Short term 15 minutes: 246 mg/m³. Short term 15 minutes: 50 ppm.
 2-(2-butoxyethoxy)ethanol	Government regulation SR c. 355/2006 (Slovakia, 6/2024) Inhalation sensitiser. TWA 8 hours: 67.5 mg/m³. STEL 15 minutes: 101.2 mg/m³. TWA 8 hours: 10 ppm. STEL 15 minutes: 15 ppm.
2-Butoxyethanol	Government regulation SR c. 355/2006 (Slovakia, 6/2024) Absorbed through skin , Inhalation sensitiser. TWA 8 hours: 98 mg/m³. TWA 8 hours: 20 ppm. STEL 15 minutes: 246 mg/m³. STEL 15 minutes: 50 ppm.
pyrithione zinc	Government regulation SR c. 355/2006 (Slovakia, 6/2024) [zinok a jeho anorganické zlúčeniny] Inhalation sensitiser. TWA 8 hours: 0.1 mg/m³ (Zinc and its inorganic compounds). Form: Respirable fraction. TWA 8 hours: 2 mg/m³ (Zinc and its inorganic compounds). Form: Inhalable fraction.
2-(2-butoxyethoxy)ethanol	Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) TWA 8 hours: 67.5 mg/m³. TWA 8 hours: 10 ppm. KTV 15 minutes: 101.2 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 15 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].
2-Butoxyethanol	Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) Absorbed through skin. TWA 8 hours: 98 mg/m³. TWA 8 hours: 20 ppm. KTV 15 minutes: 246 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 50 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].
2-(2-butoxyethoxy)ethanol	National institute of occupational safety and health (Spain, 1/2024) TWA 8 hours: 67.5 mg/m³. TWA 8 hours: 10 ppm. STEL 15 minutes: 15 ppm. STEL 15 minutes: 101.2 mg/m³.
2-Butoxyethanol	National institute of occupational safety and health (Spain, 1/2024) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m³. STEL 15 minutes: 245 mg/m³. STEL 15 minutes: 50 ppm.

SECTION 8: Exposure controls/personal protection

2-(2-butoxyethoxy)ethanol	Work environment authority Regulation 2018:1 (Sweden, 11/2022) TWA 8 hours: 10 ppm. TWA 8 hours: 68 mg/m ³ . STEL 15 minutes: 15 ppm. STEL 15 minutes: 101 mg/m ³ .
2-Butoxyethanol	Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. TWA 8 hours: 10 ppm. TWA 8 hours: 50 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m ³ .
 2-(2-butoxyethoxy)ethanol	SUVA (Switzerland, 1/2025) TWA 8 hours: 67 mg/m ³ . Form: vapour and aerosols. STEL 15 minutes: 101 mg/m ³ . Form: vapour and aerosols. STEL 15 minutes: 15 ppm. Form: vapour and aerosols. TWA 8 hours: 10 ppm. Form: vapour and aerosols.
2-Butoxyethanol	SUVA (Switzerland, 1/2025) Absorbed through skin. TWA 8 hours: 10 ppm. TWA 8 hours: 49 mg/m ³ . STEL 15 minutes: 20 ppm. STEL 15 minutes: 98 mg/m ³ .
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	SUVA (Switzerland, 1/2025) Sensitiser. STEL 15 minutes: 0.4 mg/m ³ . Form: Inhalable fraction. TWA 8 hours: 0.2 mg/m ³ . Form: Inhalable fraction.
 2-(2-butoxyethoxy)ethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m ³ . STEL 15 minutes: 15 ppm. STEL 15 minutes: 101.2 mg/m ³ .
2-Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 50 ppm. TWA 8 hours: 25 ppm. STEL 15 minutes: 246 mg/m ³ . TWA 8 hours: 123 mg/m ³ .
2-Dimethylaminoethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 22 mg/m ³ . STEL 15 minutes: 6 ppm. TWA 8 hours: 2 ppm. TWA 8 hours: 7.4 mg/m ³ .

Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
2-Butoxyethanol	Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015) Biological limit values: 0.17 mmol/mmol creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week. Biological limit values: 200 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week.
No exposure indices known.	

SECTION 8: Exposure controls/personal protection

No exposure indices known.

No exposure indices known.

No exposure indices known.

 2-Butoxyethanol

 2-Butoxyethanol

No exposure indices known.

No exposure indices known.

No exposure indices known.

 2-Butoxyethanol

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

2-Butoxyethanol

No exposure indices known.

No exposure indices known.

2-Butoxyethanol

2-Butoxyethanol

No exposure indices known.

 2-Butoxyethanol

2-Butoxyethanol

Biological limit values (BLV) - Labour Code / ANSES (France, 4/2023) [2- butoxyéthanol et son acétate]

BLV: 100 mg/g Cr, 2-butoxyacetic acid [in urine]. Sampling time: end of shift (regardless of the day of the week).

DFG BEI-values list (Germany, 7/2024) Notes: danger from percutaneous absorption (see p. 211 and p. 228).

BEI: 150 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the shift, for long-term exposures after several previous shifts.

TRGS 903 - BEI Values (Germany, 10/2024)

BEI: 150 mg/g creatinine, butoxy acetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the shift, for long-term exposure after several previous shifts.

NAOSH BGVs (Ireland, 1/2011)

BMGV: 200 mg/g creatinine, BAA [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.

Portuguese Institute of Quality (Portugal, 11/2014)

BEI: 200 mg/g creatinine, butoxyacetic acid (BAA) [in urine]. Sampling time: end of shift.

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

BAT: 150 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the work shift, at long-term exposure: at the end of the work shift after several consecutive workdays.

National institute of occupational safety and health (Spain, 1/2024)

VLB: 200 mg/g creatinine, butoxyacetic acid [in urine]. Sampling time: end of shift.

SUVA (Switzerland, 1/2025)

BEI: 150 mg/g creatinine, 2-butoxy acetic acid (after hydrolysis) [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift.

EH40/2005 BMGVs (United Kingdom (UK), 1/2020)

BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

2-(2-butoxyethoxy)ethanol

Result

DNEL - General population - Long term - Oral

6.25 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

67.5 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

101.2 mg/m³

Effects: Local

2-Butoxyethanol

DNEL - General population - Long term - Oral

6.3 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Oral

26.7 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

59 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

98 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

147 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

246 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

426 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

1091 mg/m³

Effects: Systemic

2-Dimethylaminoethanol

DNEL - Workers - Short term - Dermal

100 µg/cm²

Effects: Local

DNEL - General population - Long term - Oral

0.148 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

SECTION 8: Exposure controls/personal protection

0.25 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.43755 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Dermal

1.2 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

1.76 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

1.76 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

5.28 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

13.53 mg/m³

Effects: Local

1,2-benzisothiazol-3(2H)-one

DNEL - General population - Long term - Dermal

0.345 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.966 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

1.2 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

6.81 mg/m³

Effects: Systemic

pyrithione zinc

DNEL - Workers - Long term - Dermal

0.01 mg/kg bw/day

Effects: Systemic

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

DNEL - General population - Long term - Inhalation

0.02 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

0.02 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

0.04 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

0.04 mg/m³

Effects: Local

DNEL - General population - Long term - Oral

0.09 mg/kg bw/day

SECTION 8: Exposure controls/personal protection

Effects: Systemic

DNEL - General population - Short term - Oral

0.11 mg/kg bw/day

Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Not recommended polyvinyl alcohol (PVA) gloves

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name	°C	°F	Method
Water	100	212	
2-Butoxyethanol	171 to 171.5	339.8 to 340.7	IP 123-93

Flammability	: Not available.
Lower and upper explosion limit	: Lower: 0.8% (2-(2-butoxyethoxy)ethanol) Upper: 9.4% (2-(2-butoxyethoxy)ethanol)
Flash point	: Closed cup: >100°C (>212°F)
Auto-ignition temperature	:

Ingredient name	°C	°F	Method
2-(2-butoxyethoxy)ethanol	210	410	DIN 51794
2-Butoxyethanol	230	446	DIN 51794

Decomposition temperature	: Not available.
pH	: 8 to 9
Viscosity	: Not available.
Solubility(ies)	:
	Not available.

Solubility in water	: Not available.
Partition coefficient: n-octanol/ water	: Not applicable.
Vapour pressure	:

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	17.5	2.3				
2-Butoxyethanol	0.75006	0.1				

Relative density	: Not available.
Density	: 1.2 g/cm³
Vapour density	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties	: Not available.
Oxidising properties	: Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : No specific data.
- 10.5 Incompatible materials** : No specific data.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

2-(2-butoxyethoxy)ethanol

Result

Rabbit - Dermal - LD50

2700 mg/kg

Rat - Oral - LD50

4500 mg/kg

Toxic effects: Behavioral - Tetany Lung, Thorax, or Respiration
- Dyspnea Liver - Other changes

2-Dimethylaminoethanol

Rat - Oral - LD50

2 g/kg

Rat - Inhalation - LC50 Gas.

1641 ppm [4 hours]

Toxic effects: Eye - Lacrimation Behavioral - Ataxia Lung,
Thorax, or Respiration - Dyspnea

1,2-benzisothiazol-3(2H)-one

Rat - Oral - LD50

1020 mg/kg

pyrithione zinc

Rat - Oral - LD50

177 mg/kg

Rabbit - Dermal - LD50

100 mg/kg

Rat - Inhalation - LC50 Dusts and mists

140 mg/m³ [4 hours]

Toxic effects: Lung, Thorax, or Respiration - Acute pulmonary
edema Lung, Thorax, or Respiration - Dyspnea Gross
Metabolite Changes - Weight loss or decreased weight gain

reaction mass of: 5-chloro-2-methyl-
4-isothiazolin-3-one [EC no. 247-500-7] and
2-methyl-2H-isothiazol-3-one [EC no.
220-239-6] (3:1)

Rat - Oral - LD50

53 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed
activity) Behavioral - Ataxia Lung, Thorax, or Respiration -
Respiratory depression

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
MOTIVO COLORATO 2070-15	52465.9	N/A	573776.2	131.2	N/A
2-(2-butoxyethoxy)ethanol	4500	2700	N/A	N/A	N/A
2-Butoxyethanol	1200	N/A	N/A	3	N/A
2-Dimethylaminoethanol	2000	1100	1641	N/A	N/A
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
pyrithione zinc	221	N/A	N/A	N/A	0.14
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	53	50	N/A	0.5	N/A

Skin corrosion/irritation

Product/ingredient name

2-Butoxyethanol

Result

Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

2-Dimethylaminoethanol

Rabbit - Skin - Mild irritant

Amount/concentration applied: 445 mg

1,2-benzisothiazol-3(2H)-one

Human - Skin - Mild irritant

Duration of treatment/exposure: 48 hours

Amount/concentration applied: 5 %

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Human - Skin - Severe irritant

Amount/concentration applied: 0.01 %

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

2-(2-butoxyethoxy)ethanol

Result

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 20 mg

2-Butoxyethanol

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

2-Dimethylaminoethanol

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 5 uL

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Date of issue/Date of revision

: 05/12/2025

Date of previous issue

: 06/05/2025

Version : 1.02 19/29

MOTIVO COLORATO 2070-15 - All variants

Label No :38826

SECTION 11: Toxicological information

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

2-Dimethylaminoethanol

Result

STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Product/ingredient name

pyrithione zinc

Result

STOT RE 1, H372

Aspiration hazard

Not available.

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

SECTION 11: Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

 (2-butoxyethoxy)ethanol

Result

Acute - LC50 - Fresh water

Fish - Bluegill - *Lepomis macrochirus*

Size: 33 to 75 mm

1300000 µg/l [96 hours]

Effect: Mortality

2-Butoxyethanol

Acute - LC50 - Marine water

Fish - Inland silverside - *Menidia beryllina*

Size: 40 to 100 mm

1250000 µg/l [96 hours]

Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - *Crangon crangon*

800000 µg/l [48 hours]

Effect: Mortality

1,2-benzisothiazol-3(2H)-one

Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test]

Fish - Trout - *Onorhynchus Mykiss*

1.9 mg/l [96 hours]

Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test]

Daphnia - Daphnia - *Daphnia Magna*

3.7 mg/l [48 hours]

Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test]

Algae - Algae - *Skeletonema Costatum*

0.36 mg/l [72 hours]

Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test]

Algae - Algae - *Skeletonema Costatum*

SECTION 12: Ecological information

0.15 mg/l [72 hours]

pyrithione zinc

Acute - EC50 - Marine water

Algae - Diatom - *Thalassiosira pseudonana*

0.51 µg/l [96 hours]

Effect: Population

Chronic - EC10 - Marine water

Algae - Diatom - *Thalassiosira pseudonana*

0.36 µg/l [96 hours]

Effect: Population

Chronic - NOEC - Fresh water

US EPA

Daphnia - Water flea - *Daphnia magna*

2.7 ppb [21 days]

Effect: Growth

Acute - EC50 - Fresh water

US EPA

Daphnia - Water flea - *Daphnia magna*

Age: <24 hours

8.25 ppb [48 hours]

Effect: Intoxication

Acute - LC50 - Fresh water

US EPA

Fish - Fathead minnow - *Pimephales promelas*

Weight: 0.28 g

2.68 ppb [96 hours]

Effect: Mortality

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name

2-benzisothiazol-3(2H)-one

Result

EU

24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-(2-butoxyethoxy)ethanol	1	-	Low
2-Butoxyethanol	0.81	-	Low
2-Dimethylaminoethanol	-0.55	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low
pyrithione zinc	0.9	11 [OECD 305 E]	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
2-(2-butoxyethoxy)ethanol	1.6	36.5981
2-Butoxyethanol	1.8	67.3685
2-Dimethylaminoethanol	1.7	44.8862
1,2-benzisothiazol-3(2H)-one	1.9	73.142

Results of PMT and vPvM assessment

Date of issue/Date of revision	: 05/12/2025	Date of previous issue	: 06/05/2025	Version	: 1.02 22/29
MOTIVO COLORATO 2070-15 - All variants					Label No : 38826

SECTION 12: Ecological information

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
2-(2-butoxyethoxy)ethanol	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
2-Propenoic acid, 2-methyl-, polymer with ethyl 2-propenoate	No	No	No	No	No	No	No
2-Dimethylaminoethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one pyrrithione zinc	No	No	No	No	No	No	No
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
2-(2-butoxyethoxy)ethanol	No	N/A	N/A	No	N/A	N/A	N/A
2-Butoxyethanol	No	N/A	N/A	No	N/A	N/A	N/A
2-Propenoic acid, 2-methyl-, polymer with ethyl 2-propenoate	No	N/A	N/A	No	N/A	N/A	N/A
2-Dimethylaminoethanol	No	N/A	N/A	No	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one pyrrithione zinc	No	N/A	No	No	No	N/A	No
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	No	N/A	N/A	Yes	No	N/A	No
	No	N/A	N/A	No	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
2-(2-butoxyethoxy)ethanol	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
2-Propenoic acid, 2-methyl-, polymer with ethyl 2-propenoate	No	No	No	No	No	No	No
2-Dimethylaminoethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one pyrrithione zinc	No	No	No	No	No	No	No
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	No	No	No	No	No	No	No

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.

Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Not available.

SECTION 12: Ecological information

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : Avoid release to the environment. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC) : 08.01.19

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADN : The product is only regulated as a dangerous good when transported in tank vessels.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
MOTIVO COLORATO 2070-15 2-(2-butoxyethoxy)ethanol	≥90 ≤5	3 55 [Consumer paint]

Labelling

:

Synthetic polymer microparticles - Designation 78

Generic identity of polymer(s) : 3906 - Acrylic polymers., 3909 - Amino-resins, phenolic resins and polyurethanes.

Total percentage of synthetic polymer microparticles : 1.4%

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Austria

Limitation of the use of organic solvents : Permitted.

Belgium

Book VI carcinogenic agents annex VI.2-1 - VI.2-3

Ingredient name	Status
Silice	Listed

Czech Republic

Storage code : IV

Denmark

Date of issue/Date of revision : 05/12/2025 **Date of previous issue** : 06/05/2025 **Version** : 1.02 25/29

MOTIVO COLORATO 2070-15 - All variants

Label No : 38826

SECTION 15: Regulatory information

Fire class : IV-1

[Executive Order No. 1795/2015](#)

Ingredient name	Annex I Section A	Annex I Section B
 titanium dioxide	Listed	-

MAL-code : 1-1

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 1-1

Application: During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Gas filter mask must be worn.

When spraying in existing* spray booths, if the operator is outside the spray zone.

- Full mask with combined filter and arm protectors must be worn.

During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied half mask and eye protection must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied half mask, eye protection, coveralls and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

Restrictions on use : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

List of undesirable substances : Not listed

Carcinogenic waste : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

[Finland](#)

SECTION 15: Regulatory information

France

Social Security Code, Articles L 461-1 to L 461-7 : 2-(2-butoxyethoxy)ethanol RG 84
2-Butoxyethanol RG 84

Reinforced medical surveillance : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

Germany

Storage class (TRGS 510) : 10

Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water : 3

Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
5.2.1	Total dust	30.3
5.2.5	Organic substances	21.9
5.2.5 [I]	Organic substances	6.2

AOX : The product contains organically bound halogens and can contribute to the AOX value in waste water.

Italy

D.Lgs. 152/06 : Not determined.

Netherlands

Water Discharge Policy (ABM) : Z(1) Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioaccumulative potential/ toxicity or persistence). Decontamination effort: Z

Norway

Sweden

Switzerland

VOC content : VOC (w/w): 5.8%

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic

SECTION 16: Other information

PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 05/12/2025

Date of previous issue : 06/05/2025

Version : 1.02

MOTIVO COLORATO 2070-15

All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 05/12/2025 **Date of previous issue** : 06/05/2025 **Version** : 1.02 28/29

MOTIVO COLORATO 2070-15 - All variants

Label No : 38826

