

Reviewed on: 19/10/2021 Printing date: 19/10/2021

#### SECTION 01: Identification of the substance/mixture and of the company undertaking • 1.1 Product identifier Trade name: MOTIVO COLORATO 2077 STRUCTURE FINE Article number / Safety Data Sheet: 257700 1.2 Relevant identified uses of the substance or mixture and uses advised against Application of the substance / the preparation Coating material · 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Teknos AG Industriestrasse 7 LI-9487 Gamprin-Bendern T +423 375 94 00 F +423 375 94 99 Further information obtainable from: Product safety department. e-mail address: li-sdb@teknos.com 1.4 Emergency telephone number: Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International) SECTION 02: Hazards identification 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Void 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 Hazard pictograms Void Signal word Void Hazard statements EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5chloro-2-methyl-4- isothiazolin-3-one [EC no. 247-500-7] and 2- methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1). May produce an allergic reaction. EUH210 Safety data sheet available on request. 2.3 Other hazards Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable. SECTION 03: Composition/information on ingredients 3.2 Chemical characterization: Mixtures Description: Mixture of substances listed below with nonhazardous additions. · Dangerous components: **CAS Number** % 111-76-2 1,00- 5,00 2-butoxyethanol EC number: 203-905-0 Record number 01-2119475108-36 Acute Tox. 4 - H302, Acute Tox. 4 -H312, Acute Tox. 4 - H332, Skin Irrit. 2 -(continued on page 2) SF



Reviewed on: 19/10/2021 Printing date: 19/10/2021

PRODUCT :	MOTIVO COLORATO 2077 STRUCTURE FINE	
		(continued of page 1)
112-34-5	H315, Eye Irrit. 2 - H319 <b>2-(2-butoxyethoxy)ethanol</b> EC number: 203-961-6 Record number 01-2119475104-44 <b>()</b> Eye Irrit. 2 - H319	1,00- 5,00
13463-67-7	<b>titanium dioxide</b> EC number: 236-675-5 Record number 01-2119489379-17 � Carc. 2 - H351	10,00- 25,00
2634-33-5	<b>1,2-benzisothiazol-3(2H)-one</b> EC number: 220-120-9	0,0015- 0,50
55965-84-9	reaction mass of: 5-chloro-2-methyl-4- isothiazolin-3-one [EC no. 247-500-7] and 2- methyl-2H-isothiazol-3-one [EC no. 220-239- 6] (3: 1)	0,00-0,0015
34590-94-8	H400, Aquatic Chronic 1 - H410 <b>Dipropylene glycol monomethyl ether</b> EC number: 252-104-2 Record number 01-2119450011-60 substance with a Community workplace exposure limit.	0,0015- 0,50
<ul> <li>Additional i For the work</li> </ul>	Information: rding of the listed risk phrases refer to section 16.	

## SECTION 04: First aid measures

- 4.1 Description of first aid measures
- After inhalation:
- Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
  After eye contact:
- Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- Information for doctor:
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
   4.3 Indication of any immediate medical attention and special treatment
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SF

(continued on page 3)



(continued of page 2)

#### 4219400

Reviewed on: 19/10/2021 Printing date: 19/10/2021

# PRODUCT : MOTIVO COLORATO 2077 STRUCTURE FINE

### SECTION 05: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters
  Protective equipment:
- Mouth respiratory protective device.
- Do not inhale explosion gases or combustion gases.
- Additional information
   Cool endangered receptacles with water spray.
   Collect contaminated fire fighting water separately. It must not enter the sewage system.

# SECTION 06: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. In case of seepage into the ground inform responsible authorities. In case of gas release or seepage into the ground inform responsible authorities. Do not allow to enter sewers/ surface or ground water.
   6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
- See Section 7 for information on personal protection equipment.
- See Section 13 for disposal information.

# SECTION 07: Handling and storage

- Handling:
- 7.1 Precautions for safe handling Open and handle receptacle with care.
- Information about fire and explosion protection: Prevent impact and friction.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight.
- 7.3 Specific end use(s)
- No further relevant information available.

### SECTION 08: Exposure controls/personal protection

• 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

- HTP
- Short-term value

250

mg/m3 (continued on page 4)



Reviewed on: 19/10/2021 Printing date: 19/10/2021

			(continued of page 3)
		50	ppm
Long	j-term value	98	mg/m3
		20	ppm
iho			
112-34-5	2-(2-butoxyethox	y)ethanol	
HTP			
Long	g-term value	68	mg/m3
		10	ppm
34590-94-8	Dipropylene glyc	ol monomethyl ether	
HTP			
Long	g-term value	310	mg/m3
		50	ppm
<ul> <li>8.2 Exposure</li> <li>Personal prote</li> <li>General prote</li> <li>The usual prote</li> <li>Do not eat or</li> <li>Be sure to cle</li> <li>Respiratory p</li> </ul>	<b>Detective equipment:</b> ective and hygienic meas ecautionary measures ar drink while working. ean skin thoroughly after protection: Suitable respi	sures: e to be adhered to when handling chemic work and before breaks. ratory protective device recommended. U	
<ul> <li>8.2 Exposure</li> <li>Personal protection</li> <li>General protection</li> <li>General protection</li> <li>General protection</li> <li>Respiratory prodevice in cass</li> <li>Protection of preparation.</li> <li>preparation.</li> <li>Material of gluther</li> <li>The selection</li> <li>varies from mage of the glove mage.</li> <li>Penetration to the glove mage.</li> <li>Penetration to the selection</li> </ul>	e controls <b>Detective equipment:</b> ective and hygienic measures ar drink while working. ean skin thoroughly after protection: Suitable respin e of insufficient ventilation hands: The glove mater Due to missing tests no in the chemical mixture. See nd the degradation Imper- protecture to manufact terial can not be calculat me of glove material eak through time has to be	sures: e to be adhered to when handling chemic work and before breaks. ratory protective device recommended. Us on. ial has to be impermeable and resistant to recommendation to the glove material can lection of the glove material on considera	se suitable respiratory protective the product/ the substance/ the be given for the product/ the tion of the penetration times, rates also on further marks of quality and everal substances, the resistance of ecked prior to the application. rotective gloves and has to be

Appearance		
Appearance:		
Form:	Liquid	
Colour:	According to product specifica	
Odour:	Characteristic Characteristic	
Odour threshold:	Not determined.	
Change in condition		
Melting point/freezing point:	0°C	
Initial boiling point and boiling range:	Undetermined.	
Flash point:	Not applicable.	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	Undetermined.	
Decomposition temperature:	Not determined.	



Reviewed on: 19/10/2021 Printing date: 19/10/2021

	(continued of page 4
Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	at 20 °C 23,0000 mbar
Density:	1,1600 - 1,1800 g/cm3
Solubility in / Miscibility with	
water:	Not determined.
Viscosity:	
	Not determined.
	at 23 °C 35 - 55 s DIN 4 mm
9.2 Other information	No further relevant information available.

### SECTION 10: Stability and reactivity

- 10.1 Reactivity
- No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid
- No further relevant information available.
- 10.5 Incompatible materials:
- No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous decomposition products known.

### SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity
- LD/LC50 values relevant for classification:


#### 111-76-2 2-butoxyethanol

Oral, LD50: 1746 mg/kg (rat) Oral, LD50: 1414 mg/kg (guinea Pig) Dermal, LD50: 2000 mg/kg (rat) Dermal, LD50: 1000 mg/kg (Rabbit) Dermal, LD50: 2000 mg/kg (guinea Pig) Oral, LD50: 5660 mg/kg (rat) Dermal, LD50: 4000 mg kg (Rabbit) Oral, LD50: 8532 mg/kg (rat) Inhalative, LC50/4h: 35,7 mg/l (rat) Oral, LD50: 5660 mg/kg (rat) Dermal, LD50: 13000 mg/kg (Rabbit) Inhalative, LC50/4h: 6 mg/l (rat) Oral, LD50: >20000 mg/kg (rat) Dermal, LD50: >10000 mg/kg (Rabbit) Inhalative, LC50/4h: 6 mg/l (rat) Oral, LD50: >20000 mg/kg (rat) Dermal, LD50: >10000 mg/kg (Rabbit) Inhalative, LC50/4h: >6,82 mg/l (rat) Oral, LD50: 2000 mg/kg (rat) Dermal, LD50: 1370 mg kg (Rabbit) Inhalative, LC50/4h: 3,25 mg/l (mouse) Oral, LD50: 5135 mg/kg (rat) Dermal, LD50: >19000 mg/kg (Rabbit)

- 112-34-52-(2-butoxyethoxy)ethanol108-65-62-methoxy-1-methylethyl acetate107-98-21-methoxy-2-propanol13463-67-7titanium dioxide108-01-02-dimethylaminoethanol34590-94-8Dipropylene glycol monomethyl ether• Primary irritant effect:Skin corrosion/irritation<br/>No irritant effect.
- Serious eye damage/irritation
- No irritating effect. Respiratory or skin sensitisation
- No sensitising effects known.
- Additional toxicological information:



Reviewed on: 19/10/2021 Printing date: 19/10/2021



• 14.1 UN-Number	
ADR	Void
IMDG	Void
ΙΑΤΑ	Void
• 14.2 UN proper shipping n	ame
ADR	Void
IMDG	Void
ΙΑΤΑ	Void
<ul> <li>14.3 Transport hazard clas ADR</li> </ul>	s(es)

(continued on page 7)



Reviewed on: 19/10/2021 Printing date: 19/10/2021

		(continued of page 6)
Class	Void	
IMDG		
Class	Void	
ΙΑΤΑ		
Class	Void	
<ul> <li>14.4 Packi</li> </ul>	ng group	
ADR	Void	
IMDG	Void	
ΙΑΤΑ	Void	
Not applica	port in bulk according to Annex II of MARPOL73/7	78 and the IBC Code

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic
- equipment Annex II None of the ingredients is listed. • REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
- None of the ingredients is listed. Annex II - REPORTABLE EXPLOSIVES PRECURSORS
- None of the ingredients is listed.

#### National regulations:

- Technical instructions (air):
- Class Share in % Τ
  - 3,92
- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. • Relevant phrases

riolovani prilao	
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

(continued on page 8)

### Page : 8 / 8 MATERIAL SAFETY DATA SHEET according to 1907/2006/EC, Article 31



4219400

Reviewed on: 19/10/2021 Printing date: 19/10/2021

	(continued of page
<ul> <li>Department</li> </ul>	t issuing MSDS:
Environme	nt protection department.
<ul> <li>Abbreviation</li> </ul>	ns and acronyms:
ADR: Acco	rd européen sur le transport des marchandises dangereuses par Route (European Agreement
	the International Carriage of Dangerous Goods by Road)
	ment international concernant le transport des marchandises dangereuses par chemin de fer
	s Concerning the International Transport of Dangerous Goods by Rail)
	national Maritime Code for Dangerous Goods
	national Air Transport Association
	national Civil Aviation Organisation
	ally Harmonised System of Classification and Labelling of Chemicals
	uropean Inventory of Existing Commercial Chemical Substances
	uropean List of Notified Chemical Substances
	nical Abstracts Service (division of the American Chemical Society)
	al concentration, 50 percent
	al dose, 50 percent
	stent, Bioaccumulative and Toxic
	Persistent and very Bioaccumulative
	pared to the previous version altered.