

SAFETY DATA SHEET



NICOSIT 1340-11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : NICOSIT 1340-11

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

National contact

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Eye Dam. 1, H318

STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 - Flammable liquid and vapour.
H318 - Causes serious eye damage.
H336 - May cause drowsiness or dizziness.

Precautionary statements

Prevention : P280 - Wear eye or face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response : P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor.

Storage : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

SECTION 2: Hazards identification

| | |
|--|--|
| Disposal | : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Hazardous ingredients | : Contains: n-Butyl acetate and Propan-1-ol |
| Supplemental label elements | : Contains Formaldehyde and Maleic anhydride. May produce an allergic reaction. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : |

2.3 Other hazards

| | |
|---|---|
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : None known. |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|--|---|-----------|---|---|---------|
| n-Butyl acetate | REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1 | ≥25 - ≤50 | Flam. Liq. 3, H226 STOT SE 3, H336 EUH066 | - | [1] [2] |
| Urea, polymer with formaldehyde, butylated | CAS: 68002-19-7 | ≤10 | Aquatic Chronic 4, H413 | - | [1] |
| 1-Methoxy 2-propanol | REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3 | ≤10 | Flam. Liq. 3, H226 STOT SE 3, H336 | - | [1] [2] |
| Urea-formaldehyde-polymer | CAS: 68002-18-6 | ≤10 | Aquatic Chronic 4, H413 | - | [1] |
| Propan-1-ol | REACH #: 01-2119486761-29 EC: 200-746-9 CAS: 71-23-8 Index: 603-003-00-0 | ≤10 | Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336 | - | [1] [2] |
| Butan-1-ol | REACH #: 01-2119484630-38 EC: 200-751-6 CAS: 71-36-3 Index: 603-004-00-6 | ≤3 | Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336 | ATE [Oral] = 790 mg/kg | [1] [2] |
| Ethanol | REACH #: 01-2119457610-43 EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5 | ≤3 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 | - | [1] [2] |

SECTION 3: Composition/information on ingredients

| | | | | | |
|------------------|--|--------|---|--|---------|
| Xylene | REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9 | <1 | Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (oral, inhalation) Asp. Tox. 1, H304 | ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/ l | [1] [2] |
| Ethylbenzene | REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4 | ≤0.3 | Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) (oral, inhalation) Asp. Tox. 1, H304 | ATE [Inhalation (vapours)] = 11 mg/ l | [1] [2] |
| Formaldehyde | REACH #: 01-2119488953-20 EC: 200-001-8 CAS: 50-00-0 Index: 605-001-00-5 | <0.1 | Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H335 | ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (gases)] = 700 ppm Skin Corr. 1B, H314: C ≥ 25% Skin Irrit. 2, H315: 5% ≤ C < 25% Eye Dam. 1, H318: C ≥ 25% Eye Irrit. 2, H319: 5% ≤ C < 25% Skin Sens. 1, H317: C ≥ 0.2% STOT SE 3, H335: C ≥ 5% | [1] [2] |
| Ethyl acetate | REACH #: 01-2119475103-46 EC: 205-500-4 CAS: 141-78-6 Index: 607-022-00-5 | ≤0.1 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066 | - | [1] [2] |
| Phosphoric acid | REACH #: 01-2119485924-24 EC: 231-633-2 CAS: 7664-38-2 Index: 015-011-00-6 | ≤0.1 | Skin Corr. 1B, H314 Eye Dam. 1, H318 | Skin Corr. 1B, H314: C ≥ 25% Skin Irrit. 2, H315: 10% ≤ C < 25% | [1] [2] |
| Maleic anhydride | REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9 | <0.001 | Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (inhalation) EUH071 See Section 16 for the full text of the H statements declared above. | ATE [Oral] = 400 mg/kg Skin Sens. 1, H317: C ≥ 0.001% | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

SECTION 3: Composition/information on ingredients

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso Directive - Reporting thresholds

Danger criteria

| Category | Notification and MAPP threshold | Safety report threshold |
|----------|---------------------------------|-------------------------|
| P5c | 5000 tonne | 50000 tonne |

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|-------------------------|---|
| n-Butyl acetate | EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 966 mg/m ³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 724 mg/m ³ 8 hours. TWA: 150 ppm 8 hours. |
| 1-Methoxy 2-propanol | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 560 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m ³ 8 hours. TWA: 100 ppm 8 hours. |
| Propan-1-ol | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 625 mg/m ³ 15 minutes. STEL: 250 ppm 15 minutes. TWA: 500 mg/m ³ 8 hours. TWA: 200 ppm 8 hours. |
| Butan-1-ol | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 154 mg/m ³ 15 minutes. STEL: 50 ppm 15 minutes. |
| Ethanol | EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 1000 ppm 8 hours. TWA: 1920 mg/m ³ 8 hours. |
| Xylene | EH40/2005 WELs (United Kingdom (UK), 1/2020). [xylene, o-,m-, p- or mixed isomers] Absorbed through skin. STEL: 441 mg/m ³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 220 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes. |
| Ethylbenzene | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 552 mg/m ³ 15 minutes. STEL: 125 ppm 15 minutes. TWA: 100 ppm 8 hours. TWA: 441 mg/m ³ 8 hours. |
| Formaldehyde | EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 2.5 mg/m ³ 15 minutes. STEL: 2 ppm 15 minutes. TWA: 2 ppm 8 hours. TWA: 2.5 mg/m ³ 8 hours. |
| Ethyl acetate | EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours. STEL: 1468 mg/m ³ 15 minutes. TWA: 734 mg/m ³ 8 hours. |
| Phosphoric acid | EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 2 mg/m ³ 15 minutes. TWA: 1 mg/m ³ 8 hours. |
| Maleic anhydride | EH40/2005 WELs (United Kingdom (UK), 1/2020). Inhalation sensitiser. STEL: 3 mg/m ³ 15 minutes. TWA: 1 mg/m ³ 8 hours. |

Biological exposure indices

SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Exposure indices |
|-------------------------|---|
| Xylene | EH40/2005 BMGVs (United Kingdom (UK), 8/2018) [Xylene, o-, m-, p- or mixed isomers] BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift. |

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following:
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|-------------------------|------|-----------------------|-------------------------|--------------------|----------|
| n-Butyl acetate | DNEL | Short term Oral | 2 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Oral | 2 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 6 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 11 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 35.7 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 300 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 300 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 300 mg/m ³ | Workers | Local |
| | DNEL | Short term Inhalation | 600 mg/m ³ | Workers | Local |
| | DNEL | Short term Inhalation | 600 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 3.4 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 7 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 12 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 48 mg/m ³ | Workers | Systemic |
| 1-Methoxy 2-propanol | DNEL | Long term Oral | 33 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 43.9 mg/m ³ | General population | Systemic |
| | DNEL | Long term Dermal | 78 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 183 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 369 mg/m ³ | Workers | Systemic |
| | DNEL | Short term Inhalation | 553.5 mg/m ³ | Workers | Local |
| | DNEL | Short term Inhalation | 553.5 mg/m ³ | Workers | Systemic |
| Propan-1-ol | DNEL | Long term Oral | 61 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 80 mg/m ³ | General population | Systemic |

SECTION 8: Exposure controls/personal protection

| | | | | | |
|------------------|------|-----------------------|--------------------------|--------------------|----------|
| Butan-1-ol | DNEL | Long term Dermal | 81 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 136 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 268 mg/m ³ | Workers | Systemic |
| | DNEL | Short term Inhalation | 1036 mg/m ³ | General population | Systemic |
| | DNEL | Short term Inhalation | 1723 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Oral | 1.5625 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 3.125 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 55.357 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 155 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 310 mg/m ³ | Workers | Local |
| Ethanol | DNEL | Long term Oral | 87 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 114 mg/m ³ | General population | Systemic |
| | DNEL | Long term Dermal | 206 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 343 mg/kg bw/day | Workers | Systemic |
| | DNEL | Short term Inhalation | 950 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 950 mg/m ³ | Workers | Systemic |
| | DNEL | Short term Inhalation | 1900 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 0.375 mg/m ³ | Workers | Local |
| | DNEL | Short term Inhalation | 0.75 mg/m ³ | Workers | Local |
| | DNEL | Long term Dermal | 12 µg/cm ² | General population | Local |
| Formaldehyde | DNEL | Long term Dermal | 37 µg/cm ² | Workers | Local |
| | DNEL | Long term Inhalation | 0.1 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 3.2 mg/m ³ | General population | Systemic |
| | DNEL | Long term Oral | 4.1 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 9 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 102 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 240 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 0.081 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 0.081 mg/m ³ | Workers | Systemic |
| | DNEL | Short term Inhalation | 0.2 mg/m ³ | Workers | Local |
| Maleic anhydride | DNEL | Short term Inhalation | 0.2 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Inhalation | 0.05 mg/m ³ | General population | Systemic |
| | DNEL | Long term Oral | 0.06 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term | 0.08 mg/m ³ | General | Local |

SECTION 8: Exposure controls/personal protection

| | | | | | |
|--|------|-------------------------------|---------------------|-------------------------------------|----------|
| | DNEL | Inhalation Short term Oral | 0.1 mg/kg bw/day | population General population | Systemic |
| | DNEL | Short term Dermal | 0.1 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 0.1 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 0.2 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Dermal | 0.2 mg/kg bw/day | Workers | Systemic |

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type: A

Filter type (spray application): A P

SECTION 8: Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Colour : Colourless.
Odour : Slight
Odour threshold : Not available.
Melting point/freezing point : Not available.
Initial boiling point and boiling range :

| Ingredient name | °C | °F | Method |
|-----------------|-------|-------|--------|
| Ethanol | 78.29 | 172.9 | |
| Propan-1-ol | 97 | 206.6 | |

Flammability : Not available.
Lower and upper explosion limit : Lower: 1.4%
Upper: 19%
Flash point : Closed cup: 23°C (73.4°F)
Auto-ignition temperature :

| Ingredient name | °C | °F | Method |
|----------------------|-----|-----|---------|
| 1-Methoxy 2-propanol | 270 | 518 | |
| Butan-1-ol | 355 | 671 | EU A.15 |

Decomposition temperature : Not available.
pH : Not applicable.
Viscosity : Not available.
Solubility(ies) :
Not available.

Solubility in water : Not available.
Partition coefficient: n-octanol/ water : Not applicable.
Vapour pressure :

| Ingredient name | Vapour Pressure at 20°C | | | Vapour pressure at 50°C | | |
|-----------------|-------------------------|-----|--------|-------------------------|-----|--------|
| | mm Hg | kPa | Method | mm Hg | kPa | Method |
| Ethanol | 42.94865 | 5.7 | | | | |
| Propan-1-ol | 21.15146 | 2.8 | | | | |

Relative density : Not available.
Density : 1 g/cm³
Vapour density : Not available.
Explosive properties : Not available.
Oxidising properties : Not available.
Particle characteristics
Median particle size : Not applicable.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- 10.5 Incompatible materials** : Reactive or incompatible with the following materials:
oxidising materials
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---------------------------|------------------------|---------|--------------------------|----------|
| n-Butyl acetate | LC50 Inhalation Vapour | Rat | 0.74 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | 14112 mg/kg | - |
| | LD50 Oral | Rat | 10760 mg/kg | - |
| 1-Methoxy 2-propanol | LD50 Dermal | Rabbit | 13 g/kg | - |
| | LD50 Oral | Rat | 6600 mg/kg | - |
| Urea-formaldehyde-polymer | LD50 Dermal | Rabbit | >5 g/kg | - |
| | LD50 Oral | Rat | >5 g/kg | - |
| Propan-1-ol | LD50 Dermal | Rabbit | 5040 mg/kg | - |
| | LD50 Oral | Rat | 1870 mg/kg | - |
| Butan-1-ol | LC50 Inhalation Vapour | Rat | 24000 mg/m ³ | 4 hours |
| | LD50 Dermal | Rabbit | 3400 mg/kg | - |
| | LD50 Oral | Rat | 790 mg/kg | - |
| Ethanol | LC50 Inhalation Vapour | Rat | 124700 mg/m ³ | 4 hours |
| | LD50 Oral | Rat | 7 g/kg | - |
| Formaldehyde | LC50 Inhalation Gas. | Rat | 250 ppm | 4 hours |
| | LD50 Dermal | Rabbit | 270 mg/kg | - |
| | LD50 Oral | Rat | 100 mg/kg | - |
| Maleic anhydride | LD50 Dermal | Rabbit | 2620 mg/kg | - |
| | LD50 Oral | Rat | 400 mg/kg | - |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

| Route | ATE value |
|-------|----------------|
| Oral | 45117.08 mg/kg |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|---------------------------|--------------------------|---------|-------|-----------------|-------------|
| n-Butyl acetate | Eyes - Moderate irritant | Rabbit | - | 100 mg | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 mg | - |
| 1-Methoxy 2-propanol | Eyes - Mild irritant | Rabbit | - | 24 hours 500 mg | - |
| | Skin - Mild irritant | Rabbit | - | 500 mg | - |
| Urea-formaldehyde-polymer | Eyes - Severe irritant | Rabbit | - | 24 hours 100 uL | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hours 20 mg | - |
| Propan-1-ol | Skin - Mild irritant | Human | - | 47 hours 100 mg | - |

SECTION 11: Toxicological information

| | | | | | |
|------------------|--------------------------|--------|---|----------------------------------|---|
| Butan-1-ol | Skin - Mild irritant | Human | - | % 24 hours 100 | - |
| | Skin - Mild irritant | Rabbit | - | % 500 mg | - |
| | Eyes - Severe irritant | Rabbit | - | 0.005 MI | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 2 mg | - |
| Ethanol | Skin - Moderate irritant | Rabbit | - | 24 hours 20 mg | - |
| | Eyes - Mild irritant | Rabbit | - | 24 hours 500 mg | - |
| | Eyes - Moderate irritant | Rabbit | - | 0.066666667 minutes 100 mg | - |
| | Eyes - Moderate irritant | Rabbit | - | 100 uL | - |
| Formaldehyde | Eyes - Severe irritant | Rabbit | - | 500 mg | - |
| | Skin - Mild irritant | Rabbit | - | 400 mg | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 20 mg | - |
| | Eyes - Mild irritant | Human | - | 6 minutes 1 ppm | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 750 ug | - |
| | Eyes - Severe irritant | Rabbit | - | 750 ug | - |
| | Skin - Mild irritant | Human | - | 72 hours 150 ug l | - |
| | Skin - Mild irritant | Rabbit | - | 540 mg | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 50 mg | - |
| | Skin - Severe irritant | Human | - | 0.01 % | - |
| | Skin - Severe irritant | Rabbit | - | 0.8 % | - |
| | Skin - Severe irritant | Rabbit | - | 24 hours 2 mg | - |
| Maleic anhydride | Eyes - Severe irritant | Rabbit | - | 1 % | - |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Sensitisation

Conclusion/Summary : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|------------------------------|
| n-Butyl acetate | Category 3 | - | Narcotic effects |
| 1-Methoxy 2-propanol | Category 3 | - | Narcotic effects |
| Propan-1-ol | Category 3 | - | Narcotic effects |
| Butan-1-ol | Category 3 | - | Respiratory tract irritation |
| Formaldehyde | Category 3 | - | Narcotic effects |
| | Category 3 | - | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

SECTION 11: Toxicological information

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|--------------------|
| Maleic anhydride | Category 1 | inhalation | respiratory system |

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

SECTION 11: Toxicological information

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--------------------------------------|--|----------|
| n-Butyl acetate | Acute LC50 32 mg/l Marine water | Crustaceans - <i>Artemia salina</i> | 48 hours |
| Propan-1-ol | Acute LC50 18000 µg/l Fresh water | Fish - <i>Pimephales promelas</i> | 96 hours |
| | Acute EC50 4480000 µg/l Fresh water | Algae - <i>Selenastrum sp.</i> | 96 hours |
| | Acute LC50 1000000 µg/l Fresh water | Crustaceans - <i>Gammarus pulex</i> | 48 hours |
| | Acute LC50 2950000 µg/l Fresh water | Daphnia - <i>Daphnia pulex</i> | 48 hours |
| Butan-1-ol | Acute LC50 3800000 µg/l Marine water | Fish - <i>Alburnus alburnus</i> | 96 hours |
| | Acute EC50 1983000 µg/l Fresh water | Daphnia - <i>Daphnia magna</i> | 48 hours |
| Ethanol | Acute LC50 1730000 µg/l Fresh water | Fish - <i>Pimephales promelas</i> | 96 hours |
| | Acute EC50 17.921 mg/l Marine water | Algae - <i>Ulva pertusa</i> | 96 hours |
| | Acute EC50 2000 µg/l Fresh water | Daphnia - <i>Daphnia magna</i> | 48 hours |
| | Acute LC50 25500 µg/l Marine water | Crustaceans - <i>Artemia franciscana</i> - Larvae | 48 hours |
| | Acute LC50 42000 µg/l Fresh water | Fish - <i>Oncorhynchus mykiss</i> | 4 days |
| | Chronic NOEC 4.995 mg/l Marine water | Algae - <i>Ulva pertusa</i> | 96 hours |
| | Chronic NOEC 100 µl/L Fresh water | Daphnia - <i>Daphnia magna</i> - Neonate | 21 days |
| | Chronic NOEC 0.375 µl/L Fresh water | Fish - <i>Gambusia holbrooki</i> - Larvae | 12 weeks |
| Formaldehyde | Acute EC50 3.48 mg/l Fresh water | Algae - <i>Desmodesmus subspicatus</i> | 72 hours |
| | Acute EC50 0.788 mg/l Marine water | Algae - <i>Ulva pertusa</i> | 96 hours |
| | Acute EC50 12.98 mg/l Fresh water | Crustaceans - <i>Ceriodaphnia dubia</i> - Neonate | 48 hours |
| | Acute EC50 5800 µg/l Fresh water | Daphnia - <i>Daphnia pulex</i> - Neonate | 48 hours |
| | Acute LC50 1.41 ppm Fresh water | Fish - <i>Oncorhynchus mykiss</i> | 96 hours |
| | Chronic NOEC 0.005 mg/l Marine water | Algae - <i>Isochrysis galbana</i> - Exponential growth phase | 96 hours |
| | Chronic NOEC 953.9 ppm Fresh water | Fish - <i>Oncorhynchus tshawytscha</i> - Egg | 43 days |
| Maleic anhydride | Acute LC50 230000 µg/l Fresh water | Fish - <i>Gambusia affinis</i> - Adult | 96 hours |

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Conclusion/Summary : This product has not been tested for biodegradation.

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| n-Butyl acetate | 2.3 | - | Low |
| 1-Methoxy 2-propanol | <1 | - | Low |
| Propan-1-ol | 0.2 | - | Low |
| Butan-1-ol | 1 | - | Low |
| Ethanol | -0.35 | - | Low |
| Maleic anhydride | -2.78 | - | Low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

| | | | |
|--|--|--------------------|-------------------------|
| Date of issue/Date of revision : 10/05/2024 | Date of previous issue : No previous validation | Version : 1 | 15/20 |
| NICOSIT 1340-11 | | | Label No : 51776 |

SECTION 12: Ecological information

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.






European waste catalogue (EWC) : 08.01.11

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|---------------------------------|--|--|---|--|
| 14.1 UN number or ID number | UN1993 | UN1993 | UN1993 | UN1993 |
| 14.2 UN proper shipping name | FLAMMABLE LIQUID, N.O.S. (n-butyl acetate, 1-methoxy-2-propanol) | FLAMMABLE LIQUID, N.O.S. (n-butyl acetate, 1-methoxy-2-propanol) | FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol) | FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol) |
| 14.3 Transport hazard class(es) | 3  | 3  | 3   | 3  |
| 14.4 Packing group | III | III | III | III |
| 14.5 Environmental hazards | No. | Yes. | Yes. | Yes. The environmentally hazardous substance mark is not required. |

Additional information

ADR/RID : **Tunnel code** (D/E)

ADN : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.

SECTION 14: Transport information

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Product/ingredient name | % | Designation [Usage] |
|-------------------------|------|---------------------|
| NICOSIT 1340-11 | ≥90 | 3 |
| Formaldehyde | <0.1 | 72 |

Labelling :

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

| Category |
|----------|
| P5c |

National regulations

SECTION 15: Regulatory information

| Product/ingredient name | List name | Name on list | Classification | Notes |
|-------------------------|--|------------------------|----------------|-------|
| Formaldehyde | UK Occupational Exposure Limits EH40 - WEL | formaldehyde; methanal | Carc. | - |

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|---|---|
| Flam. Liq. 3, H226 Eye Dam. 1, H318 STOT SE 3, H336 | On basis of test data Calculation method Calculation method |

Full text of abbreviated H statements

| | |
|------|--|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H311 | Toxic in contact with skin. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation. |

Date of issue/Date of revision

: 10/05/2024

Date of previous issue

: No previous validation

Version : 1

18/20

NICOSIT 1340-11

Label No :51776

SECTION 16: Other information

| | |
|--------|--|
| H336 | May cause drowsiness or dizziness. |
| H341 | Suspected of causing genetic defects. |
| H350 | May cause cancer. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H413 | May cause long lasting harmful effects to aquatic life. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| EUH071 | Corrosive to the respiratory tract. |

[Full text of classifications \[CLP/GHS\]](#)

| | |
|-------------------|---|
| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Aquatic Chronic 4 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4 |
| Asp. Tox. 1 | ASPIRATION HAZARD - Category 1 |
| Carc. 1B | CARCINOGENICITY - Category 1B |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| Eye Irrit. 2 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 |
| Flam. Liq. 2 | FLAMMABLE LIQUIDS - Category 2 |
| Flam. Liq. 3 | FLAMMABLE LIQUIDS - Category 3 |
| Muta. 2 | GERM CELL MUTAGENICITY - Category 2 |
| Resp. Sens. 1 | RESPIRATORY SENSITISATION - Category 1 |
| Skin Corr. 1B | SKIN CORROSION/IRRITATION - Category 1B |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITISATION - Category 1 |
| Skin Sens. 1A | SKIN SENSITISATION - Category 1A |
| STOT RE 1 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |
| STOT RE 2 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |
| STOT SE 3 | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |

Date of issue/ Date of revision : 10/05/2024

Date of previous issue : No previous validation

Version : 1

NICOSIT 1340-11

All variants

[Notice to reader](#)

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

