

SAFETY DATA SHEET



NORDICA EKO 3894-22 - TST 101308 CHESTNUT

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : NORDICA EKO 3894-22 - TST 101308 CHESTNUT

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

National contact

Teknos (UK) Limited, 7 Longlands Rd, Bicester, Oxfordshire OX26 5AH, United Kingdom. Tel. +44 (0) 1869 208005.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Skin Sens. 1, H317

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 - May cause an allergic skin reaction.

Precautionary statements

Prevention : P280 - Wear protective gloves.
P261 - Avoid breathing vapour.

Response : P362 + P364 - Take off contaminated clothing and wash it before reuse.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : Contains biocidal products for dry film and in-can preservation: IPBC and BIT and Bronopol and MIT and OIT and C(M)IT/MIT (3:1) and DTBMA and MBIT. Risk of skin sensitisation.

Date of issue/Date of revision : 27/11/2023 **Date of previous issue** : 07/06/2023

Version : 1.02 1/20

NORDICA EKO 3894-22 - TST 101308 CHESTNUT

Label No : 51038

SECTION 2: Hazards identification

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	<1	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
EO bis(benztriazolyl) phenylpropionat	REACH #: 01-0000015075-76 EC: 400-830-7 CAS: 104810-48-2 Index: 607-176-00-3	<1	Skin Sens. 1A, H317 Aquatic Chronic 2, H411	[1]
Propylene glycol	REACH #: 01-2119456809-23 EC: 200-338-0 CAS: 57-55-6	≤0.3	Not classified.	[2]
2,4,7,9-tetramethyl-5-decyne-4,7-diol	REACH #: 01-2119954390-39 EC: 204-809-1 CAS: 126-86-3	≤0.3	Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	[1]
Ethanediol	REACH #: 01-2119456816-28 EC: 203-473-3 CAS: 107-21-1 Index: 603-027-00-1	≤0.3	Acute Tox. 4, H302 STOT RE 2, H373 (oral)	[1] [2]
Dipropyleneglycolmethylether	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤0.3	Not classified.	[2]
Diethylene glycol	REACH #: 01-2119457857-21 EC: 203-872-2 CAS: 111-46-6	≤0.3	Acute Tox. 4, H302	[1] [2]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]
1-Methoxy 2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1	≤0.1	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]

Date of issue/Date of revision : 27/11/2023 **Date of previous issue** : 07/06/2023

Version : 1.02 2/20

NORDICA EKO 3894-22 - TST 101308 CHESTNUT

Label No : 51038

SECTION 3: Composition/information on ingredients

Ammonia	CAS: 107-98-2 Index: 603-064-00-3 REACH #: 01-2119488876-14 EC: 215-647-6	<0.1	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1] [2]
Bronopol	CAS: 1336-21-6 Index: 007-001-01-2 EC: 200-143-0 CAS: 52-51-7 Index: 603-085-00-8	≤0.1	Aquatic Acute 1, H400 (M=1) Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=10)	[1]
2-Ethoxyethanol	EC: 203-804-1 CAS: 110-80-5 Index: 603-012-00-X	<0.1	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 3, H331 Repr. 1B, H360FD	[1] [2]
2-methyl-2H-isothiazol-3-one	EC: 220-239-6 CAS: 2682-20-4	<0.01	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1) EUH071	[1]
2-Octyl-2H-isothiazol-3-one	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.0025	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071 See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

SECTION 4: First aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

5.3 Advice for firefighters

SECTION 5: Firefighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

SECTION 7: Handling and storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

<input checked="" type="checkbox"/> Butoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. STEL: 246 mg/m ³ 15 minutes. TWA: 123 mg/m ³ 8 hours.
Propylene glycol	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 mg/m ³ 8 hours. Form: Particulate TWA: 474 mg/m ³ 8 hours. Form: total vapour and particulates TWA: 150 ppm 8 hours. Form: total vapour and particulates
Ethanediol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. TWA: 10 mg/m ³ 8 hours. Form: Particulate TWA: 20 ppm 8 hours. Form: Vapour STEL: 40 ppm 15 minutes. Form: Vapour TWA: 52 mg/m ³ 8 hours. Form: Vapour STEL: 104 mg/m ³ 15 minutes. Form: Vapour
Dipropyleneglycolmethylether	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. TWA: 308 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
Diethylene glycol	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 101 mg/m ³ 8 hours. TWA: 23 ppm 8 hours.
1-Methoxy 2-propanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 560 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m ³ 8 hours. TWA: 100 ppm 8 hours.
Ammonia	EH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia anhydrous] STEL: 25 mg/m ³ 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m ³ 8 hours. Form: anhydrous
2-Ethoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. TWA: 2 ppm 8 hours. TWA: 8 mg/m ³ 8 hours.

Biological exposure indices

Product/ingredient name	Exposure indices
<input checked="" type="checkbox"/> Butoxyethanol	EH40/2005 BMGVs (United Kingdom (UK), 8/2018) BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
2-Butoxyethanol	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	59 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	98 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	147 mg/m ³	General population	Local
	DNEL	Short term Inhalation	246 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	426 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	1091 mg/m ³	Workers	Systemic
Propylene glycol	DNEL	Long term Inhalation	10 mg/m ³	General population	Local
	DNEL	Long term Inhalation	10 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	50 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	168 mg/m ³	Workers	Systemic
2,4,7,9-tetramethyl-5-decyne-4,7-diol	DNEL	Long term Oral	0.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.43 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	0.5 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	0.75 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.75 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	1.29 mg/m ³	General population	Systemic
	DNEL	Short term Dermal	1.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.76 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	5.28 mg/m ³	Workers	Systemic
Ethanediol	DNEL	Long term Inhalation	7 mg/m ³	General population	Local
	DNEL	Long term Inhalation	35 mg/m ³	Workers	Local
	DNEL	Long term Dermal	53 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	106 mg/kg bw/day	Workers	Systemic
Dipropylenglycolmethylether	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	37.2 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	121 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	283 mg/kg bw/day	Workers	Systemic

SECTION 8: Exposure controls/personal protection

Diethylene glycol	DNEL	Long term Inhalation	308 mg/m ³	Workers	Systemic	
	DNEL	Long term Dermal	21 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	43 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	44 mg/m ³	Workers	Systemic	
	DNEL	Long term Inhalation	12 mg/m ³	General population	Local	
	DNEL	Long term Inhalation	12 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	60 mg/m ³	Workers	Local	
	3-iodo-2-propynyl-butyl carbamate	DNEL	Long term Inhalation	0.023 mg/m ³	Workers	Systemic
		DNEL	Short term Inhalation	0.07 mg/m ³	Workers	Systemic
DNEL		Short term Inhalation	1.16 mg/m ³	Workers	Local	
DNEL		Long term Inhalation	1.16 mg/m ³	Workers	Local	
DNEL		Long term Dermal	2 mg/kg bw/day	Workers	Systemic	
1-Methoxy 2-propanol		DNEL	Long term Oral	33 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	43.9 mg/m ³	General population	Systemic
		DNEL	Long term Dermal	78 mg/kg bw/day	General population	Systemic
		DNEL	Long term Dermal	183 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	369 mg/m ³	Workers	Systemic	
	DNEL	Short term Inhalation	553.5 mg/m ³	Workers	Local	
	DNEL	Short term Inhalation	553.5 mg/m ³	Workers	Systemic	
	Bronopol	DNEL	Short term Dermal	4 µg/cm ²	General population	Local
		DNEL	Long term Dermal	4 µg/cm ²	General population	Local
DNEL		Short term Dermal	8 µg/cm ²	Workers	Local	
DNEL		Long term Dermal	8 µg/cm ²	Workers	Local	
DNEL		Long term Oral	0.18 mg/kg bw/day	General population	Systemic	
DNEL		Short term Oral	0.5 mg/kg bw/day	General population	Systemic	
DNEL		Short term Inhalation	0.6 mg/m ³	General population	Local	
DNEL		Long term Inhalation	0.6 mg/m ³	General population	Systemic	
DNEL		Long term Dermal	0.7 mg/kg bw/day	General population	Systemic	
DNEL		Short term Inhalation	1.8 mg/m ³	General population	Systemic	
DNEL		Long term Dermal	2 mg/kg bw/day	Workers	Systemic	
DNEL		Short term Dermal	2.1 mg/kg bw/day	General population	Systemic	
DNEL		Short term Inhalation	2.5 mg/m ³	Workers	Local	
DNEL		Long term Inhalation	2.5 mg/m ³	Workers	Local	
DNEL		Long term Inhalation	3.5 mg/m ³	Workers	Systemic	

SECTION 8: Exposure controls/personal protection

2-Ethoxyethanol	DNEL	Short term Dermal	6 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	10.5 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	83 µg/m ³	Workers	Systemic
	DNEL	Long term Dermal	0.3 mg/kg bw/day	Workers	Systemic
2-methyl-2H-isothiazol-3-one	DNEL	Long term Inhalation	0.021 mg/m ³	General population	Local
	DNEL	Long term Inhalation	0.021 mg/m ³	Workers	Local
	DNEL	Long term Oral	0.027 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.043 mg/m ³	General population	Local
	DNEL	Short term Inhalation	0.043 mg/m ³	Workers	Local
	DNEL	Short term Oral	0.053 mg/kg bw/day	General population	Systemic

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Not recommended polyvinyl alcohol (PVA) gloves

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

SECTION 8: Exposure controls/personal protection

Filter type (spray application): A P

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Colour : Brown.
Odour : Slight
Odour threshold : Not available.
Melting point/freezing point : Not available.
Initial boiling point and boiling range :

Ingredient name	°C	°F	Method
Water	100	212	
Ethyldiglycol	196	384.8	

Flammability (solid, gas) : Not available.
Upper/lower flammability or explosive limits : Lower: Not applicable.
Upper: Not applicable.
Flash point : Closed cup: >100°C (>212°F)
Auto-ignition temperature :

Ingredient name	°C	°F	Method
Ethyldiglycol	204	399.2	

Decomposition temperature : Not available.
pH : Not applicable.
Viscosity : Not available.
Solubility(ies) :
Not available.

Solubility in water : Not available.
Partition coefficient: n-octanol/ water : Not applicable.

Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	17.5	2.3				
Ethyldiglycol	0.14	0.019				

Relative density : Not available.
Density : 1 g/cm³
Vapour density : Not available.
Explosive properties : Not available.
Oxidising properties : Not available.
Particle characteristics
Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propylene glycol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
Ethanediol	LD50 Oral	Rat	4700 mg/kg	-
Diethylene glycol	LD50 Dermal	Rabbit	11890 mg/kg	-
	LD50 Oral	Rat	12000 mg/kg	-
3-iodo-2-propynyl-butyl carbamate	LC50 Inhalation Dusts and mists	Rat	0.67 g/m ³	4 hours
	LC50 Inhalation Dusts and mists	Rat	0.763 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
1-Methoxy 2-propanol	LD50 Oral	Rat	400 mg/kg	-
	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	6600 mg/kg	-
Ammonia	LD50 Oral	Rat	350 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>0.588 mg/l	4 hours
2-Ethoxyethanol	LD50 Dermal	Rat	4750 mg/kg	-
	LD50 Oral	Rat	307 mg/kg	-
	LD50 Dermal	Rabbit	3.6 g/kg	-
2-methyl-2H-isothiazol-3-one	LD50 Dermal	Rat	3900 mg/kg	-
	LD50 Oral	Rat	2125 mg/kg	-
2-Octyl-2H-isothiazol-3-one	LC50 Inhalation Dusts and mists	Rat	0.11 mg/l	4 hours
	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Route	ATE value
Not available.	

Irritation/Corrosion

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
Propylene glycol	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Human	-	168 hours 500 mg	-
	Skin - Mild irritant	Woman	-	96 hours 30 %	-
	Skin - Moderate irritant	Child	-	96 hours 30 % C	-
2,4,7,9-tetramethyl-5-decyne-4,7-diol	Skin - Moderate irritant	Human	-	72 hours 104 mg l	-
	Eyes - Severe irritant	Rabbit	-	0.1 MI	-
Ethanediol	Skin - Mild irritant	Rabbit	-	0.5 g	-
	Eyes - Mild irritant	Rabbit	-	1 hours 100 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Moderate irritant	Rabbit	-	6 hours 1440 mg	-
Dipropyleneglycolmethylether	Skin - Mild irritant	Rabbit	-	555 mg	-
	Eyes - Mild irritant	Human	-	8 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
Diethylene glycol	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Mild irritant	Rabbit	-	50 mg	-
	Skin - Mild irritant	Human	-	72 hours 112 mg l	-
3-iodo-2-propynyl-butyl carbamate	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Severe irritant	Rabbit	-	-	-
1-Methoxy 2-propanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
Ammonia	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Severe irritant	Rabbit	-	0.5 minutes 1 mg	-
Bronopol	Eyes - Severe irritant	Rabbit	-	250 ug	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
2-Ethoxyethanol	Skin - Moderate irritant	Human	-	10 mg	-
	Skin - Moderate irritant	Rabbit	-	80 mg	-
	Eyes - Mild irritant	Guinea pig	-	10 ug	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Moderate irritant	Rabbit	-	50 mg	-
2-Octyl-2H-isothiazol-3-one	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
3-iodo-2-propynyl-butyl carbamate	skin	Guinea pig	Not sensitizing

Conclusion/Summary : May cause an allergic skin reaction.

Mutagenicity

SECTION 11: Toxicological information

Product/ingredient name	Test	Experiment	Result
3-iodo-2-propynyl-butyl carbamate	-	Experiment: In vitro Subject: Bacteria	Negative

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
3-iodo-2-propynyl-butyl carbamate	Negative	-	Negative	Rabbit - Female	Oral: 20 mg/kg	13 days; 7 days per week
	Positive	-	Negative	Rabbit - Female	Oral: 50 mg/kg	13 days; 7 days per week

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl-butyl carbamate	Negative - Oral	Rabbit - Female	50 mg/kg	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1-Methoxy 2-propanol	Category 3	-	Narcotic effects
Ammonia	Category 3	-	Respiratory tract irritation
Bronopol	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Ethanediol	Category 2	oral	-
3-iodo-2-propynyl-butyl carbamate	Category 1	-	larynx

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
irritation
redness
Ingestion : No specific data.

Date of issue/Date of revision : 27/11/2023 **Date of previous issue** : 07/06/2023 **Version** : 1.02 13/20

NORDICA EKO 3894-22 - TST 101308 CHESTNUT

Label No : 51038

SECTION 11: Toxicological information

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-Butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	48 hours
	Acute LC50 800000 µg/l Marine water	Crustaceans - Common shrimp, sand shrimp - <i>Crangon crangon</i>	48 hours
	Acute LC50 1250000 µg/l Marine water	Fish - Inland silverside - <i>Menidia beryllina</i>	96 hours
Propylene glycol	Acute EC50 19300 mg/l Fresh water	Algae - Algae	96 hours
	Acute EC50 43500 mg/l Fresh water	Daphnia - Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 18340000 µg/l Fresh water	Crustaceans - Water flea - <i>Ceriodaphnia dubia</i>	48 hours
2,4,7,9-tetramethyl-5-decyne-4,7-diol	Acute LC50 40613 mg/l Fresh water	Fish - Trout - <i>Oncorhynchus mykiss</i>	96 hours
	EC50 91 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours
Ethanediol	LC50 42 mg/l	Fish - <i>Cyprinus carpio</i>	96 hours
	Acute LC50 6900000 µg/l Fresh water	Crustaceans - Water flea - <i>Ceriodaphnia dubia</i> - Neonate	48 hours
	Acute LC50 41000000 µg/l Fresh water	Daphnia - Water flea - <i>Daphnia magna</i> - Neonate	48 hours
Diethylene glycol	Acute LC50 8050000 µg/l Fresh water	Fish - Fathead minnow - <i>Pimephales promelas</i>	96 hours
	Acute LC50 75200000 µg/l Fresh water	Fish - Fathead minnow - <i>Pimephales promelas</i>	96 hours
3-iodo-2-propynyl-butyl carbamate	Acute EC50 0.022 mg/l Fresh water	Algae - Algae - <i>Scenedemus subspicatus</i>	72 hours
	Acute EC50 0.16 mg/l Fresh water	Daphnia - Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 0.067 mg/l Fresh water	Fish - Trout - <i>Oncorhynchus mykiss</i>	96 hours
	Acute NOEC 0.049 mg/l Fresh water	Fish - Trout - <i>Oncorhynchus mykiss</i>	96 hours
	Chronic NOEC 0.05 mg/l Fresh water	Daphnia - Daphnia - <i>Daphnia Magna</i>	21 days

Date of issue/Date of revision : 27/11/2023 Date of previous issue : 07/06/2023 Version : 1.02 14/20

NORDICA EKO 3894-22 - TST 101308 CHESTNUT

Label No : 51038

SECTION 12: Ecological information

Ammonia	Acute LC50 37 ppm Fresh water	Fish - Western mosquitofish - <i>Gambusia affinis</i> - Adult	96 hours
Bronopol	Acute EC50 0.4 mg/l	Algae	72 hours
	Acute EC50 0.02 ppm Fresh water	Algae - Green algae - <i>Scenedesmus subspicatus</i>	96 hours
	Acute EC50 1.4 mg/l	Daphnia	48 hours
	Acute LC50 41.2 mg/l	Fish	96 hours
	Acute LC50 11.17 ppm Fresh water	Fish - Bluegill - <i>Lepomis macrochirus</i>	96 hours
2-Ethoxyethanol	Chronic NOEC 1.94 ppm	Fish - Rainbow trout, donaldson trout - <i>Oncorhynchus mykiss</i>	49 days
	Acute LC50 >10000000 µg/l Fresh water	Fish - Bluegill - <i>Lepomis macrochirus</i>	96 hours
2-methyl-2H-isothiazol-3-one	Acute EC50 0.18 ppm Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	48 hours
2-Octyl-2H-isothiazol-3-one	Acute LC50 0.07 ppm Fresh water	Fish - Rainbow trout, donaldson trout - <i>Oncorhynchus mykiss</i>	96 hours
	Acute EC50 107 ppb Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	48 hours
	Acute LC50 47 ppb Fresh water	Fish - Rainbow trout, donaldson trout - <i>Oncorhynchus mykiss</i>	96 hours
	Chronic NOEC 74 ppb Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	21 days
	Chronic NOEC 8.5 ppb	Fish - Fathead minnow - <i>Pimephales promelas</i>	35 days

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Conclusion/Summary : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Propylene glycol	-	-	Readily
3-iodo-2-propynyl-butyl carbamate	-	-	Not readily
Bronopol	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-Butoxyethanol	0.81	-	Low
Propylene glycol	-1.07	-	Low
Ethanediol	-1.36	-	Low
Dipropyleneglycolmethylether	0.004	-	Low
Diethylene glycol	-1.98	100	Low
3-iodo-2-propynyl-butyl carbamate	>1	-	Low
1-Methoxy 2-propanol	<1	-	Low
Bronopol	0.18	-	Low
2-Ethoxyethanol	-0.32	-	Low
2-Octyl-2H-isothiazol-3-one	2.45	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 12: Ecological information

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC) : 080112

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

SECTION 15: Regulatory information

Substances of very high concern

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
Toxic to reproduction	2-ethoxyethanol	Candidate	-	12/15/2010

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

No listed substance

Seveso Directive

This product is not controlled under the Seveso Directive.

EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = GB CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic

Date of issue/Date of revision : 27/11/2023 **Date of previous issue** : 07/06/2023

Version : 1.02 17/20

NORDICA EKO 3894-22 - TST 101308 CHESTNUT

Label No : 51038

SECTION 16: Other information

PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Skin Sens. 1, H317	Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 27/11/2023

Date of previous issue : 07/06/2023

Version : 1.02

NORDICA EKO 3894-22_TST 101308 CHESTNUT TST 101308 CHESTNUT

Notice to reader

Date of issue/Date of revision : 27/11/2023 **Date of previous issue** : 07/06/2023 **Version** : 1.02 18/20

NORDICA EKO 3894-22 - TST 101308 CHESTNUT

Label No : 51038

SECTION 16: Other information

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

