

# SAFETY DATA SHEET



PENTOL UV PROTECT PLUS 0783-30 - All variants

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : PENTOL UV PROTECT PLUS 0783-30 - All variants

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : In an emergency, call 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

☒ Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Signal word** : ☒ No signal word.

**Hazard statements** : ☒ H412 - Harmful to aquatic life with long lasting effects.

#### Precautionary statements

**Prevention** : ☒ P273 - Avoid release to the environment.

**Response** : ☒ Not applicable.

**Storage** : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label elements** : ☒ Contains Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene), adipohydrazide, bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, 3-iodo-2-propynyl-butyl carbamate, 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1). May produce an allergic reaction.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

## SECTION 2: Hazards identification

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

| Product/ingredient name                                                                                                                                                                                                                                                                         | Identifiers                                                                            | %      | Classification                                                                                                                                                     | Specific Conc. Limits, M-factors and ATEs                                                                     | Type    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|---------|
| Zinc oxide                                                                                                                                                                                                                                                                                      | REACH #:<br>01-2119463881-32<br>EC: 215-222-5<br>CAS: 1314-13-2<br>Index: 030-013-00-7 | ≤1.8   | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                                                                   | M [Acute] = 1<br>M [Chronic] = 1                                                                              | [1]     |
| 2-Butoxyethanol                                                                                                                                                                                                                                                                                 | REACH #:<br>01-2119475108-36<br>EC: 203-905-0<br>CAS: 111-76-2<br>Index: 603-014-00-0  | ≤3     | Acute Tox. 4, H302<br>Acute Tox. 3, H331<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319                                                                              | ATE [Oral] = 1200 mg/kg<br>ATE [Inhalation (vapours)] = 3 mg/l                                                | [1] [2] |
| Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly(oxyethylene) | EC: 400-830-7<br>Index: 607-176-00-3                                                   | <1     | Skin Sens. 1, H317<br>Aquatic Chronic 2, H411                                                                                                                      | -                                                                                                             | [1]     |
| adipohydrazide                                                                                                                                                                                                                                                                                  | REACH #:<br>01-2119962900-36<br>EC: 213-999-5<br>CAS: 1071-93-8                        | <1     | Skin Sens. 1, H317<br>Aquatic Chronic 2, H411                                                                                                                      | -                                                                                                             | [1]     |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate                                                                                                                                                                                                                                                 | REACH #:<br>01-2119491304-40<br>EC: 255-437-1<br>CAS: 41556-26-7                       | ≤0.43  | Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                                                                             | M [Acute] = 1<br>M [Chronic] = 1                                                                              | [1]     |
| 3-iodo-2-propynyl-butyl carbamate                                                                                                                                                                                                                                                               | EC: 259-627-5<br>CAS: 55406-53-6<br>Index: 616-212-00-7                                | ≤0.2   | Acute Tox. 4, H302<br>Acute Tox. 3, H331<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>STOT RE 1, H372 (larynx)<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 | ATE [Oral] = 400 mg/kg<br>ATE [Inhalation (dusts and mists)] = 0.67 mg/l<br>M [Acute] = 10<br>M [Chronic] = 1 | [1]     |
| 1,2-benzisothiazol-3(2H)-one                                                                                                                                                                                                                                                                    | EC: 220-120-9<br>CAS: 2634-33-5<br>Index: 613-088-00-6                                 | <0.036 | Acute Tox. 4, H302<br>Acute Tox. 2, H330<br>Skin Irrit. 2, H315                                                                                                    | ATE [Oral] = 450 mg/kg<br>ATE [Inhalation                                                                     | [1]     |

## SECTION 3: Composition/information on ingredients

|                                                                                                                                              |                                                                  |                  |                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                              |            |
|----------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <p>reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)</p> | <p>EC: 911-418-6<br/>CAS: 55965-84-9<br/>Index: 613-167-00-5</p> | <p>&lt;0.001</p> | <p>Eye Dam. 1, H318<br/>Skin Sens. 1A, H317<br/>Aquatic Acute 1, H400<br/>Aquatic Chronic 1, H410</p> <p>Acute Tox. 3, H301<br/>Acute Tox. 2, H310<br/>Acute Tox. 2, H330<br/>Skin Corr. 1C, H314<br/>Eye Dam. 1, H318<br/>Skin Sens. 1A, H317<br/>Aquatic Acute 1, H400<br/>Aquatic Chronic 1, H410<br/>EUH071</p> <p><b>See Section 16 for the full text of the H statements declared above.</b></p> | <p>(dusts and mists)] = 0.21 mg/l<br/>Skin Sens. 1, H317: C ≥ 0.036%<br/>M [Acute] = 1<br/>M [Chronic] = 1</p> <p>ATE [Oral] = 53 mg/kg<br/>ATE [Dermal] = 50 mg/kg<br/>ATE [Inhalation (vapours)] = 0.5 mg/l<br/>Skin Corr. 1C, H314: C ≥ 0.6%<br/>Eye Dam. 1, H318: C ≥ 0.6%<br/>Eye Irrit. 2, H319: 0.06% ≤ C &lt; 0.6%<br/>Skin Sens. 1, H317: C ≥ 0.0015%<br/>M [Acute] = 100<br/>M [Chronic] = 100</p> | <p>[1]</p> |
|----------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## SECTION 4: First aid measures

**Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** :  No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

SECTION 6: Accidental release measures

6.4 Reference to other sections : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations : Not available.
- Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name                                                                                                               | Exposure limit values                                                                                                                                                                                                       |
|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2-Butoxyethanol                                                                                                                       | Regulation on Limit Values - MAC (Austria, 12/2024) Absorbed through skin.<br>TWA 8 hours: 20 ppm.<br>TWA 8 hours: 98 mg/m³.<br>PEAK 30 minutes: 40 ppm 4 times per shift.<br>PEAK 30 minutes: 200 mg/m³ 4 times per shift. |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | Regulation on Limit Values - MAC (Austria, 12/2024) [5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on (Gemisch im Verhältnis 3:1)] Skin sensitiser.<br>TWA 8 hours: 0.05 mg/m³.          |
| 2-Butoxyethanol                                                                                                                       | Limit values (Belgium, 12/2023) Absorbed through skin.<br>TWA 8 hours: 20 ppm.<br>TWA 8 hours: 98 mg/m³.<br>STEL 15 minutes: 50 ppm.<br>STEL 15 minutes: 246 mg/m³.                                                         |

## SECTION 8: Exposure controls/personal protection

|                  |                                                                                                                                                                                                                                                                                                                                                             |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2-Butoxyethanol  | <p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024)</b> Absorbed through skin.</p> <p>Limit value 8 hours: 98 mg/m<sup>3</sup>.<br/> Limit value 15 minutes: 246 mg/m<sup>3</sup>.<br/> Limit value 15 minutes: 50 ppm.<br/> Limit value 8 hours: 20 ppm.</p>                                  |
| Propylene glycol | <p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023)</b></p> <p>ELV 8 hours: 10 mg/m<sup>3</sup>. Form: only particles.<br/> ELV 8 hours: 474 mg/m<sup>3</sup>. Form: total vapour and particles.<br/> ELV 8 hours: 150 ppm. Form: total vapour and particles.</p> |
| 2-Butoxyethanol  | <p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023)</b> Absorbed through skin.</p> <p>STELV 15 minutes: 246 mg/m<sup>3</sup>.<br/> STELV 15 minutes: 50 ppm.<br/> ELV 8 hours: 98 mg/m<sup>3</sup>.<br/> ELV 8 hours: 20 ppm.</p>                                 |
| 2-Butoxyethanol  | <p><b>Department of labour inspection (Cyprus, 7/2021)</b> Absorbed through skin.</p> <p>STEL 15 minutes: 50 ppm.<br/> STEL 15 minutes: 246 mg/m<sup>3</sup>.<br/> TWA 8 hours: 20 ppm.<br/> TWA 8 hours: 98 mg/m<sup>3</sup>.</p>                                                                                                                          |
| 2-Butoxyethanol  | <p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023)</b> Absorbed through skin.</p> <p>TWA 8 hours: 98 mg/m<sup>3</sup>.<br/> TWA 8 hours: 20 ppm.<br/> STEL 15 minutes: 200 mg/m<sup>3</sup>.<br/> STEL 15 minutes: 40.7 ppm.</p>                                                                                             |
| 2-Butoxyethanol  | <p><b>Working Environment Authority (Denmark, 12/2024)</b> Absorbed through skin.</p> <p>TWA 8 hours: 20 ppm.<br/> TWA 8 hours: 98 mg/m<sup>3</sup>.<br/> STEL 15 minutes: 246 mg/m<sup>3</sup>.<br/> STEL 15 minutes: 50 ppm.</p>                                                                                                                          |
| 2-Butoxyethanol  | <p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024)</b> Absorbed through skin , Sensitiser.</p> <p>TWA 8 hours: 98 mg/m<sup>3</sup>.<br/> TWA 8 hours: 20 ppm.<br/> STEL 15 minutes: 246 mg/m<sup>3</sup>.<br/> STEL 15 minutes: 50 ppm.</p>                                                                                           |
| 2-Butoxyethanol  | <p><b>EU OEL (Europe, 1/2022)</b> Absorbed through skin.</p> <p>TWA 8 hours: 20 ppm.<br/> TWA 8 hours: 98 mg/m<sup>3</sup>.<br/> STEL 15 minutes: 50 ppm.<br/> STEL 15 minutes: 246 mg/m<sup>3</sup>.</p>                                                                                                                                                   |
| 2-Butoxyethanol  | <p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021)</b> Absorbed through skin.</p> <p>TWA 8 hours: 20 ppm.<br/> TWA 8 hours: 98 mg/m<sup>3</sup>.<br/> STEL 15 minutes: 50 ppm.<br/> STEL 15 minutes: 250 mg/m<sup>3</sup>.</p>                                                                                           |

## SECTION 8: Exposure controls/personal protection

|                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2-Butoxyethanol                                                                                      | <p><b>Ministry of Labor (France, 6/2024)</b> Absorbed through skin.<br/>TWA 8 hours: 10 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)<br/>TWA 8 hours: 49 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)<br/>STEL 15 minutes: 246 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)<br/>STEL 15 minutes: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p> |
|  2-Butoxyethanol    | <p><b>TRGS 900 OEL (Germany, 6/2024)</b> Absorbed through skin.<br/>TWA 8 hours: 49 mg/m<sup>3</sup>.<br/>PEAK 15 minutes: 98 mg/m<sup>3</sup>.<br/>TWA 8 hours: 10 ppm.<br/>PEAK 15 minutes: 20 ppm.<br/><b>DFG MAC-values list (Germany, 7/2024)</b> Develop C. Absorbed through skin.<br/>TWA 8 hours: 10 ppm.<br/>PEAK 15 minutes: 20 ppm 4 times per shift [Interval: 1 hour].<br/>TWA 8 hours: 49 mg/m<sup>3</sup>.<br/>PEAK 15 minutes: 98 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].</p>                               |
| 3-iodo-2-propynyl-butyl carbamate                                                                    | <p><b>TRGS 900 OEL (Germany, 6/2024)</b> Skin sensitiser.<br/>PEAK 15 minutes: 0.116 mg/m<sup>3</sup>.<br/>PEAK 15 minutes: 0.01 ppm.<br/>TWA 8 hours: 0.058 mg/m<sup>3</sup>.<br/>TWA 8 hours: 0.005 ppm.<br/><b>DFG MAC-values list (Germany, 7/2024)</b> Develop C. Skin sensitiser.<br/>PEAK 15 minutes: 0.116 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].<br/>PEAK 15 minutes: 0.01 ppm 4 times per shift [Interval: 1 hour].<br/>TWA 8 hours: 0.058 mg/m<sup>3</sup>.<br/>TWA 8 hours: 0.005 ppm.</p>                     |
| 1,2-benzisothiazol-3(2H)-one                                                                         | <p><b>DFG MAC-values list (Germany, 7/2024)</b> Skin sensitiser.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|  2-Butoxyethanol  | <p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024)</b> Absorbed through skin.<br/>TWA 8 hours: 25 ppm.<br/>TWA 8 hours: 120 mg/m<sup>3</sup>.</p>                                                                                                                                                                                                                                                                                                                                                     |
|  2-Butoxyethanol  | <p><b>5/2020. (II. 6.) ITM Decree (Hungary, 1/2025)</b> Absorbed through skin.<br/>TWA 8 hours: 98 mg/m<sup>3</sup>.<br/>PEAK 15 minutes: 246 mg/m<sup>3</sup>.<br/>PEAK 15 minutes: 50 ppm.<br/>TWA 8 hours: 20 ppm.</p>                                                                                                                                                                                                                                                                                                                  |
|  2-Butoxyethanol  | <p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024)</b> Absorbed through skin.<br/>STEL 15 minutes: 246 mg/m<sup>3</sup>.<br/>STEL 15 minutes: 50 ppm.<br/>TWA 8 hours: 100 mg/m<sup>3</sup>.<br/>TWA 8 hours: 20 ppm.</p>                                                                                                                                                                                                                                                                                               |
|  Propylene glycol | <p><b>NAOSH (Ireland, 4/2024)</b> Notes: Advisory Occupational Exposure Limit Values (OELVs)<br/>OELV 8 hours: 10 mg/m<sup>3</sup>. Form: particulate.<br/>OELV 8 hours: 470 mg/m<sup>3</sup>. Form: vapour and particulates.<br/>OELV 8 hours: 150 ppm. Form: vapour and particulates.</p>                                                                                                                                                                                                                                                |
| Polyethylene wax                                                                                     | <p><b>NAOSH (Ireland, 4/2024)</b> Notes: Advisory Occupational Exposure Limit Values (OELVs)<br/>OELV 8 hours: 2 mg/m<sup>3</sup>. Form: fume.<br/>OELV 15 minutes: 6 mg/m<sup>3</sup>. Form: fume.</p>                                                                                                                                                                                                                                                                                                                                    |
| Zinc oxide                                                                                           | <p><b>NAOSH (Ireland, 4/2024)</b> Notes: Advisory Occupational Exposure Limit Values (OELVs)<br/>OELV 8 hours: 2 mg/m<sup>3</sup>. Form: respirable fraction.<br/>OELV 15 minutes: 10 mg/m<sup>3</sup>. Form: fume.</p>                                                                                                                                                                                                                                                                                                                    |

## SECTION 8: Exposure controls/personal protection

|                                                                                                      |                                                                                                                                                                                                                                                                                                                         |
|------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2-Butoxyethanol                                                                                      | <b>NAOSH (Ireland, 4/2024)</b> Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values<br>OELV 8 hours: 20 ppm.<br>OELV 8 hours: 98 mg/m <sup>3</sup> .<br>OELV 15 minutes: 50 ppm.<br>OELV 15 minutes: 246 mg/m <sup>3</sup> .                                                                     |
|  2-Butoxyethanol    | <b>Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024)</b><br>Absorbed through skin.<br>Limit value 8 hours: 20 ppm.<br>Limit value 8 hours: 98 mg/m <sup>3</sup> .<br>Short Term 15 minutes: 50 ppm.<br>Short Term 15 minutes: 246 mg/m <sup>3</sup> . |
| Propylene glycol                                                                                     | <b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)</b><br>TWA 8 hours: 7 mg/m <sup>3</sup> .                                                                                                                                                                                                                |
| 2-Butoxyethanol                                                                                      | <b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)</b><br>Absorbed through skin.<br>TWA 8 hours: 98 mg/m <sup>3</sup> .<br>TWA 8 hours: 20 ppm.<br>STEL 15 minutes: 50 ppm.<br>STEL 15 minutes: 246 mg/m <sup>3</sup> .                                                                                     |
|  Propylene glycol   | <b>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)</b><br>TWA 8 hours: 7 mg/m <sup>3</sup> .                                                                                                                                                                                                                      |
| Zinc oxide                                                                                           | <b>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)</b><br>TWA 8 hours: 5 mg/m <sup>3</sup> .                                                                                                                                                                                                                      |
| 2-Butoxyethanol                                                                                      | <b>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)</b><br>Absorbed through skin.<br>TWA 8 hours: 50 mg/m <sup>3</sup> .<br>TWA 8 hours: 10 ppm.<br>STEL 15 minutes: 100 mg/m <sup>3</sup> .<br>STEL 15 minutes: 20 ppm.                                                                                           |
| 2-Butoxyethanol                                                                                      | <b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021)</b> Absorbed through skin.<br>TWA 8 hours: 20 ppm.<br>TWA 8 hours: 98 mg/m <sup>3</sup> .<br>STEL 15 minutes: 50 ppm.<br>STEL 15 minutes: 246 mg/m <sup>3</sup> .                                                                         |
| 2-Butoxyethanol                                                                                      | <b>EU OEL (Europe, 1/2022)</b> Absorbed through skin.<br>TWA 8 hours: 20 ppm.<br>TWA 8 hours: 98 mg/m <sup>3</sup> .<br>STEL 15 minutes: 50 ppm.<br>STEL 15 minutes: 246 mg/m <sup>3</sup> .                                                                                                                            |
| 2-Butoxyethanol                                                                                      | <b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024)</b> Absorbed through skin.<br>TWA 8 hours: 100 mg/m <sup>3</sup> .<br>STEL 15 minutes: 246 mg/m <sup>3</sup> .<br>TWA 8 hours: 20.4 ppm.<br>STEL 15 minutes: 50 ppm.                                                             |
|  Propylene glycol | <b>FOR-2011-12-06-1358 (Norway, 5/2024)</b><br>TWA 8 hours: 79 mg/m <sup>3</sup> .<br>TWA 8 hours: 25 ppm.                                                                                                                                                                                                              |
| 2-Butoxyethanol                                                                                      | <b>FOR-2011-12-06-1358 (Norway, 5/2024)</b> Absorbed through skin.<br>TWA 8 hours: 10 ppm.<br>TWA 8 hours: 50 mg/m <sup>3</sup> .                                                                                                                                                                                       |

## SECTION 8: Exposure controls/personal protection

|                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Propylene glycol                                                                                                                      | Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024)<br>TWA 8 hours: 100 mg/m <sup>3</sup> . Form: vapor and inhalable fraction.                                                                                                                                                                   |
| 2-Butoxyethanol                                                                                                                       | Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) Absorbed through skin.<br>TWA 8 hours: 98 mg/m <sup>3</sup> .<br>STEL 15 minutes: 200 mg/m <sup>3</sup> .                                                                                                                                     |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) Absorbed through skin.<br>TWA 8 hours: 0.2 mg/m <sup>3</sup> .<br>STEL 15 minutes: 0.4 mg/m <sup>3</sup> .                                                                                                                                    |
| 2-Butoxyethanol                                                                                                                       | Portuguese Institute of Quality (Portugal, 11/2014) A3.<br>TWA 8 hours: 20 ppm.<br>Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) Absorbed through skin.<br>STEL 15 minutes: 50 ppm.<br>STEL 15 minutes: 246 mg/m <sup>3</sup> .<br>TWA 8 hours: 20 ppm.<br>TWA 8 hours: 98 mg/m <sup>3</sup> .                                                                                                                                                         |
| 2-Butoxyethanol                                                                                                                       | HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) Absorbed through skin.<br>VLA 8 hours: 98 mg/m <sup>3</sup> .<br>VLA 8 hours: 20 ppm.<br>Short term 15 minutes: 246 mg/m <sup>3</sup> .<br>Short term 15 minutes: 50 ppm.                                                                                                                                                                                                                                    |
| 2-Butoxyethanol                                                                                                                       | Government regulation SR c. 355/2006 (Slovakia, 6/2024) Absorbed through skin , Inhalation sensitiser.<br>TWA 8 hours: 98 mg/m <sup>3</sup> .<br>TWA 8 hours: 20 ppm.<br>STEL 15 minutes: 246 mg/m <sup>3</sup> .<br>STEL 15 minutes: 50 ppm.                                                                                                                                                                                                                                                     |
| 2-Butoxyethanol                                                                                                                       | Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) Absorbed through skin.<br>TWA 8 hours: 98 mg/m <sup>3</sup> .<br>TWA 8 hours: 20 ppm.<br>KTV 15 minutes: 246 mg/m <sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].<br>KTV 15 minutes: 50 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. |
| 3-iodo-2-propynyl-butyl carbamate                                                                                                     | Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) KTV 15 minutes: 0.01 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].<br>TWA 8 hours: 0.005 ppm.<br>KTV 15 minutes: 0.116 mg/m <sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].<br>TWA 8 hours: 0.058 mg/m <sup>3</sup> .                 |

## SECTION 8: Exposure controls/personal protection

|                                                                                                                                       |                                                                                                                                                                                                                                                                                                         |
|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2-Butoxyethanol                                                                                                                       | <b>National institute of occupational safety and health (Spain, 1/2024)</b> Absorbed through skin.<br>TWA 8 hours: 20 ppm.<br>TWA 8 hours: 98 mg/m <sup>3</sup> .<br>STEL 15 minutes: 245 mg/m <sup>3</sup> .<br>STEL 15 minutes: 50 ppm.                                                               |
|  Zinc oxide                                          | <b>Work environment authority Regulation 2018:1 (Sweden, 11/2022)</b><br>TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Total dust.                                                                                                                                                                           |
| 2-Butoxyethanol                                                                                                                       | <b>Work environment authority Regulation 2018:1 (Sweden, 11/2022)</b> Absorbed through skin.<br>TWA 8 hours: 10 ppm.<br>TWA 8 hours: 50 mg/m <sup>3</sup> .<br>STEL 15 minutes: 50 ppm.<br>STEL 15 minutes: 246 mg/m <sup>3</sup> .                                                                     |
|  2-Butoxyethanol                                     | <b>SUVA (Switzerland, 1/2025)</b> Absorbed through skin.<br>TWA 8 hours: 10 ppm.<br>TWA 8 hours: 49 mg/m <sup>3</sup> .<br>STEL 15 minutes: 20 ppm.<br>STEL 15 minutes: 98 mg/m <sup>3</sup> .                                                                                                          |
| 3-iodo-2-propynyl-butyl carbamate                                                                                                     | <b>SUVA (Switzerland, 1/2025)</b> Sensitiser.<br>STEL 15 minutes: 0.24 mg/m <sup>3</sup> . Form: vapour and aerosols.<br>STEL 15 minutes: 0.02 ppm. Form: vapour and aerosols.<br>TWA 8 hours: 0.01 ppm. Form: vapour and aerosols.<br>TWA 8 hours: 0.12 mg/m <sup>3</sup> . Form: vapour and aerosols. |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | <b>SUVA (Switzerland, 1/2025)</b> Sensitiser.<br>STEL 15 minutes: 0.4 mg/m <sup>3</sup> . Form: Inhalable fraction.<br>TWA 8 hours: 0.2 mg/m <sup>3</sup> . Form: Inhalable fraction.                                                                                                                   |
| 2-Butoxyethanol                                                                                                                       | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b> Absorbed through skin.<br>STEL 15 minutes: 50 ppm.<br>TWA 8 hours: 25 ppm.<br>STEL 15 minutes: 246 mg/m <sup>3</sup> .<br>TWA 8 hours: 123 mg/m <sup>3</sup> .                                                                                      |

### Biological exposure indices

| Product/ingredient name    | Exposure indices                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 2-Butoxyethanol            | <b>Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015)</b><br>Biological limit values: 0.17 mmol/mmol creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week.<br>Biological limit values: 200 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week. |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

## SECTION 8: Exposure controls/personal protection

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2-Butoxyethanol            | <p><b>Biological limit values (BLV) - Labour Code / ANSES (France, 4/2023) [2- butoxyéthanol et son acétate]</b><br/>BLV: 100 mg/g Cr, 2-butoxyacetic acid [in urine]. Sampling time: end of shift (regardless of the day of the week).</p> <p><b>DFG BEI-values list (Germany, 7/2024)</b> Notes: danger from percutaneous absorption (see p. 211 and p. 228).<br/>BEI: 150 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the shift, for long-term exposures after several previous shifts.</p> <p><b>TRGS 903 - BEI Values (Germany, 10/2024)</b><br/>BEI: 150 mg/g creatinine, butoxy acetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the shift, for long-term exposure after several previous shifts.</p> |
| 2-Butoxyethanol            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 2-Butoxyethanol            | <p><b>NAOSH BGVs (Ireland, 1/2011)</b><br/>BMGV: 200 mg/g creatinine, BAA [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 2-Butoxyethanol            | <p><b>Portuguese Institute of Quality (Portugal, 11/2014)</b><br/>BEI: 200 mg/g creatinine, butoxyacetic acid (BAA) [in urine]. Sampling time: end of shift.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 2-Butoxyethanol            | <p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)</b><br/>BAT: 150 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the work shift, at long-term exposure: at the end of the work shift after several consecutive workdays.</p>                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 2-Butoxyethanol            | <p><b>National institute of occupational safety and health (Spain, 1/2024)</b><br/>VLB: 200 mg/g creatinine, butoxyacetic acid [in urine]. Sampling time: end of shift.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| No exposure indices known. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 2-Butoxyethanol            | <p><b>SUVA (Switzerland, 1/2025)</b><br/>BEI: 150 mg/g creatinine, 2-butoxy acetic acid (after hydrolysis) [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| 2-Butoxyethanol            | <p><b>EH40/2005 BMGVs (United Kingdom (UK), 1/2020)</b><br/>BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## SECTION 8: Exposure controls/personal protection

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following:  
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

#### Product/ingredient name

-Butoxyethanol

#### Result

##### **DNEL - General population - Long term - Oral**

6.3 mg/kg bw/day

Effects: Systemic

##### **DNEL - General population - Short term - Oral**

26.7 mg/kg bw/day

Effects: Systemic

##### **DNEL - General population - Long term - Inhalation**

59 mg/m<sup>3</sup>

Effects: Systemic

##### **DNEL - Workers - Long term - Inhalation**

98 mg/m<sup>3</sup>

Effects: Systemic

##### **DNEL - General population - Short term - Inhalation**

147 mg/m<sup>3</sup>

Effects: Local

##### **DNEL - Workers - Short term - Inhalation**

246 mg/m<sup>3</sup>

Effects: Local

##### **DNEL - General population - Short term - Inhalation**

426 mg/m<sup>3</sup>

Effects: Systemic

##### **DNEL - Workers - Short term - Inhalation**

1091 mg/m<sup>3</sup>

Effects: Systemic

adipohydrazide

##### **DNEL - Workers - Long term - Inhalation**

17.5 mg/m<sup>3</sup>

Effects: Systemic

3-iodo-2-propynyl-butyl carbamate

##### **DNEL - Workers - Long term - Inhalation**

0.023 mg/m<sup>3</sup>

Effects: Systemic

##### **DNEL - Workers - Short term - Inhalation**

0.07 mg/m<sup>3</sup>

Effects: Systemic

##### **DNEL - Workers - Short term - Inhalation**

1.16 mg/m<sup>3</sup>

Effects: Local

##### **DNEL - Workers - Long term - Inhalation**

1.16 mg/m<sup>3</sup>

Effects: Local

## SECTION 8: Exposure controls/personal protection

1,2-benzisothiazol-3(2H)-one

### **DNEL - Workers - Long term - Dermal**

2 mg/kg bw/day

Effects: Systemic

### **DNEL - General population - Long term - Dermal**

0.345 mg/kg bw/day

Effects: Systemic

### **DNEL - Workers - Long term - Dermal**

0.966 mg/kg bw/day

Effects: Systemic

### **DNEL - General population - Long term - Inhalation**

1.2 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - Workers - Long term - Inhalation**

6.81 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - General population - Long term - Inhalation**

0.02 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Long term - Inhalation**

0.02 mg/m<sup>3</sup>

Effects: Local

### **DNEL - General population - Short term - Inhalation**

0.04 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Short term - Inhalation**

0.04 mg/m<sup>3</sup>

Effects: Local

### **DNEL - General population - Long term - Oral**

0.09 mg/kg bw/day

Effects: Systemic

### **DNEL - General population - Short term - Oral**

0.11 mg/kg bw/day

Effects: Systemic

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

### **PNECs**

Not available.

## **8.2 Exposure controls**

### **Appropriate engineering controls**

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### **Individual protection measures**

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## SECTION 8: Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Recommendations : Wear suitable gloves tested to EN374.
- > 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
- Not recommended polyvinyl alcohol (PVA) gloves
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

| Ingredient name | °C           | °F             | Method    |
|-----------------|--------------|----------------|-----------|
| Water           | 100          | 212            |           |
| 2-Butoxyethanol | 171 to 171.5 | 339.8 to 340.7 | IP 123-93 |

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: 2.6% (propane-1,2-diol)  
Upper: 12.6% (propane-1,2-diol)
- Flash point** : Closed cup: >100°C (>212°F)
- Auto-ignition temperature** :

## SECTION 9: Physical and chemical properties

| Ingredient name  | °C     | °F    | Method    |
|------------------|--------|-------|-----------|
| 2-Butoxyethanol  | 230    | 446   | DIN 51794 |
| Polyethylene wax | 244.85 | 472.7 |           |

**Decomposition temperature** : Not available.  
**pH** : 7.5 to 8.5 [Conc. (% w/w): 100%]  
**Viscosity** : Not available.  
**Solubility(ies)** :  
Not available.

**Solubility in water** : Not available.  
**Partition coefficient: n-octanol/ water** : Not applicable.  
**Vapour pressure** :

| Ingredient name | Vapour Pressure at 20°C |     |        | Vapour pressure at 50°C |     |        |
|-----------------|-------------------------|-----|--------|-------------------------|-----|--------|
|                 | mm Hg                   | kPa | Method | mm Hg                   | kPa | Method |
| Water           | 17.5                    | 2.3 |        |                         |     |        |
| 2-Butoxyethanol | 0.75006                 | 0.1 |        |                         |     |        |

**Relative density** : Not available.  
**Density** : 1 g/cm<sup>3</sup>  
**Vapour density** : Not available.  
**Particle characteristics**  
**Median particle size** : Not applicable.

### 9.2 Other information

#### 9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available.  
**Oxidising properties** : Not available.

#### 9.2.2 Other safety characteristics

Not applicable.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

**10.5 Incompatible materials** : No specific data.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product/ingredient name

3-iodo-2-propynyl-butyl carbamate

##### Result

###### Rat - Oral - LD50

400 mg/kg

###### Rat - Dermal - LD50

>2000 mg/kg

###### Rat - Inhalation - LC50 Dusts and mists

0.763 mg/l [4 hours]

###### Rat - Inhalation - LC50 Dusts and mists

0.67 g/m<sup>3</sup> [4 hours]

1,2-benzisothiazol-3(2H)-one

###### Rat - Oral - LD50

1020 mg/kg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

###### Rat - Oral - LD50

53 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

**Conclusion/Summary [Product]** : Not available.

#### Acute toxicity estimates

| Product/ingredient name                                                                                                               | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---------------------------------------------------------------------------------------------------------------------------------------|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| PENTOL UV PROTECT PLUS 0783-30                                                                                                        | 107142.9     | N/A            | N/A                      | 267.9                       | 446.7                               |
| 2-Butoxyethanol                                                                                                                       | 1200         | N/A            | N/A                      | 3                           | N/A                                 |
| 3-iodo-2-propynyl-butyl carbamate                                                                                                     | 400          | N/A            | N/A                      | N/A                         | 0.67                                |
| 1,2-benzisothiazol-3(2H)-one                                                                                                          | 450          | N/A            | N/A                      | N/A                         | 0.21                                |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | 53           | 50             | N/A                      | 0.5                         | N/A                                 |

#### Skin corrosion/irritation

##### Product/ingredient name

Zinc oxide

##### Result

###### Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

2-Butoxyethanol

###### Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

1,2-benzisothiazol-3(2H)-one

###### Human - Skin - Mild irritant

Duration of treatment/exposure: 48 hours

Amount/concentration applied: 5 %

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

###### Human - Skin - Severe irritant

Amount/concentration applied: 0.01 %

**Conclusion/Summary [Product]** : Not available.

#### Serious eye damage/eye irritation

**Date of issue/Date of revision**

: 29/01/2026

**Date of previous issue**

: 05/06/2025

**Version** : 1.02 16/28

PENTOL UV PROTECT PLUS 0783-30 - All variants

**Label No** : 36892

## SECTION 11: Toxicological information

### Product/ingredient name

Zinc oxide

### Result

#### Rabbit - Eyes - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

2-Butoxyethanol

#### Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

#### Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

3-iodo-2-propynyl-butyl carbamate

#### Rabbit - Eyes - Severe irritant

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

#### Product/ingredient name

3-iodo-2-propynyl-butyl carbamate

#### Result

##### Guinea pig - skin

Result: Not sensitizing

#### Skin

**Conclusion/Summary [Product]** : Not available.

#### Respiratory

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

#### Product/ingredient name

3-iodo-2-propynyl-butyl carbamate

#### Result

##### In vitro - Bacteria

Result: Negative

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

#### Product/ingredient name

3-iodo-2-propynyl-butyl carbamate

#### Result

##### Rabbit - Female - Oral

50 mg/kg [7 days per week] [13 days]

Maternal toxicity: Positive

Developmental: Negative

##### Rabbit - Female - Oral

20 mg/kg [7 days per week] [13 days]

Maternal toxicity: Negative

Developmental: Negative

**Conclusion/Summary [Product]** : Not available.

## SECTION 11: Toxicological information

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

#### **Product/ingredient name**

3-iodo-2-propynyl-butyl carbamate

#### **Result**

STOT RE 1, H372 (larynx)

### Aspiration hazard

Not available.

### Information on likely routes of exposure

Not available.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : ☒ No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.  
**Inhalation** : No specific data.  
**Skin contact** : ☒ No specific data.  
**Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

**General** : ☒ No known significant effects or critical hazards.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product/ingredient name

Zinc oxide

#### Result

##### Acute - LC50 - Fresh water

Daphnia - Water flea - *Daphnia magna* - Neonate

Age: <24 hours

98 µg/l [48 hours]

Effect: Mortality

##### Acute - IC50 - Fresh water

Algae - Green algae - *Pseudokirchneriella subcapitata* -

Exponential growth phase

46 µg/l [72 hours]

Effect: Population

##### Acute - LC50 - Fresh water

US EPA

Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss*

Weight: 0.78 g

1.1 ppm [96 hours]

Effect: Mortality

2-Butoxyethanol

##### Acute - LC50 - Marine water

Fish - Inland silverside - *Menidia beryllina*

Size: 40 to 100 mm

1250000 µg/l [96 hours]

Effect: Mortality

##### Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - *Crangon crangon*

800000 µg/l [48 hours]

Effect: Mortality

3-iodo-2-propynyl-butyl carbamate

##### Acute - LC50 - Fresh water

EU

Fish - Trout - *Oncorhynchus mykiss*

0.067 mg/l [96 hours]

##### Acute - NOEC - Fresh water

EU

Fish - Trout - *Oncorhynchus mykiss*

0.049 mg/l [96 hours]

##### Acute - EC50 - Fresh water

EU

Daphnia - Daphnia - *Daphnia magna*

0.16 mg/l [48 hours]

##### Chronic - NOEC - Fresh water

EU

Daphnia - Daphnia - *Daphnia Magna*

0.05 mg/l [21 days]

##### Acute - EC50 - Fresh water

EU

Algae - Algae - *Scenedemus subspicatus*

0.022 mg/l [72 hours]

1,2-benzisothiazol-3(2H)-one

##### Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test]

Fish - Trout - *Onorhynchus Mykiss*

1.9 mg/l [96 hours]

##### Acute - EC50

## SECTION 12: Ecological information

OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test]

Daphnia - Daphnia - *Daphnia Magna*

3.7 mg/l [48 hours]

### Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test]

Algae - Algae - *Skeletonema Costatum*

0.36 mg/l [72 hours]

### Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test]

Algae - Algae - *Skeletonema Costatum*

0.15 mg/l [72 hours]

**Conclusion/Summary [Product]** : Not available.

## 12.2 Persistence and degradability

### Product/ingredient name

2-benzisothiazol-3(2H)-one

### Result

EU

24% [28 days]

**Conclusion/Summary [Product]** : Not available.

| Product/ingredient name           | Aquatic half-life | Photolysis | Biodegradability |
|-----------------------------------|-------------------|------------|------------------|
| 3-iodo-2-propynyl-butyl carbamate | -                 | -          | Not readily      |
| 1,2-benzisothiazol-3(2H)-one      | -                 | -          | Inherent         |

## 12.3 Bioaccumulative potential

| Product/ingredient name           | LogP <sub>ow</sub> | BCF   | Potential |
|-----------------------------------|--------------------|-------|-----------|
| Zinc oxide                        | -                  | 28960 | High      |
| 2-Butoxyethanol                   | 0.81               | -     | Low       |
| 3-iodo-2-propynyl-butyl carbamate | >1                 | -     | Low       |
| 1,2-benzisothiazol-3(2H)-one      | -                  | 3.2   | Low       |

## 12.4 Mobility in soil

### Soil/water partition coefficient

| Product/ingredient name                         | logKoc | Koc     |
|-------------------------------------------------|--------|---------|
| 2-Butoxyethanol                                 | 1.8    | 67.3685 |
| adipohydrazide                                  | 1.7    | 55.2165 |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | 5      | 101050  |
| 3-iodo-2-propynyl-butyl carbamate               | 1.1    | 13.4558 |
| 1,2-benzisothiazol-3(2H)-one                    | 1.9    | 73.142  |

### Results of PMT and vPvM assessment

| Product/ingredient name                                                                                                                                                                 | PMT | P  | M  | T  | vPvM | vP | vM |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----|----|----|------|----|----|
| Zinc oxide                                                                                                                                                                              | No  | No | No | No | No   | No | No |
| 2-Butoxyethanol                                                                                                                                                                         | No  | No | No | No | No   | No | No |
| Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) | No  | No | No | No | No   | No | No |

Date of issue/Date of revision

: 29/01/2026

Date of previous issue

: 05/06/2025

Version : 1.02 20/28

PENTOL UV PROTECT PLUS 0783-30 - All variants

Label No : 36892

## SECTION 12: Ecological information

|                                                                                                                                       |    |    |    |    |    |    |    |
|---------------------------------------------------------------------------------------------------------------------------------------|----|----|----|----|----|----|----|
| propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly (oxyethylene)                              |    |    |    |    |    |    |    |
| adipohydrazide                                                                                                                        | No | No | No | No | No | No | No |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate                                                                                       | No | No | No | No | No | No | No |
| 3-iodo-2-propynyl-butyl carbamate                                                                                                     | No | No | No | No | No | No | No |
| 1,2-benzisothiazol-3(2H)-one                                                                                                          | No | No | No | No | No | No | No |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | No | No | No | No | No | No | No |

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment

#### Regulation (EC) No. 1907/2006 [REACH]

| Product/ingredient name                                                                                                                                                                                                                                                                          | PBT | P   | B   | T   | vPvB | vP  | vB  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-----|-----|-----|------|-----|-----|
| Zinc oxide                                                                                                                                                                                                                                                                                       | No  | No  | No  | No  | No   | No  | No  |
| 2-Butoxyethanol                                                                                                                                                                                                                                                                                  | No  | N/A | N/A | No  | N/A  | N/A | N/A |
| Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly (oxyethylene) | No  | N/A | N/A | No  | N/A  | N/A | N/A |
| adipohydrazide                                                                                                                                                                                                                                                                                   | No  | N/A | N/A | No  | N/A  | N/A | N/A |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate                                                                                                                                                                                                                                                  | No  | N/A | N/A | No  | N/A  | N/A | N/A |
| 3-iodo-2-propynyl-butyl carbamate                                                                                                                                                                                                                                                                | N/A | N/A | N/A | Yes | N/A  | N/A | N/A |
| 1,2-benzisothiazol-3(2H)-one                                                                                                                                                                                                                                                                     | No  | N/A | No  | No  | No   | N/A | No  |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)                                                                                                                                                            | No  | N/A | N/A | No  | N/A  | N/A | N/A |

#### Regulation (EC) No. 1272/2008 [CLP]

| Product/ingredient name                                                                                                                                           | PBT | P  | B  | T  | vPvB | vP | vB |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----|----|----|------|----|----|
| Zinc oxide                                                                                                                                                        | No  | No | No | No | No   | No | No |
| 2-Butoxyethanol                                                                                                                                                   | No  | No | No | No | No   | No | No |
| Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert- | No  | No | No | No | No   | No | No |

**Date of issue/Date of revision** : 29/01/2026 **Date of previous issue** : 05/06/2025 **Version** : 1.02 21/28

PENTOL UV PROTECT PLUS 0783-30 - All variants

**Label No** : 36892

## SECTION 12: Ecological information

|                                                                                                                                                                    |    |    |    |    |    |    |    |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|----|----|----|----|----|----|
| butyl-4-hydroxyphenyl)<br>propionyl-omega-3-(3-(2H-<br>benzotriazol-2-yl)-5-tert-<br>butyl-4-hydroxyphenyl)<br>propionyloxypoly<br>(oxyethylene)<br>adipohydrazide | No | No | No | No | No | No | No |
| bis(1,2,2,6,6-pentamethyl-<br>4-piperidyl) sebacate                                                                                                                | No | No | No | No | No | No | No |
| 3-iodo-2-propynyl-butyl<br>carbamate                                                                                                                               | No | No | No | No | No | No | No |
| 1,2-benzisothiazol-3(2H)-one                                                                                                                                       | No | No | No | No | No | No | No |
| reaction mass of: 5-chloro-<br>2-methyl-4-isothiazolin-<br>3-one [EC no. 247-500-7]<br>and 2-methyl-2H-isothiazol-<br>3-one [EC no. 220-239-6] (3:<br>1)           | No | No | No | No | No | No | No |

**Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP]** : The product does not meet the criteria to be considered as a PBT or vPvB.

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : Avoid release to the environment. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**European waste catalogue (EWC)** : 08.01.19

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

## SECTION 14: Transport information

|                                 | ADR/RID        | ADN                                                 | IMDG           | IATA           |
|---------------------------------|----------------|-----------------------------------------------------|----------------|----------------|
| 14.1 UN number or ID number     | Not regulated. | 9006                                                | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name    | -              | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | -              | -              |
| 14.3 Transport hazard class(es) | -              | 9                                                   | -              | -              |
| 14.4 Packing group              | -              | -                                                   | -              | -              |
| 14.5 Environmental hazards      | No.            | Yes.                                                | No.            | No.            |

### Additional information

#### ADN

: The product is only regulated as a dangerous good when transported in tank vessels.

#### IATA

: The environmentally hazardous substance mark may appear if required by other transportation regulations.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

#### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Product/ingredient name        | %   | Designation [Usage] |
|--------------------------------|-----|---------------------|
| PENTOL UV PROTECT PLUS 0783-30 | ≥90 | 3                   |

#### Labelling

:

#### Synthetic polymer microparticles - Designation 78

**Generic identity of polymer(s)** : 9006 - Acrylic polymers.

**Total percentage of synthetic polymer microparticles** : 0.19%

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

#### Other EU regulations

## SECTION 15: Regulatory information

**Industrial emissions  
(integrated pollution  
prevention and control) -  
Air** : Not listed

**Industrial emissions  
(integrated pollution  
prevention and control) -  
Water** : Not listed

**Explosive precursors** : Not applicable.

### Ozone depleting substances (EU 2024/590)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Persistent Organic Pollutants

Not listed.

### Seveso Directive

This product is not controlled under the Seveso Directive.

### National regulations

#### Austria

**Limitation of the use of  
organic solvents** : Permitted.

#### Belgium

#### Czech Republic

**Storage code** : IV

#### Denmark

**Fire class** : IV-1

**MAL-code** : 1-5

**Protection based on MAL** : **According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:**

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 1-5

**Application:** When using scraper or knife, brush, roller etc. for pre- and post-treatments in a spray booth where the operator is outside the spray zone and when working in similar new\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in new\* booths and cabins with non-atomizing guns. When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Protective clothing must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

## SECTION 15: Regulatory information

- Gas filter mask and protective clothing must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Air-supplied full mask and protective clothing must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied half mask, protective clothing and eye protection must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, protective clothing and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

**Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

**List of undesirable substances** : Not listed

### Finland

### France

**Social Security Code, Articles L 461-1 to L 461-7** : 2-Butoxyethanol RG 84

**Reinforced medical surveillance** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

### Germany

**Storage class (TRGS 510)** : 10

### Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

**Hazard class for water** : 2

### Technical instruction on air quality control (TA Luft)

| Number [Class] | Description                  | %     |
|----------------|------------------------------|-------|
| 5.2.1          | Total dust                   | 27.2  |
| 5.2.4 [III]    | Gaseous inorganic substances | 0.069 |
| 5.2.5          | Organic substances           | 4.9   |
| 5.2.5 [I]      | Organic substances           | 1.6   |
| 5.2.10         | Soil polluting substances    | 1.4   |

**AOX** : The product contains organically bound halogens and can contribute to the AOX value in waste water.

### Italy

**D.Lgs. 152/06** : Not determined.

### Netherlands

## SECTION 15: Regulatory information

**Water Discharge Policy (ABM)** : A(2) Toxic for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A

[Norway](#)

[Sweden](#)

[Switzerland](#)

**VOC content** : Exempt.

[International regulations](#)

[Chemical Weapon Convention List Schedules I, II & III Chemicals](#)

Not listed.

[Montreal Protocol](#)

Not listed.

[Stockholm Convention on Persistent Organic Pollutants](#)

Not listed.

[Rotterdam Convention on Prior Informed Consent \(PIC\)](#)

Not listed.

[UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

🔄 Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

[Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

| Classification           | Justification      |
|--------------------------|--------------------|
| 🔄Aquatic Chronic 3, H412 | Calculation method |

[Full text of abbreviated H statements](#)

|       |                                                                 |
|-------|-----------------------------------------------------------------|
| 🔄H301 | Toxic if swallowed.                                             |
| H302  | Harmful if swallowed.                                           |
| H310  | Fatal in contact with skin.                                     |
| H314  | Causes severe skin burns and eye damage.                        |
| H315  | Causes skin irritation.                                         |
| H317  | May cause an allergic skin reaction.                            |
| H318  | Causes serious eye damage.                                      |
| H319  | Causes serious eye irritation.                                  |
| H330  | Fatal if inhaled.                                               |
| H331  | Toxic if inhaled.                                               |
| H372  | Causes damage to organs through prolonged or repeated exposure. |
| H400  | Very toxic to aquatic life.                                     |
| H410  | Very toxic to aquatic life with long lasting effects.           |
| H411  | Toxic to aquatic life with long lasting effects.                |
| H412  | Harmful to aquatic life with long lasting effects.              |

## SECTION 16: Other information

EUH071

Corrosive to the respiratory tract.

### [Full text of classifications \[CLP/GHS\]](#)

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| Acute Tox. 2      | ACUTE TOXICITY - Category 2                                     |
| Acute Tox. 3      | ACUTE TOXICITY - Category 3                                     |
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                     |
| Aquatic Acute 1   | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1                  |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1                 |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2                 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3                 |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                  |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                  |
| Skin Corr. 1C     | SKIN CORROSION/IRRITATION - Category 1C                         |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                          |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                                 |
| Skin Sens. 1A     | SKIN SENSITISATION - Category 1A                                |
| STOT RE 1         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |

**Date of issue/ Date of revision** : 29/01/2026

**Date of previous issue** : 05/06/2025

**Version** : 1.02

PENTOL UV PROTECT PLUS 0783-30

All variants

### [Notice to reader](#)

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

