according to 2001/58 EC



3048614

Reviewed on: 30/06/2021 Printing date: 01/07/2021

01 Identification of the hazardous chemical and of the supplier

- · Product identifier
- · Trade name: PREMIUM TEAK OIL 6151-00
- Article number / Safety Data Sheet: 615100
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
- Teknos AG
- Industriestrasse 7

LI-9487 Gamprin-Bendern

T +423 375 94 00

F +423 375 94 99

- Further information obtainable from:
 - Product safety department. e-mail address: li-sdb@teknos.com
- Emergency telephone number:
- Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

02 Hazard identification

Classification of the substance or mixture



GHS08

Asp. Haz. - H304 May be fatal if swallowed and enters airways.



GHS07

STOT SE 3 - H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

- Label elements
- GHS label elements
- Hazard pictograms





GHS08 GHS07

Signal word

Hazard-determining components of labelling:

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclenes, <2% aromatics

/ Hydrocarbons, C10, aromatics, <1% naphthalene

Hazard statements

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/ gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

according to 2001/58 EC



3048614

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: PREMIUM TEAK OIL 6151-00

(continued of page 1)

03 Composition and information of the ingredients of the hazardous chemical

- · Chemical characterization: Mixtures
- · Description:

Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS Number %

64742-82-1 hydrocarbons, C10-C13, n-alkanes, 40,00- 60,00

isoalkanes, cyclenes, <2% aromatics EC number: 918-481-9

Record number 01-2119457273-39

♣ Asp. Haz. - H304

1189173-42-9 Hydrocarbons, C10, aromatics, <1% 15,00- 25,00

naphthalene

EC number: 918-811-1

55406-53-6 3-lodo-2-propynylbutylcarbamate 0,00- 0,50

EC number: 259-627-5

Eye Dam. 1 - H318;
 Acute Tox. 3
 - H331;
 STOT RE 1 - H372;
 Acute

Tox. 4 - H302, Skin Sens. 1 - H317; ♦
Aquatic Acute 1 - H400, Aquatic Chronic 1 -

H410

04 First-aid measures

- After inhalation:
- Supply fresh air; consult doctor in case of complaints.
- After skin contact:

Immediately wash with water and soap and rinse thoroughly.

- After eye contact:
 - Rinse opened eye for several minutes under running water.
- · After swallowing:

Do not induce vomiting; call for medical help immediately.

05 Fire-fighting measures

- Suitable extinguishing agents:
 - CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

MAL

(continued on page 3)

according to 2001/58 EC



3048614

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: PREMIUM TEAK OIL 6151-00

(continued of page 2)

06 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

07 Handling and storage

- · Handling:
- · Precautions for safe handling

Take note of emission threshold.

· Information about fire - and explosion protection:

No special measures required.

- Storage:
- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Information about storage in one common storage facility:

Not required.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Specific end use(s)

No further relevant information available.

08 Exposure controls and personal protection

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

The lists valid during the making were used as basis.

- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

- · Respiratory protection: Suitable respiratory protective device recommended.
- Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the
 preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the
 preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates
 of diffusion and the degradation Impervious gloves
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- Eye protection: Safety glasses
- · Body protection: Protective work clothing

according to 2001/58 EC



3048614

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: PREMIUM TEAK OIL 6151-00

(continued of page 3)

Appearance Appearance: Form: Liquid

09 Physical and chemical properties

Colour:According to product specificaOdour:Characteristic Characteristic

Odour threshold: Not determined.

Change in condition

Initial boiling point and boiling range: Undetermined. 60 °C Flash point: C.C. Flammability (solid, gas): Not applicable. Ignition temperature: Undetermined. **Decomposition temperature:** Not determined. Auto-ignition temperature: Not determined. **Explosive properties:** Not determined. **Explosion limits:** Not determined. Lower: Upper: Not determined. Vapour pressure: Not determined. Density: 0,8500 g/cm3 Solubility in / Miscibility with water: Not determined. Viscosity: Not determined. 40 °C 20 mm2/s

No further relevant information available.

10 Stability and reactivity

Other information

- Thermal decomposition / conditions to be avoided:
 - No decomposition if used according to specifications.
- Incompatible materials:
- No further relevant information available.
- · Hazardous decomposition products:

No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity
- · LD/LC50 values relevant for classification:

55406-53-6 3-lodo-2-propynylbutylcarbamate

Oral, LD50: 1470 mg/kg (rat) Dermal, LD50: >2000 mg/kg (rat) Inhalative, LC50/4h: >6,89 mg/l (rat)

- · Primary irritant effect:
- Skin corrosion/irritation
 - No irritant effect.
- Serious eye damage/irritation
- No irritating effect.
- Respiratory or skin sensitisation No sensitising effects known.

according to 2001/58 EC



3048614

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: PREMIUM TEAK OIL 6151-00

(continued of page 4)

12 Ecological information

- · Aquatic toxicity:
- No further relevant information available.
- Persistence and degradability
- No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential

No further relevant information available.

- · Ecotoxical effects:
- Remark:
- Harmful to fish
- Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

13 Disposal information

- · Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

14 Transportation information

UN-Number

ADR Void IMDG Void IATA Void

UN proper shipping name

ADR Void IMDG Void IATA Void

• Transport hazard class(es)

ADR

Class Void IMDG Class Void IATA

Class Void

· Packing group

ADR Void
IMDG Void
IATA Void

- · Environmental hazards:
 - Not applicable.
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
- Transport/Additional information:

Not applicable.

according to 2001/58 EC



3048614

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: PREMIUM TEAK OIL 6151-00

(continued of page 5)

15 Regulatory information

- · National regulations:
- · Classification according to VbF:

_

Waterhazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H317 May cause allergic skin reaction. H318 Causes serious eye damage.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

Department issuing MSDS:

Environment protection department.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids,

Austria)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

* Data compared to the previous version altered.