

1489413

Reviewed on: 03/04/2023

Printing date: 03/04/2023

SECTION 01: Identification of the substance/mixture and of the company undertaking

• 1.1 Product identifier

- Trade name:
RAPIFILL 1080-00
- Article number / Safety Data Sheet:
108000
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the preparation
Coating material

• 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:
Teknos AG
Industriestrasse 7
LI-9487 Gamprin-Bendern
T +423 375 94 00
F +423 375 94 99

- Further information obtainable from:
Product safety department. e-mail address: li-sdb@teknos.com
- 1.4 Emergency telephone number:
Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

SECTION 02: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 - H226 Flammable liquid and vapour.



GHS07

- * Skin Sens. 1 - H317 May cause an allergic skin reaction.
- * STOT SE 3 - H336 May cause drowsiness or dizziness.
- * Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

• 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms



GHS02

GHS07

- Signal word
Warning

- * Hazard-determining components of labelling:
n-butyl acetate / methyl methacrylate / Fatty acids, C14-18 and C16-18-unsatd., maleated / maleic anhydride
- * Hazard statements
H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- * Precautionary statements

(continued on page 2)

1489413

Reviewed on: 03/04/2023

Printing date: 03/04/2023

PRODUCT : RAPIFILL 1080-00

(continued of page 1)

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- * P302+P352 IF ON SKIN: Wash with plenty of water.
- * P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- * P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.
- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT:
Not applicable.
- vPvB:
Not applicable.

SECTION 03: Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- Description:
Mixture of substances listed below with nonhazardous additions.

- Dangerous components:

CAS Number		%
* 80-62-6	methyl methacrylate EC number: 201-297-1 Record number 01-2119452498-28 ⚠ Flam. Liq. 2 - H225; ⚠ Skin Irrit. 2 - H315, Skin Sens. 1 - H317, STOT SE 3 - H335	0,0015- 0,50
* 123-86-4	n-butyl acetate EC number: 204-658-1 Record number 01-2119485493-29 ⚠ Flam. Liq. 3 - H226; ⚠ STOT SE 3 - H336; EUH066	10,00- 25,00
* 108-65-6	2-methoxy-1-methylethyl acetate EC number: 203-603-9 Record number 01-2119475791-29 substance with a Community workplace exposure limit. ⚠ Flam. Liq. 3 - H226	5,00- 10,00
1330-20-7	xylene EC number: 215-535-7 Record number 01-2119488216-32 ⚠ Flam. Liq. 3 - H226; ⚠ Acute Tox. 4 - H312, Acute Tox. 4 - H332, Skin Irrit. 2 - H315	5,00- 10,00
100-41-4	ethylbenzene EC number: 202-849-4 Record number 01-2119489370-35 ⚠ Flam. Liq. 2 - H225; ⚠ STOT RE 2 - H373, Asp. Tox. 1 - H304; ⚠ Acute Tox. 4 - H332	1,00- 5,00

(continued on page 3)

according to 1907/2006/EC, Article 31

1489413

Reviewed on: 03/04/2023

Printing date: 03/04/2023

PRODUCT : RAPIFILL 1080-00

(continued of page 3)

SECTION 04: First aid measures

- 4.1 *Description of first aid measures*
- * **After inhalation:**
Supply fresh air and to be sure call for a doctor.
- * In case of unconsciousness place patient stably in side position for transportation.
- * **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
- * **After eye contact:**
Immediately rinse with water.
- **After eye contact:**
Rinse opened eye for several minutes under running water.
- **After swallowing:**
Do not induce vomiting; call for medical help immediately.
- **Information for doctor:**
- 4.2 *Most important symptoms and effects, both acute and delayed*
No further relevant information available.
- 4.3 *Indication of any immediate medical attention and special treatment needed*
No further relevant information available.

SECTION 05: Firefighting measures

- 5.1 *Extinguishing media*
- **Suitable extinguishing agents:**
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:**
Water with full jet
- 5.2 *Special hazards arising from the substance or mixture*
Formation of toxic gases is possible during heating or in case of fire.
- 5.3 *Advice for firefighters*
- **Protective equipment:**
Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 06: Accidental release measures

- 6.1 *Personal precautions, protective equipment and emergency procedures*
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- 6.2 *Environmental precautions:*
Do not allow product to reach sewage system or any water course.
- * Prevent seepage into sewage system, workpits and cellars.
- * Inform respective authorities in case of seepage into water course or sewage system.
- * In case of seepage into the ground inform responsible authorities.
- * In case of gas release or seepage into the ground inform responsible authorities.
Do not allow to enter sewers/ surface or ground water.
- 6.3 *Methods and material for containment and cleaning up:*
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- * Dispose contaminated material as waste according to item 13.
- * Ensure adequate ventilation.
- 6.4 *Reference to other sections*
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

GB

(continued on page 5)

according to 1907/2006/EC, Article 31

1489413

Reviewed on: 03/04/2023

Printing date: 03/04/2023

PRODUCT : RAPIFILL 1080-00

(continued of page 4)

SECTION 07: Handling and storage

- **Handling:**
- **7.1 Precautions for safe handling**
- * Open and handle receptacle with care.
Take note of emission threshold.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- **Information about fire - and explosion protection:**
- * Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- * Prevent impact and friction.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store only in the original receptacle.
- **Information about storage in one common storage facility:**
Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)**
No further relevant information available.

SECTION 08: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

80-62-6	methyl methacrylate		
WEL			
	Short-term value	416	mg/m3
		100	ppm
	Long-term value	208	mg/m3
		50	ppm
123-86-4	n-butyl acetate		
WEL			
	Short-term value	966	mg/m3
		200	ppm
	Long-term value	724	mg/m3
		150	ppm
108-65-6	2-methoxy-1-methylethyl acetate		
WEL			
	Short-term value	548	mg/m3
		100	ppm
	Long-term value	274	mg/m3
		50	ppm
	Sk		
1330-20-7	xylene		
WEL			
	Short-term value	441	mg/m3
		100	ppm

(continued on page 6)

according to 1907/2006/EC, Article 31

1489413

Reviewed on: 03/04/2023

Printing date: 03/04/2023

PRODUCT : RAPIFILL 1080-00

(continued of page 5)

	Long-term value	220	mg/m3
		50	ppm
	Sk; BMGV		
100-41-4	ethylbenzene		
WEL			
	Short-term value	552	mg/m3
		125	ppm
	Long-term value	441	mg/m3
		100	ppm
	Sk		
108-83-8	2,6-dimethylheptan-4-one		
WEL			
	Long-term value	148	mg/m3
		25	ppm
9004-34-6	Cellulose		
WEL			
	Short-term value	20*	mg/m3
	Long-term value	10* 4**	mg/m3
	*inhalable dust **respirable		
71-36-3	butan-1-ol		
WEL			
	Short-term value	154	mg/m3
		50	ppm
	Sk		

- Ingredients with biological limit values:

1330-20-7 xylene

BMGV

650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

- *Additional information:*

The lists valid during the making were used as basis.

- *8.2 Exposure controls*

- **Personal protective equipment:**

- *General protective and hygienic measures:*

The usual precautionary measures are to be adhered to when handling chemicals.

* Immediately remove all soiled and contaminated clothing

* Avoid contact with the eyes and skin.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

- *Respiratory protection: Suitable respiratory protective device recommended.*

- *Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Protective gloves Impervious gloves*

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(continued on page 7)

according to 1907/2006/EC, Article 31

1489413

Reviewed on: 03/04/2023

Printing date: 03/04/2023

PRODUCT : RAPIFILL 1080-00

(continued of page 6)

- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.
- * • *Eye protection: Safety glasses*
- *Body protection: Protective work clothing*

SECTION 09: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Appearance:

Form:	Liquid
Colour:	According to product specifica
Odour:	Characteristic Characteristic
Odour threshold:	Not determined.

Change in condition

Initial boiling point and boiling range:	124 °C
Flash point:	27 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	315 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined.
Explosion limits:	
Lower:	1 Vol %
Upper:	7 Vol %
Vapour pressure:	at 20 °C 10,7000 mbar at 50 °C 55,0000 mbar
* Density:	1,4400 g/cm3
Solubility in / Miscibility with water:	Not determined.
Viscosity:	
•	Not determined.
•	at 23 °C 90 - 100 s DIN 4 mm
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- *10.1 Reactivity*
No further relevant information available.
- *10.2 Chemical stability*
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- *10.3 Possibility of hazardous reactions*
No dangerous reactions known.
- *10.4 Conditions to avoid*
No further relevant information available.
- **10.5 Incompatible materials:**

(continued on page 8)

according to 1907/2006/EC, Article 31

1489413

Reviewed on: 03/04/2023

Printing date: 03/04/2023

PRODUCT : RAPIFILL 1080-00

(continued of page 7)

No further relevant information available.

• **10.6 Hazardous decomposition products:**

No dangerous decomposition products known.

SECTION 11: Toxicological information

• **11.1 Information on toxicological effects**

• **Acute toxicity**

• *LD/LC50 values relevant for classification:*

80-62-6 methyl methacrylate

Oral, LD50: 7872 mg/kg (rat)

123-86-4 n-butyl acetate

Oral, LD50: 13100 mg/kg (rat)

Dermal, LD50: >5000 mg/kg (Rabbit)

Inhalative, LC50/4h: >21 mg/l (rat)

868-77-9 2-hydroxyethyl methacrylate

Oral, LD50: 5050 mg/kg (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral, LD50: 8532 mg/kg (rat)

Inhalative, LC50/4h: 35,7 mg/l (rat)

1330-20-7 xylene

Oral, LD50: 4300 mg/kg (rat)

Dermal, LD50: 2000 mg/kg (Rabbit)

100-41-4 ethylbenzene

Oral, LD50: 3500 mg/kg (rat)

Dermal, LD50: 17800 mg/kg (Rabbit)

108-83-8 2,6-dimethylheptan-4-one

Oral, LD50: 5750 mg/kg (rat)

Dermal, LD50: 16000 mg/kg (Rabbit)

108-31-6 maleic anhydride

Oral, LD50: 400 mg/kg (rat)

Dermal, LD50: 2620 mg/kg (Rabbit)

13463-67-7 titanium dioxide

Oral, LD50: >20000 mg/kg (rat)

Dermal, LD50: >10000 mg/kg (Rabbit)

Inhalative, LC50/4h: >6,82 mg/l (rat)

7631-86-9 silicon dioxide, chemically prepared

Oral, LD50: 10000 mg/kg (rat)

71-36-3 butan-1-ol

Oral, LD50: 790 mg/kg (rat)

Dermal, LD50: 3400 mg/kg (Rabbit)

Inhalative, LC50/4h: 8000 mg/l (rat)

78-83-1 butanol

Oral, LD50: 2460 mg/kg (rat)

Dermal, LD50: 3400 mg/kg (Rabbit)

122-51-0 triethyl orthoformate

Dermal, LD50: 20000 mg/kg (Rabbit)

77-58-7 dibutyltin dilaurate

Oral, LD50: 175 mg/kg (rat)

• *Primary irritant effect:*

• Skin corrosion/irritation

No irritant effect.

• Serious eye damage/irritation

No irritating effect.

• *Respiratory or skin sensitisation*

Sensitisation possible through skin contact.

• **Additional toxicological information:**

(continued on page 9)

according to 1907/2006/EC, Article 31

1489413

Reviewed on: 03/04/2023

Printing date: 03/04/2023

PRODUCT : RAPIFILL 1080-00

(continued of page 8)

- * The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
- * Irritant
- * **11.2 Information on other hazards**
- * **Endocrine disrupting properties**
- * 541-02-6 decamethylcyclopentasiloxane : II
- * 556-67-2 octamethylcyclotetrasiloxane : II; III

SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity:
No further relevant information available.
- **12.2 Persistence and degradability**
No further relevant information available.
- **Behaviour in environmental systems:**
- **12.3 Bioaccumulative potential**
No further relevant information available.
- 12.4 Mobility in soil
No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:**
- * Harmful to fish
- **Additional ecological information:**
- **General notes:**
- * Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:**
Not applicable.
- **vPvB:**
Not applicable.
- **12.6 Other adverse effects**
No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **European and swiss waste code**
08
WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01
wastes from MFSU and removal of paint and varnish
08 01 11
waste paint and varnish containing organic solvents or other hazardous substances
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.

GB

(continued on page 10)

1489413

Reviewed on: 03/04/2023

Printing date: 03/04/2023

PRODUCT : RAPIFILL 1080-00*(continued of page 9)***SECTION 14: Transport information**• **14.1 UN-Number**

ADR UN1263

IMDG UN1263

IATA UN1263

• **14.2 UN proper shipping name**

ADR 1263 PAINT

IMDG PAINT

IATA PAINT

• **14.3 Transport hazard class(es)**

ADR

Class 3 Flammable liquids.

Label

3



IMDG

Class 3 Flammable liquids.

Label

3



IATA

Class 3 Flammable liquids.

Label

3

• **14.4 Packing group**

ADR III

IMDG III

IATA III

• **14.5 Environmental hazards:**

Not applicable.

• **14.6 Special precautions for user**

Warning: Flammable liquids.

Danger code (Kemler): 30

EMS Number: F-E,S-E

• **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

• **Transport/Additional information:**

Not applicable.

Excepted quantities (EQ): E1

Limited quantities (LQ): 5L

(continued on page 11)

1489413

Reviewed on: 03/04/2023

Printing date: 03/04/2023

PRODUCT : RAPIFILL 1080-00

(continued of page 10)

Transport category	3
Tunnel restriction code	D/E
Remarks:	ADR/RID 2.2.3.1.5 (<= 450 l)
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	E1
Remarks:	IMDG 2.3.2.5 (<= 30 l)
• UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- * **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- * DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II
- * None of the ingredients is listed.
- * REGULATION (EU) 2019/1148
- * Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
- * None of the ingredients is listed.
- * Annex II - REPORTABLE EXPLOSIVES PRECURSORS
- * None of the ingredients is listed.
- * REGULATION (EC) No 1907/2006 ANNEX XVII
- * Conditions of restriction: 3, 40
- National regulations:**
- Technical instructions (air):**
- * Class Share in %

III	20, 63
II	8, 17
I	
- Waterhazard class:**
- Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment:**
- A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- * Relevant phrases
- * EUH066 Repeated exposure may cause skin dryness or cracking.
- * H225 Highly flammable liquid and vapour.
- * H226 Flammable liquid and vapour.
- * H302 Harmful if swallowed.
- * H304 May be fatal if swallowed and enters airways.
- * H311 Toxic in contact with skin.
- * H312 Harmful in contact with skin.
- * H314 Causes severe skin burns and eye damage.
- * H315 Causes skin irritation.
- * H317 May cause an allergic skin reaction.
- * H318 Causes serious eye damage.
- * H332 Harmful if inhaled.
- * H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- * H335 May cause respiratory irritation.
- * H336 May cause drowsiness or dizziness.
- * H351 Suspected of causing cancer.
- * H372 Causes damage to organs through prolonged or repeated exposure.

(continued on page 12)

according to 1907/2006/EC, Article 31

1489413

Reviewed on: 03/04/2023

Printing date: 03/04/2023

PRODUCT : RAPIFILL 1080-00

(continued of page 11)

- | | | |
|---|------|--|
| * | H373 | May cause damage to organs through prolonged or repeated exposure. |
| * | H400 | Very toxic to aquatic life. |
| * | H410 | Very toxic to aquatic life with long lasting effects. |

- **Department issuing MSDS:**

Environment protection department.

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

- * *Data compared to the previous version altered.*