

SAFETY DATA SHEET



RAPIFILL 1080-00 - All variants

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : RAPIFILL 1080-00 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Sens. 1, H317

STOT SE 3, H336

Aquatic Chronic 3, H412


The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 - Flammable liquid and vapour.
H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P280 - Wear protective gloves.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.

Response : P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Storage : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

SECTION 2: Hazards identification

Hazardous ingredients	: Contains: n-Butyl acetate; Fatty acids, C14-18 and C16-18-unsatd., maleated; Methyl methacrylate and Maleic anhydride
Supplemental label elements	:
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
n-Butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥10 - ≤25	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
Xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	<10	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (oral, inhalation) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
Ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≤3	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) (oral, inhalation) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates	EC: 269-662-8 CAS: 68308-64-5	<1	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 3, H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg ATE [Dermal] = 528 mg/kg M [Acute] = 1 M [Chronic] = 1	[1]
Fatty acids, C14-18 and	REACH #:	≤0.3	Skin Irrit. 2, H315	-	[1]

SECTION 3: Composition/information on ingredients

C16-18-unsatd., maleated	01-2119976378-19 EC: 288-306-2 CAS: 85711-46-2		Skin Sens. 1, H317		
Methyl methacrylate	REACH #: 01-2119452498-28 EC: 201-297-1 CAS: 80-62-6 Index: 607-035-00-6	≤0.3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	-	[1] [2]
Maleic anhydride	REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9	≤0.01	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (inhalation) EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 400 mg/kg Skin Sens. 1, H317: C ≥ 0.001%	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

- : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

- : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

- : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

- : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SECTION 4: First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

SECTION 7: Handling and storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
n-Butyl acetate	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 966 mg/m ³ . STEL 15 minutes: 200 ppm. TWA 8 hours: 724 mg/m ³ . TWA 8 hours: 150 ppm.
Xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020) [xylene, o-, m-, p- or mixed isomers] Absorbed through skin. STEL 15 minutes: 441 mg/m ³ . TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m ³ . STEL 15 minutes: 100 ppm.
Ethylbenzene	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 552 mg/m ³ . STEL 15 minutes: 125 ppm. TWA 8 hours: 100 ppm. TWA 8 hours: 441 mg/m ³ .
Methyl methacrylate	EH40/2005 WELs (United Kingdom (UK), 1/2020) STEL 15 minutes: 416 mg/m ³ . STEL 15 minutes: 100 ppm. TWA 8 hours: 208 mg/m ³ . TWA 8 hours: 50 ppm.
Maleic anhydride	EH40/2005 WELs (United Kingdom (UK), 1/2020) Inhalation sensitiser. STEL 15 minutes: 3 mg/m ³ . TWA 8 hours: 1 mg/m ³ .

Biological exposure indices

Product/ingredient name	Exposure indices
Xylene	EH40/2005 BMGVs (United Kingdom (UK), 1/2020) [Xylene, o-, m-, p- or mixed isomers] BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift.

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

 Butyl acetate

Result

DNEL - General population - Long term - Oral

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Oral

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

3.4 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

6 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

7 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Dermal

11 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

12 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

35.7 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

48 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

300 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

300 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

300 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

600 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

SECTION 8: Exposure controls/personal protection

Xylene

600 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

65.3 mg/m³

Effects: Local

DNEL - General population - Long term - Inhalation

65.3 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

125 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

212 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

221 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

221 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

260 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

260 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

442 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

442 mg/m³

Effects: Systemic

2-Methoxy-1-methylethyl acetate

DNEL - General population - Long term - Inhalation

33 mg/m³

Effects: Local

DNEL - General population - Long term - Inhalation

33 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

36 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

275 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

320 mg/kg bw/day

Effects: Systemic

SECTION 8: Exposure controls/personal protection

DNEL - Workers - Short term - Inhalation

550 mg/m³

Effects: Local

DNEL - Workers - Long term - Dermal

796 mg/kg bw/day

Effects: Systemic

DMEL - Workers - Long term - Inhalation

442 mg/m³

Effects: Local

DMEL - Workers - Short term - Inhalation

884 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

1.6 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

15 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

77 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

180 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Inhalation

293 mg/m³

Effects: Local

DNEL - General population - Long term - Oral

1.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

1.5 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

3 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

1.5 mg/cm²

Effects: Local

DNEL - General population - Long term - Dermal

1.5 mg/cm²

Effects: Local

DNEL - Workers - Short term - Dermal

1.5 mg/cm²

Effects: Local

DNEL - Workers - Long term - Dermal

1.5 mg/cm²

Effects: Local

DNEL - General population - Long term - Oral

Ethylbenzene

Fatty acids, C14-18 and C16-18-unsatd.,
maleated

Methyl methacrylate

SECTION 8: Exposure controls/personal protection

8.2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

8.2 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

13.67 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

74.3 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

104 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

208 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

208 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

348.4 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

416 mg/m³

Effects: Local

Maleic anhydride

DNEL - General population - Long term - Inhalation

0.05 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

0.06 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.08 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

0.081 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

0.081 mg/m³

Effects: Systemic

DNEL - General population - Short term - Oral

0.1 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

0.1 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

0.1 mg/kg bw/day

Effects: Systemic

SECTION 8: Exposure controls/personal protection

DNEL - Workers - Short term - Dermal

0.2 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.2 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Inhalation

0.2 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

0.2 mg/m³

Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.

Body protection

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection

- : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Filter type: A
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
Colour : Various
Odour : Slight
Odour threshold : Not available.
Melting point/freezing point : Not available.
Initial boiling point and boiling range :

Ingredient name	°C	°F	Method
n-Butyl acetate	126	258.8	OECD 103
Ethylbenzene	136.1	277	OECD 104

- Flammability** : Not available.
Lower and upper explosion limit : Lower: 0.8% (xylene)
Upper: 7.6% (n-butyl acetate)
Flash point : Closed cup: 27°C (80.6°F)
Auto-ignition temperature :

Ingredient name	°C	°F	Method
2-Methoxy-1-methylethyl acetate	333	631.4	DIN 51794
n-Butyl acetate	415	779	EU A.15

- Decomposition temperature** : Not available.
pH : Not applicable.
Viscosity : Not available.
Solubility(ies) :
Not available.

- Solubility in water** : Not available.
Partition coefficient: n-octanol/ water : Not applicable.
Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
n-Butyl acetate	11.25096	1.5	DIN EN 13016-2			
Ethylbenzene	9.30076	1.2				

- Relative density** : Not available.
Density : 1.4 g/cm³
Vapour density : Not available.

SECTION 9: Physical and chemical properties

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

Oxidising properties : Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials : Reactive or incompatible with the following materials:
oxidising materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

☒ Butyl acetate

Result

Rat - Oral - LD50

10760 mg/kg

EU

Rabbit - Dermal - LD50

14112 mg/kg

Rat - Inhalation - LC50 Vapour

0.74 mg/l [4 hours]

Xylene

Rat - Oral - LD50

4300 mg/kg

Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other changes

Rat - Inhalation - LC50 Vapour

21.7 mg/l [4 hours]

2-Methoxy-1-methylethyl acetate

Rat - Oral - LD50

8532 mg/kg

Rabbit - Dermal - LD50

>5 g/kg

Ethylbenzene

Rat - Oral - LD50

3500 mg/kg

Rabbit - Dermal - LD50

Date of issue/Date of revision : 31/03/2026 **Date of previous issue** : 19/08/2025

Version : 1.02 13/23

RAPIFILL 1080-00 - All variants

Label No : ☒ 28237

SECTION 11: Toxicological information

15400 mg/kg

Rat - Inhalation - LC50 Dusts and mists

29000 mg/l [4 hours]

Methyl methacrylate

Rat - Oral - LD50

7872 mg/kg

Toxic effects: Behavioral - Muscle weakness Behavioral - Coma Lung, Thorax, or Respiration - Respiratory depression

Rabbit - Dermal - LD50

>5 g/kg

Toxic effects: Skin After systemic exposure - Dermatitis, other

Rat - Inhalation - LC50 Vapour

78000 mg/m³ [4 hours]

Maleic anhydride

Rat - Oral - LD50

400 mg/kg

Rabbit - Dermal - LD50

2620 mg/kg

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
RAPIFILL 1080-00	N/A	14083.6	N/A	134.9	N/A
n-Butyl acetate	10760	14112	N/A	N/A	N/A
Xylene	4300	1100	N/A	11	N/A
2-Methoxy-1-methylethyl acetate	8532	N/A	N/A	N/A	N/A
Ethylbenzene	3500	15400	N/A	11	29000
Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates	500	528	N/A	N/A	N/A
Methyl methacrylate	7872	N/A	N/A	78	N/A
Maleic anhydride	400	2620	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name

n-Butyl acetate

Result

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Xylene

Rat - Skin - Mild irritant

Duration of treatment/exposure: 8 hours

Amount/concentration applied: 60 uL

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Ethylbenzene

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 15 mg

Conclusion/Summary [Product] : Not available.

SECTION 11: Toxicological information

Serious eye damage/eye irritation

Product/ingredient name

 Butyl acetate

Xylene

Ethylbenzene

Maleic anhydride

Result

Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 mg

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 87 mg

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 500 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 1 %

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

Result

SECTION 11: Toxicological information

n-Butyl acetate	STOT SE 3, H336 (Narcotic effects)
Xylene	STOT SE 3, H335 (Respiratory tract irritation)
Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates	STOT SE 3, H335 (Respiratory tract irritation)
Methyl methacrylate	STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
Xylene	STOT RE 2, H373 (oral, inhalation)
Ethylbenzene	STOT RE 2, H373 (hearing organs) (oral, inhalation)
Maleic anhydride	STOT RE 1, H372 (respiratory system) (inhalation)

Aspiration hazard

Product/ingredient name	Result
Xylene	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product]	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

SECTION 11: Toxicological information

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

n-Butyl acetate

Result

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*
Age: 31 to 32 days; Size: 21.6 mm; Weight: 0.175 g
18000 µg/l [96 hours]
Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Brine shrimp - *Artemia salina*
32 mg/l [48 hours]
Effect: Mortality

Methyl methacrylate

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas* - Adult
130000 µg/l [96 hours]
Effect: Mortality

Maleic anhydride

Acute - LC50 - Fresh water

Fish - Western mosquitofish - *Gambusia affinis* - Adult
230000 µg/l [96 hours]
Effect: Mortality

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
n-Butyl acetate	2.3	-	Low
Xylene	3.12	8.1 to 25.9	Low
2-Methoxy-1-methylethyl acetate	1.2	-	Low
Ethylbenzene	3.6	-	Low
Methyl methacrylate	1.38	-	Low
Maleic anhydride	-2.78	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
n-Butyl acetate	1.5	33.2139
2-Methoxy-1-methylethyl acetate	0.36	2.31363
Ethylbenzene	2.2	170.406
Methyl methacrylate	1.2	16.6906
Maleic anhydride	1.1	11.4841

Results of PMT and vPvM assessment

SECTION 12: Ecological information

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
✓ Butyl acetate	No	No	No	No	No	No	No
Xylene	No	No	No	No	No	No	No
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Ethylbenzene	No	No	No	No	No	No	No
Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates	No	No	No	No	No	No	No
Fatty acids, C14-18 and C16-18-unsatd., maleated	No	No	No	No	No	No	No
Methyl methacrylate	No	No	No	No	No	No	No
Maleic anhydride	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
✓ Butyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
Xylene	No	N/A	No	Yes	No	N/A	No
2-Methoxy-1-methylethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
Ethylbenzene	N/A	N/A	N/A	Yes	N/A	N/A	N/A
Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates	No	N/A	N/A	No	N/A	N/A	N/A
Fatty acids, C14-18 and C16-18-unsatd., maleated	No	N/A	N/A	No	N/A	N/A	N/A
Methyl methacrylate	No	N/A	N/A	No	N/A	N/A	N/A
Maleic anhydride	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
✓ Butyl acetate	No	No	No	No	No	No	No
Xylene	No	No	No	No	No	No	No
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Ethylbenzene	No	No	No	No	No	No	No
Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates	No	No	No	No	No	No	No
Fatty acids, C14-18 and C16-18-unsatd., maleated	No	No	No	No	No	No	No
Methyl methacrylate	No	No	No	No	No	No	No
Maleic anhydride	No	No	No	No	No	No	No

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.

Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

SECTION 12: Ecological information

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC) : 08 01 11

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADR/RID :  **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.
Tunnel code (D/E)

ADN :  The product is only regulated as an environmentally hazardous substance when transported in tank vessels.
Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

IMDG :  **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

SECTION 14: Transport information

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
RAPIFILL 1080-00	≥90	3

Labelling :

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

SECTION 15: Regulatory information

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226 Skin Sens. 1, H317 STOT SE 3, H336 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

SECTION 16: Other information

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 31/03/2026

Date of previous issue : 19/08/2025

Version : 1.02

RAPIFILL 1080-00

All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

