SAFETY DATA SHEET



RENSA ETCHING

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : RENSA ETCHING

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Cleaner.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person

: Prod-safe@teknos.com

responsible for this SDS

National contact

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

1.4 Emergency telephone number

National advisory body/Poison Centre Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Corr. 1, H314 Eye Dam. 1, H318 STOT SE 3, H335

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :





Signal word : Danger

Hazard statements : H314 - Causes severe skin burns and eye damage.

H335 - May cause respiratory irritation.

Precautionary statements

General: P102 - Keep out of reach of children.

Prevention : P280 - Wear protective gloves, protective clothing and eye or face protection.

Response : P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor. P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

Storage : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Hazardous ingredients : methanesulphonic acid

Date of issue/Date of revision: 30/11/2022Date of previous issue: No previous validationVersion: 11/13RENSA ETCHINGLabel No :43064

SECTION 2: Hazards identification

Supplemental label elements

:

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
methanesulphonic acid	REACH #: 01-2119491166-34 EC: 200-898-6 CAS: 75-75-2 Index: 607-145-00-4	≥10 - <25	Met. Corr. 1, H290 Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg	[1]
Oxirane, 2-methyl-, polymer with oxirane, mono- C10-16-alkyl ethers, phosphates	CAS: 68649-29-6	≤3	Skin Irrit. 2, H315 Eye Dam. 1, H318 See Section 16 for the full text of the H	-	[1]
			statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Date of issue/Date of revision: 30/11/2022Date of previous issue: No previous validationVersion: 12/13RENSA ETCHINGLabel No :43064

SECTION 4: First aid measures

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

> watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

: None known.

media

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides

Date of issue/Date of revision : 30/11/2022 Version:1 3/13 Date of previous issue : No previous validation Label No: 43064

RENSA ETCHING

SECTION 5: Firefighting measures

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. The spilled material may be neutralized with sodium carbonate, sodium bicarbonate or sodium hydroxide. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from alkalis. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/Date of revision : 30/11/2022 Date of previous issue Version:1 4/13 : No previous validation **RENSA ETCHING** Label No: 43064

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Separate from alkalis. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
No exposure limit value known.	

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
methanesulphonic acid	DNEL	Long term Inhalation	1.44 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	6.76 mg/m ³		Systemic
	DNEL	Long term Oral	8.33 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	8.33 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	19.44 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.42 mg/m³	General population	Local
	DNEL	Long term Inhalation	0.7 mg/m ³	Workers	Local

PNECs

No PNECs available

8.2 Exposure controls

Date of issue/Date of revision: 30/11/2022Date of previous issue: No previous validationVersion: 15/13RENSA ETCHINGLabel No :43064

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas. vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations: Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm Not recommended polyvinyl alcohol (PVA) gloves

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

: Liquid. Physical state Colour Various Odour Slight Not available. **Odour threshold**

Melting point/freezing point Initial boiling point and

boiling range

: Not available.

Date of issue/Date of revision . 30/11/2022 Version:1 6/13 Date of previous issue : No previous validation

RENSA ETCHING Label No: 43064

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
water	100	212	
methanesulphonic acid	122	251.6	

Flammability : Not available.

Lower and upper explosion

limit

: Lower: Not applicable. Upper: Not applicable.

Flash point : Closed cup: >100°C (>212°F)

Auto-ignition temperature

Ingredient name	°C	°F	Method
methanesulphonic acid	535	995	DIN 51794

Decomposition temperature: Not available.

pH : 0 to 1

Viscosity : Not available.

Solubility(ies) :

Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure :

	Vapour Pressure at 20°C		Va	oour pressu	re at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	23.8	3.2				
methanesulphonic acid	0	0	OECD 104			

Relative density : Not available.

Density : 1.1 g/cm³

Vapour density: Not available.Explosive properties: Not available.Oxidising properties: Not available.

Particle characteristics

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : Attacks many metals producing extremely flammable hydrogen gas which can form

explosive mixtures with air.

Reactive or incompatible with the following materials:

alkalis

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of revision : 30/11/2022 Date of previous issue : No previous validation Version : 1 7/13

RENSA ETCHING Label No :43064

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
methanesulphonic acid	LD50 Oral	Rat	200 mg/kg	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

Route	ATE value	
	2222.22 mg/kg	
Dermal	4888.89 mg/kg	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
methanesulphonic acid	Eyes - Severe irritant	Rabbit	-	0.1 MI	-

Conclusion/Summary

Sensitisation

Mutagenicity

: Causes severe skin burns and eye damage.

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
methanesulphonic acid	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes : Not available.

of exposure

Potential acute health effects

Eye contact : Causes serious eye damage. Inhalation : May cause respiratory irritation.

Skin contact : Causes severe burns.

: No known significant effects or critical hazards. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation Adverse symptoms may include the following:

respiratory tract irritation

coughing

Date of issue/Date of revision : 30/11/2022 Date of previous issue Version :1 8/13 : No previous validation

RENSA ETCHING Label No: 43064

SECTION 11: Toxicological information

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion: Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Conclusion/Summary: This product has not been tested for biodegradation.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
methanesulphonic acid	-2.38	-	low

12.4 Mobility in soil

Soil/water partition : Not available.

coefficient (Koc)

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

Date of issue/Date of revision: 30/11/2022Date of previous issue: No previous validationVersion: 19/13RENSA ETCHINGLabel No :43064

SECTION 12: Ecological information

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

European waste catalogue (EWC)

The classification of the product may meet the criteria for a hazardous waste.
 200129*

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3265	UN3265	UN3265	UN3265
14.2 UN proper shipping name	Corrosive liquid, acidic, organic, n.o.s. (methanesulphonic acid)	Corrosive liquid, acidic, organic, n.o.s. (methanesulphonic acid)	Corrosive liquid, acidic, organic, n.o.s. (methanesulphonic acid)	Corrosive liquid, acidic, organic, n.o.s. (methanesulphonic acid)
14.3 Transport hazard class(es)	8	8	8	8
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

Date of issue/Date of revision: 30/11/2022Date of previous issue: No previous validationVersion: 110/13RENSA ETCHINGLabel No :43064

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Industrial emissions : Listed

(integrated pollution prevention and control) -

Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

Date of issue/Date of revision: 30/11/2022Date of previous issue: No previous validationVersion: 111/13RENSA ETCHINGLabel No :43064

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent. Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Corr. 1, H314	On basis of test data
Eye Dam. 1, H318	On basis of test data
STOT SE 3, H335	Calculation method

Full text of abbreviated H statements

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4	
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
Met. Corr. 1	CORROSIVE TO METALS - Category 1	
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1	
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3	

Date of issue/ Date of

revision

: 30/11/2022

Date of previous issue : No previous validation

Version : 1

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 30/11/2022 12/13 Date of previous issue : No previous validation Label No: 43064

RENSA ETCHING

Date of issue/Date of revision: 30/11/2022Date of previous issue: No previous validationVersion: 113/13RENSA ETCHINGLabel No :43064