

SAFETY DATA SHEET



RENSA WOOD OIL POLISH 4584-00 - All variants

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : RENSA WOOD OIL POLISH 4584-00 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H319 - Causes serious eye irritation.

Precautionary statements

Prevention : P280 - Wear eye or face protection.

Response : P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label elements : Contains Orange, sweet, ext. - and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

SECTION 2: Hazards identification

Annex XVII - Restrictions :
on the manufacture,
placing on the market and
use of certain dangerous
substances, mixtures and
articles

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
ammonium dodecyl sulphate	EC: 218-793-9 CAS: 2235-54-3	<1.5	Skin Irrit. 2, H315 Eye Dam. 1, H318	-	[1]
Poly(oxy-1,2-ethanediyl), α -(3-carboxy-1-oxo-3-sulfopropyl)- ω -(dodecyloxy)-, sodium salt (1:2)	CAS: 39354-45-5	<1.5	Eye Dam. 1, H318	-	[1]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	<1	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
Orange, sweet, ext. -	EC: 232-433-8 CAS: 8028-48-6	≤ 0.3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	-	[1]
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C $\geq 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]
pyrithione zinc	REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7 Index: 613-333-00-7	≤ 0.0015	Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 221 mg/kg ATE [Inhalation (dusts and mists)] = 0.14 mg/l M [Acute] = 1000 M [Chronic] = 10	[1]

SECTION 3: Composition/information on ingredients

			See Section 16 for the full text of the H statements declared above.		
--	--	--	--	--	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Butoxyethanol	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m ³ .

Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Result
-------------------------	--------

SECTION 8: Exposure controls/personal protection

2-Butoxyethanol

DNEL - General population - Long term - Oral

6.3 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Oral

26.7 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

59 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

98 mg/m³

Effects: Systemic

DNEL - General population - Short term - Inhalation

147 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

246 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

426 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

1091 mg/m³

Effects: Systemic

Orange, sweet, ext. -

DNEL - General population - Short term - Dermal

92.9 µg/cm²

Effects: Local

DNEL - Workers - Short term - Dermal

185.8 µg/cm²

Effects: Local

DNEL - General population - Long term - Oral

4.44 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

4.44 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

7.78 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

8.89 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

31.1 mg/m³

Effects: Systemic

1,2-benzisothiazol-3(2H)-one

DNEL - General population - Long term - Dermal

0.345 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

SECTION 8: Exposure controls/personal protection

0.966 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

1.2 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

6.81 mg/m³

Effects: Systemic

pyrithione zinc

DNEL - Workers - Long term - Dermal

0.01 mg/kg bw/day

Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Not recommended polyvinyl alcohol (PVA) gloves

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

SECTION 8: Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Colour : Various
Odour : Slight
Odour threshold : Not available.
Melting point/freezing point : Not available.
Initial boiling point and boiling range :

Ingredient name	°C	°F	Method
water	100	212	

Flammability : Not available.
Lower and upper explosion limit : Lower: Not applicable.
Upper: Not applicable.
Flash point : Closed cup: >100°C (>212°F)
Auto-ignition temperature : Not available.
Decomposition temperature : Not available.
pH : 6.5 to 7.5 [Conc. (% w/w): 100%]
Viscosity : Not available.
Solubility(ies) :
Not available.

Solubility in water : Not available.
Partition coefficient: n-octanol/ water : Not applicable.
Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				

Relative density : Not available.
Density : 1 g/cm³
Vapour density : Not available.
Particle characteristics
Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.
Oxidising properties : Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : No specific data.
- 10.5 Incompatible materials** : No specific data.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

1,2-benzisothiazol-3(2H)-one

pyrithione zinc

Result

Rat - Oral - LD50

1020 mg/kg

Rat - Oral - LD50

177 mg/kg

Rabbit - Dermal - LD50

100 mg/kg

Rat - Inhalation - LC50 Dusts and mists

140 mg/m³ [4 hours]

Toxic effects: Lung, Thorax, or Respiration - Acute pulmonary edema Lung, Thorax, or Respiration - Dyspnea Gross Metabolite Changes - Weight loss or decreased weight gain

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
RENSA WOOD OIL POLISH 4584-00	N/A	N/A	N/A	892.5	N/A
2-Butoxyethanol	1200	N/A	N/A	3	N/A
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
pyrithione zinc	221	N/A	N/A	N/A	0.14

Skin corrosion/irritation

Product/ingredient name

ammonium dodecyl sulphate

Poly(oxy-1,2-ethanediyl), α-(3-carboxy-1-oxo-3-sulfopropyl)-ω-(dodecyloxy)-, sodium salt (1:2)

2-Butoxyethanol

Result

Rabbit - Skin - Severe irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 uL

Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

SECTION 11: Toxicological information

1,2-benzisothiazol-3(2H)-one

Human - Skin - Mild irritant

Duration of treatment/exposure: 48 hours

Amount/concentration applied: 5 %

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

ammonium dodecyl sulphate

Result

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 uL

2-Butoxyethanol

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 100 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Date of issue/Date of revision

: 30/10/2025

Date of previous issue

: No previous validation

Version : 1

10/18

RENSA WOOD OIL POLISH 4584-00 - All variants

Label No : 119980

SECTION 11: Toxicological information

Product/ingredient name

pyrithione zinc

Result

STOT RE 1, H372

Aspiration hazard

Product/ingredient name

Orange, sweet, ext. -

Result

ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary [Product]** : Not available.
General : No known significant effects or critical hazards.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

- Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

2-Butoxyethanol

Result

Acute - LC50 - Marine water

Fish - Inland silverside - *Menidia beryllina*

Size: 40 to 100 mm

1250000 µg/l [96 hours]

Effect: Mortality

Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - *Crangon crangon*

800000 µg/l [48 hours]

Effect: Mortality

1,2-benzisothiazol-3(2H)-one

Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test]

Fish - Trout - *Onorhynchus Mykiss*

1.9 mg/l [96 hours]

Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test]

Daphnia - Daphnia - *Daphnia Magna*

3.7 mg/l [48 hours]

Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test]

Algae - Algae - *Skeletonema Costatum*

0.36 mg/l [72 hours]

Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test]

Algae - Algae - *Skeletonema Costatum*

0.15 mg/l [72 hours]

pyrithione zinc

Acute - EC50 - Marine water

Algae - Diatom - *Thalassiosira pseudonana*

0.51 µg/l [96 hours]

Effect: Population

Chronic - EC10 - Marine water

Algae - Diatom - *Thalassiosira pseudonana*

0.36 µg/l [96 hours]

Effect: Population

Chronic - NOEC - Fresh water

US EPA

Daphnia - Water flea - *Daphnia magna*

2.7 ppb [21 days]

Effect: Growth

Acute - EC50 - Fresh water

US EPA

Daphnia - Water flea - *Daphnia magna*

Age: <24 hours

8.25 ppb [48 hours]

Effect: Intoxication

Acute - LC50 - Fresh water

US EPA

Fish - Fathead minnow - *Pimephales promelas*

Weight: 0.28 g

2.68 ppb [96 hours]

Effect: Mortality

SECTION 12: Ecological information

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name

1,2-benzisothiazol-3(2H)-one

Result

EU

24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-Butoxyethanol	0.81	-	Low
Orange, sweet, ext. -	2.78 to 4.88	1.502 to 2.597	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low
pyrithione zinc	0.9	11 [OECD 305 E]	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
ammonium dodecyl sulphate	3.1	1234.14
2-Butoxyethanol	1.8	67.3685
1,2-benzisothiazol-3(2H)-one	1.9	73.142

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
ammonium dodecyl sulphate	No	No	No	No	No	No	No
Poly(oxy-1,2-ethanediyl), α-(3-carboxy-1-oxo-3-sulfopropyl)-ω-(dodecyloxy)-, sodium salt (1:2)	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
Orange, sweet, ext. -	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
pyrithione zinc	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
ammonium dodecyl sulphate	No	N/A	N/A	No	N/A	N/A	N/A
Poly(oxy-1,2-ethanediyl), α-(3-carboxy-1-oxo-3-sulfopropyl)-ω-(dodecyloxy)-, sodium salt (1:2)	No	N/A	N/A	No	N/A	N/A	N/A
2-Butoxyethanol	No	N/A	N/A	No	N/A	N/A	N/A
Orange, sweet, ext. -	No	N/A	No	No	No	N/A	No
1,2-benzisothiazol-3(2H)-one	No	N/A	No	No	No	N/A	No
pyrithione zinc	No	N/A	No	Yes	No	N/A	No

Regulation (EC) No. 1272/2008 [CLP]

SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
ammonium dodecyl sulphate	No	No	No	No	No	No	No
Poly(oxy-1,2-ethanediyl), α-(3-carboxy-1-oxo-3-sulfopropyl)-ω-(dodecyloxy)-, sodium salt (1:2)	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
Orange, sweet, ext. -	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
pyrithione zinc	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : Avoid release to the environment. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC) : 08.01.11

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-

Date of issue/Date of revision : 30/10/2025 **Date of previous issue** : No previous validation **Version** : 1 **14/18**

RENSA WOOD OIL POLISH 4584-00 - All variants

Label No : 119980

SECTION 14: Transport information

14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADN : The product is only regulated as a dangerous good when transported in tank vessels.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
RENSA WOOD OIL POLISH 4584-00	≥90	3

Mixture is subject to Entry 78 of REACH Annex XVII Restrictions.

Labelling :

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

SECTION 15: Regulatory information

[Chemical Weapon Convention List Schedules I, II & III Chemicals](#)

Not listed.

[Montreal Protocol](#)

Not listed.

[Stockholm Convention on Persistent Organic Pollutants](#)

Not listed.

[Rotterdam Convention on Prior Informed Consent \(PIC\)](#)

Not listed.

[UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

[Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Classification	Justification
Eye Irrit. 2, H319	Calculation method

[Full text of abbreviated H statements](#)

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

[Full text of classifications \[CLP/GHS\]](#)

SECTION 16: Other information

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1

Date of issue/ Date of revision : 30/10/2025

Date of previous issue : No previous validation

Version : 1

RENSA WOOD OIL POLISH 4584-00

All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

