Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET



SILOKSAN CAVE - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier Product name

: SILOKSAN CAVE - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number: In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	Warning
Hazard statements	H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
General	P102 - Keep out of reach of children.
Prevention	P280 - Wear protective gloves. P273 - Avoid release to the environment. P261 - Avoid breathing vapour.
Response	P362 + P364 - Take off contaminated clothing and wash it before reuse.
Storage	Not applicable.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

SECTION 2: Hazards identification

Hazardous ingredients	 Contains: 3-iodo-2-propynyl-butyl carbamate; 4,5-dichloro-2-octyl-2H-isothiazol- 3-one; 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
Supplemental label elements	: ₩arning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for dry film and in-can preservation: IPBC and DCOIT and BIT and EGForm and 2,2'-dithiobis[N- methylbenzamide] and C(M)IT/MIT (3:1) and MBIT and OIT. Risk of skin sensitisation.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

Iffanium dioxide REACH #: 01-2119489379-17 EC: 256-675-5 CAS: 13463-67-7 ≤ 10 Carc. 2, H351 (inhalation) - [1] [*] 3-iodo-2-propynyl-butyl carbamate EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7 ≤ 0.11 Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 ATE [Oral] = 400 mg/kg [1] 4,5-dichloro-2-octyl-2H- isothiazol-3-one EC: 264-843-8 CAS: 64359-81-5 Index: 613-335-00-8 ≤ 0.022 Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Acute 1, H400 Aquatic Acute 1, H410 ATE [Oral] = 567 mg/kg [1] 4.5-dichloro-2-octyl-2H- isothiazol-3-one EC: 264-843-8 CAS: 64359-81-5 Index: 613-335-00-8 ≤ 0.022 Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1, H314 (Justs and mists)] = 0.16 mg/l Skin Corr. 1, H314 (Justs and mists)] = 0.16 mg/l Skin Corr. 1, H314: C $\geq 5\%$ Skin Irnt. 2, H315: 0.025% eC < 5% Eye Dam. 1, H318: C $\geq 3\%$ Eye Irnt. 2, H319: 0.025% eC < 3% Skin Sens. 1, H317: C $\geq 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
carbamateCAS: 55406-53-6 Index: 616-212-00-7Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410 mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Acute] = 10 M [Chronic] = 14,5-dichloro-2-octyl-2H- isothiazol-3-oneEC: 264-843-8 CAS: 64359-81-5 Index: 613-335-00-8 ≤ 0.022 Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410ATE [Oral] = 567 mg/kg ATE [Inhalation (dusts and mists)] $= 0.16 mg/l$ Skin Corr. 1, H314: $C \geq 5\%$ [1] Skin Irrit. 2, H315: $0.025\% \leq C < 3\%$ Eye Dam. 1, H318: $C \geq 3\%$ Eye Irrit. 2, H319: $0.025\% \leq C < 3\%$ Skin Sens. 1, H317; $C \geq 0.0015\%$ M [Acute] = 100	titanium dioxide	01-2119489379-17 EC: 236-675-5	≤10		-	[1] [*]
isothiazol-3-one CAS: 64359-81-5 Index: 613-335-00-8 Acute Tox. 2, H330 $[dusts and mists]$ Skin Corr. 1, H314 $[dusts and mists]$ Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 $C \ge 5\%$ Skin Irrit. 2, H315: 0.025% $\le C < 5\%$ EUH071 Skin Sens. 1, H318: $C \ge 3\%$ Eye Dam. 1, H318: $C \ge 3\%$ Eye Dam. 1, H318: $C \ge 3\%$ Eye Irrit. 2, H319: 0.025% $\le C < 3\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100		CAS: 55406-53-6	≤0.11	Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1,	mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10	[1]
		CAS: 64359-81-5	≤0.022	Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	mg/kg ATE [Inhalation (dusts and mists)] = 0.16 mg/l Skin Corr. 1, H314: C ≥ 5% Skin Irrit. 2, H315: 0.025% ≤ C < 5% Eye Dam. 1, H318: C ≥ 3% Eye Irrit. 2, H319: 0.025% ≤ C < 3% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100	[1]

1,2-benzisothiazol-3(2H)-	EC: 220-120-9	<0.036	Acute Tox. 4, H302	ATE [Oral] = 450	[1]
one	CAS: 2634-33-5 Index: 613-088-00-6		Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C $\geq 0.036\%$ M [Acute] = 1 M [Chronic] = 1	
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	
2-Methyl-1,2-benzisothiazol- 3(2H)-one	EC: 695-989-4 CAS: 2527-66-4 Index: 613-336-00-3	<0.0015	Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 175 mg/kg ATE [Dermal] = 1100 mg/kg Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid	d measures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SECTION 4: First aid measures

Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising f	rom	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

: 16/04/2025 Date of previous issue

SECTION 5: Firefighting measures

Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves)
	conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pr	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmenta pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material fo	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

SECTION 7: Handling and storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3	Specific	end	use(s)	1
_				

Recommendations: Not available.Industrial sector specific: Not available.solutions: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Feaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Regulation on Limit Values - MAC (Austria, 4/2021) [5-Chlor- 2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-di- hydroisothiazol-3-on (Gemisch im Verhältnis 3:1)] Skin sensitiser. TWA 8 hours: 0.05 mg/m ³ .
No exposure limit value known.	
No exposure limit value known.	
Propylene glycol	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) ELV 8 hours: 10 mg/m ³ . Form: only particles. ELV 8 hours: 474 mg/m ³ . Form: total vapour and particles. ELV 8 hours: 150 ppm. Form: total vapour and particles.
No exposure limit value known.	
Fiodo-2-propynyl-butyl carbamate	 TRGS 900 OEL (Germany, 6/2024) Skin sensitiser. PEAK 15 minutes: 0.116 mg/m³. PEAK 15 minutes: 0.01 ppm. TWA 8 hours: 0.058 mg/m³. TWA 8 hours: 0.005 ppm. DFG MAC-values list (Germany, 7/2023) Develop C. Skin sensitiser. PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hour]. PEAK 15 minutes: 0.01 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 0.058 mg/m³. TWA 8 hours: 0.058 mg/m³. TWA 8 hours: 0.059 ppm.
1,2-benzisothiazol-3(2H)-one	DFG MAC-values list (Germany, 7/2023) Skin sensitiser.
No exposure limit value known.	
No exposure limit value known.	
No exposure limit value known.	
Date of issue/Date of revision : 16/04/2025 D	ate of previous issue : 07/09/2022 Version : 6 6/24

SILOKSAN CAVE - All variants

ECTION 8: Exposure controls/personal protection			
Propylene glycol	 NAOSH (Ireland, 4/2024) Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV 8 hours: 10 mg/m³. Form: particulate. OELV 8 hours: 470 mg/m³. Form: vapour and particulates. OELV 8 hours: 150 ppm. Form: vapour and particulates. 		
No exposure limit value known.			
Propylene glycol	Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) TWA 8 hours: 7 mg/m ³ .		
✓ropylene glycol	Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) TWA 8 hours: 7 mg/m ³ .		
No exposure limit value known.			
No exposure limit value known.			
No exposure limit value known.			
Propylene glycol	FOR-2011-12-06-1358 (Norway, 12/2022) TWA 8 hours: 79 mg/m³. TWA 8 hours: 25 ppm.		
▶ ropylene glycol	Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 8/2023) TWA 8 hours: 100 mg/m ³ . Form: vapor and inhalable fraction.		
No exposure limit value known.			
No exposure limit value known.			
No exposure limit value known.			
<mark>≆</mark> -iodo-2-propynyl-butyl carbamate	 Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) KTV 15 minutes: 0.01 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes] TWA 8 hours: 0.005 ppm. KTV 15 minutes: 0.116 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes] TWA 8 hours: 0.058 mg/m³. 		
No exposure limit value known.			
No exposure limit value known.			
3-iodo-2-propynyl-butyl carbamate	SUVA (Switzerland, 1/2024) Sensitiser. STEL 15 minutes: 0.24 mg/m ³ . Form: vapour and aerosols. STEL 15 minutes: 0.02 ppm. Form: vapour and aerosols. TWA 8 hours: 0.01 ppm. Form: vapour and aerosols. TWA 8 hours: 0.12 mg/m ³ . Form: vapour and aerosols.		
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	SUVA (Switzerland, 1/2024) Sensitiser. STEL 15 minutes: 0.4 mg/m ³ . Form: Inhalable fraction. TWA 8 hours: 0.2 mg/m ³ . Form: Inhalable fraction.		
No exposure limit value known.			
Biological exposure indices			
Product/ingredient name	Exposure indices		
No exposure indices known.			
No exposure indices known.			
No exposure indices known			

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

Date of issue/Date of revision SILOKSAN CAVE - All variants : 16/04/2025 Date of previous issue

Version : 6 7/24 Label No : 15583

SECTION 8: Exposure	controls/pe	ersonal protection
No exposure indices known.		
No exposure indices known.		
No exposure indices known.		
Recommended monitoring : procedures	European Stand assessment of e values and mea atmospheres - C of exposure to c (Workplace atm for the measure	ald be made to monitoring standards, such as the following: dard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit asurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 hospheres - General requirements for the performance of procedures ement of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be
DNELs/DMELs		
Product/ingredient name		Result
iitanium dioxide		DNEL - General population - Long term - Inhalation 28 μg/m³ <u>Effects</u> : Local
		DNEL - Workers - Long term - Inhalation 170 μg/m³ <u>Effects</u> : Local
3-iodo-2-propynyl-butyl carbam	ate	DNEL - Workers - Long term - Inhalation 0.023 mg/m³ <u>Effects</u> : Systemic
		DNEL - Workers - Short term - Inhalation
Date of issue/Date of revision	· 16/04/2025	te of previous issue : 07/09/2022 Version : 6 8/24

: 16/04/2025 Date of previous issue

	-
	0.07 mg/m³ <u>Effects</u> : Systemic
	DNEL - Workers - Short term - Inhalation 1.16 mg/m³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Inhalation 1.16 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Dermal 2 mg/kg bw/day <u>Effects</u> : Systemic
1,2-benzisothiazol-3(2H)-one	DNEL - General population - Long term - Dermal 0.345 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 0.966 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 1.2 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 6.81 mg/m ³ <u>Effects</u> : Systemic
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL - General population - Long term - Inhalation 0.02 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Inhalation 0.02 mg/m ³ <u>Effects</u> : Local
	DNEL - General population - Short term - Inhalation 0.04 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Short term - Inhalation 0.04 mg/m ³ <u>Effects</u> : Local
	DNEL - General population - Long term - Oral 0.09 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Short term - Oral 0.11 mg/kg bw/day <u>Effects</u> : Systemic
<u>PNECs</u> Not available.	
8.2 Exposure controlsAppropriate engineering controls: Good general contaminants	l ventilation should be sufficient to control worker exposure to airborne S.
Date of issue/Date of revision: 16/04/2025SILOKSAN CAVE - All variants	Date of previous issue : 07/09/2022 Version : 6 9/24 Label No<:

SECTION 8: Exposure controls/personal protection

SECTION 8: Exposure controls/personal protection

•	• •	
Individual protection measu		
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working perio Appropriate techniques should be used to remove potentially contaminated clothi Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.	
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mist gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses wi side-shields.	ts,
Skin protection		
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard show be worn at all times when handling chemical products if a risk assessment indicat this is necessary. Considering the parameters specified by the glove manufactur check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.	tes er,
	Recommendations : Wear suitable gloves tested to EN374.	
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm	
	Not recommended polyvinyl alcohol (PVA) gloves	
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	ί
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	3
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other importa aspects of use.	
	Filter type (spray application): A P	
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the proces equipment will be necessary to reduce emissions to acceptable levels.	

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	÷
Ingradient neme	•

	Ingredient name	°C	°F	Method
	water	100	212	
	Propylene glycol	188.2	370.8	
F	lammability : Not ava	ilable.		

Flammability	:	Not ava

: 16/04/2025 Date of previous issue

SECTION 9: Physical and chemical properties Lower and upper explosion : Kower: 2.6% (propane-1.2-diol) Upper: 12.6% (propane-1,2-diol) limit Closed cup: >100°C (>212°F) **Flash point** 2 **Auto-ignition temperature** ÷. Ingredient name °C °F Method Propylene glycol 371 699.8 2,2,4-trimethylpentane-1,3-diol isobutyrate 393 7394 : Not available. **Decomposition temperature** 8.5 to 9.2 [Conc. (% w/w): 100%] pН 2 ÷. Not available. Viscosity Solubility(ies) t Not available. : Not available. Solubility in water Partition coefficient: n-octanol/ : Not applicable. water ż Vapour pressure Vapour Pressure at 20°C Vapour pressure at 50°C kPa Method kPa **Method** Ingredient name mm Hg mm Hg water 17.5 2.3 0.15 EU A.4 Propylene glycol 0.02 **Relative density** : Not available. Density : 1.3 g/cm³ Vapour density : Not available. **Particle characteristics** Median particle size : Not applicable. 9.2 Other information 9.2.1 Information with regard to physical hazard classes **Explosive properties** : Not available. **Oxidising properties** : Not available. 9.2.2 Other safety characteristics Not applicable. **SECTION 10: Stability and reactivity 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients. : The product is stable. **10.2 Chemical stability** 10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions 10.4 Conditions to avoid : No specific data. 10.5 Incompatible materials : No specific data. 10.6 Hazardous : Under normal conditions of storage and use, hazardous decomposition products should not be produced. decomposition products

: 16/04/2025 Date of previous issue

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

3-iodo-2-propynyl-butyl carbamate

Result

Rat - Oral - LD50 400 mg/kg

Rat - Dermal - LD50 >2000 mg/kg

Rat - Inhalation - LC50 Dusts and mists 0.763 mg/l [4 hours]

Rat - Inhalation - LC50 Dusts and mists 0.67 g/m³ [4 hours]

4,5-dichloro-2-octyl-2H-isothiazol-3-one

Rat - Oral - LD50 1585 mg/kg OECD [Acute Oral Toxicity]

Rabbit - Dermal - LD50 >652 mg/kg OECD [Acute Dermal Toxicity]

Rat - Male, Female - Inhalation - LC50 Dusts and mists 0.26 mg/l [4 hours] OECD [Acute Inhalation Toxicity]

1,2-benzisothiazol-3(2H)-one

Rat - Oral - LD50 1020 mg/kg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Rat - Oral - LD50

53 mg/kg <u>Toxic effects</u>: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration -Respiratory depression

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
SILOKSAN CAVE	N/A	N/A	N/A	N/A	630.4
3-iodo-2-propynyl-butyl carbamate	400	N/A	N/A	N/A	0.67
4,5-dichloro-2-octyl-2H-isothiazol-3-one	567	N/A	N/A	N/A	0.16
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	53	50	N/A	0.5	N/A
2-Methyl-1,2-benzisothiazol-3(2H)-one	175	1100	N/A	N/A	N/A

Skin corrosion/irritation Product/ingredient name

Result

Human - Skin - Mild irritant Duration of treatment/exposure: 72 hours Amount/concentration applied: 300 ug l

1,2-benzisothiazol-3(2H)-one

Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %

Date of issue/Date of revision SILOKSAN CAVE - All variants : 16/04/2025 Date of previous issue

SECTION 11: Toxicological informat	ion
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Human - Skin - Severe irritant Amount/concentration applied: 0.01 %
Conclusion/Summary [Product] : Not availabl	e.
Serious eye damage/eye irritation	
Product/ingredient name	Result
 	Rabbit - Eyes - Severe irritant
Conclusion/Summary [Product] : Not availabl	e.
Respiratory corrosion/irritation	
Not available.	
Conclusion/Summary [Product] : Not availabl	e.
Respiratory or skin sensitization	
Product/ingredient name	Result
J-iodo-2-propynyl-butyl carbamate	Guinea pig - skin <u>Result</u> : Not sensitizing
Skin	
Conclusion/Summary [Product] : Not availabl	e.
Respiratory	
Conclusion/Summary [Product] : Not availabl	е.
Germ cell mutagenicity	
Product/ingredient name	Result
3-iodo-2-propynyl-butyl carbamate	In vitro - Bacteria <u>Result</u> : Negative
Conclusion/Summary [Product] : Not availabl	e.
<u>Carcinogenicity</u>	
It has been observed that the carcinogenic hazard o leading to significant impairment of particle clearanc Not available.	f this product arises when respirable dust is inhaled in quantities e mechanisms in the lung.
Conclusion/Summary [Product] : Not availabl	e.
Reproductive toxicity	
Product/ingredient name	Result
iodo-2-propynyl-butyl carbamate	Rabbit - Female - Oral
	50 mg/kg [7 days per week] [13 days] Maternal toxicity: Positive
	<u>Developmental</u> : Negative
	Rabbit - Female - Oral

Rabbit - Female - Oral 20 mg/kg [7 days per week] [13 days] <u>Maternal toxicity</u>: Negative <u>Developmental</u>: Negative

: 16/04/2025 Date of previous issue

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Not available.

Product/ingredient name	Result
Fiodo-2-propynyl-butyl carba	ate STOT RE 1, H372 (larynx)
Aspiration hazard	
Not available.	
Information on likely routes	<u>f exposure</u>
Not available. Potential acute health effect	
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	sical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
-	s as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects Potential chronic health effe	: Not available. ts
Not available.	
Conclusion/Summary [Pro General	 uct] : Not available. : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
1.2 Information on other ha	rds
11.2.1 Endocrine disrupting Not available.	roperties
Conclusion/Summary [Pro	 interproduct does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC No. 1907/2006 or Regulation (EC) No 1272/2008.
11.2.2 Other information Not available.	

SILOKSAN CAVE - All variants

SECTION 12: Ecological information

12.1 Toxicity Product/ingredient name

titanium dioxide

3-iodo-2-propynyl-butyl carbamate

4,5-dichloro-2-octyl-2H-isothiazol-3-one

Result

Acute - LC50 - Marine water

Fish - Mummichog - *Fundulus heteroclitus* >100000 µg/l [96 hours] <u>Effect</u>: Mortality

Acute - LC50 - Fresh water

Crustaceans - Water flea - *Ceriodaphnia dubia* - Neonate <u>Age</u>: <24 hours 3 mg/l [48 hours] <u>Effect</u>: Mortality

Acute - LC50 - Fresh water

EU Fish - Trout - *Oncorhynchus mykiss* 0.067 mg/l [96 hours]

Acute - NOEC - Fresh water

EU Fish - Trout - *Oncorhynchus mykiss* 0.049 mg/l [96 hours]

Acute - EC50 - Fresh water

EU Daphnia - Daphnia - *Daphnia magna* 0.16 mg/l [48 hours]

Chronic - NOEC - Fresh water

EU Daphnia - Daphnia - *Daphnia Magna* 0.05 mg/l [21 days]

Acute - EC50 - Fresh water

EU Algae - Algae - *Scenedemus subspicatus* 0.022 mg/l [72 hours]

Acute - EC50 - Fresh water

Algae - Green algae - *Pseudokirchneriella subcapitata* 0.003 mg/l [72 hours] Effect: Population

Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna* 0.001 mg/l [48 hours] <u>Effect</u>: Intoxication

Acute - LC50 - Fresh water

US EPA Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss* <u>Weight</u>: 1.2 g 2.7 ppb [96 hours] <u>Effect</u>: Mortality

Chronic - NOEC

US EPA Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss* 0.56 ppb [97 days] <u>Effect</u>: Growth

Chronic - NOEC - Marine water OECD Algae - Diatom - *Nitzschia pungen*

Algae - Diatom - Nitzschia pungens

: 16/04/2025 Date of previous issue

e : 07/09/2022

SECTION 12: Ecological informa	ation
	19.789 µg/l [96 hours] <u>Effect</u> : Population
1,2-benzisothiazol-3(2H)-one	Acute - LC50 - Fresh water OECD [Fish, Acute Toxicity Test] Fish - Trout - <i>Onorhynchus Mykiss</i> 1.9 mg/l [96 hours]
	Acute - EC50 OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - <i>Daphnia Magna</i> 3.7 mg/l [48 hours]
	Acute - EC50 - Marine water OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.36 mg/l [72 hours]
	Acute - NOEC - Marine water OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.15 mg/l [72 hours]
2-Methyl-1,2-benzisothiazol-3(2H)-one	Acute - EC50 - Fresh water US EPA Daphnia - Water flea - <i>Daphnia magna</i> <u>Age</u> : <24 hours 0.92 ppm [48 hours] <u>Effect</u> : Intoxication
	Acute - EC50 - Fresh water US EPA Algae - Green algae - <i>Pseudokirchneriella subcapitata</i> 0.22 ppm [96 hours] <u>Effect</u> : Population
	Acute - LC50 - Fresh water US EPA Fish - Rainbow trout,donaldson trout - <i>Oncorhynchus mykiss</i> Juvenile (Fledgling, Hatchling, Weanling) 0.24 ppm [96 hours] <u>Effect</u> : Mortality
	Chronic - NOEC US EPA Fish - Fathead minnow - <i>Pimephales promelas</i> 0.16 ppm [32 days]
Conclusion/Summary [Product] : Not av	vailable.
12.2 Persistence and degradability Product/ingredient name 17,2-benzisothiazol-3(2H)-one	<mark>Result</mark> EU 24% [28 days]
Conclusion/Summary [Product] · · Not a	valable

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-li	fe	Photolysis	i	Biodegradabi	lity	
riodo-2-propynyl-butyl carbamate	-		-		Not readily		
1,2-benzisothiazol-3(2H)-one	-		-		Inherent		
Date of issue/Date of revision	: 16/04/2025	Date of previous	issue	:07/09/2022	Version :	6	16/24

SILOKSAN CAVE - All variants

ſ

Label No : 1715583

SECTION 12: Ecological information

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
	>1	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
₿-iodo-2-propynyl-butyl carbamate	1.13	13.4558
4,5-dichloro-2-octyl-2H-isothiazol-3-one	3.41	2562.01
1,2-benzisothiazol-3(2H)-one	1.86	73.142
2-Methyl-1,2-benzisothiazol-3(2H)-one	1.72	52.5063

Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	М	Т	vPvM	vP	٧M
titanium dioxide	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
4,5-dichloro-2-octyl-2H- isothiazol-3-one	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No
2-Methyl-1,2-benzisothiazol- 3(2H)-one	No	No	No	No	No	No	No
Mobility	: Not av	ailable.			I		

Conclusion/Summary

: $\overline{\mathbf{r}}$ he product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Ρ	В	Т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
4,5-dichloro-2-octyl-2H- isothiazol-3-one	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No
2 ⁻ Methyl-1,2-benzisothiazol- 3(2H)-one	No	No	No	No	No	No	No

Regulation (EC) No. 1272/2008 [CLP]

SECTION 12: Ecological information

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
ti tanium dioxide	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
4,5-dichloro-2-octyl-2H- isothiazol-3-one	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No
2-Methyl-1,2-benzisothiazol- 3(2H)-one	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

```
Conclusion/Summary [Product]
```

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
European waste catalogue (EWC)	: 080111*, 200127*
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

SECTION 14: Transport information						
	ADR/RID	ADN	IMDG	IATA		
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.		
14.2 UN proper shipping name	-	-	-	-		
14.3 Transport hazard class(es)	-	-	-	-		
14.4 Packing group	-	-	-	-		
14.5 Environmental hazards	No.	No.	No.	No.		

: Not relevant/applicable due to nature of the product.

user

14.6 Special precautions for : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]	
SILOKSAN CAVE	≥90	3	
Labelling :			
Other EU regulations			
Industrial emissions : Not liste (integrated pollution prevention and control) - Air	d		
Industrial emissions : Not liste (integrated pollution prevention and control) - Water	d		
Explosive precursors : Not appl	icable.		
Ozone depleting substances (EU 2024	<u>/590)</u>		
Not listed.			
Prior Informed Consent (PIC) (649/201	<u>2/EU)</u>		
Not listed.			
Persistent Organic Pollutants			
ate of issue/Date of revision : 16/04/2	025 Date of prev	ious issue : 07/09/2022	Version : 6 19/24
ILOKSAN CAVE - All variants			Label No :115583

Seveso Directive					
This product is not controlled	under the Seveso Directive.				
ational regulations					
Austria					
Limitation of the use of	: Permitted.				
organic solvents					
<u>Belgium</u>					
Book VI carcinogenic agen	<u>ts annex VI.2-1 - VI.2-3</u>				
Ingredient name			Status		
Noirs de charbon			Listed		
Czech Republic					
Storage code	: 🕅				
Denmark	. P V				
Fire class	: 🕅-1				
Executive Order No. 1795/2					
Ingredient name		Annex I Section A	Annex Section B		
titanium dioxide			Annex I Section B		
manium dioxide		Listed	-		
MAL-code	: 1-3				
	General: Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.				
	respiratory protection and arm prote		bllowing must be worr		
	respiratory protection and arm prote	ctors/apron/coveralls/prot or knife, brush, roller, etc,	ollowing must be worr tective clothing as for pre- and post-		
	 respiratory protection and arm prote appropriate or as instructed. MAL-code: 1-3 Application: When using scraper of treatments in cabins or booths of the scraper of the scraper	ctors/apron/coveralls/prot or knife, brush, roller, etc,	ollowing must be worn tective clothing as for pre- and post-		
	MAL-code: 1-3 MAL-code: 1-3 Application: When using scraper of treatments in cabins or booths of the the spray zone.	ctors/apron/coveralls/prot or knife, brush, roller, etc, e existing* facility type, if t air in closed facilities, spr	ollowing must be worr tective clothing as for pre- and post- the operator is inside		
	 respiratory protection and arm prote appropriate or as instructed. MAL-code: 1-3 Application: When using scraper of treatments in cabins or booths of the the spray zone. Coveralls must be worn. During downtimes, cleaning and rep 	ctors/apron/coveralls/prof or knife, brush, roller, etc, e existing* facility type, if t air in closed facilities, spr int or organic solvents.	ollowing must be worr tective clothing as for pre- and post- the operator is inside		
	 respiratory protection and arm prote appropriate or as instructed. MAL-code: 1-3 Application: When using scraper of treatments in cabins or booths of the the spray zone. Coveralls must be worn. During downtimes, cleaning and rep there is a risk of contact with wet pair 	ctors/apron/coveralls/prof or knife, brush, roller, etc, e existing* facility type, if t air in closed facilities, spr int or organic solvents.	ollowing must be worr tective clothing as for pre- and post- the operator is inside ray booths or cabins,		
	 respiratory protection and arm prote appropriate or as instructed. MAL-code: 1-3 Application: When using scraper of treatments in cabins or booths of the the spray zone. Coveralls must be worn. During downtimes, cleaning and rep there is a risk of contact with wet pair - Gas filter mask and coveralls must 	ctors/apron/coveralls/prof or knife, brush, roller, etc, e existing* facility type, if t air in closed facilities, spr int or organic solvents. be worn. oths, if the operator is our	bllowing must be worr tective clothing as for pre- and post- the operator is inside ray booths or cabins, tside the spray zone.		
	 respiratory protection and arm prote appropriate or as instructed. MAL-code: 1-3 Application: When using scraper of treatments in cabins or booths of the the spray zone. Coveralls must be worn. During downtimes, cleaning and rep there is a risk of contact with wet pair - Gas filter mask and coveralls must When spraying in existing* spray bo 	ctors/apron/coveralls/prof or knife, brush, roller, etc, e existing* facility type, if t air in closed facilities, spr int or organic solvents. be worn. oths, if the operator is our protectors and apron mu isting* facilities of the cor	bllowing must be worr tective clothing as for pre- and post- the operator is inside ray booths or cabins, tside the spray zone. ust be worn. nbined-cabin, spray-		
	 respiratory protection and arm prote appropriate or as instructed. MAL-code: 1-3 Application: When using scraper of treatments in cabins or booths of the the spray zone. Coveralls must be worn. During downtimes, cleaning and rep there is a risk of contact with wet pair - Gas filter mask and coveralls must When spraying in existing* spray bo Full mask with combined filter, arm During non-atomising spraying in ex 	ctors/apron/coveralls/prof or knife, brush, roller, etc, e existing* facility type, if t air in closed facilities, spr int or organic solvents. be worn. oths, if the operator is our protectors and apron mu isting* facilities of the cor ie operator is working ins	bllowing must be worr tective clothing as for pre- and post- the operator is inside ray booths or cabins, tside the spray zone. ust be worn. nbined-cabin, spray-		

- Air-supplied full mask, coveralls and hood must be worn.

		Drying: Items for drying/drying ovens that are temporarily placed on such the rack trolleys, etc, must be equipped with a mechanical exhaust system to prefumes from wet items from passing through workers' inhalation zone.	•
		Polishing: When polishing treated surfaces, a mask with dust filter must be When machine grinding, eye protection must be worn. Work gloves must alworn.	
		Caution The regulations contain other stipulations in addition to the above.	
		*See Regulations.	
Restrictions on use	:	Not to be used by professional users below 18 years of age. See the Nation Working Environment Authorities Executive Order regarding Young People	
List of undesirable substances	:	Not listed	
Carcinogenic waste	:	Waste containers must be labeled: Contains a substance or substances reg by Danish working environment legislation on cancer risks.	gulated
Finland			
France			
Reinforced medical surveillance	:	Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable	ł
Germany			
Storage class (TRGS 510	n :	10	
Hazardous incident ordin			
		- nder the Germany Hazardous Incident Ordinance.	
•	eu ui	-	
Hazard class for water	1	3	
Technical instruction on	air q	uality control (I A Luft)	
Number [Class]		Description	%
5.2.1		Total dust	48.3
5.2.5		Organic substances Organic substances	4.2 0.42
5.2.5 [I] AOX	:	The product contains organically bound halogens and can contribute to the	-
		value in waste water.	
<u>Italy</u>			
D.Lgs. 152/06	:	Not determined.	
Netherlands			
Water Discharge Policy (ABM)	:	A(2) Toxic for aquatic organisms, may have long-term hazardous effects in environment. Decontamination effort: A	aquati
Norway			
Product registration number		6 72186	
Sweden	:		
	:		
Switzerland	:		
		Exempt	
VOC content		Exempt.	
VOC content	:		
VOC content nternational regulations hemical Weapon Conven	:	Exempt. List Schedules I, II & III Chemicals	
<u>Switzerland</u> VOC content <u>nternational regulations</u> <u>chemical Weapon Conven</u> Not listed.	:		
VOC content nternational regulations hemical Weapon Conven	:		
VOC content nternational regulations chemical Weapon Conven Not listed. Iontreal Protocol	:		
VOC content <u>nternational regulations</u> <u>hemical Weapon Conven</u> Not listed. <u>Iontreal Protocol</u> Not listed.	:	List Schedules I, II & III Chemicals	
VOC content <u>iternational regulations</u> <u>hemical Weapon Conven</u> lot listed. <u>Iontreal Protocol</u>	: ntion		21/2

SILOKSAN CAVE - All variants

SECTION 15: Regulatory information

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety	1	This product contains substances for which Chemical Safety Assessments are still
assessment		required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
uoronymo	1272/2008]
	-
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
	Calculation method Calculation method

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1

Date of issue/Date of revision	: 16/04/2025	Date of previous issue	:07/09/2022	Version	:6	22/24
SILOKSAN CAVE - All variants				Label No	1155	83

SECTION 16: Of	ner information	
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C	
Skin Irrit. 2 Skin Sens. 1	SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1	
Skin Sens. 1A STOT RE 1	SKIN SENSITISATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1	
Date of issue/ Date of revision	: 16/04/2025	
Date of previous issue	: 07/09/2022	
Version	: 6	
	SILOKSAN CAVE All variants	

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision SILOKSAN CAVE - All variants : 16/04/2025 Date of previous issue