Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

SAFETY DATA SHEET



SILOKSAN FACADE - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier
Product name

: SILOKSAN FACADE - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

- Telephone number
- : Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Members of the public Number (8 am-10 pm): +353 (0)1 809 2166 Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	: Warning
Hazard statements	 H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
General	: P102 - Keep out of reach of children.
Prevention	: P280 - Wear protective gloves. P273 - Avoid release to the environment. P261 - Avoid breathing vapour.
Response	: P362 + P364 - Take off contaminated clothing and wash it before reuse.
Storage	: Not applicable.

SECTION 2: Hazards identification

SECTION 2: Hazarus		IEIIIIICALIUII
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Contains: 4,5-dichloro-2-octyl-2H-isothiazol-3-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
Supplemental label elements	:	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for dry film and in-can preservation: IPBC and DCOIT and EGForm and C(M)IT/MIT (3:1) and OIT. Risk of skin sensitisation.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do	:	None known.

not result in classification

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 400 mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
4,5-dichloro-2-octyl-2H- isothiazol-3-one	EC: 264-843-8 CAS: 64359-81-5 Index: 613-335-00-8	≤0.023	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 567 mg/kg ATE [Inhalation (dusts and mists)] = 0.16 mg/l Skin Corr. 1, H314: $C \ge 5\%$ Skin Irrit. 2, H315: 0.025% $\le C < 5\%$ Eye Dam. 1, H318: $C \ge 3\%$ Eye Irrit. 2, H319: 0.025% $\le C < 3\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
Date of issue/Date of revision	: 30/04/2025 Date	e of previous is	ssue : 16/04/2025	Version : 3	2/18
SILOKSAN FACADE - All va	riants			Label No :115	598

SECTION 3. Composition/information on ingredients

or of the station of							
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]		
			See Section 16 for the full text of the H statements declared above.				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower Eve contact eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs. Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. 2 If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Skin contact Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. Ingestion : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. **Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Date of issue/Date of revision : 30/04/2025 Date of previous issue · 16/04/2025 Version : 3 3/18 SILOKSAN FACADE - All variants Label No:115598

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed **Over-exposure signs/symptoms** Eye contact : No specific data. Inhalation : No specific data. **Skin contact** : Adverse symptoms may include the following: irritation redness Ingestion : No specific data. 4.3 Indication of any immediate medical attention and special treatment needed Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. : No specific treatment. Specific treatments **SECTION 5: Firefighting measures**

5.1 Extinguishing media Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising f	irom	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Date of issue/Date of revision	: 30/04/2025	Date of previous issue	: 16/04/2025	Version	: 3	4/18
SILOKSAN FACADE - All variants				Label No	:11559	98

SECTION 6: Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations Industrial sector spec : Not available.

Industrial sector specific solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
No exposure limit value known.	

Biological exposure indices

Date of issue/Date of revision SILOKSAN FACADE - All variants :16/04/2025

Product/ingredient name	Exposure indices
No exposure indices known.	
brocedures European Standa assessment of exvalues and meas atmospheres - G of exposure to ch (Workplace atmos for the measurem	d be made to monitoring standards, such as the following: ard EN 689 (Workplace atmospheres - Guidance for the xposure by inhalation to chemical agents for comparison with limit surement strategy) European Standard EN 14042 (Workplace nuide for the application and use of procedures for the assessment hemical and biological agents) European Standard EN 482 ospheres - General requirements for the performance of procedure nent of chemical agents) Reference to national guidance hethods for the determination of hazardous substances will also be
DNELs/DMELs	
Product/ingredient name	Result
titanium dioxide	DNEL - General population - Long term - Inhalation 28 μg/m³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Inhalation 170 μg/m³ <u>Effects</u> : Local
3-iodo-2-propynyl-butyl carbamate	DNEL - Workers - Long term - Inhalation 0.023 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Short term - Inhalation 0.07 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Short term - Inhalation 1.16 mg/m³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Inhalation 1.16 mg/m³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Dermal 2 mg/kg bw/day <u>Effects</u> : Systemic
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL - General population - Long term - Inhalation 0.02 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Inhalation 0.02 mg/m³ <u>Effects</u> : Local
	DNEL - General population - Short term - Inhalation 0.04 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Short term - Inhalation 0.04 mg/m³ <u>Effects</u> : Local
	DNEL - General population - Long term - Oral 0.09 mg/kg bw/day <u>Effects</u> : Systemic

:16/04/2025

SECTION 8: Exposure controls/personal protection

DNEL - General population - Short term - Oral 0.11 mg/kg bw/day <u>Effects</u>: Systemic

PNECs

Not available.

8.2 Exposure controls		
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airbo contaminants.	rne
Individual protection meas	<u>ires</u>	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated cloth Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.	
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a ris assessment indicates this is necessary to avoid exposure to liquid splashes, mis gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses w side-shields.	sts,
Skin protection		
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard sho be worn at all times when handling chemical products if a risk assessment indica this is necessary. Considering the parameters specified by the glove manufactu check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.	ates irer,
	Recommendations : Wear suitable gloves tested to EN374.	
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm	
	Not recommended polyvinyl alcohol (PVA) gloves	
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	k
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should b approved by a specialist before handling this product.	е
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other import aspects of use.	
	Filter type (spray application): A P	
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation In some cases, fume scrubbers, filters or engineering modifications to the proces equipment will be necessary to reduce emissions to acceptable levels.	

: 30/04/2025 Date of previous issue

: 16/04/2025

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and	:
boiling range	

	Ingredient name			°C	°F	Method
	water			100	212	
F	lammability	:	Not avail	lable.		ļ]
	ower and upper explosion mit	:		lot applicable. lot applicable.		
F	lash point	:	Closed c	up: >100°C (>212	²°F)	
A	uto-ignition temperature	:	Not avail	lable.		
D	ecomposition temperature	:	Not avail	lable.		
р	н	:	8.5 to 9.2	2 [Conc. (% w/w):	100%]	
V	/iscosity	:	Not avail	lable.		
S	olubility(ies) Not available.	:				
S	olubility in water	:	Not avail	lable.		
	artition coefficient: n-octanol/ /ater	:	Not appli	icable.		

Vapour pressure

	Va	apour Press	sure at 20°C	V	apour pres	sure at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
Relative density	: Not	available.				
Density	: 1.4	g/cm³				
Vapour density	: Not	available.				
Particle characteristics						
Median particle size	: Not	applicable.				

9.2 Other information

9.2.1 Information with regard to physical hazard classesExplosive properties: Not available.Oxidising properties: Not available.

ŝ

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stabilit	ty and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in	Regulation (EC) No 1272/2008
Acute toxicity	
Product/ingredient name	Result
3-iodo-2-propynyl-butyl carbamate	Rat - Oral - LD50 400 mg/kg
	Rat - Dermal - LD50 >2000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists 0.763 mg/l [4 hours]
	Rat - Inhalation - LC50 Dusts and mists 0.67 g/m ³ [4 hours]
4,5-dichloro-2-octyl-2H-isothiazol-3-one	Rat - Oral - LD50 1585 mg/kg OECD [Acute Oral Toxicity]
	Rabbit - Dermal - LD50 >652 mg/kg OECD [Acute Dermal Toxicity]
	Rat - Male, Female - Inhalation - LC50 Dusts and mists 0.26 mg/l [4 hours] OECD [Acute Inhalation Toxicity]
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Rat - Oral - LD50 53 mg/kg <u>Toxic effects</u> : Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression
Conclusion/Summary [Product] : Not availa	able.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists (mg/l)
3-iodo-2-propynyl-butyl carbamate 4,5-dichloro-2-octyl-2H-isothiazol-3-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	400 567 53	N/A N/A 50	N/A N/A N/A	N/A N/A 0.5	0.67 0.16 N/A
kin corrosion/irritation					
Product/ingredient name	Result				
itanium dioxide	Human - S		itant (<u>posure</u> : 72 ho <u>pplied</u> : 300 uç		
reaction mass of: 5-chloro-2-methyl- 1-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)		Skin - Severe oncentration a	i rritant pplied: 0.01 %	0	
Conclusion/Summary [Product] : Not availab	le.				
erious eye damage/eye irritation					
Product/ingredient name	Result				
3-iodo-2-propynyl-butyl carbamate	Rabbit - E	yes - Severe	irritant		
Conclusion/Summary [Product] : Not availab	le.				
Respiratory corrosion/irritation Not available.					
Conclusion/Summary [Product] : Not availab	le.				
espiratory or skin sensitization					
Product/ingredient name	Result				
3-iodo-2-propynyl-butyl carbamate	Guinea pi <u>Result</u> : No	g - skin t sensitizing			
Skin					
Conclusion/Summary [Product] : Not availab	le.				
Respiratory					

Germ cell mutagenicity Product/ingredient name 3-iodo-2-propynyl-butyl carbamate

Result

In vitro - Bacteria Result: Negative

Conclusion/Summary [Product] : Not available.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Date of issue/Date of revision	: 30/04/2025	Date of previous issue	: 16/04/2025	Version : 3 10/18
SILOKSAN FACADE - All variants				Label No :115598

SECTION 11: Toxicological information

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Product/ingredient name 3-iodo-2-propynyl-butyl carbamate

Result

Rabbit - Female - Oral 50 mg/kg [7 days per week] [13 days] <u>Maternal toxicity</u>: Positive <u>Developmental</u>: Negative

Rabbit - Female - Oral 20 mg/kg [7 days per week] [13 days] <u>Maternal toxicity</u>: Negative <u>Developmental</u>: Negative

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Not available.

Product/ingredient name	Result
3-iodo-2-propynyl-butyl carbamate	STOT RE 1, H372 (larynx)

Aspiration hazard

Not available.

Information on likely routes	of	oxposuro.
Not available.	01	exposure
Potential acute health effect	te	
		No known aignificant affacts or aritical bazarda
Eye contact		No known significant effects or critical hazards.
Inhalation		No known significant effects or critical hazards.
Skin contact	1	May cause an allergic skin reaction.
Ingestion	1	No known significant effects or critical hazards.
Symptoms related to the ph	ysi	cal, chemical and toxicological characteristics
Eye contact	1	No specific data.
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Delayed and immediate effe	cts	as well as chronic effects from short and long-term exposure
Delayed and immediate effe Short term exposure	<u>cts</u>	as well as chronic effects from short and long-term exposure
		as well as chronic effects from short and long-term exposure Not available.
Short term exposure Potential immediate	:	
Short term exposure Potential immediate effects	:	Not available.
Short term exposure Potential immediate effects Potential delayed effects	:	Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate	: :	Not available. Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects	: : :	Not available. Not available. Not available. Not available.
Short term exposurePotential immediateeffectsPotential delayed effectsLong term exposurePotential immediateeffectsPotential delayed effectsPotential delayed effects	: : :	Not available. Not available. Not available. Not available.

: 30/04/2025 Date of previous issue

SECTION 11: Toxicological information

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	
Carcinogenicity	: No known significant effects or critical hazards.	
Mutagenicity	: No known significant effects or critical hazards.	
Reproductive to	 No known significant effects or critical hazards. 	

11.2 Information on other hazards

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity	
Product/ingredient name titanium dioxide	Result Acute - LC50 - Marine water Fish - Mummichog - <i>Fundulus heteroclitus</i> >1000000 μg/l [96 hours] <u>Effect</u> : Mortality
	Acute - LC50 - Fresh water Crustaceans - Water flea - <i>Ceriodaphnia dubia</i> - Neonate <u>Age</u> : <24 hours 3 mg/l [48 hours] <u>Effect</u> : Mortality
3-iodo-2-propynyl-butyl carbamate	Acute - LC50 - Fresh water EU Fish - Trout - <i>Oncorhynchus mykiss</i> 0.067 mg/l [96 hours]
	Acute - NOEC - Fresh water EU Fish - Trout - <i>Oncorhynchus mykiss</i> 0.049 mg/l [96 hours]
	Acute - EC50 - Fresh water EU Daphnia - Daphnia - <i>Daphnia magna</i> 0.16 mg/l [48 hours]
	Chronic - NOEC - Fresh water EU Daphnia - Daphnia - <i>Daphnia Magna</i> 0.05 mg/l [21 days]
	Acute - EC50 - Fresh water EU Algae - Algae - <i>Scenedemus subspicatus</i> 0.022 mg/l [72 hours]
4,5-dichloro-2-octyl-2H-isothiazol-3-one	Acute - EC50 - Fresh water Algae - Green algae - <i>Pseudokirchneriella subcapitata</i> 0.003 mg/l [72 hours] <u>Effect</u> : Population
	Acute - EC50 - Fresh water Daphnia - Water flea - <i>Daphnia magna</i>

ssue : 16/04/2025

SECTION 12: Ecological information

0.001 mg/l [48 hours] <u>Effect</u>: Intoxication

Acute - LC50 - Fresh water

US EPA Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss* <u>Weight</u>: 1.2 g 2.7 ppb [96 hours] <u>Effect</u>: Mortality

Chronic - NOEC US EPA Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss* 0.56 ppb [97 days] Effect: Growth

Chronic - NOEC - Marine water

OECD Algae - Diatom - *Nitzschia pungens* 19.789 µg/l [96 hours] <u>Effect</u>: Population

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-iodo-2-propynyl-butyl carbamate	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-iodo-2-propynyl-butyl carbamate	>1	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
3-iodo-2-propynyl-butyl carbamate	1.13	13.4558
4,5-dichloro-2-octyl-2H-isothiazol-3-one	3.41	2562.01

Results of PMT and vPvM assessment

	PMT	Р	M	т	vPvM	vP	vM
itanium dioxide	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
1,5-dichloro-2-octyl-2H- sothiazol-3-one	No	No	No	No	No	No	No
eaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3	No :	No	No	No	No	No	No

Date of previous issue

Mobility Conclusion/Summary : Not available.

: 30/04/2025

: The product does not meet the criteria to be considered as a PMT or vPvM.

Date of issue/Date of revision SILOKSAN FACADE - All variants

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB	
titanium dioxide	No	No	No	No	No	No	No	
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No	
4,5-dichloro-2-octyl-2H- isothiazol-3-one	No	No	No	No	No	No	No	
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No	

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
4,5-dichloro-2-octyl-2H- isothiazol-3-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No
Conclusion/Summary	immary : The product does not meet the criteria to be considered as a PBT or vPvB.						

Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Not available.

- Conclusion/Summary [Product]
- : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

3.1 Waste treatment method	ods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: 🗡 es.
European waste catalogi	ue (EWC)

: 30/04/2025 Date of previous issue

:16/04/2025

SECTION 13: Disposal considerations

Waste code	Waste designation
Ø8 01 11* 20 01 27*	waste paint and varnish containing organic solvents or other hazardous substances paint, inks, adhesives and resins containing hazardous substances
Packaging	
Methods of disposal	 The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	-							
	ADR/RID	ADN	IMDG	ΙΑΤΑ				
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.				
14.2 UN proper shipping name	-	-	-	-				
14.3 Transport hazard class(es)	-	-	-	-				
14.4 Packing group	-	-	-	-				
14.5 Environmental hazards	No.	No.	No.	No.				

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

ż

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
SILOKSAN FACADE	≥90	3

Labelling

Other EU regulations

SECTION 15: Regulatory information

SECTION 15. Regulatory information			
Industrial emissions : Not listed (integrated pollution prevention and control) - Air			
Industrial emissions : Not listed (integrated pollution prevention and control) - Water			
Explosive precursors : Not applicable.			
Ozone depleting substances (EU 2024/590)			
Not listed.			
Prior Informed Consent (PIC) (649/2012/EU) Not listed.			
Persistent Organic Pollutants Not listed.			
Seveso Directive			
This product is not controlled under the Seveso Directive.			
International regulations			
Chemical Weapon Convention List Schedules I, II & III Chemicals			
Not listed.			
Montreal Protocol Not listed.			
Stockholm Convention on Persistent Organic Pollutants Not listed.			
Rotterdam Convention on Prior Informed Consent (PIC) Not listed.			

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety
assessment: This product contains substances for which Chemical Safety Assessments are still
required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
acronyms	
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

SECTION 16: Other information					
H301	Toxic if swallowed.				
H302	Harmful if swallowed.				
H310	Fatal in contact with skin.				
H314	Causes severe skin burns and eye damage.				
H317	May cause an allergic skin reaction.				
H318	Causes serious eye damage.				
H330	Fatal if inhaled.				
H331	Toxic if inhaled.				
H351	Suspected of causing cancer.				
H372	Causes damage to organs through prolonged or repeated exposure.				
H400	Very toxic to aquatic life.				
H410	Very toxic to aquatic life with long lasting effects.				
H412	Harmful to aquatic life with long lasting effects.				
EUH071	Corrosive to the respiratory tract.				
Full text of class	ifications [CLP/GHS]				
Acute Tox. 2	ACUTE TOXICITY - Category 2				
Acute Tox. 3	ACUTE TOXICITY - Category 3				
Acute Tox. 4	ACUTE TOXICITY - Category 4				
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1				
Aquatic Chronic					
Aquatic Chronic					
Carc. 2	CARCINOGENICITY - Category 2				
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1				
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1				
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C				
Skin Sens. 1	SKIN SENSITISATION - Category 1				
Skin Sens. 1A	SKIN SENSITISATION - Category 1A				
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1				

STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category		
Date of issue/ Date of revision	: 30/04/2025		
Date of previous issue	: 16/04/2025		
Version	: 3		

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision SILOKSAN FACADE - All variants

: 30/04/2025 Date of previous issue