# SAFETY DATA SHEET

SUPREMO KLARLACK 3990-05 - All variants

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

**Product name** : SUPREMO KLARLACK 3990-05 - All variants

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

### 1.4 Emergency telephone number

**National advisory body/Poison Centre**

**Telephone number** : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Flam. Liq. 2, H225
Eye Irrit. 2, H319
Skin Sens. 1, H317
STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** :
H225 - Highly flammable liquid and vapour.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

**Precautionary statements**

**Prevention** :
P280 - Wear protective gloves. Wear eye or face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing vapour.

**Response** : P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

**Storage** : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

## SECTION 2: Hazards identification

**Hazardous ingredients** : Contains: n-Butyl acetate; Ethyl acetate; Methyl methacrylate and Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly(oxyethylene)

**Supplemental label elements** :

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|---|---|---|---|---|---|
| n-Butyl acetate | REACH #: 01-2119485493-29<br>EC: 204-658-1<br>CAS: 123-86-4<br>Index: 607-025-00-1 | ≥25 - ≤50 | Flam. Liq. 3, H226<br>STOT SE 3, H336<br>EUH066 | - | [1] [2] |
| Ethyl acetate | REACH #: 01-2119475103-46<br>EC: 205-500-4<br>CAS: 141-78-6<br>Index: 607-022-00-5 | ≥10 - ≤25 | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336<br>EUH066 | - | [1] [2] |
| 2-Methoxy-1-methylethyl acetate | REACH #: 01-2119475791-29<br>EC: 203-603-9<br>CAS: 108-65-6<br>Index: 607-195-00-7 | ≤5 | Flam. Liq. 3, H226 | - | [2] |
| 2-Butoxyethanol | REACH #: 01-2119475108-36<br>EC: 203-905-0<br>CAS: 111-76-2<br>Index: 603-014-00-0 | ≤5 | Acute Tox. 4, H302<br>Acute Tox. 3, H331<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319 | ATE [Oral] = 1200 mg/kg<br>ATE [Inhalation (vapours)] = 3 mg/l | [1] [2] |
| Methyl methacrylate | REACH #: 01-2119452498-28<br>EC: 201-297-1<br>CAS: 80-62-6<br>Index: 607-035-00-6 | <1 | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>STOT SE 3, H335 | - | [1] [2] |
| Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H- | EC: 400-830-7<br>Index: 607-176-00-3 | ≤0.3 | Skin Sens. 1, H317<br>Aquatic Chronic 2, H411 | - | [1] |

## SECTION 3: Composition/information on ingredients

| | | | | | |
|---|---|---|---|---|---|
| benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly (oxyethylene) | | | | | |
| Fatty acids, C14-18 and C16-18-unsatd., maleated | REACH #: 01-2119976378-19<br>EC: 288-306-2<br>CAS: 85711-46-2 | ≤0.3 | Skin Irrit. 2, H315<br>Skin Sens. 1, H317 | - | [1] |
| Maleic anhydride | REACH #: 01-2119472428-31<br>EC: 203-571-6<br>CAS: 108-31-6<br>Index: 607-096-00-9 | ≤0.01 | Acute Tox. 4, H302<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Resp. Sens. 1, H334<br>Skin Sens. 1A, H317<br>STOT RE 1, H372 (respiratory system) (inhalation)<br>EUH071 | ATE [Oral] = 400 mg/kg<br>Skin Sens. 1, H317: C ≥ 0.001% | [1] |

Type

[1] Substance classified with a health or environmental hazard
[2] Substance with a workplace exposure limit

**See Section 16 for the full text of the H statements declared above.**

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

## SECTION 4: First aid measures

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

**Over-exposure signs/symptoms**

**Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

**Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

**Skin contact** : Adverse symptoms may include the following:
irritation
redness

**Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, $CO_2$, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

**Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

## SECTION 7: Handling and storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. See Section 10 for incompatible materials before handling or use.

**Seveso Directive - Reporting thresholds**

**Danger criteria**

| Category | Notification and MAPP threshold | Safety report threshold |
|---|---|---|
| P5c | 5000 tonnes | 50000 tonnes |

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

**Occupational exposure limits**

| Product/ingredient name | Exposure limit values |
|---|---|
| n-Butyl acetate | **EU OEL (Europe, 1/2022)**<br>STEL 15 minutes: 150 ppm.<br>STEL 15 minutes: 723 mg/m³.<br>TWA 8 hours: 241 mg/m³.<br>TWA 8 hours: 50 ppm. |
| Ethyl acetate | **EU OEL (Europe, 1/2022)**<br>STEL 15 minutes: 400 ppm.<br>STEL 15 minutes: 1468 mg/m³.<br>TWA 8 hours: 200 ppm.<br>TWA 8 hours: 734 mg/m³. |
| 2-Methoxy-1-methylethyl acetate | **EU OEL (Europe, 1/2022)** Absorbed through skin.<br>TWA 8 hours: 50 ppm.<br>TWA 8 hours: 275 mg/m³.<br>STEL 15 minutes: 100 ppm.<br>STEL 15 minutes: 550 mg/m³. |
| 2-Butoxyethanol | **EU OEL (Europe, 1/2022)** Absorbed through skin.<br>TWA 8 hours: 20 ppm.<br>TWA 8 hours: 98 mg/m³.<br>STEL 15 minutes: 50 ppm.<br>STEL 15 minutes: 246 mg/m³. |
| Methyl methacrylate | **EU OEL (Europe, 1/2022)**<br>TWA 8 hours: 50 ppm.<br>STEL 15 minutes: 100 ppm. |

**Biological exposure indices**

| Product/ingredient name | Exposure indices |
|---|---|
| No exposure indices known. | |

## SECTION 8: Exposure controls/personal protection

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

| Product/ingredient name | Result |
|---|---|
| n-Butyl acetate | **DNEL - General population - Long term - Oral**<br>2 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - General population - Short term - Oral**<br>2 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - General population - Long term - Dermal**<br>3.4 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - General population - Short term - Dermal**<br>6 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - Workers - Long term - Dermal**<br>7 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - Workers - Short term - Dermal**<br>11 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - General population - Long term - Inhalation**<br>12 mg/m³<br>Effects: Systemic<br><br>**DNEL - General population - Long term - Inhalation**<br>35.7 mg/m³<br>Effects: Local<br><br>**DNEL - Workers - Long term - Inhalation**<br>48 mg/m³<br>Effects: Systemic<br><br>**DNEL - General population - Short term - Inhalation**<br>300 mg/m³<br>Effects: Local<br><br>**DNEL - General population - Short term - Inhalation**<br>300 mg/m³<br>Effects: Systemic<br><br>**DNEL - Workers - Long term - Inhalation**<br>300 mg/m³<br>Effects: Local<br><br>**DNEL - Workers - Short term - Inhalation**<br>600 mg/m³<br>Effects: Local<br><br>**DNEL - Workers - Short term - Inhalation** |

| | |
|---|---|
| | 600 mg/m³<br>Effects: Systemic |
| Ethyl acetate | **DNEL - General population - Long term - Oral**<br>4.5 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - General population - Long term - Dermal**<br>37 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - Workers - Long term - Dermal**<br>63 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - General population - Long term - Inhalation**<br>367 mg/m³<br>Effects: Local<br><br>**DNEL - General population - Long term - Inhalation**<br>367 mg/m³<br>Effects: Systemic<br><br>**DNEL - General population - Short term - Inhalation**<br>734 mg/m³<br>Effects: Local<br><br>**DNEL - General population - Short term - Inhalation**<br>734 mg/m³<br>Effects: Systemic<br><br>**DNEL - Workers - Long term - Inhalation**<br>734 mg/m³<br>Effects: Local<br><br>**DNEL - Workers - Long term - Inhalation**<br>734 mg/m³<br>Effects: Systemic<br><br>**DNEL - Workers - Short term - Inhalation**<br>1468 mg/m³<br>Effects: Local<br><br>**DNEL - Workers - Short term - Inhalation**<br>1468 mg/m³<br>Effects: Systemic |
| 2-Methoxy-1-methylethyl acetate | **DNEL - General population - Long term - Inhalation**<br>33 mg/m³<br>Effects: Local<br><br>**DNEL - General population - Long term - Inhalation**<br>33 mg/m³<br>Effects: Systemic<br><br>**DNEL - General population - Long term - Oral**<br>36 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - Workers - Long term - Inhalation**<br>275 mg/m³<br>Effects: Systemic<br><br>**DNEL - General population - Long term - Dermal**<br>320 mg/kg bw/day<br>Effects: Systemic |

**DNEL - Workers - Short term - Inhalation**
550 mg/m³
Effects: Local

**DNEL - Workers - Long term - Dermal**
796 mg/kg bw/day
Effects: Systemic

2-Butoxyethanol

**DNEL - General population - Long term - Oral**
6.3 mg/kg bw/day
Effects: Systemic

**DNEL - General population - Short term - Oral**
26.7 mg/kg bw/day
Effects: Systemic

**DNEL - General population - Long term - Inhalation**
59 mg/m³
Effects: Systemic

**DNEL - Workers - Long term - Inhalation**
98 mg/m³
Effects: Systemic

**DNEL - General population - Short term - Inhalation**
147 mg/m³
Effects: Local

**DNEL - Workers - Short term - Inhalation**
246 mg/m³
Effects: Local

**DNEL - General population - Short term - Inhalation**
426 mg/m³
Effects: Systemic

**DNEL - Workers - Short term - Inhalation**
1091 mg/m³
Effects: Systemic

Methyl methacrylate

**DNEL - General population - Short term - Dermal**
1.5 mg/cm²
Effects: Local

**DNEL - General population - Long term - Dermal**
1.5 mg/cm²
Effects: Local

**DNEL - Workers - Short term - Dermal**
1.5 mg/cm²
Effects: Local

**DNEL - Workers - Long term - Dermal**
1.5 mg/cm²
Effects: Local

**DNEL - General population - Long term - Oral**
8.2 mg/kg bw/day
Effects: Systemic

**DNEL - General population - Long term - Dermal**
8.2 mg/kg bw/day
Effects: Systemic

**DNEL - Workers - Long term - Dermal**

| | |
|---|---|
| | 13.67 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - General population - Long term - Inhalation**<br>74.3 mg/m³<br>Effects: Systemic<br><br>**DNEL - General population - Long term - Inhalation**<br>104 mg/m³<br>Effects: Local<br><br>**DNEL - General population - Short term - Inhalation**<br>208 mg/m³<br>Effects: Local<br><br>**DNEL - Workers - Long term - Inhalation**<br>208 mg/m³<br>Effects: Local<br><br>**DNEL - Workers - Long term - Inhalation**<br>348.4 mg/m³<br>Effects: Systemic<br><br>**DNEL - Workers - Short term - Inhalation**<br>416 mg/m³<br>Effects: Local |
| Fatty acids, C14-18 and C16-18-unsatd., maleated | **DNEL - General population - Long term - Oral**<br>1.5 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - General population - Long term - Dermal**<br>1.5 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - Workers - Long term - Dermal**<br>3 mg/kg bw/day<br>Effects: Systemic |
| Maleic anhydride | **DNEL - General population - Long term - Inhalation**<br>0.05 mg/m³<br>Effects: Systemic<br><br>**DNEL - General population - Long term - Oral**<br>0.06 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - General population - Long term - Inhalation**<br>0.08 mg/m³<br>Effects: Local<br><br>**DNEL - Workers - Long term - Inhalation**<br>0.081 mg/m³<br>Effects: Local<br><br>**DNEL - Workers - Long term - Inhalation**<br>0.081 mg/m³<br>Effects: Systemic<br><br>**DNEL - General population - Short term - Oral**<br>0.1 mg/kg bw/day<br>Effects: Systemic<br><br>**DNEL - General population - Short term - Dermal**<br>0.1 mg/kg bw/day<br>Effects: Systemic |

**DNEL - General population - Long term - Dermal**
0.1 mg/kg bw/day
Effects: Systemic

**DNEL - Workers - Short term - Dermal**
0.2 mg/kg bw/day
Effects: Systemic

**DNEL - Workers - Long term - Dermal**
0.2 mg/kg bw/day
Effects: Systemic

**DNEL - Workers - Short term - Inhalation**
0.2 mg/m³
Effects: Local

**DNEL - Workers - Short term - Inhalation**
0.2 mg/m³
Effects: Systemic

**PNECs**

Not available.

### 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Skin protection**

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.

## SECTION 8: Exposure controls/personal protection

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type: A

Filter type (spray application): A P

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

**Appearance**

**Physical state** : Liquid.

**Colour** : Various

**Odour** : Slight

**Odour threshold** : Not available.

**Melting point/freezing point** : Not available.

**Initial boiling point and boiling range** :

| Ingredient name | °C | °F | Method |
|---|---|---|---|
| Ethyl acetate | 77.1 | 170.8 | |
| n-Butyl acetate | 126 | 258.8 | OECD 103 |

**Flammability** : Not available.

**Lower and upper explosion limit** : Lower: 1.4% (n-butyl acetate)
Upper: 11.5% (ethyl acetate)

**Flash point** : Closed cup: -1°C (30.2°F)

**Auto-ignition temperature** :

| Ingredient name | °C | °F | Method |
|---|---|---|---|
| 2-Butoxyethanol | 230 | 446 | DIN 51794 |
| 2-Methoxy-1-methylethyl acetate | 333 | 631.4 | DIN 51794 |

**Decomposition temperature** : Not available.

**pH** : Not applicable.

**Viscosity** : Not available.

**Solubility(ies)** :

Not available.

**Solubility in water** : Not available.

**Partition coefficient: n-octanol/water** : Not applicable.

**Vapour pressure** :

## SECTION 9: Physical and chemical properties

| Ingredient name | Vapour Pressure at 20°C | | | Vapour pressure at 50°C | | |
|---|---|---|---|---|---|---|
| | mm Hg | kPa | Method | mm Hg | kPa | Method |
| Ethyl acetate | 81.59163 | 10.9 | | | | |
| n-Butyl acetate | 11.25096 | 1.5 | DIN EN 13016-2 | | | |

**Relative density** : Not available.

**Density** : 1 g/cm³

**Vapour density** : Not available.

**Particle characteristics**

**Median particle size** : Not applicable.

### 9.2 Other information

#### 9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

#### 9.2.2 Other safety characteristics

Not applicable.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**10.5 Incompatible materials** : Reactive or incompatible with the following materials: oxidising materials

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity**

| Product/ingredient name | Result |
|---|---|
| n-Butyl acetate | **Rat - Oral - LD50**<br>10760 mg/kg<br>EU<br><br>**Rabbit - Dermal - LD50**<br>14112 mg/kg<br><br>**Rat - Inhalation - LC50 Vapour**<br>0.74 mg/l [4 hours] |
| Ethyl acetate | **Rat - Oral - LD50**<br>5620 mg/kg |
| 2-Methoxy-1-methylethyl acetate | **Rat - Oral - LD50**<br>8532 mg/kg<br><br>**Rabbit - Dermal - LD50** |

>5 g/kg

Methyl methacrylate

**Rat - Oral - LD50**
7872 mg/kg
Toxic effects: Behavioral - Muscle weakness Behavioral - Coma Lung, Thorax, or Respiration - Respiratory depression

**Rabbit - Dermal - LD50**
>5 g/kg
Toxic effects: Skin After systemic exposure - Dermatitis, other

**Rat - Inhalation - LC50 Vapour**
78000 mg/m³ [4 hours]

Maleic anhydride

**Rat - Oral - LD50**
400 mg/kg

**Rabbit - Dermal - LD50**
2620 mg/kg

**Conclusion/Summary [Product]** : Not available.

**Acute toxicity estimates**

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|---|---|---|---|---|
| SUPREMO KLARLACK 3990-05 | 26666.7 | N/A | N/A | 66.7 | N/A |
| n-Butyl acetate | 10760 | 14112 | N/A | N/A | N/A |
| Ethyl acetate | 5620 | N/A | N/A | N/A | N/A |
| 2-Methoxy-1-methylethyl acetate | 8532 | N/A | N/A | N/A | N/A |
| 2-Butoxyethanol | 1200 | N/A | N/A | 3 | N/A |
| Methyl methacrylate | 7872 | N/A | N/A | 78 | N/A |
| Maleic anhydride | 400 | 2620 | N/A | N/A | N/A |

**Skin corrosion/irritation**

| Product/ingredient name | Result |
|---|---|
| n-Butyl acetate | **Rabbit - Skin - Moderate irritant**<br>Duration of treatment/exposure: 24 hours<br>Amount/concentration applied: 500 mg |
| 2-Butoxyethanol | **Rabbit - Skin - Mild irritant**<br>Amount/concentration applied: 500 mg |

**Conclusion/Summary [Product]** : Not available.

**Serious eye damage/eye irritation**

| Product/ingredient name | Result |
|---|---|
| n-Butyl acetate | **Rabbit - Eyes - Moderate irritant**<br>Amount/concentration applied: 100 mg |
| 2-Butoxyethanol | **Rabbit - Eyes - Moderate irritant**<br>Duration of treatment/exposure: 24 hours<br>Amount/concentration applied: 100 mg<br><br>**Rabbit - Eyes - Severe irritant**<br>Amount/concentration applied: 100 mg |
| Maleic anhydride | **Rabbit - Eyes - Severe irritant**<br>Amount/concentration applied: 1 % |

**Conclusion/Summary [Product]** : Not available.

**Respiratory corrosion/irritation**

Not available.

**Conclusion/Summary [Product]** : Not available.

**Respiratory or skin sensitization**

Not available.

**Skin**

**Conclusion/Summary [Product]** : Not available.

**Respiratory**

**Conclusion/Summary [Product]** : Not available.

**Germ cell mutagenicity**

Not available.

**Conclusion/Summary [Product]** : Not available.

**Carcinogenicity**

Not available.

**Conclusion/Summary [Product]** : Not available.

**Reproductive toxicity**

Not available.

**Conclusion/Summary [Product]** : Not available.

**Specific target organ toxicity (single exposure)**

| Product/ingredient name | Result |
|---|---|
| n-Butyl acetate | STOT SE 3, H336 (Narcotic effects) |
| Ethyl acetate | STOT SE 3, H336 (Narcotic effects) |
| Methyl methacrylate | STOT SE 3, H335 (Respiratory tract irritation) |

**Specific target organ toxicity (repeated exposure)**

| Product/ingredient name | Result |
|---|---|
| Maleic anhydride | STOT RE 1, H372 (respiratory system) (inhalation) |

**Aspiration hazard**

Not available.

**Information on likely routes of exposure**

Not available.

**Potential acute health effects**

**Eye contact** : Causes serious eye irritation.

**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

**Skin contact** : May cause an allergic skin reaction.

**Ingestion** : Can cause central nervous system (CNS) depression.

**Symptoms related to the physical, chemical and toxicological characteristics**

## SECTION 11: Toxicological information

**Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

**Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

**Skin contact** : Adverse symptoms may include the following:
irritation
redness

**Ingestion** : No specific data.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Short term exposure**

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

**Long term exposure**

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

**Potential chronic health effects**

Not available.

**Conclusion/Summary [Product]** : Not available.

**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name | Result |
|---|---|
| n-Butyl acetate | **Acute - LC50 - Fresh water**<br>Fish - Fathead minnow - *Pimephales promelas*<br>Age: 31 to 32 days; Size: 21.6 mm; Weight: 0.175 g<br>18000 µg/l [96 hours]<br>Effect: Mortality<br><br>**Acute - LC50 - Marine water**<br>Crustaceans - Brine shrimp - *Artemia salina*<br>32 mg/l [48 hours]<br>Effect: Mortality |
| Ethyl acetate | **Acute - LC50 - Fresh water**<br>Daphnia - Water flea - *Daphnia cucullata*<br>Age: 11 days |

154000 µg/l [48 hours]
Effect: Mortality

**Acute - LC50 - Fresh water**
Fish - Indian catfish - *Heteropneustes fossilis*
Size: 14.16 cm; Weight: 25.54 g
212500 µg/l [96 hours]
Effect: Mortality

**Acute - EC50 - Fresh water**
Algae - Green algae - *Selenastrum sp.*
2500000 µg/l [96 hours]

**Chronic - NOEC - Fresh water**
Daphnia - Water flea - *Daphnia magna*
12 mg/l [21 days]
Effect: Behavior

**Chronic - NOEC - Fresh water**
Fish - Fathead minnow - *Pimephales promelas* - Embryo
Age: <24 hours
75.6 mg/l [32 days]
Effect: Mortality

2-Butoxyethanol

**Acute - LC50 - Marine water**
Fish - Inland silverside - *Menidia beryllina*
Size: 40 to 100 mm
1250000 µg/l [96 hours]
Effect: Mortality

**Acute - LC50 - Marine water**
Crustaceans - Common shrimp, sand shrimp - *Crangon crangon*
800000 µg/l [48 hours]
Effect: Mortality

Methyl methacrylate

**Acute - LC50 - Fresh water**
Fish - Fathead minnow - *Pimephales promelas* - Adult
130000 µg/l [96 hours]
Effect: Mortality

Maleic anhydride

**Acute - LC50 - Fresh water**
Fish - Western mosquitofish - *Gambusia affinis* - Adult
230000 µg/l [96 hours]
Effect: Mortality

**Conclusion/Summary [Product]** : Not available.

### 12.2 Persistence and degradability

Not available.

**Conclusion/Summary [Product]** : Not available.

### 12.3 Bioaccumulative potential

| Product/ingredient name | $LogP_{ow}$ | BCF | Potential |
|---|---|---|---|
| n-Butyl acetate | 2.3 | - | Low |
| Ethyl acetate | 0.68 | 30 | Low |
| 2-Methoxy-1-methylethyl acetate | 1.2 | - | Low |
| 2-Butoxyethanol | 0.81 | - | Low |
| Methyl methacrylate | 1.38 | - | Low |
| Maleic anhydride | -2.78 | - | Low |

## SECTION 12: Ecological information

### 12.4 Mobility in soil

**Soil/water partition coefficient**

| Product/ingredient name | Value |
|---|---|
| n-Butyl acetate | logKoc: 1.5<br>Koc: 33.2139 |
| Ethyl acetate | logKoc: 1.3<br>Koc: 18.1744 |
| 2-Methoxy-1-methylethyl acetate | logKoc: 0.36<br>Koc: 2.31363 |
| 2-Butoxyethanol | logKoc: 1.8<br>Koc: 67.3685 |
| Methyl methacrylate | logKoc: 1.2<br>Koc: 16.6906 |
| Maleic anhydride | logKoc: 1.1<br>Koc: 11.4841 |

**Results of PMT and vPvM assessment**

| Product/ingredient name | PMT | P | M | T | vPvM | vP | vM |
|---|---|---|---|---|---|---|---|
| n-Butyl acetate | No | No | No | No | No | No | No |
| Ethyl acetate | No | No | No | No | No | No | No |
| 2-Methoxy-1-methylethyl acetate | No | No | No | No | No | No | No |
| 2-Butoxyethanol | No | No | No | No | No | No | No |
| Methyl methacrylate | No | No | No | No | No | No | No |
| Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly (oxyethylene) | No | No | No | No | No | No | No |
| Fatty acids, C14-18 and C16-18-unsatd., maleated | No | No | No | No | No | No | No |
| Maleic anhydride | No | No | No | No | No | No | No |

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment

**Regulation (EC) No. 1907/2006 [REACH]**

| Product/ingredient name | PBT | P | B | T | vPvB | vP | vB |
|---|---|---|---|---|---|---|---|
| n-Butyl acetate | No | N/A | N/A | No | N/A | N/A | N/A |
| Ethyl acetate | No | N/A | No | No | No | N/A | No |
| 2-Methoxy-1-methylethyl acetate | No | N/A | N/A | No | N/A | N/A | N/A |
| 2-Butoxyethanol | No | N/A | N/A | No | N/A | N/A | N/A |
| Methyl methacrylate | No | N/A | N/A | No | N/A | N/A | N/A |
| Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) | No | N/A | N/A | No | N/A | N/A | N/A |

## SECTION 12: Ecological information

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly (oxyethylene) | | | | | | | |
| Fatty acids, C14-18 and C16-18-unsatd., maleated | No | N/A | N/A | No | N/A | N/A | N/A |
| Maleic anhydride | N/A | N/A | N/A | Yes | N/A | N/A | N/A |

**Regulation (EC) No. 1272/2008 [CLP]**

| Product/ingredient name | PBT | P | B | T | vPvB | vP | vB |
|---|---|---|---|---|---|---|---|
| n-Butyl acetate | No | No | No | No | No | No | No |
| Ethyl acetate | No | No | No | No | No | No | No |
| 2-Methoxy-1-methylethyl acetate | No | No | No | No | No | No | No |
| 2-Butoxyethanol | No | No | No | No | No | No | No |
| Methyl methacrylate | No | No | No | No | No | No | No |
| Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyloxypoly (oxyethylene) | No | No | No | No | No | No | No |
| Fatty acids, C14-18 and C16-18-unsatd., maleated | No | No | No | No | No | No | No |
| Maleic anhydride | No | No | No | No | No | No | No |

**Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP]** : The product does not meet the criteria to be considered as a PBT or vPvB.

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

**Product**

**Methods of disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations. Avoid release to the environment. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**European waste catalogue (EWC)** : 08 01 11*

**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

## SECTION 13: Disposal considerations

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|---|---|---|---|---|
| **14.1 UN number or ID number** | UN1263 | UN1263 | UN1263 | UN1263 |
| **14.2 UN proper shipping name** | PAINT | PAINT | PAINT | PAINT |
| **14.3 Transport hazard class(es)** | 3  | 3  | 3  | 3  |
| **14.4 Packing group** | II | II | II | II |
| **14.5 Environmental hazards** | No. | Yes. | No. | No. |

**Additional information**

**ADR/RID** : **Special provisions** 640 (C)
**Tunnel code** (D/E)

**ADN** : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.
**Special provisions** 640 (C)

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

| Product/ingredient name | % | Designation [Usage] |
|---|---|---|
| SUPREMO KLARLACK 3990-05 | ≥90 | 3 |

**Labelling** :

## SECTION 15: Regulatory information

### Synthetic polymer microparticles - Designation 78

**Generic identity of polymer(s)** : 3901 - Polymers of ethylene., 3907 - Polyacetals, other polyethers and epoxide resins; polycarbonates, alkyd resins, polyallyl esters and other polyesters.

**Total percentage of synthetic polymer microparticles** : 0.92%

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

### Other EU regulations

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**Explosive precursors** : Not applicable.

### (EC) No 273/2004 on drug precursors

Not listed.

### (EC) No 111/2005 Trade between the Union and third countries in drug precursors

| Ingredient name | % | Status |
|---|---|---|
| Toluene and its salts | ≤0.0015 | Category 3 |

### Ozone depleting substances (EU 2024/590)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Persistent Organic Pollutants

Not listed.

### Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

| Category |
|---|
| P5c |

### International regulations

### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### Montreal Protocol

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

## SECTION 15: Regulatory information

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

| Classification | Justification |
|---|---|
| Flam. Liq. 2, H225 | On basis of test data |
| Eye Irrit. 2, H319 | Calculation method |
| Skin Sens. 1, H317 | Calculation method |
| STOT SE 3, H336 | Calculation method |

**Full text of abbreviated H statements**

| | |
|---|---|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| EUH071 | Corrosive to the respiratory tract. |

**Full text of classifications [CLP/GHS]**

| | |
|---|---|
| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| Eye Irrit. 2 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 |
| Flam. Liq. 2 | FLAMMABLE LIQUIDS - Category 2 |
| Flam. Liq. 3 | FLAMMABLE LIQUIDS - Category 3 |
| Resp. Sens. 1 | RESPIRATORY SENSITISATION - Category 1 |
| Skin Corr. 1B | SKIN CORROSION/IRRITATION - Category 1B |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITISATION - Category 1 |
| Skin Sens. 1A | SKIN SENSITISATION - Category 1A |
| STOT RE 1 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |
| STOT SE 3 | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |

**Date of issue/ Date of revision** : 20/10/2026

**Date of previous issue** : 05/03/2026

**Version** : 1.02

## SECTION 16: Other information



### Notice to reader

**The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.**