Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET



TEKNOBRUSH 6600-00 - BASE 1

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

•		
1.1 Product identifier		
Product name	: FEKNOBRUSH 6600-00 - BASE 1	
1.2 Relevant identified us	ses of the substance or mixture and uses advised against	
Product use	: Paint.	
1.3 Details of the supplie	r of the safety data sheet	
• •	tie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.	
e-mail address of perso responsible for this SD	n : ₱rod-safe@teknos.com S	
National contact		
<mark>™</mark> eknos Group Oy, Takka	tie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.	
1.4 Emergency telephone	e number	
National advisory body	Poison Centre	
Telephone number	: 🕅 an emergency, call 112	

SECTION 2: Hazards identification

 2.1 Classification of the substance or mixture

 Product definition
 : Mixture

 Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Contains adipohydrazide, 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol- 3-one, 2-Octyl-2H-isothiazol-3-one, reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) and 2-Methyl-1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and DTBMA and Bronopol and MIT and OIT and MBIT.

SECTION 2: Hazards identification

÷

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

2.3 Other hazards

Product meets the criteria : for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do :

not result in classification

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures Product/ingredient name	: Mixture	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
propylidynetrimethanol	REACH #: 01-2119486799-10 EC: 201-074-9 CAS: 77-99-6	≤0.3	Repr. 2, H361fd	-	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
2-methyl-2H-isothiazol- 3-one	EC: 220-239-6 CAS: 2682-20-4	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C $\geq 0.0015\%$ M [Acute] = 10 M [Chronic] = 1	[1]
2-Octyl-2H-isothiazol-3-one	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 125 mg/kg ATE [Dermal] = 311 mg/kg ATE [Inhalation (dusts and mists)] = 0.27 mg/l Skin Sens. 1, H317: C $\geq 0.0015\%$ M [Acute] = 100	[1]

				M [Chronic] = 100	
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
2-Methyl-1,2-benzisothiazol- 3(2H)-one	CAS: 2527-66-4 Index: 613-336-00-3	<0.0015	Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 175 mg/kg ATE [Dermal] = 1100 mg/kg Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

Substance classified with a health or environmental hazard

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

an Beeenption of motula i	
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: \mathbf{N} o action shall be taken involving any personal risk or without suitable training.

4.2 Most important sympto	ms and effects, both acute and delayed	
<u>Over-exposure signs/sym</u>	<u>ptoms</u>	
Eye contact	: No specific data.	
Inhalation	: No specific data.	
Date of issue/Date of revision	: 24/10/2023 Date of previous issue : 27/11/2019	Version : 1.09 3/19
FEKNOBRUSH 6600-00 - BA	ASE 1	Label No : <mark>5</mark> 1987

SECTION 4: First aid	easures	
Skin contact	No specific data.	
Ingestion	No specific data.	
4.3 Indication of any immedi	medical attention and special treatment needed	
Notes to physician	Freat symptomatically. Contact poison treatment specialist immediately if quantities have been ingested or inhaled.	large
Specific treatments	No specific treatment.	
SECTION 5: Firefigh	g measures	
5.1 Extinguishing media		
Suitable extinguishing media	$ ot\!$	
Unsuitable extinguishing media	None known.	
5.2 Special hazards arising f	the substance or mixture	
Hazards from the substance or mixture	$\mathbf{\overline{m}}$ a fire or if heated, a pressure increase will occur and the container may	burst.
Hazardous combustion products	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	Fromptly isolate the scene by removing all persons from the vicinity of the there is a fire. No action shall be taken involving any personal risk or with suitable training.	
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contal breathing apparatus (SCBA) with a full face-piece operated in positive pre mode. Clothing for fire-fighters (including helmets, protective boots and g conforming to European standard EN 469 will provide a basic level of prot chemical incidents.	essure loves)
SECTION 6: Accider	release measures	

6.1 Personal precautions, pro	ective equipment and emergency procedures	
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.	
For emergency responders	✓ specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	Kvoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmen pollution (sewers, waterways, soil or air).	
6.3 Methods and material for	ontainment and cleaning up	

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop
	up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

: 24/10/2023 Date of previous issue

SECTION 6: Accidental release measures

OFOLION OF VECTOR			
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.		
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment.		

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

See Section 13 for additional waste treatment information.

7.1 Precautions for safe handling

Protective measures
 Advice on general occupational hygiene
 If ut on appropriate personal protective equipment (see Section 8).
 If ating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

: Not available. : Not available.

Recommendations Industrial sector specific solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Ethyldiglycol	Regulation on Limit Values - MAC (Austria, 4/2021).
	PEAK: 140 mg/m ³ , 4 times per shift, 15 minutes.
	PEAK: 24 ppm, 4 times per shift, 15 minutes.
	TWA: 35 mg/m ³ 8 hours.
	TWA: 6 ppm 8 hours.
2-methyl-2H-isothiazol-3-one	Regulation on Limit Values - MAC (Austria, 4/2021). [5-chloro-
	2-methyl-2,3-dihydroisothiazol-3-one and 2-methyl-2,3-di-
	hydroisothiazol-3-one (mixture in the ratio 3:1)] Skin
	sensitiser.
	TWA: 0.05 mg/m ³ 8 hours.
2-Octyl-2H-isothiazol-3-one	Regulation on Limit Values - MAC (Austria, 4/2021). Absorbed
	through skin. Sensitization potential.
	TWA: 0.05 mg/m ³ 8 hours. Form: Inhalable fraction
	CEIL: 0.05 mg/m ³ 15 minutes. Form: Inhalable fraction
reaction mass of: 5-chloro-2-methyl-	Regulation on Limit Values - MAC (Austria, 4/2021). [5-chloro-
4-isothiazolin-3-one [EC no. 247-500-7] and	2-methyl-2,3-dihydroisothiazol-3-one and 2-methyl-2,3-di-
2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	hydroisothiazol-3-one (mixture in the ratio 3:1)] Skin
Date of issue/Date of revision : 24/10/2023	Date of previous issue : 27/11/2019 Version : 1.09 5/19

	sensitiser.
No exposure limit value known.	TWA: 0.05 mg/m ³ 8 hours.
propylidynetrimethanol	Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021). Limit value 8 hours: 50 mg/m³ 8 hours.
No exposure limit value known.	
Ethyldiglycol 1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazol-3-one 2-Octyl-2H-isothiazol-3-one	 DFG MAC-values list (Germany, 7/2022). PEAK: 100 mg/m³, 4 times per shift, 15 minutes. Form: inhalab fraction TWA: 50 mg/m³ 8 hours. Form: inhalable fraction TRGS 900 OEL (Germany, 6/2022). TWA: 35 mg/m³ 8 hours. PEAK: 70 mg/m³ 15 minutes. TWA: 6 ppm 8 hours. PEAK: 12 ppm 15 minutes. DFG MAC-values list (Germany, 7/2022). Skin sensitiser. DFG MAC-values list (Germany, 7/2022). Skin sensitiser. TRGS 900 OEL (Germany, 6/2022). Absorbed through skin. TWA: 0.05 mg/m³ 8 hours. Form: Inhalable fraction PEAK: 0.1 mg/m³ 15 minutes. Form: inhalable fraction PEAK: 0.1 mg/m³, 4 times per shift, 15 minutes. Form: inhalable
No exposure limit value known.	fraction
No exposure limit value known.	
oropylidynetrimethanol	Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022). CEIL: 5 ppm
No exposure limit value known.	

SECTION 8: Exposure controls/personal protection

• •	•
Ethyldiglycol	Regulation on protection of workers from the risks related to
	exposure to chemical substances at work (Slovenia, 5/2021).
	KTV: 12 ppm, 4 times per shift, 15 minutes.
	TWA: 6 ppm 8 hours.
	KTV: 70 mg/m ³ , 4 times per shift, 15 minutes.
	TWA: 35 mg/m ³ 8 hours.
2-Octyl-2H-isothiazol-3-one	Regulation on protection of workers from the risks related to
	exposure to chemical substances at work (Slovenia, 5/2021).
	Absorbed through skin.
	TWA: 0.05 mg/m ³ 8 hours. Form: Inhalable fraction
	KTV: 0.1 mg/m ³ , 4 times per shift, 15 minutes. Form: Inhalable
	fraction
No exposure limit value known.	
₽ thyldiglycol	Work environment authority Regulation 2018:1 (Sweden,
	2/2018). Absorbed through skin.
	TWA: 15 ppm 8 hours.
	TWA: 80 mg/m ³ 8 hours.
	STEL: 30 ppm 15 minutes.
	STEL: 170 mg/m ³ 15 minutes.
₽ thyldiglycol	SUVA (Switzerland, 1/2023).
	STEL: 100 mg/m ³ 15 minutes. Form: Inhalable fraction of Vapor
	and aerosols
	TWA: 50 mg/m ³ 8 hours. Form: Inhalable fraction of Vapor and
	aerosols
2-Octyl-2H-isothiazol-3-one	SUVA (Switzerland, 1/2023). Absorbed through skin. Skin
	sensitiser.
	TWA: 0.05 mg/m ³ 8 hours. Form: Inhalable fraction
	STEL: 0.1 mg/m ³ 15 minutes. Form: Inhalable fraction
reaction mass of: 5-chloro-2-methyl-	SUVA (Switzerland, 1/2023). Skin sensitiser.
4-isothiazolin-3-one [EC no. 247-500-7] and	
2-methyl-2H-isothiazol-3-one [EC no.	
220-239-6] (3:1)	
	STEL: 0.4 mg/m ³ 15 minutes. Form: Inhalable fraction
	TWA: 0.2 mg/m ³ 8 hours. Form: Inhalable fraction
No exposure limit value known.	
· ·	

Biological exposure indices

Product/ingredient name			Exposure indic	es
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
No exposure indices known.				
ate of issue/Date of revision : 24/	/10/2023	Date of previous issue	: 27/11/2019	Version : 1.09 7/1

SECTION 8: Exposure cont	rols/personal protection	
No exposure indices known.		

procedures

European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
adipohydrazide	DNEL	Long term Inhalation	17.5 mg/m ³	Workers	Systemic
propylidynetrimethanol	DNEL	Long term Oral	0.34 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.34 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.58 mg/m ³		Systemic
	DNEL	Long term Dermal	0.94 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	3.3 mg/m ³	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m³	Workers	Systemic
2-methyl-2H-isothiazol-3-one	DNEL	Long term Inhalation	0.021 mg/ m³	General population	Local
	DNEL	Long term Inhalation	0.021 mg/ m³	Workers	Local
	DNEL	Long term Oral	0.027 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.043 mg/	General population	Local
	DNEL	Short term	0.043 mg/	Workers	Local
e of issue/Date of revision : 24/	10/2023	Date of previous issue	: 27/11/20	019	Version : 1.09 8/19
KNOBRUSH 6600-00 - BASE 1				La	abel No : <mark>5</mark> 1987

SECTION 8: Exposure cont	rols/p	ersonal prote	ction		
	DNEL	Inhalation Short term Oral	m³ 0.053 mg/ kg bw/day	General population	Systemic
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL	Long term Inhalation	0.02 mg/m ³	General population	Local
	DNEL	Long term Inhalation	0.02 mg/m³	Workers	Local
	DNEL	Short term Inhalation	0.04 mg/m ³	General population	Local
	DNEL	Short term Inhalation	0.04 mg/m ³	Workers	Local
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/ kg bw/day	General population	Systemic

PNECs

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Sood general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	<u>ires</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Mitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Propriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): 🛛 🕅 P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

: 24/10/2023 Date of previous issue

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: 🗾 Iquid.
Colour	: 🖉 olourless.
Odour	: <mark>S</mark> light
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and	:
boiling range	

Ingredient name	°C	°F	Method
water	100	212	
Ethyldiglycol	196	384.8	

Flammability

: Not available.

Lower and upper explosion	: 🔽 wer: Not applicable.
limit	Upper: Not applicable.
Flash point	: ℤlosed cup: >100°C (>212°F)

Flash point

Auto-ignition	temperature	:	

Ingredient name	°C	°F	Method
<mark>,</mark> €thyldiglycol	204	399.2	

Decomposition temperature	: Not available.
рН	: Not available.
Viscosity	: Not available.
Solubility(ies)	:
Not available.	
Solubility in water	: Not available.

Partition coefficient: n-octanol/	:	Not applicable.
water		

2

Vapour pressure

	Va	pour Pressu	re at 20°C	Va	pour pressu	re at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
Ethyldiglycol	0.14	0.019				

Relative density	: Not available.
Density	: 1.2 g/cm ³
Vapour density	: Not available.
Explosive properties	: Not available.
Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stabilit	and reactivity	
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients	s.
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Vinder normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: No specific data.	
10.5 Incompatible materials	: No specific data.	
10.6 Hazardous decomposition products	: Inder normal conditions of storage and use, hazardous decomposition products should not be produced.	

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
propylidynetrimethanol	LD50 Oral	Rat	14000 mg/kg	-
1,2-benzisothiazol-3(2H)- one	LD50 Oral	Rat	1020 mg/kg	-
2-methyl-2H-isothiazol- 3-one	LC50 Inhalation Dusts and mists	Rat	0.11 mg/l	4 hours
2-Octyl-2H-isothiazol-3-one	LD50 Dermal LD50 Oral	Rabbit Rat	690 mg/kg 550 mg/kg	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin-	LD50 Oral	Rat	53 mg/kg	-
3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:				
1)				

Conclusion/Summary

: **B**ased on available data, the classification criteria are not met.

Acute toxicity estimates

Route	ATE value
halation (vapours)	386.11 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
<mark>ti</mark> tanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
1,2-benzisothiazol-3(2H)-one	Skin - Mild irritant	Human	-	48 hours 5 %	-
2-Octyl-2H-isothiazol-3-one	Eyes - Severe irritant	Rabbit	-	100 mg	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Severe irritant	Human	-	0.01 %	-
Conclusion/Summary	: Based on available data, the	classification cr	iteria are	not met.	
Sensitisation					
Conclusion/Summary	: Based on available data, the	classification cr	iteria are	not met.	
Mutagenicity					
Conclusion/Summary <u>Carcinogenicity</u>	: Based on available data, the o	classification cr	iteria are	not met.	

: 24/10/2023 Date of previous issue

SECTION 11: Toxico	logical information
	carcinogenic hazard of this product arises when respirable dust is inhaled in quantities
	ent of particle clearance mechanisms in the lung.
Conclusion/Summary	: B ased on available data, the classification criteria are not met.
Reproductive toxicity	
Conclusion/Summary	: B ased on available data, the classification criteria are not met.
Teratogenicity	
Conclusion/Summary	: B ased on available data, the classification criteria are not met.
Specific target organ toxici	<u>ty (single exposure)</u>
Not available.	
Specific target organ toxici	ty (repeated exposure)
Not available.	
Aspiration hazard	
Not available.	
Information on likely routed	: Not available.
Information on likely routes of exposure	
Potential acute health effects	s
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
ingootion	
Symptoms related to the phy	vsical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: 📈 specific data.
Deleved and immediate offer	
Short term exposure	cts as well as chronic effects from short and long-term exposure
Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
Not available.	
Conclusion/Summary	: Not available.
General	. No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
11.2 Information on other ha	zards
11.2.1 Endocrine disrupting	
Not available	, <u> </u>

Not available.

11.2.2 Other information

: 24/10/2023 Date of previous issue

SECTION 11: Toxicological information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia	48 hours
	Acute LC50 6.5 mg/l Fresh water	<i>dubia</i> - Neonate Daphnia - <i>Daphnia pulex</i> - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours
propylidynetrimethanol	Acute EC50 13000000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 14400000 µg/l Marine water	Fish - Cyprinodon variegatus	96 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.36 mg/l Marine water	Algae - Skeletonema Costatum	72 hours
	Acute EC50 3.7 mg/l	Daphnia - <i>Daphnia Magna</i>	48 hours
	Acute LC50 1.9 mg/l Fresh water	Fish - Onorhynchus Mykiss	96 hours
	Acute NOEC 0.15 mg/l Marine water	Algae - Skeletonema Costatum	72 hours
2-methyl-2H-isothiazol-3-one	Acute EC50 0.18 ppm Fresh water	Daphnia - Daphnia magna	48 hours
-	Acute LC50 0.07 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
2-Octyl-2H-isothiazol-3-one	Acute EC50 107 ppb Fresh water	Daphnia - Daphnia magna	48 hours
-	Acute LC50 47 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 74 ppb Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 8.5 ppb	Fish - Pimephales promelas	35 days
2-Methyl-1,2-benzisothiazol- 3(2H)-one	Acute EC50 0.22 ppm Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 0.92 ppm Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 0.24 ppm Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 0.16 ppm	Fish - Pimephales promelas	32 days

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
7,2-benzisothiazol-3(2H)-one	EU	24 % - 28 days		-	-
Conclusion/Summary : This product has not been tested for biodegradation.					
Product/ingredient name	Aquatic half-life		Photolysis	5	Biodegradability
7,2-benzisothiazol-3(2H)-one	-		-		Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
propylidynetrimethanol 1,2-benzisothiazol-3(2H)-one	-0.47	<1 3.2	Low Low
2-Octyl-2H-isothiazol-3-one	2.45	-	Low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.



SECTION 12: Ecological information

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

	-
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	Mithin the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
European waste catalogue (EWC)	: 🕅 80112
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	-			
	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name				
14.3 Transport hazard class(es)				
14.4 Packing group				
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

: 24/10/2023 Date of previous issue

SECTION 15: Regulatory information

5	,		
	onmental regulations/legislation specif	fic for the substance o	or mixture
EU Regulation (EC) No. 190			
	inces subject to authorisation		
Annex XIV			
None of the components a	are listed.		
Substances of very high			
None of the components a	are listed.		
Annex XVII - Restrictions of	n the manufacture, placing on the mark	tet and use of certain	dangerous_
substances, mixtures and a	articles		-
Labelling	:		
Other EU regulations			
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed		
Industrial emissions	: Not listed		
(integrated pollution prevention and control) -			
Water			
Explosive precursors	: Not applicable.		
Ozone depleting substand Not listed.	<u>;es (1005/2009/EU)</u>		
Prior Informed Consent (P Not listed.	<u>'IC) (649/2012/EU)</u>		
Persistent Organic Polluta Not listed.	<u>ants</u>		
Seveso Directive	d under the Seveso Directive.		
National regulations			
Austria			
VbF class	: Not regulated.		
Limitation of the use of organic solvents	: P ermitted.		
Czech Republic			
Storage code	: 🕅		
<u>Denmark</u>			
Danish fire class	: 🕂 -1		
Executive Order No. 1795/	/2015		
Ingredient name		Annex I Section A	Annex I Section B
titanium dioxide		Listed	-
•			
MAL-code			a du ata tha fallouina.
Protection based on MAL	: According to the regulations on work stipulations apply to the use of per		
	General: Gloves must be worn for al coveralls/protective clothing must be clothes do not adequately protect skir shield must be worn in work involving case, other recommended use of eye	worn when soiling is so against contact with th spattering if a full mask	great that regular work e product. A face t is not required. In this
	In all spraying operations in which the respiratory protection and arm protect		
Date of issue/Date of revision	: 24/10/2023 Date of previous issue	: 27/11/2019	Version : 1.09 15/19
EKNOBRUSH 6600-00 - BAS	SE 1		Label No : <mark>5</mark> 1987

appropriate or as instructed.

		MAL-code: 00-1 Application: When spraying in existing* spray booths, if the operator is outside the spray zone.
		- Arm protectors must be worn.
		During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cab or booth.
		- Full mask with combined filter, coveralls and hood must be worn.
		Drying: Items for drying/drying ovens that are temporarily placed on such things rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.
		Polishing: When polishing treated surfaces, a mask with dust filter must be worn When machine grinding, eye protection must be worn. Work gloves must always worn.
		Caution The regulations contain other stipulations in addition to the above.
		*See Regulations.
Restrictions on use	:	Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Wo
List of undesirable substances	:	Not listed
Carcinogenic waste	:	Waste containers must be labeled: Contains a substance or substances regulate by Danish working environment legislation on cancer risks.
Finland		
France Reinforced medical surveillance	:	Ct of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable
<u>Germany</u>		
Storage class (TRGS 510)		
Hazardous incident ordina		
Hazard class for water		nder the Germany Hazardous Incident Ordinance.
Technical instruction on		A-Luft Number 5.2.5: 4.3%
air quality control AOX	:	The product contains organically bound halogens and can contribute to the AOX
Italy		value in waste water.
D.Lgs. 152/06	۰.	Not determined.
Netherlands		
Water Discharge Policy (ABM)	:	$\mathbf{K}(3)$ Hazardous for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A
<u>Norway</u>		
<u>Sweden</u>		
Switzerland		
VOC content	1	Exempt.
nternational regulations		

FEKNOBRUSH 6600-00 - BASE 1

SECTION 15: Regulatory information

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety

: Not applicable.

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

Full text of abbreviated H statements

⊮ 301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H351	Suspected of causing cancer.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

SECTION 16: Other information

Acute Tox. 2	ACUTE TOXICITY - Category 2	
Acute Tox. 3	ACUTE TOXICITY - Category 3	
Acute Tox. 4	ACUTE TOXICITY - Category 4	
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1	
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1	
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	
Carc. 2	CARCINOGENICITY - Category 2	
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
Repr. 2	REPRODUCTIVE TOXICITY - Category 2	
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1	
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B	
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
Skin Sens. 1	SKIN SENSITISATION - Category 1	
Skin Sens. 1A	SKIN SENSITISATION - Category 1A	
Date of issue/ Date of	: 24/10/2023	
revision		
Date of previous issue	e : 27/11/2019	
Version	: 1.09	
	KNOBRUSH 6600-00_BASE 1	

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

: 24/10/2023 Date of previous issue