

# SAFETY DATA SHEET



TEKNOCOAT 1687-58

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : TEKNOCOAT 1687-58

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

Telephone number : In an emergency, call 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225

Eye Irrit. 2, H319

STOT SE 3, H336


The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 - Highly flammable liquid and vapour.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.

#### Precautionary statements

Prevention : P280 - Wear eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 - Avoid breathing vapour.

Response : P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Storage : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : Contains: n-Butyl acetate; Propan-2-ol and Ethyl acetate

Date of issue/Date of revision

: 12/06/2026

Date of previous issue

: 14/05/2024

Version : 1.01 1/45

TEKNOCOAT 1687-58

Label No : 31488

## SECTION 2: Hazards identification

**Supplemental label elements** :  Contains Formaldehyde. May produce an allergic reaction.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :


### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
 Butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
Ethanol	REACH #: 01-2119457610-43 EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5	≥10 - ≤25	Flam. Liq. 2, H225 Eye Irrit. 2, H319	-	[1]
Propan-2-ol	REACH #: 01-2119457558-25 EC: 200-661-7 CAS: 67-63-0 Index: 603-117-00-0	≤10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	-	[1]
Urea, polymer with formaldehyde, butylated	CAS: 68002-19-7	≤5	Aquatic Chronic 4, H413	-	[1]
Ethyl acetate	REACH #: 01-2119475103-46 EC: 205-500-4 CAS: 141-78-6 Index: 607-022-00-5	≤5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	-	[1] [2]
2-Methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≤3	Flam. Liq. 3, H226	-	[2]
Reaction mass of: 2-[2-(benzoyloxy)ethoxy]ethyl benzoate, 1-[2-(benzoyloxy)propoxy]propan-2-yl benzoate and 2-[2-[2-(benzoyloxy)ethoxy]ethoxy] ethyl benzoate	EC: 907-434-8	≤3	Aquatic Chronic 3, H412	-	[1]

## SECTION 3: Composition/information on ingredients

Urea-formaldehyde-polymer	CAS: 68002-18-6	≤3	Aquatic Chronic 4, H413	-	
Formaldehyde	REACH #: 01-2119488953-20 EC: 200-001-8 CAS: 50-00-0 Index: 605-001-00-5	<0.1	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H335 EUH071	ATE [Oral] = 500 mg/kg ATE [Inhalation (gases)] = 100 ppm Skin Corr. 1B, H314: C ≥ 25% Skin Irrit. 2, H315: 5% ≤ C < 25% Eye Dam. 1, H318: C ≥ 25% Eye Irrit. 2, H319: 5% ≤ C < 25% STOT SE 3, H335: C ≥ 5%	[1] [2]

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

### See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

#### Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

#### Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

#### Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

Date of issue/Date of revision

: 12/06/2026

Date of previous issue

: 14/05/2024

Version : 1.01 3/45

TEKNOCOAT 1687-58

Label No : 31488

## SECTION 4: First aid measures

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures


**For non-emergency personnel** :  No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour. Put on appropriate personal protective equipment.


**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

## SECTION 6: Accidental release measures

**6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** :  Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** :  Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage


The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.


**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

 Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
 5c	5000 tonnes	50000 tonnes

### 7.3 Specific end use(s)

**Recommendations** : Not available.

## SECTION 7: Handling and storage

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection



The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
<input checked="" type="checkbox"/> Butyl acetate	<b>Regulation on Limit Values - MAC (Austria, 12/2025) [Butylacetat alle Isomeren außer tert-Butylacet]</b> CEIL: 480 mg/m <sup>3</sup> . CEIL: 100 ppm. TWA 8 hours: 241 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm.
Ethanol	<b>Regulation on Limit Values - MAC (Austria, 12/2025)</b> TWA 8 hours: 1000 ppm. TWA 8 hours: 1900 mg/m <sup>3</sup> . CEIL 60 minutes: 2000 ppm 3 times per shift. CEIL 60 minutes: 3800 mg/m <sup>3</sup> 3 times per shift.
Propan-2-ol	<b>Regulation on Limit Values - MAC (Austria, 12/2025)</b> TWA 8 hours: 200 ppm. TWA 8 hours: 500 mg/m <sup>3</sup> . PEAK 15 minutes: 800 ppm 4 times per shift. PEAK 15 minutes: 2000 mg/m <sup>3</sup> 4 times per shift.
Ethyl acetate	<b>Regulation on Limit Values - MAC (Austria, 12/2025)</b> TWA 8 hours: 200 ppm. TWA 8 hours: 734 mg/m <sup>3</sup> . PEAK 15 minutes: 1468 mg/m <sup>3</sup> 4 times per shift. PEAK 15 minutes: 400 ppm 4 times per shift.
2-Methoxy-1-methylethyl acetate	<b>Regulation on Limit Values - MAC (Austria, 12/2025) Absorbed through skin.</b> TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m <sup>3</sup> . CEIL 5 minutes: 100 ppm 8 times per shift. CEIL 5 minutes: 550 mg/m <sup>3</sup> 8 times per shift.
Formaldehyde	<b>Regulation on Limit Values - MAC (Austria, 12/2025) Carc 1B.</b> Skin sensitiser. TWA 8 hours: 0.3 ppm. TWA 8 hours: 0.37 mg/m <sup>3</sup> . CEIL: 0.6 ppm. CEIL: 0.74 mg/m <sup>3</sup> .
<input checked="" type="checkbox"/> Butyl acetate	<b>Limit values (Belgium, 12/2023) [butylacetaat]</b> STEL 15 minutes: 712 mg/m <sup>3</sup> . STEL 15 minutes: 150 ppm. TWA 8 hours: 238 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm.
Ethanol	<b>Limit values (Belgium, 12/2023)</b> TWA 8 hours: 1000 ppm. TWA 8 hours: 1907 mg/m <sup>3</sup> .
Propan-2-ol	<b>Limit values (Belgium, 12/2023)</b> TWA 8 hours: 200 ppm. TWA 8 hours: 500 mg/m <sup>3</sup> . STEL 15 minutes: 400 ppm. STEL 15 minutes: 1000 mg/m <sup>3</sup> .
Ethyl acetate	<b>Limit values (Belgium, 12/2023)</b> TWA 8 hours: 200 ppm. TWA 8 hours: 734 mg/m <sup>3</sup> . STEL 15 minutes: 1468 mg/m <sup>3</sup> . STEL 15 minutes: 400 ppm.



## SECTION 8: Exposure controls/personal protection

2-Methoxy-1-methylethyl acetate	<p><b>Limit values (Belgium, 12/2023)</b> Absorbed through skin.</p> <p>TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>Limit values (Belgium, 12/2023) C.</b></p> <p>Limit value - M: 0.3 ppm. Limit value - M: 0.38 mg/m<sup>3</sup>.</p>
 Butyl acetate	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024)</b></p> <p>Limit value 8 hours: 241 mg/m<sup>3</sup>. Limit value 15 minutes: 723 mg/m<sup>3</sup>. Limit value 15 minutes: 150 ppm. Limit value 8 hours: 50 ppm.</p>
Ethanol	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024)</b></p> <p>Limit value 8 hours: 1000 mg/m<sup>3</sup>.</p>
Propan-2-ol	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024)</b></p> <p>Limit value 8 hours: 980 mg/m<sup>3</sup>. Limit value 15 minutes: 1225 mg/m<sup>3</sup>.</p>
Ethyl acetate	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024)</b></p> <p>Limit value 8 hours: 734 mg/m<sup>3</sup>. Limit value 15 minutes: 400 ppm. Limit value 15 minutes: 1468 mg/m<sup>3</sup>. Limit value 8 hours: 200 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024)</b> Absorbed through skin.</p> <p>Limit value 8 hours: 275 mg/m<sup>3</sup>. Limit value 15 minutes: 550 mg/m<sup>3</sup>. Limit value 15 minutes: 100 ppm. Limit value 8 hours: 50 ppm.</p>
Formaldehyde	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 10/2003 (OEL). (Bulgaria, 4/2024)</b> Skin sensitiser.</p> <p>Limit value 15 minutes: 0.74 mg/m<sup>3</sup>. Limit value 8 hours: 0.37 mg/m<sup>3</sup>. Limit value 15 minutes: 0.5 ppm. Form: For the healthcare, funeral and embalming sectors. Limit value 8 hours: 0.62 mg/m<sup>3</sup>. Form: For the healthcare, funeral and embalming sectors. Limit value 15 minutes: 0.6 ppm. Limit value 8 hours: 0.3 ppm.</p>
 Butyl acetate	<p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 10/2025)</b></p> <p>STELV 15 minutes: 723 mg/m<sup>3</sup>. STELV 15 minutes: 150 ppm. ELV 8 hours: 241 mg/m<sup>3</sup>. ELV 8 hours: 50 ppm.</p>
Ethanol	<p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 10/2025)</b></p> <p>ELV 8 hours: 1900 mg/m<sup>3</sup>. ELV 8 hours: 1000 ppm.</p>
Propan-2-ol	<p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 10/2025)</b></p> <p>STELV 15 minutes: 1250 mg/m<sup>3</sup>. STELV 15 minutes: 500 ppm.</p>

## SECTION 8: Exposure controls/personal protection

Ethyl acetate	<p>ELV 8 hours: 999 mg/m<sup>3</sup>.                      ELV 8 hours: 400 ppm.</p> <p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 10/2025)</b></p> <p>STELV 15 minutes: 400 ppm.                      ELV 8 hours: 200 ppm.                      STELV 15 minutes: 1468 mg/m<sup>3</sup>.                      ELV 8 hours: 734 mg/m<sup>3</sup>.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 10/2025)</b> Absorbed through skin.</p> <p>STELV 15 minutes: 550 mg/m<sup>3</sup>.                      STELV 15 minutes: 100 ppm.                      ELV 8 hours: 275 mg/m<sup>3</sup>.                      ELV 8 hours: 50 ppm.</p>
Formaldehyde	<p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 10/2025)</b> Carc 1B. Skin sensitiser.</p> <p>STELV 15 minutes: 0.74 mg/m<sup>3</sup>.                      STELV 15 minutes: 0.6 ppm.                      ELV 8 hours: 0.37 mg/m<sup>3</sup>.                      ELV 8 hours: 0.3 ppm.</p>
n-Butyl acetate	<p><b>Department of Labor Inspection, Chemical Agents (Cyprus, 11/2025)</b></p> <p>STEL 15 minutes: 150 ppm.                      STEL 15 minutes: 723 mg/m<sup>3</sup>.                      TWA 8 hours: 50 ppm.                      TWA 8 hours: 241 mg/m<sup>3</sup>.</p>
Ethyl acetate	<p><b>Department of Labor Inspection, Chemical Agents (Cyprus, 11/2025)</b></p> <p>STEL 15 minutes: 400 ppm.                      STEL 15 minutes: 1468 mg/m<sup>3</sup>.                      TWA 8 hours: 200 ppm.                      TWA 8 hours: 734 mg/m<sup>3</sup>.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Department of Labor Inspection, Chemical Agents (Cyprus, 11/2025)</b> Absorbed through skin.</p> <p>STEL 15 minutes: 100 ppm.                      STEL 15 minutes: 550 mg/m<sup>3</sup>.                      TWA 8 hours: 50 ppm.                      TWA 8 hours: 275 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>EU OEL (Europe, 3/2024)</b> Skin sensitiser.</p> <p>STEL 15 minutes: 0.6 ppm.                      STEL 15 minutes: 0.74 mg/m<sup>3</sup>.                      TWA 8 hours: 0.3 ppm.                      TWA 8 hours: 0.37 mg/m<sup>3</sup>.</p>
n-Butyl acetate	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 11/2025)</b></p> <p>TWA 8 hours: 241 mg/m<sup>3</sup>.                      STEL 15 minutes: 723 mg/m<sup>3</sup>.                      STEL 15 minutes: 150 ppm.                      TWA 8 hours: 50 ppm.</p>
Ethanol	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 11/2025)</b></p> <p>TWA 8 hours: 1000 mg/m<sup>3</sup>.                      TWA 8 hours: 522 ppm.                      STEL 15 minutes: 3000 mg/m<sup>3</sup>.                      STEL 15 minutes: 1566 ppm.</p>
Propan-2-ol	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 11/2025)</b></p> <p>TWA 8 hours: 500 mg/m<sup>3</sup>.                      TWA 8 hours: 200 ppm.</p>


## SECTION 8: Exposure controls/personal protection

Ethyl acetate	<p>STEL 15 minutes: 1000 mg/m<sup>3</sup>. STEL 15 minutes: 400 ppm.</p> <p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 11/2025)</b></p> <p>TWA 8 hours: 700 mg/m<sup>3</sup>. TWA 8 hours: 191.1 ppm. STEL 15 minutes: 900 mg/m<sup>3</sup>. STEL 15 minutes: 245.7 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 11/2025)</b> Absorbed through skin.</p> <p>TWA 8 hours: 275 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. STEL 15 minutes: 550 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm.</p>
Formaldehyde	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 11/2025)</b> Carc. Sensitiser.</p> <p>TWA 8 hours: 0.37 mg/m<sup>3</sup>. TWA 8 hours: 0.3 ppm. STEL 15 minutes: 0.74 mg/m<sup>3</sup>. STEL 15 minutes: 0.6 ppm.</p>
 Butyl acetate	<p><b>Working Environment Authority (Denmark, 11/2025)</b> <b>[butylacetat, alle isomerer]</b></p> <p>TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m<sup>3</sup>. STEL 15 minutes: 723 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm.</p>
Ethanol	<p><b>Working Environment Authority (Denmark, 11/2025)</b></p> <p>TWA 8 hours: 1000 ppm. TWA 8 hours: 1900 mg/m<sup>3</sup>. STEL 15 minutes: 3800 mg/m<sup>3</sup>. STEL 15 minutes: 2000 ppm.</p>
Propan-2-ol	<p><b>Working Environment Authority (Denmark, 11/2025)</b></p> <p>TWA 8 hours: 200 ppm. TWA 8 hours: 490 mg/m<sup>3</sup>. STEL 15 minutes: 980 mg/m<sup>3</sup>. STEL 15 minutes: 400 ppm.</p>
Ethyl acetate	<p><b>Working Environment Authority (Denmark, 11/2025)</b></p> <p>TWA 8 hours: 150 ppm. TWA 8 hours: 540 mg/m<sup>3</sup>. STEL 15 minutes: 1468 mg/m<sup>3</sup>. STEL 15 minutes: 400 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Working Environment Authority (Denmark, 11/2025)</b> <b>[2-methoxy-1-methylethylacetat]</b> Absorbed through skin.</p> <p>TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m<sup>3</sup>. STEL 15 minutes: 550 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm.</p>
Formaldehyde	<p><b>Working Environment Authority (Denmark, 11/2025)</b> K. Skin sensitiser.</p> <p>TWA 8 hours: 0.37 mg/m<sup>3</sup>. TWA 8 hours: 0.3 ppm. STEL 15 minutes: 0.74 mg/m<sup>3</sup>. STEL 15 minutes: 0.6 ppm.</p>
 Butyl acetate	<p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024)</b></p> <p>STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m<sup>3</sup>.</p>
Ethanol	<p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024)</b></p> <p>TWA 8 hours: 1000 mg/m<sup>3</sup>.</p>

## SECTION 8: Exposure controls/personal protection

Propan-2-ol	<p>TWA 8 hours: 500 ppm.          STEL 15 minutes: 1900 mg/m<sup>3</sup>.          STEL 15 minutes: 1000 ppm.</p> <p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024)</b></p> <p>TWA 8 hours: 350 mg/m<sup>3</sup>.          TWA 8 hours: 150 ppm.          STEL 15 minutes: 600 mg/m<sup>3</sup>.          STEL 15 minutes: 250 ppm.</p>
Ethyl acetate	<p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024)</b></p> <p>TWA 8 hours: 500 mg/m<sup>3</sup>.          TWA 8 hours: 150 ppm.          STEL 15 minutes: 1100 mg/m<sup>3</sup>.          STEL 15 minutes: 300 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024)</b> Absorbed through skin , Sensitiser.</p> <p>STEL 15 minutes: 100 ppm.          STEL 15 minutes: 550 mg/m<sup>3</sup>.          TWA 8 hours: 275 mg/m<sup>3</sup>.          TWA 8 hours: 50 ppm.</p>
Formaldehyde	<p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024)</b> Carc. Sensitiser.</p> <p>TWA 8 hours: 0.37 mg/m<sup>3</sup>.          TWA 8 hours: 0.3 ppm.          STEL 5 minutes: 0.6 ppm.          STEL 5 minutes: 0.74 mg/m<sup>3</sup>.          TWA 8 hours: 0.5 ppm. Form: In the healthcare, funeral and embalming sector.          TWA 8 hours: 0.62 mg/m<sup>3</sup>. Form: In the healthcare, funeral and embalming sector.</p>
n-Butyl acetate	<p><b>EU OEL (Europe, 1/2022)</b></p> <p>STEL 15 minutes: 150 ppm.          STEL 15 minutes: 723 mg/m<sup>3</sup>.          TWA 8 hours: 241 mg/m<sup>3</sup>.          TWA 8 hours: 50 ppm.</p>
Ethyl acetate	<p><b>EU OEL (Europe, 1/2022)</b></p> <p>STEL 15 minutes: 400 ppm.          STEL 15 minutes: 1468 mg/m<sup>3</sup>.          TWA 8 hours: 200 ppm.          TWA 8 hours: 734 mg/m<sup>3</sup>.</p>
2-Methoxy-1-methylethyl acetate	<p><b>EU OEL (Europe, 1/2022)</b> Absorbed through skin.</p> <p>TWA 8 hours: 50 ppm.          TWA 8 hours: 275 mg/m<sup>3</sup>.          STEL 15 minutes: 100 ppm.          STEL 15 minutes: 550 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>EU OEL (Europe, 3/2024)</b> Skin sensitiser.</p> <p>STEL 15 minutes: 0.6 ppm.          STEL 15 minutes: 0.74 mg/m<sup>3</sup>.          TWA 8 hours: 0.3 ppm.          TWA 8 hours: 0.37 mg/m<sup>3</sup>.</p>
n-Butyl acetate	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 2/2025)</b></p> <p>TWA 8 hours: 150 ppm.          TWA 8 hours: 720 mg/m<sup>3</sup>.          STEL 15 minutes: 200 ppm.          STEL 15 minutes: 960 mg/m<sup>3</sup>.</p>
Ethanol	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 2/2025)</b></p> <p>TWA 8 hours: 200 ppm.          TWA 8 hours: 380 mg/m<sup>3</sup>.          STEL 15 minutes: 800 ppm.</p>

## SECTION 8: Exposure controls/personal protection

Propan-2-ol	<p>STEL 15 minutes: 1520 mg/m<sup>3</sup>.  <b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 2/2025)</b>  TWA 8 hours: 200 ppm.  TWA 8 hours: 500 mg/m<sup>3</sup>.  STEL 15 minutes: 250 ppm.  STEL 15 minutes: 620 mg/m<sup>3</sup>.</p>
Ethyl acetate	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 2/2025)</b>  TWA 8 hours: 200 ppm.  TWA 8 hours: 730 mg/m<sup>3</sup>.  STEL 15 minutes: 400 ppm.  STEL 15 minutes: 1470 mg/m<sup>3</sup>.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 2/2025)</b> Absorbed through skin.  TWA 8 hours: 50 ppm.  TWA 8 hours: 270 mg/m<sup>3</sup>.  STEL 15 minutes: 100 ppm.  STEL 15 minutes: 550 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 2/2025)</b> CARC. Skin sensitiser.  TWA 8 hours: 0.3 ppm.  TWA 8 hours: 0.37 mg/m<sup>3</sup>.  STEL 15 minutes: 0.74 mg/m<sup>3</sup>.  STEL 15 minutes: 0.6 ppm.</p>
 Butyl acetate	<p><b>Ministry of Labor (France, 6/2024)</b>  TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)  TWA 8 hours: 241 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)  STEL 15 minutes: 150 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)  STEL 15 minutes: 723 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p>
Ethanol	<p><b>Ministry of Labor (France, 6/2024)</b>  TWA 8 hours: 1000 ppm. Notes: Permissible limit values (circulars)  TWA 8 hours: 1900 mg/m<sup>3</sup>. Notes: Permissible limit values (circulars)  STEL 15 minutes: 5000 ppm. Notes: Permissible limit values (circulars)  STEL 15 minutes: 9500 mg/m<sup>3</sup>. Notes: Permissible limit values (circulars)</p>
Propan-2-ol	<p><b>Ministry of Labor (France, 6/2024)</b>  STEL 15 minutes: 400 ppm. Notes: Permissible limit values (circulars)  STEL 15 minutes: 980 mg/m<sup>3</sup>. Notes: Permissible limit values (circulars)</p>
Ethyl acetate	<p><b>Ministry of Labor (France, 6/2024)</b>  TWA 8 hours: 200 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)  TWA 8 hours: 734 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)  STEL 15 minutes: 1468 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)  STEL 15 minutes: 400 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p>
2-Methoxy-1-methylethyl acetate	<p><b>Ministry of Labor (France, 6/2024)</b> Absorbed through skin.  STEL 15 minutes: 550 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)  STEL 15 minutes: 100 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)  TWA 8 hours: 275 mg/m<sup>3</sup>. Notes: Binding regulatory limit values</p>

## SECTION 8: Exposure controls/personal protection

Formaldehyde	<p>(article R. 4412-149 of the Labor Code) TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p> <p><b>Ministry of Labor (France, 6/2024)</b> Carc 1B, Muta 2. Skin sensitiser. TWA 8 hours: 0.3 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 0.6 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 0.74 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 0.37 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p>
n-Butyl acetate	<p><b>TRGS 900 OEL (Germany, 12/2025)</b> TWA 8 hours: 300 mg/m<sup>3</sup>. TWA 8 hours: 62 ppm. PEAK 15 minutes: 600 mg/m<sup>3</sup>. PEAK 15 minutes: 124 ppm.</p> <p><b>DFG MAC-values list (Germany, 7/2025)</b> Develop C. TWA 8 hours: 100 ppm. PEAK 15 minutes: 200 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 480 mg/m<sup>3</sup>. PEAK 15 minutes: 960 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].</p>
Ethanol	<p><b>TRGS 900 OEL (Germany, 12/2025)</b> TWA 8 hours: 380 mg/m<sup>3</sup>. PEAK 15 minutes: 1520 mg/m<sup>3</sup>. TWA 8 hours: 200 ppm. PEAK 15 minutes: 800 ppm.</p> <p><b>DFG MAC-values list (Germany, 7/2025)</b> Carc 5, Muta 5, Develop C. TWA 8 hours: 200 ppm. PEAK 15 minutes: 800 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 380 mg/m<sup>3</sup>. PEAK 15 minutes: 1520 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].</p>
Propan-2-ol	<p><b>TRGS 900 OEL (Germany, 12/2025)</b> TWA 8 hours: 500 mg/m<sup>3</sup>. PEAK 15 minutes: 1000 mg/m<sup>3</sup>. TWA 8 hours: 200 ppm. PEAK 15 minutes: 400 ppm.</p> <p><b>DFG MAC-values list (Germany, 7/2025)</b> Develop C. TWA 8 hours: 200 ppm. PEAK 15 minutes: 400 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 500 mg/m<sup>3</sup>. PEAK 15 minutes: 1000 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].</p>
Ethyl acetate	<p><b>TRGS 900 OEL (Germany, 12/2025)</b> TWA 8 hours: 730 mg/m<sup>3</sup>. PEAK 15 minutes: 1460 mg/m<sup>3</sup>. TWA 8 hours: 200 ppm. PEAK 15 minutes: 400 ppm.</p> <p><b>DFG MAC-values list (Germany, 7/2025)</b> Develop C. TWA 8 hours: 200 ppm. PEAK 15 minutes: 400 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 750 mg/m<sup>3</sup>. PEAK 15 minutes: 1500 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].</p>
2-Methoxy-1-methylethyl acetate	<p><b>TRGS 900 OEL (Germany, 12/2025)</b> TWA 8 hours: 270 mg/m<sup>3</sup>. PEAK 15 minutes: 270 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. PEAK 15 minutes: 50 ppm.</p> <p><b>DFG MAC-values list (Germany, 7/2025)</b> Develop C. TWA 8 hours: 50 ppm. PEAK 15 minutes: 50 ppm 4 times per shift [Interval: 1 hour].</p>



## SECTION 8: Exposure controls/personal protection

Formaldehyde	<p>TWA 8 hours: 270 mg/m<sup>3</sup>. PEAK 15 minutes: 270 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].</p> <p><b>TRGS 900 OEL (Germany, 12/2025)</b> Skin sensitiser. TWA 8 hours: 0.37 mg/m<sup>3</sup>. TWA 8 hours: 0.3 ppm. PEAK 15 minutes: 0.6 ppm. PEAK 15 minutes: 0.74 mg/m<sup>3</sup>.</p> <p><b>DFG MAC-values list (Germany, 7/2025)</b> Carc 4, Muta 5, Develop C. Skin sensitiser. TWA 8 hours: 0.3 ppm. CEIL: 1 ml/m<sup>3</sup>. TWA 8 hours: 0.37 mg/m<sup>3</sup>. CEIL: 1.2 mg/m<sup>3</sup>. PEAK 15 minutes: 0.74 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour]. PEAK 15 minutes: 0.6 ppm 4 times per shift [Interval: 1 hour].</p>
n-Butyl acetate	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024)</b> TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m<sup>3</sup>.</p>
Ethanol	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024)</b> TWA 8 hours: 1000 ppm. TWA 8 hours: 1900 mg/m<sup>3</sup>.</p>
Propan-2-ol	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024)</b> TWA 8 hours: 400 ppm. TWA 8 hours: 980 mg/m<sup>3</sup>. STEL 15 minutes: 500 ppm. STEL 15 minutes: 1225 mg/m<sup>3</sup>.</p>
Ethyl acetate	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024)</b> TWA 8 hours: 200 ppm. TWA 8 hours: 734 mg/m<sup>3</sup>. STEL 15 minutes: 1468 mg/m<sup>3</sup>. STEL 15 minutes: 400 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024)</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024)</b> Skin sensitiser. TWA 8 hours: 0.3 ppm. TWA 8 hours: 0.37 mg/m<sup>3</sup>. STEL 15 minutes: 0.6 ppm. STEL 15 minutes: 0.74 mg/m<sup>3</sup>.</p>
n-Butyl acetate	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 2/2026)</b> Sensitiser. TWA 8 hours: 241 mg/m<sup>3</sup>. PEAK 15 minutes: 723 mg/m<sup>3</sup>. PEAK 15 minutes: 150 ppm. TWA 8 hours: 50 ppm.</p>
Ethanol	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 2/2026)</b> TWA 8 hours: 1900 mg/m<sup>3</sup>. PEAK 15 minutes: 3800 mg/m<sup>3</sup>. PEAK 15 minutes: 2000 ppm. TWA 8 hours: 1000 ppm.</p>
Propan-2-ol	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 2/2026)</b> Absorbed through skin.</p>

## SECTION 8: Exposure controls/personal protection

Ethyl acetate	TWA 8 hours: 500 mg/m <sup>3</sup> . PEAK 15 minutes: 1000 mg/m <sup>3</sup> . PEAK 15 minutes: 400 ppm. TWA 8 hours: 200 ppm. <b>5/2020. (II. 6.) ITM Decree (Hungary, 2/2026)</b> Sensitiser. TWA 8 hours: 734 mg/m <sup>3</sup> . PEAK 15 minutes: 1468 mg/m <sup>3</sup> . PEAK 15 minutes: 400 ppm. TWA 8 hours: 200 ppm.
2-Methoxy-1-methylethyl acetate	<b>5/2020. (II. 6.) ITM Decree (Hungary, 2/2026)</b> TWA 8 hours: 275 mg/m <sup>3</sup> . PEAK 15 minutes: 550 mg/m <sup>3</sup> . PEAK 15 minutes: 100 ppm. TWA 8 hours: 50 ppm.
Formaldehyde	<b>5/2020. (II. 6.) ITM Decree (Hungary, 2/2026)</b> k(1B). Absorbed through skin , Sensitiser. TWA 8 hours: 0.37 mg/m <sup>3</sup> . PEAK 15 minutes: 0.74 mg/m <sup>3</sup> . PEAK 15 minutes: 0.6 ppm. TWA 8 hours: 0.3 ppm.
Butyl acetate	<b>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) [bútýlasetat, allir ísómerar]</b> TWA 8 hours: 241 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm. STEL 15 minutes: 723 mg/m <sup>3</sup> . STEL 15 minutes: 150 ppm.
Ethanol	<b>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024)</b> TWA 8 hours: 1900 mg/m <sup>3</sup> . TWA 8 hours: 1000 ppm.
Propan-2-ol	<b>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024)</b> Absorbed through skin. TWA 8 hours: 490 mg/m <sup>3</sup> . TWA 8 hours: 200 ppm.
Ethyl acetate	<b>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024)</b> TWA 8 hours: 540 mg/m <sup>3</sup> . TWA 8 hours: 150 ppm.
2-Methoxy-1-methylethyl acetate	<b>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024)</b> Absorbed through skin. STEL 15 minutes: 550 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm. TWA 8 hours: 275 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm.
Formaldehyde	<b>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024)</b> K. Absorbed through skin. STEL 15 minutes: 0.74 mg/m <sup>3</sup> . STEL 15 minutes: 0.6 ppm. TWA 8 hours: 0.37 mg/m <sup>3</sup> . TWA 8 hours: 0.3 ppm.
Butyl acetate	<b>NAOSH (Ireland, 4/2024)</b> Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 50 ppm. OELV 8 hours: 241 mg/m <sup>3</sup> . OELV 15 minutes: 150 ppm. OELV 15 minutes: 723 mg/m <sup>3</sup> .
Ethanol	<b>NAOSH (Ireland, 4/2024)</b> Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV 15 minutes: 1000 ppm.
Propan-2-ol	<b>NAOSH (Ireland, 4/2024)</b> Absorbed through skin. Notes: Advisory Occupational Exposure Limit Values (OELVs) OELV 8 hours: 200 ppm. OELV 15 minutes: 400 ppm.
Ethyl acetate	<b>NAOSH (Ireland, 4/2024)</b> Notes: EU derived Occupational

## SECTION 8: Exposure controls/personal protection

2-Methoxy-1-methylethyl acetate	<p>Exposure Limit Values                      OELV 8 hours: 200 ppm.                      OELV 15 minutes: 400 ppm.                      OELV 15 minutes: 1468 mg/m<sup>3</sup>.                      OELV 8 hours: 734 mg/m<sup>3</sup>.</p> <p><b>NAOSH (Ireland, 4/2024)</b> Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values                      OELV 8 hours: 50 ppm.                      OELV 8 hours: 275 mg/m<sup>3</sup>.                      OELV 15 minutes: 100 ppm.                      OELV 15 minutes: 550 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>NAOSH (Ireland, 4/2024)</b> Carc 1B. Sensitiser. Notes: EU derived Occupational Exposure Limit Values                      OELV 8 hours: 0.3 ppm.                      OELV 15 minutes: 0.6 ppm.                      OELV 15 minutes: 0.738 mg/m<sup>3</sup>.                      OELV 8 hours: 0.37 mg/m<sup>3</sup>.</p>
 Butyl acetate	<p><b>Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024)</b>                      Short Term 15 minutes: 150 ppm.                      Short Term 15 minutes: 723 mg/m<sup>3</sup>.                      Limit value 8 hours: 50 ppm.                      Limit value 8 hours: 241 mg/m<sup>3</sup>.</p>
Ethyl acetate	<p><b>Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024)</b>                      Short Term 15 minutes: 400 ppm.                      Short Term 15 minutes: 1468 mg/m<sup>3</sup>.                      Limit value 8 hours: 200 ppm.                      Limit value 8 hours: 734 mg/m<sup>3</sup>.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024)</b>                      Absorbed through skin.                      Limit value 8 hours: 50 ppm.                      Limit value 8 hours: 275 mg/m<sup>3</sup>.                      Short Term 15 minutes: 100 ppm.                      Short Term 15 minutes: 550 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024)</b>                      Skin sensitiser.                      Short Term 15 minutes: 0.6 ppm.                      Short Term 15 minutes: 0.74 mg/m<sup>3</sup>.                      Limit value 8 hours: 0.3 ppm.                      Limit value 8 hours: 0.37 mg/m<sup>3</sup>.</p>
 Butyl acetate	<p><b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)</b>                      TWA 8 hours: 241 mg/m<sup>3</sup>.                      STEL 15 minutes: 150 ppm.                      STEL 15 minutes: 723 mg/m<sup>3</sup>.                      TWA 8 hours: 50 ppm.</p>
Ethanol	<p><b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)</b>                      TWA 8 hours: 1000 mg/m<sup>3</sup>.</p>
Propan-2-ol	<p><b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)</b>                      TWA 8 hours: 350 mg/m<sup>3</sup>.                      STEL 15 minutes: 600 mg/m<sup>3</sup>.</p>
Ethyl acetate	<p><b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)</b>                      TWA 8 hours: 200 mg/m<sup>3</sup>.                      STEL 15 minutes: 400 ppm.                      STEL 15 minutes: 1468 mg/m<sup>3</sup>.                      TWA 8 hours: 54 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)</b>                      Absorbed through skin.                      TWA 8 hours: 50 ppm.                      TWA 8 hours: 275 mg/m<sup>3</sup>.</p>

## SECTION 8: Exposure controls/personal protection

Formaldehyde	<p>STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m<sup>3</sup>.</p> <p><b>Ministers Cabinet Regulations No. 803 of 2008 - OEL (Latvia, 3/2024)</b> Carc. 1B. Skin sensitiser.</p> <p>STEL 15 minutes: 0.6 ppm. STEL 15 minutes: 0.74 mg/m<sup>3</sup>. TWA 8 hours: 0.3 ppm. TWA 8 hours: 0.37 mg/m<sup>3</sup>.</p>
<input checked="" type="checkbox"/> Butyl acetate	<p><b>Lithuanian Hygiene Standard HN 23 (Lithuania, 10/2025)</b></p> <p>TWA 8 hours: 241 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. STEL 15 minutes: 723 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm.</p>
Ethanol	<p><b>Lithuanian Hygiene Standard HN 23 (Lithuania, 10/2025)</b></p> <p>TWA 8 hours: 1000 mg/m<sup>3</sup>. TWA 8 hours: 500 ppm. STEL 15 minutes: 1900 mg/m<sup>3</sup>. STEL 15 minutes: 1000 ppm.</p>
Propan-2-ol	<p><b>Lithuanian Hygiene Standard HN 23 (Lithuania, 10/2025)</b></p> <p>TWA 8 hours: 350 mg/m<sup>3</sup>. TWA 8 hours: 150 ppm. STEL 15 minutes: 600 mg/m<sup>3</sup>. STEL 15 minutes: 250 ppm.</p>
Ethyl acetate	<p><b>Lithuanian Hygiene Standard HN 23 (Lithuania, 10/2025)</b></p> <p>TWA 8 hours: 500 mg/m<sup>3</sup>. TWA 8 hours: 150 ppm. CEIL: 1100 mg/m<sup>3</sup>. CEIL: 300 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Lithuanian Hygiene Standard HN 23 (Lithuania, 10/2025)</b></p> <p>Absorbed through skin. TWA 8 hours: 250 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. STEL 15 minutes: 400 mg/m<sup>3</sup>. STEL 15 minutes: 75 ppm.</p>
Formaldehyde	<p><b>Lithuanian Hygiene Standard HN 23 (Lithuania, 10/2025)</b> Carc. Sensitiser.</p> <p>TWA 8 hours: 0.37 mg/m<sup>3</sup>. TWA 8 hours: 0.3 ppm. STEL 15 minutes: 0.6 ppm. STEL 15 minutes: 0.74 mg/m<sup>3</sup>.</p>
<input checked="" type="checkbox"/> Butyl acetate	<p><b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021)</b></p> <p>STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m<sup>3</sup>.</p>
Ethyl acetate	<p><b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021)</b></p> <p>STEL 15 minutes: 400 ppm. STEL 15 minutes: 1468 mg/m<sup>3</sup>. TWA 8 hours: 200 ppm. TWA 8 hours: 734 mg/m<sup>3</sup>.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021)</b> Absorbed through skin.</p> <p>TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>Grand-Duchy Regulation 2016. Carcinogens or mutagens agents. Annex III (Luxembourg, 3/2025)</b> Skin sensitiser.</p> <p>STEL 15 minutes: 0.6 ppm. STEL 15 minutes: 0.74 mg/m<sup>3</sup>.</p>

## SECTION 8: Exposure controls/personal protection

n-Butyl acetate	<p>TWA 8 hours: 0.3 ppm. TWA 8 hours: 0.37 mg/m<sup>3</sup>.</p> <p><b>EU OEL (Europe, 1/2022)</b> STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m<sup>3</sup>. TWA 8 hours: 241 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm.</p>
Ethyl acetate	<p><b>EU OEL (Europe, 1/2022)</b> STEL 15 minutes: 400 ppm. STEL 15 minutes: 1468 mg/m<sup>3</sup>. TWA 8 hours: 200 ppm. TWA 8 hours: 734 mg/m<sup>3</sup>.</p>
2-Methoxy-1-methylethyl acetate	<p><b>EU OEL (Europe, 1/2022)</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>Ministry of Health (Malta, 10/2025)</b> Skin sensitiser. TWA 8 hours: 0.3 ppm. TWA 8 hours: 0.37 mg/m<sup>3</sup>. STEL 15 minutes: 0.74 mg/m<sup>3</sup>. STEL 15 minutes: 0.6 ppm.</p>
n-Butyl acetate	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 11/2025)</b> TWA 8 hours: 241 mg/m<sup>3</sup>. STEL 15 minutes: 723 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm.</p>
Ethanol	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 11/2025)</b> Carc B2. Absorbed through skin. TWA 8 hours: 260 mg/m<sup>3</sup>. STEL 15 minutes: 1900 mg/m<sup>3</sup>. STEL 15 minutes: 1000 ppm. TWA 8 hours: 137 ppm.</p>
Ethyl acetate	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 11/2025)</b> STEL 15 minutes: 1468 mg/m<sup>3</sup>. TWA 8 hours: 734 mg/m<sup>3</sup>. STEL 15 minutes: 400 ppm. TWA 8 hours: 200 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 11/2025)</b> TWA 8 hours: 550 mg/m<sup>3</sup>. TWA 8 hours: 100 ppm.</p>
Formaldehyde	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 11/2025)</b> Carc B1. Skin sensitiser. TWA 8 hours: 0.15 mg/m<sup>3</sup>. STEL 15 minutes: 0.5 mg/m<sup>3</sup>. STEL 15 minutes: 0.41 ppm. TWA 8 hours: 0.12 ppm.</p>
n-Butyl acetate	<p><b>FOR-2011-12-06-1358 (Norway, 12/2025)</b> STEL 15 minutes: 723 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. TWA 8 hours: 241 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm.</p>
Ethanol	<p><b>FOR-2011-12-06-1358 (Norway, 12/2025)</b> TWA 8 hours: 500 ppm. TWA 8 hours: 950 mg/m<sup>3</sup>.</p>
Propan-2-ol	<p><b>FOR-2011-12-06-1358 (Norway, 12/2025)</b> TWA 8 hours: 100 ppm. TWA 8 hours: 245 mg/m<sup>3</sup>.</p>
Ethyl acetate	<p><b>FOR-2011-12-06-1358 (Norway, 12/2025)</b></p>



## SECTION 8: Exposure controls/personal protection

2-Methoxy-1-methylethyl acetate	<p>TWA 8 hours: 200 ppm. TWA 8 hours: 734 mg/m<sup>3</sup>. STEL 15 minutes: 1468 mg/m<sup>3</sup>. STEL 15 minutes: 400 ppm.</p> <p><b>FOR-2011-12-06-1358 (Norway, 12/2025)</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 270 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>FOR-2011-12-06-1358 (Norway, 12/2025)</b> Carc. Sensitiser. TWA 8 hours: 0.3 ppm. TWA 8 hours: 0.37 mg/m<sup>3</sup>. CEIL: 1 ppm. CEIL: 1.2 mg/m<sup>3</sup>. STEL 15 minutes: 0.74 mg/m<sup>3</sup>. STEL 15 minutes: 0.6 ppm.</p>
n-Butyl acetate	<p><b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024)</b> TWA 8 hours: 240 mg/m<sup>3</sup>. STEL 15 minutes: 720 mg/m<sup>3</sup>.</p>
Ethanol	<p><b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024)</b> TWA 8 hours: 1900 mg/m<sup>3</sup>.</p>
Propan-2-ol	<p><b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024)</b> Absorbed through skin. TWA 8 hours: 900 mg/m<sup>3</sup>. STEL 15 minutes: 1200 mg/m<sup>3</sup>.</p>
Ethyl acetate	<p><b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024)</b> TWA 8 hours: 734 mg/m<sup>3</sup>. STEL 15 minutes: 1468 mg/m<sup>3</sup>. STEL 15 minutes: 400 ppm. TWA 8 hours: 200 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024)</b> Absorbed through skin. TWA 8 hours: 260 mg/m<sup>3</sup>. STEL 15 minutes: 520 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024)</b> Absorbed through skin , Skin sensitiser. TWA 8 hours: 0.37 mg/m<sup>3</sup>. STEL 15 minutes: 0.74 mg/m<sup>3</sup>.</p>

## SECTION 8: Exposure controls/personal protection

n-Butyl acetate	<p><b>Portuguese Institute of Quality (Portugal, 11/2014)</b> TWA 8 hours: 150 ppm. STEL 15 minutes: 200 ppm.</p> <p><b>Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021)</b> STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m<sup>3</sup>.</p>
Ethanol	<b>Portuguese Institute of Quality (Portugal, 11/2014) A3.</b> STEL 15 minutes: 1000 ppm.
Propan-2-ol	<b>Portuguese Institute of Quality (Portugal, 11/2014) A4.</b> TWA 8 hours: 200 ppm. STEL 15 minutes: 400 ppm.
Ethyl acetate	<p><b>Portuguese Institute of Quality (Portugal, 11/2014)</b> TWA 8 hours: 400 ppm.</p> <p><b>Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021)</b> STEL 15 minutes: 400 ppm. STEL 15 minutes: 1468 mg/m<sup>3</sup>. TWA 8 hours: 200 ppm. TWA 8 hours: 734 mg/m<sup>3</sup>.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021)</b> Absorbed through skin. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>Portuguese Institute of Quality (Portugal, 11/2014) A2.</b> Sensitiser. CEIL: 0.3 ppm.</p> <p><b>Decree-Law 301/2000 - Occupational exposure limits for carcinogenic and mutagenic agents (Portugal, 5/2025)</b> Skin sensitiser. STEL 15 minutes: 0.6 ppm. STEL 15 minutes: 0.74 mg/m<sup>3</sup>. TWA 8 hours: 0.3 ppm. TWA 8 hours: 0.37 mg/m<sup>3</sup>.</p>
n-Butyl acetate	<p><b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024)</b> VLA 8 hours: 241 mg/m<sup>3</sup>. VLA 8 hours: 50 ppm. Short term 15 minutes: 723 mg/m<sup>3</sup>. Short term 15 minutes: 150 ppm.</p>
Ethanol	<p><b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024)</b> VLA 8 hours: 1900 mg/m<sup>3</sup>. VLA 8 hours: 1000 ppm. Short term 15 minutes: 9500 mg/m<sup>3</sup>. Short term 15 minutes: 5000 ppm.</p>
Propan-2-ol	<p><b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024)</b> VLA 8 hours: 200 mg/m<sup>3</sup>. VLA 8 hours: 81 ppm. Short term 15 minutes: 500 mg/m<sup>3</sup>. Short term 15 minutes: 203 ppm.</p>
Ethyl acetate	<p><b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024)</b> VLA 8 hours: 734 mg/m<sup>3</sup>. VLA 8 hours: 200 ppm. Short term 15 minutes: 1468 mg/m<sup>3</sup>. Short term 15 minutes: 400 ppm.</p>

## SECTION 8: Exposure controls/personal protection

2-Methoxy-1-methylethyl acetate	<p><b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024)</b> Absorbed through skin.</p> <p>VLA 8 hours: 275 mg/m<sup>3</sup>. VLA 8 hours: 50 ppm. Short term 15 minutes: 550 mg/m<sup>3</sup>. Short term 15 minutes: 100 ppm.</p>
Formaldehyde	<p><b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024)</b> C2. Skin sensitiser.</p> <p>VLA 8 hours: 0.37 mg/m<sup>3</sup>. VLA 8 hours: 0.3 ppm. Short term 15 minutes: 0.74 mg/m<sup>3</sup>. Short term 15 minutes: 0.6 ppm.</p>
 Butyl acetate	<p><b>Government regulation SR c. 355/2006 (Slovakia, 6/2024)</b> [butylacetáty] Inhalation sensitiser.</p> <p>TWA 8 hours: 241 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. STEL 15 minutes: 723 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm.</p>
Ethanol	<p><b>Government regulation SR c. 355/2006 (Slovakia, 6/2024)</b> Inhalation sensitiser.</p> <p>TWA 8 hours: 960 mg/m<sup>3</sup>. TWA 8 hours: 500 ppm. STEL 15 minutes: 1920 mg/m<sup>3</sup>. STEL 15 minutes: 1000 ppm.</p>
Propan-2-ol	<p><b>Government regulation SR c. 355/2006 (Slovakia, 6/2024)</b> Inhalation sensitiser.</p> <p>TWA 8 hours: 500 mg/m<sup>3</sup>. TWA 8 hours: 200 ppm. STEL 15 minutes: 1000 mg/m<sup>3</sup>. STEL 15 minutes: 400 ppm.</p>
Ethyl acetate	<p><b>Government regulation SR c. 355/2006 (Slovakia, 6/2024)</b> Inhalation sensitiser.</p> <p>TWA 8 hours: 734 mg/m<sup>3</sup>. TWA 8 hours: 200 ppm. STEL 15 minutes: 1468 mg/m<sup>3</sup>. STEL 15 minutes: 400 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Government regulation SR c. 355/2006 (Slovakia, 6/2024)</b> Absorbed through skin , Inhalation sensitiser.</p> <p>TWA 8 hours: 275 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. STEL 15 minutes: 550 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm.</p>
Formaldehyde	<p><b>Government regulation SR c. 356/2006 (Slovakia, 9/2020)</b> Carc 1B. Sensitiser.</p> <p>STEL 15 minutes: 0.74 mg/m<sup>3</sup>. STEL 15 minutes: 0.6 ppm. Technical guidance value 8 hours: 0.37 mg/m<sup>3</sup>. Technical guidance value 8 hours: 0.3 ppm.</p>
 Butyl acetate	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2025)</b></p> <p>TWA 8 hours: 241 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. KTV 15 minutes: 723 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 150 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p>
Ethanol	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2025)</b></p> <p>TWA 8 hours: 960 mg/m<sup>3</sup>. TWA 8 hours: 500 ppm. KTV 15 minutes: 1920 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p>

## SECTION 8: Exposure controls/personal protection

Propan-2-ol	<p>KTV 15 minutes: 1000 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p> <p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2025)</b></p> <p>TWA 8 hours: 500 mg/m<sup>3</sup>. TWA 8 hours: 200 ppm.</p> <p>KTV 15 minutes: 1000 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p> <p>KTV 15 minutes: 400 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p>
Ethyl acetate	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2025)</b></p> <p>TWA 8 hours: 734 mg/m<sup>3</sup>. TWA 8 hours: 200 ppm.</p> <p>KTV 15 minutes: 1468 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p> <p>KTV 15 minutes: 400 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p>
2-Methoxy-1-methylethyl acetate	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2025)</b></p> <p>Absorbed through skin.</p> <p>TWA 8 hours: 275 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm.</p> <p>KTV 15 minutes: 550 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p> <p>KTV 15 minutes: 100 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p>
Formaldehjde	<p><b>Regulation on the protection of workers from the risks related to exposure to carcinogens, mutagens or reprotoxic substances at work (OEL) (Slovenia, 4/2025)</b> Carc 1B, Muta 2.</p> <p>Absorbed through skin , Skin sensitiser.</p> <p>Peak 15 minutes: 0.6 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p> <p>Peak 15 minutes: 0.74 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].</p> <p>TWA 8 hours: 0.3 ppm. TWA 8 hours: 0.37 mg/m<sup>3</sup>.</p>
n-Butyl acetate	<p><b>National institute of occupational safety and health (Spain, 3/2025)</b></p> <p>TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m<sup>3</sup>.</p>
Ethanol	<p><b>National institute of occupational safety and health (Spain, 3/2025)</b></p> <p>STEL 15 minutes: 1000 ppm. STEL 15 minutes: 1910 mg/m<sup>3</sup>.</p>
Propan-2-ol	<p><b>National institute of occupational safety and health (Spain, 3/2025)</b></p> <p>TWA 8 hours: 200 ppm. TWA 8 hours: 500 mg/m<sup>3</sup>. STEL 15 minutes: 400 ppm. STEL 15 minutes: 1000 mg/m<sup>3</sup>.</p>
Ethyl acetate	<p><b>National institute of occupational safety and health (Spain, 3/2025)</b></p> <p>TWA 8 hours: 200 ppm. TWA 8 hours: 734 mg/m<sup>3</sup>. STEL 15 minutes: 1468 mg/m<sup>3</sup>. STEL 15 minutes: 400 ppm.</p>
2-Methoxy-1-methylethyl acetate	<p><b>National institute of occupational safety and health (Spain, 3/2025)</b> Absorbed through skin.</p> <p>TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m<sup>3</sup>.</p>

## SECTION 8: Exposure controls/personal protection

Formaldehyde	<p>STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m<sup>3</sup>.</p> <p><b>National institute of occupational safety and health (Spain, 3/2025)</b> Carc 1B. Skin sensitiser. STEL 15 minutes: 0.6 ppm. STEL 15 minutes: 0.74 mg/m<sup>3</sup>. TWA 8 hours: 0.37 mg/m<sup>3</sup>. TWA 8 hours: 0.3 ppm.</p>
n-Butyl acetate	<p><b>Work environment authority Regulation 2023:14 (Sweden, 6/2025) [butyl acetate]</b> TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m<sup>3</sup>.</p>
Ethanol	<p><b>Work environment authority Regulation 2023:14 (Sweden, 6/2025)</b> TWA 8 hours: 500 ppm. TWA 8 hours: 1000 mg/m<sup>3</sup>. STEL 15 minutes: 1000 ppm. STEL 15 minutes: 1900 mg/m<sup>3</sup>.</p>
Propan-2-ol	<p><b>Work environment authority Regulation 2023:14 (Sweden, 6/2025)</b> TWA 8 hours: 150 ppm. TWA 8 hours: 350 mg/m<sup>3</sup>. STEL 15 minutes: 250 ppm. STEL 15 minutes: 600 mg/m<sup>3</sup>.</p>
Ethyl acetate	<p><b>Work environment authority Regulation 2023:14 (Sweden, 6/2025)</b> TWA 8 hours: 150 ppm. TWA 8 hours: 550 mg/m<sup>3</sup>. STEL 15 minutes: 300 ppm. STEL 15 minutes: 1100 mg/m<sup>3</sup>.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Work environment authority Regulation 2023:14 (Sweden, 6/2025)</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>Work environment authority Regulation 2023:14 (Sweden, 6/2025)</b> Carc. Absorbed through skin , Skin sensitiser. TWA 8 hours: 0.3 ppm. TWA 8 hours: 0.37 mg/m<sup>3</sup>. STEL 15 minutes: 0.6 ppm. STEL 15 minutes: 0.74 mg/m<sup>3</sup>.</p>
n-Butyl acetate	<p><b>SUVA (Switzerland, 1/2026)</b> TWA 8 hours: 50 ppm. TWA 8 hours: 240 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. STEL 15 minutes: 720 mg/m<sup>3</sup>.</p>
Ethanol	<p><b>SUVA (Switzerland, 1/2026)</b> Carc 1A, Repr 1A. TWA 8 hours: 500 ppm. TWA 8 hours: 960 mg/m<sup>3</sup>. STEL 15 minutes: 1000 ppm. STEL 15 minutes: 1920 mg/m<sup>3</sup>.</p>
Propan-2-ol	<p><b>SUVA (Switzerland, 1/2026)</b> TWA 8 hours: 200 ppm. TWA 8 hours: 500 mg/m<sup>3</sup>. STEL 15 minutes: 400 ppm. STEL 15 minutes: 1000 mg/m<sup>3</sup>.</p>
Ethyl acetate	<p><b>SUVA (Switzerland, 1/2026)</b> STEL 15 minutes: 400 ppm.</p>

## SECTION 8: Exposure controls/personal protection

2-Methoxy-1-methylethyl acetate	<p>STEL 15 minutes: 1460 mg/m<sup>3</sup>.  TWA 8 hours: 200 ppm.  TWA 8 hours: 730 mg/m<sup>3</sup>.</p> <p><b>SUVA (Switzerland, 1/2026)</b>  TWA 8 hours: 50 ppm.  TWA 8 hours: 275 mg/m<sup>3</sup>.  STEL 15 minutes: 50 ppm.  STEL 15 minutes: 275 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>SUVA (Switzerland, 1/2026) Carc 1B. Sensitiser.</b>  TWA 8 hours: 0.3 ppm.  TWA 8 hours: 0.37 mg/m<sup>3</sup>.  STEL 15 minutes: 0.6 ppm.  STEL 15 minutes: 0.74 mg/m<sup>3</sup>.</p>
<input checked="" type="checkbox"/> Butyl acetate	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b>  STEL 15 minutes: 966 mg/m<sup>3</sup>.  STEL 15 minutes: 200 ppm.  TWA 8 hours: 724 mg/m<sup>3</sup>.  TWA 8 hours: 150 ppm.</p>
Ethanol	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b>  TWA 8 hours: 1000 ppm.  TWA 8 hours: 1920 mg/m<sup>3</sup>.</p>
Propan-2-ol	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b>  STEL 15 minutes: 1250 mg/m<sup>3</sup>.  STEL 15 minutes: 500 ppm.  TWA 8 hours: 999 mg/m<sup>3</sup>.  TWA 8 hours: 400 ppm.</p>
Ethyl acetate	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b>  STEL 15 minutes: 400 ppm.  TWA 8 hours: 200 ppm.  STEL 15 minutes: 1468 mg/m<sup>3</sup>.  TWA 8 hours: 734 mg/m<sup>3</sup>.</p>
Formaldehyde	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020) Carc.</b>  STEL 15 minutes: 2.5 mg/m<sup>3</sup>.  STEL 15 minutes: 2 ppm.  TWA 8 hours: 2 ppm.  TWA 8 hours: 2.5 mg/m<sup>3</sup>.</p>

### Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
<input checked="" type="checkbox"/> Propan-2-ol	<p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, biological limit values (Annex IV) (Croatia, 10/2025)</b>  BEI: 50 mg/l, acetone [in urine]. Sampling time: at the end of the work shift.  BEI: 50 mg/l, acetone [in blood]. Sampling time: at the end of the work shift.  BEI: 0.86 µmol/l, acetone [in urine]. Sampling time: at the end of the work shift.  BEI: 0.86 µmol/l, acetone [in blood]. Sampling time: at the end of the work shift.</p>
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	

## SECTION 8: Exposure controls/personal protection

No exposure indices known.

No exposure indices known.

Propan-2-ol

### **DFG BEI-values list (Germany, 7/2025)**

BEI: 25 mg/l, acetone [in blood]. Sampling time: end of exposure or end of shift.

BEI: 25 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift.

### **TRGS 903 - BEI Values (Germany, 12/2025)**

BEI: 25 mg/l, acetone [in whole blood]. Sampling time: end of exposure or end of shift.

BEI: 25 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift.

No exposure indices known.

Propan-2-ol

### **5/2020. (II. 6.) ITM Decree (Hungary, 12/2023)**

BEI: 430 µmol/l, acetone [in urine]. Sampling time: at the end of the shift.

BEI: 25 mg/l, acetone [in urine]. Sampling time: at the end of the shift.

No exposure indices known.

Propan-2-ol

### **NAOSH BGVs (Ireland, 1/2011)**

BMGV: 40 mg/l, acetone [in urine]. Sampling time: end of shift at end of workweek.

No exposure indices known.

Propan-2-ol

### **Minister Cabinet Regulations No.325 - BEI (Latvia, 3/2024)**

BEI: 25 mg/l, acetone [in urine]. Sampling time: at the end of the exposure or at the end of the shift.

BEI: 25 mg/l, acetone [in blood]. Sampling time: at the end of the exposure or at the end of the shift.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

Propan-2-ol

### **Portuguese Institute of Quality (Portugal, 11/2014)**

BEI: 40 mg/l, acetone [in urine]. Sampling time: end of shift at the end of the workweek.

Propan-2-ol

### **HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2024)**

OBLV: 50 mg/l, acetone [in urine]. Sampling time: end of shift.

No exposure indices known.

Propan-2-ol

### **Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2025)**

BLV: 25 mg/l, acetone [in urine]. Sampling time: at the end of the work shift.

BLV: 25 mg/l, acetone [in blood]. Sampling time: at the end of the work shift.

Propan-2-ol

### **National institute of occupational safety and health (Spain, 3/2025)**

BLV: 40 mg/l, acetone [in urine]. Sampling time: end of workweek.

No exposure indices known.

## SECTION 8: Exposure controls/personal protection

Propan-2-ol

### SUVA (Switzerland, 1/2026)

BEI: 0.4 mmol/l, acetone [in blood]. Sampling time: immediately after exposure or after working hours.

BEI: 25 mg/l, acetone [in blood]. Sampling time: immediately after exposure or after working hours.

BEI: 0.4 mmol/l, acetone [in urine]. Sampling time: immediately after exposure or after working hours.

BEI: 25 mg/l, acetone [in urine]. Sampling time: immediately after exposure or after working hours.

No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

#### Product/ingredient name

Butyl acetate

#### Result

##### DNEL - General population - Long term - Oral

2 mg/kg bw/day

Effects: Systemic

##### DNEL - General population - Short term - Oral

2 mg/kg bw/day

Effects: Systemic

##### DNEL - General population - Long term - Dermal

3.4 mg/kg bw/day

Effects: Systemic

##### DNEL - General population - Short term - Dermal

6 mg/kg bw/day

Effects: Systemic

##### DNEL - Workers - Long term - Dermal

7 mg/kg bw/day

Effects: Systemic

##### DNEL - Workers - Short term - Dermal

11 mg/kg bw/day

Effects: Systemic

##### DNEL - General population - Long term - Inhalation

12 mg/m<sup>3</sup>

Effects: Systemic

##### DNEL - General population - Long term - Inhalation

35.7 mg/m<sup>3</sup>

Effects: Local

##### DNEL - Workers - Long term - Inhalation

48 mg/m<sup>3</sup>

Effects: Systemic

##### DNEL - General population - Short term - Inhalation

300 mg/m<sup>3</sup>

Effects: Local

##### DNEL - General population - Short term - Inhalation

## SECTION 8: Exposure controls/personal protection

300 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

300 mg/m<sup>3</sup>  
Effects: Local

**DNEL - Workers - Short term - Inhalation**

600 mg/m<sup>3</sup>  
Effects: Local

**DNEL - Workers - Short term - Inhalation**

600 mg/m<sup>3</sup>  
Effects: Systemic

Ethanol

**DNEL - Workers - Long term - Inhalation**

380 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - General population - Long term - Oral**

87 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Long term - Inhalation**

114 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - General population - Long term - Dermal**

206 mg/kg bw/day  
Effects: Systemic

**DNEL - Workers - Long term - Dermal**

343 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Short term - Inhalation**

950 mg/m<sup>3</sup>  
Effects: Local

**DNEL - Workers - Short term - Inhalation**

1900 mg/m<sup>3</sup>  
Effects: Local

Propan-2-ol

**DNEL - Workers - Long term - Inhalation**

500 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - Workers - Long term - Dermal**

888 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Long term - Oral**

26 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Short term - Oral**

51 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Long term - Inhalation**

89 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - General population - Short term - Inhalation**

178 mg/m<sup>3</sup>

## SECTION 8: Exposure controls/personal protection

Effects: Systemic

**DNEL - General population - Long term - Dermal**

319 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Short term - Inhalation**

1000 mg/m<sup>3</sup>

Effects: Systemic

Ethyl acetate

**DNEL - General population - Long term - Oral**

4.5 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Dermal**

37 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Long term - Dermal**

63 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Inhalation**

367 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Long term - Inhalation**

367 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Short term - Inhalation**

734 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Short term - Inhalation**

734 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

734 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Long term - Inhalation**

734 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation**

1468 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Short term - Inhalation**

1468 mg/m<sup>3</sup>

Effects: Systemic

2-Methoxy-1-methylethyl acetate

**DNEL - General population - Long term - Inhalation**

33 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Long term - Inhalation**

33 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Long term - Oral**

36 mg/kg bw/day

Effects: Systemic

## SECTION 8: Exposure controls/personal protection

### **DNEL - Workers - Long term - Inhalation**

275 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - General population - Long term - Dermal**

320 mg/kg bw/day

Effects: Systemic

### **DNEL - Workers - Short term - Inhalation**

550 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Long term - Dermal**

796 mg/kg bw/day

Effects: Systemic

Formaldehyde

### **DNEL - General population - Long term - Dermal**

12 µg/cm<sup>2</sup>

Effects: Local

### **DNEL - Workers - Long term - Dermal**

37 µg/cm<sup>2</sup>

Effects: Local

### **DNEL - General population - Long term - Inhalation**

0.1 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Long term - Inhalation**

0.375 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Short term - Inhalation**

0.75 mg/m<sup>3</sup>

Effects: Local

### **DNEL - General population - Long term - Inhalation**

3.2 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - General population - Long term - Oral**

4.1 mg/kg bw/day

Effects: Systemic

### **DNEL - Workers - Long term - Inhalation**

9 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - General population - Long term - Dermal**

102 mg/kg bw/day

Effects: Systemic

### **DNEL - Workers - Long term - Dermal**

240 mg/kg bw/day

Effects: Systemic

### **PNECs**

Not available.

## **8.2 Exposure controls**

## SECTION 8: Exposure controls/personal protection

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type: A

Filter type (spray application): A P

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.  
**Colour** : Colourless.  
**Odour** : Slight  
**Odour threshold** : Not available.  
**Melting point/freezing point** : Not available.  
**Initial boiling point and boiling range** :

## SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
Ethyl acetate	77.1	170.8	
Ethanol	78.29	172.9	

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: 1.4% (n-butyl acetate)  
Upper: 19% (ethanol)
- Flash point** : Closed cup: >13°C (>55.4°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Methoxy-1-methylethyl acetate	333	631.4	DIN 51794
Propan-2-ol	399	750.2	

- Decomposition temperature** : Not available.
- pH** : Not applicable.
- Viscosity** : Not available.
- Solubility(ies)** :  
Not available.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Ethyl acetate	81.59163	10.9				
Ethanol	42.94865	5.7				

- Relative density** : Not available.
- Density** : 0.9 g/cm<sup>3</sup>
- Vapour density** : Not available.
- Particle characteristics**
- Median particle size** : Not applicable.

### 9.2 Other information

#### 9.2.1 Information with regard to physical hazard classes

- Explosive properties** : Not available.
- Oxidising properties** : Not available.

#### 9.2.2 Other safety characteristics

Not applicable.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

- 10.2 Chemical stability** : The product is stable.

- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

- 10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

## SECTION 10: Stability and reactivity

**10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
oxidising materials

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product/ingredient name

Butyl acetate

##### Result

###### Rat - Oral - LD50

10760 mg/kg  
EU

###### Rabbit - Dermal - LD50

14112 mg/kg

###### Rat - Inhalation - LC50 Vapour

0.74 mg/l [4 hours]

Ethanol

###### Rat - Oral - LD50

7 g/kg

###### Rat - Inhalation - LC50 Vapour

124700 mg/m<sup>3</sup> [4 hours]

Propan-2-ol

###### Rabbit - Dermal - LD50

12800 mg/kg

###### Rat - Oral - LD50

5000 mg/kg

Toxic effects: Behavioral - General anesthetic

Ethyl acetate

###### Rat - Oral - LD50

5620 mg/kg

2-Methoxy-1-methylethyl acetate

###### Rat - Oral - LD50

8532 mg/kg

###### Rabbit - Dermal - LD50

>5 g/kg

Urea-formaldehyde-polymer

###### Rat - Oral - LD50

>5 g/kg

Toxic effects: Olfaction - Other changes Behavioral - Somnolence (general depressed activity) Behavioral - Food intake (animal)

###### Rabbit - Dermal - LD50

>5 g/kg

Toxic effects: Skin After systemic exposure - Dermatitis, other

Formaldehyde

###### Rat - Oral - LD50

100 mg/kg

###### Rabbit - Dermal - LD50

270 mg/kg

###### Rat - Inhalation - LC50 Gas.

250 ppm [4 hours]

**Conclusion/Summary [Product]** :  Not available.

## SECTION 11: Toxicological information

### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Butyl acetate	10760	14112	N/A	N/A	N/A
Ethanol	7000	N/A	N/A	124.7	N/A
Propan-2-ol	5000	12800	N/A	N/A	N/A
Ethyl acetate	5620	N/A	N/A	N/A	N/A
2-Methoxy-1-methylethyl acetate	8532	N/A	N/A	N/A	N/A
Formaldehyde	500	N/A	100	N/A	N/A

### Skin corrosion/irritation

#### Product/ingredient name

Butyl acetate

#### Result

**Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Ethanol

**Rabbit - Skin - Mild irritant**

Amount/concentration applied: 400 mg

**Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

Propan-2-ol

**Rabbit - Skin - Mild irritant**

Amount/concentration applied: 500 mg

Formaldehyde

**Human - Skin - Mild irritant**

Duration of treatment/exposure: 72 hours

Amount/concentration applied: 150 ug l

**Human - Skin - Severe irritant**

Amount/concentration applied: 0.01 %

**Rabbit - Skin - Mild irritant**

Amount/concentration applied: 540 mg

**Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 50 mg

**Rabbit - Skin - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 2 mg

**Rabbit - Skin - Severe irritant**

Amount/concentration applied: 0.8 %

**Mouse - Skin - Moderate irritant**

Amount/concentration applied: 7 %

**Rat - Skin - Moderate irritant**

Amount/concentration applied: 7 %

**Rabbit - Skin - Severe irritant**

Duration of treatment/exposure: 72 hours

Amount/concentration applied: 0.8 %

**Conclusion/Summary [Product]** : Not available.

### Serious eye damage/eye irritation

Date of issue/Date of revision

: 12/06/2026

Date of previous issue

: 14/05/2024

Version : 1.01 32/45

TEKNOCOAT 1687-58

Label No : 31488

## SECTION 11: Toxicological information

### Product/ingredient name

Butyl acetate

Ethanol

Propan-2-ol

Urea-formaldehyde-polymer

Formaldehyde

### Result

**Rabbit - Eyes - Moderate irritant**

Amount/concentration applied: 100 mg

**Rabbit - Eyes - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

**Rabbit - Eyes - Moderate irritant**

Duration of treatment/exposure: 0.066666667 minutes

Amount/concentration applied: 100 mg

**Rabbit - Eyes - Moderate irritant**

Amount/concentration applied: 100 uL

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 500 mg

**Rabbit - Eyes - Mild irritant**

Duration of treatment/exposure: 1 hours

Amount/concentration applied: 50 pph

**Rabbit - Eyes - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

**Rabbit - Eyes - Moderate irritant**

Amount/concentration applied: 10 mg

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 100 mg

**Rabbit - Eyes - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 uL

**Human - Eyes - Mild irritant**

Duration of treatment/exposure: 6 minutes

Amount/concentration applied: 1 ppm

**Rabbit - Eyes - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 750 ug

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 750 ug

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 37 %

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 10 mg

**Mouse - Eyes - Moderate irritant**

Amount/concentration applied: 3 %

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

## SECTION 11: Toxicological information

### Respiratory or skin sensitization

Not available.

### **Skin**

**Conclusion/Summary [Product]** : Not available.

### **Respiratory**

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** :  Not available.

### Carcinogenicity

Not available.

**Conclusion/Summary [Product]** :  Not available.

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** :  Not available.

### Specific target organ toxicity (single exposure)

#### **Product/ingredient name**

Butyl acetate  
Propan-2-ol  
Ethyl acetate  
Formaldehyde

#### **Result**

STOT SE 3, H336 (Narcotic effects)  
STOT SE 3, H336 (Narcotic effects)  
STOT SE 3, H336 (Narcotic effects)  
STOT SE 3, H335 (Respiratory tract irritation)

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

### Information on likely routes of exposure

Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.  
**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

## SECTION 11: Toxicological information

- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

- Conclusion/Summary [Product]** : Not available.
- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

- Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product/ingredient name

Butyl acetate

#### Result

##### Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*  
Age: 31 to 32 days; Size: 21.6 mm; Weight: 0.175 g  
18000 µg/l [96 hours]  
Effect: Mortality

##### Acute - LC50 - Marine water

Crustaceans - Brine shrimp - *Artemia salina*  
32 mg/l [48 hours]  
Effect: Mortality

Ethanol

##### Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*  
2000 µg/l [48 hours]  
Effect: Physiology

##### Acute - LC50 - Fresh water

Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*  
42000 µg/l [4 days]  
Effect: Mortality

## SECTION 12: Ecological information

### Acute - EC50 - Marine water

Algae - Green algae - *Ulva pertusa*

17.921 mg/l [96 hours]

Effect: Reproduction

### Chronic - NOEC - Marine water

Algae - Green algae - *Ulva pertusa*

4.995 mg/l [96 hours]

Effect: Reproduction

### Chronic - NOEC - Fresh water

Fish - Eastern mosquitofish - *Gambusia holbrooki* - Larvae

Age: 3 days

0.375 µl/l [12 weeks]

Effect: Morphology

### Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna* - Neonate

Age: <24 hours

100 µl/l [21 days]

Effect: Mortality

Propan-2-ol

### Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - *Crangon crangon*

1400000 µg/l [48 hours]

Effect: Mortality

### Acute - LC50 - Fresh water

Fish - Harlequinfish, red rasbora - *Rasbora heteromorpha*

Size: 1 to 3 cm

4200000 µg/l [96 hours]

Effect: Mortality

Ethyl acetate

### Acute - LC50 - Fresh water

Daphnia - Water flea - *Daphnia cucullata*

Age: 11 days

154000 µg/l [48 hours]

Effect: Mortality

### Acute - LC50 - Fresh water

Fish - Indian catfish - *Heteropneustes fossilis*

Size: 14.16 cm; Weight: 25.54 g

212500 µg/l [96 hours]

Effect: Mortality

### Acute - EC50 - Fresh water

Algae - Green algae - *Selenastrum sp.*

2500000 µg/l [96 hours]

### Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*

12 mg/l [21 days]

Effect: Behavior

### Chronic - NOEC - Fresh water

Fish - Fathead minnow - *Pimephales promelas* - Embryo

Age: <24 hours

75.6 mg/l [32 days]

Effect: Mortality

Formaldehyde

### Acute - EC50 - Fresh water

Daphnia - Water flea - *Daphnia pulex* - Neonate

Age: <24 hours

5800 µg/l [48 hours]

## SECTION 12: Ecological information

Effect: Intoxication

### Acute - EC50 - Marine water

Algae - Green algae - *Ulva pertusa*

0.788 mg/l [96 hours]

Effect: Reproduction

### Acute - LC50 - Fresh water

US EPA

Fish - Rainbow trout, donaldson trout - *Oncorhynchus mykiss*

1.41 ppm [96 hours]

Effect: Mortality

### Chronic - NOEC - Fresh water

Fish - Chinook salmon - *Oncorhynchus tshawytscha* - Egg

953.9 ppm [43 days]

Effect: Mortality

### Chronic - NOEC - Marine water

Algae - Haptophyte - *Isochrysis galbana* - Exponential growth phase

Age: 4 to 5 days

0.005 mg/l [96 hours]

Effect: Population

**Conclusion/Summary [Product]** :  Not available.

### 12.2 Persistence and degradability

Not available.

**Conclusion/Summary [Product]** :  Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
<input checked="" type="checkbox"/> Butyl acetate	2.3	-	Low
Ethanol	-0.35	-	Low
Propan-2-ol	0.05	-	Low
Ethyl acetate	0.68	30	Low
2-Methoxy-1-methylethyl acetate	1.2	-	Low
Formaldehyde	0.35	-	Low

### 12.4 Mobility in soil

#### Soil/water partition coefficient

Product/ingredient name	Value
<input checked="" type="checkbox"/> Butyl acetate	logKoc: 1.5 Koc: 33.2139
Ethanol	logKoc: 0.2 Koc: 1.59008
Propan-2-ol	logKoc: 0.54 Koc: 3.4364
Ethyl acetate	logKoc: 1.3 Koc: 18.1744
2-Methoxy-1-methylethyl acetate	logKoc: 0.36 Koc: 2.31363
Formaldehyde	logKoc: 0.44 Koc: 2.72646

#### Results of PMT and vPvM assessment

## SECTION 12: Ecological information

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Butyl acetate	No	No	No	No	No	No	No
Ethanol	No	No	No	No	No	No	No
Propan-2-ol	No	No	No	No	No	No	No
Urea, polymer with formaldehyde, butylated	No	No	No	No	No	No	No
Ethyl acetate	No	No	No	No	No	No	No
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Reaction mass of: 2-[2-(benzoyloxy)ethoxy]ethyl benzoate, 1-[2-(benzoyloxy)propoxy]propan-2-yl benzoate and 2-[2-(benzoyloxy)ethoxy]ethoxy ethyl benzoate	No	No	No	No	No	No	No
Urea-formaldehyde-polymer	No	No	No	No	No	No	No
Formaldehyde	No	No	No	No	No	No	No

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment

#### Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Butyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
Ethanol	No	N/A	N/A	No	N/A	N/A	N/A
Propan-2-ol	No	N/A	N/A	No	N/A	N/A	N/A
Urea, polymer with formaldehyde, butylated	No	N/A	N/A	No	N/A	N/A	N/A
Ethyl acetate	No	N/A	No	No	No	N/A	No
2-Methoxy-1-methylethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
Reaction mass of: 2-[2-(benzoyloxy)ethoxy]ethyl benzoate, 1-[2-(benzoyloxy)propoxy]propan-2-yl benzoate and 2-[2-(benzoyloxy)ethoxy]ethoxy ethyl benzoate	No	N/A	N/A	No	N/A	N/A	N/A
Urea-formaldehyde-polymer	No	N/A	N/A	No	N/A	N/A	N/A
Formaldehyde	N/A	N/A	N/A	Yes	N/A	N/A	N/A

#### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Butyl acetate	No	No	No	No	No	No	No
Ethanol	No	No	No	No	No	No	No
Propan-2-ol	No	No	No	No	No	No	No
Urea, polymer with formaldehyde, butylated	No	No	No	No	No	No	No
Ethyl acetate	No	No	No	No	No	No	No
2-Methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
Reaction mass of: 2-[2-(benzoyloxy)ethoxy]ethyl benzoate, 1-[2-(benzoyloxy)propoxy]propan-2-yl benzoate and 2-[2-(benzoyloxy)ethoxy]ethoxy ethyl benzoate	No	No	No	No	No	No	No
Urea-formaldehyde-polymer	No	No	No	No	No	No	No
Formaldehyde	No	No	No	No	No	No	No

## SECTION 12: Ecological information

**Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP]** : The product does not meet the criteria to be considered as a PBT or vPvB.

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.





**European waste catalogue (EWC)** : 08.01.11

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	Yes.	No.	No.

#### Additional information

Date of issue/Date of revision

: 12/06/2026

Date of previous issue

: 14/05/2024

Version : 1.01 39/45

TEKNOCOAT 1687-58

Label No : 31488

## SECTION 14: Transport information

**ADR/RID** : **Special provisions** 640 (C)  
**Tunnel code** (D/E)

**ADN** : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.  
**Special provisions** 640 (C)

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

Product/ingredient name	%	Designation [Usage]
TEKNOCOAT 1687-58 Formaldehyde	≥90 <0.1	3 72

**Labelling** :

**Other EU regulations**

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**Explosive precursors** : Not applicable.

**(EC) No 273/2004 on drug precursors**

Not listed.

**(EC) No 111/2005 Trade between the Union and third countries in drug precursors**

Ingredient name	%	Status
Methylethylketone	≤0.3	Category 3

**Ozone depleting substances (EU 2024/590)**

Not listed.

**Prior Informed Consent (PIC) (649/2012/EU)**

Not listed.

**Persistent Organic Pollutants**

Not listed.

**Seveso Directive**

This product is controlled under the Seveso Directive.

## SECTION 15: Regulatory information

### Danger criteria

#### Category

P5c

### National regulations

#### Austria

VbF class : Category 2

Limitation of the use of organic solvents : Permitted.

#### Belgium

#### Czech Republic

Storage code : I

#### Denmark

Fire class : F+1

#### Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
Propan-2-ol	Listed	-

MAL-code : 3-1

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, respiratory protection with air supply and arm protectors/apron/coveralls/protective clothing must be worn as appropriate or as instructed.

MAL-code: 3-1

**Application:** When spraying in new\* booths if the operator is outside the spray zone. When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin. During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Air-supplied half mask and eye protection must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Air-supplied full mask and arm protectors must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied full mask must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, coveralls and hood must be worn.

## SECTION 15: Regulatory information

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

- Low-boiling liquids** : This product contains low-boiling point liquids. Any respiratory protective equipment should be air-fed.
- Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
- List of undesirable substances** : Not listed
- Carcinogenic waste** :  Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

### Finland

### France

- Social Security Code, Articles L 461-1 to L 461-7** :  Butyl acetate RG 84  
Ethanol RG 84  
Propan-2-ol RG 84  
Ethyl acetate RG 84  
2-Methoxy-1-methylethyl acetate RG 84  
Formaldehyde RG 43, RG 43bis, RG 84

- Reinforced medical surveillance** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

### Germany

- Storage class (TRGS 510)** : 3

### Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

#### Danger criteria

Category	Reference number
P5c	1.2.5.3

- Hazard class for water** : 1

### Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
<input checked="" type="checkbox"/> 5.2.1	Total dust	29.9
5.2.5	Organic substances	69.4
5.2.5 [I]	Organic substances	67.3
5.2.7.1.1 [Formaldehyde]	Carcinogenic substances	0.014

### Italy

- D.Lgs. 152/06** : Not determined.

### Netherlands

**Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances**

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development	Harmful via breastfeeding
ethanol	Listed	-	Fertility 1A	Development 1A	Listed

## SECTION 15: Regulatory information

**Water Discharge Policy (ABM)** : Z(1) Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioaccumulative potential/ toxicity or persistence). Decontamination effort: Z

### Norway

### Sweden

**Flammable liquid class (SRVFS 2005:10)** : 1

### Switzerland

**VOC content** : VOC (w/w): 67.3%

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
✔ Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	On basis of test data Calculation method Calculation method

#### Full text of abbreviated H statements

✔ H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

**Date of issue/Date of revision** : 12/06/2026 **Date of previous issue** : 14/05/2024 **Version** : 1.01 43/45

TEKNOCOAT 1687-58

**Label No** : 31488

## SECTION 16: Other information

H341	Suspected of causing genetic defects.
H350	May cause cancer.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

### Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Carc. 1B	CARCINOGENICITY - Category 1B
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Muta. 2	GERM CELL MUTAGENICITY - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of issue/ Date of revision** : 12/06/2026

**Date of previous issue** : 14/05/2024

**Version** : 1.01

TEKNOCOAT 1687-58

All variants

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

