Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

SAFETY DATA SHEET



TEKNOCOAT AQUA 1878-81 - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1	Product	identifier	

Product name : TEKNOCOAT AQUA 1878-81 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number

 Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.
 Members of the public Number (8 am-10 pm): +353 (0)1 809 2166 Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Contains adipohydrazide, 2-mercaptoethanol, 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: Bronopol and C(M)IT/MIT (3:1).

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures Product/ingredient name	: Mixture	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
3-Butoxypropan-2-ol	REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319	-	[1]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
2-mercaptoethanol	EC: 200-464-6 CAS: 60-24-2	<0.1	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 2, H361 STOT RE 2, H373 Aquatic Acute 1, H400	ATE [Oral] = 244 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 3 mg/l M [Acute] = 1	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C $\ge 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l	[1]
Date of issue/Date of revision		e of previous is	sue : 25/10/2023	Version : 2 Label No :9849	2/17

SECTION 3: Composition/information on ingredients

SECTION 5. Compos	Silion/information on in	igreatents	
		Aquatic Chronic 1, H410 EUH071	Skin Corr. 1C,H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100M [Chronic] = 100
		See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms			
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: No specific data.		
Ingestion	: No specific data.		

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

Date of previous issue

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	

Date of issue/Date of revision	:07/03/2025
TEKNOCOAT AQUA 1878-81 - /	All variants

SECTION 5: Firefighting measures

 Hazards from the substance or mixture Hazardous combustion products Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides 	.2 Special hazards arising from the substance or mixture		
products carbon dioxide carbon monoxide metal oxide/oxides	: In a fire or if heated, a pressure in	ase will occur and the container may burst.	
	carbon dioxide carbon monoxide	the following materials:	
5.3 Advice for firefighters			
Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident there is a fire. No action shall be taken involving any personal risk or without suitable training.	there is a fire. No action shall be		
Special protective equipment for fire-fighters is Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	breathing apparatus (SCBA) with a mode. Clothing for fire-fighters (ir conforming to European standard	Ill face-piece operated in positive pressure iding helmets, protective boots and gloves)	

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/Date of revision	: 07/03/2025	Date of previous issue	: 25/10/2023	Version	:2	4/17
TEKNOCOAT AQUA 1878-81 - A	Il variants			Label No	9 849	96

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Industrial sector specific :

: Not available.

Industrial sector specific : Not available. solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient		Exposure limit values
No exposure limit value known		
Biological exposure indices		
Product/ingredient	name	Exposure indices
No exposure indices known.		
Recommended monitoring sprocedures	European Stand assessment of e values and mea atmospheres - C of exposure to c (Workplace atm for the measure	Id be made to monitoring standards, such as the following: lard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit surement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment hemical and biological agents) European Standard EN 482 ospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance hethods for the determination of hazardous substances will also be
DNELs/DMELs		
Product/ingredient name		Result
Manium dioxide		DNEL - General population - Long term - Inhalation 28 μg/m ³ <u>Effects</u> : Local
		DNEL - Workers - Long term - Inhalation 170 μg/m³ <u>Effects</u> : Local
3-Butoxypropan-2-ol		DNEL - General population - Long term - Oral 12.5 mg/kg bw/day <u>Effects</u> : Systemic
		DNEL - General population - Long term - Dermal 22 mg/kg bw/day <u>Effects</u> : Systemic
		DNEL - General population - Long term - Inhalation 43 mg/m ³ <u>Effects</u> : Systemic
		DNEL - Workers - Long term - Dermal 52 mg/kg bw/day
Date of issue/Date of revision	:07/03/2025 Da	te of previous issue : 25/10/2023 Version : 2 5/17
FEKNOCOAT AQUA 1878-81 - A	All variants	Label No : <mark>9</mark> 8496

SECTION 8: Exposure controls/personal protection

adipohydrazide

2-mercaptoethanol

1,2-benzisothiazol-3(2H)-one

Effects: Systemic

DNEL - Workers - Long term - Inhalation 147 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Inhalation 17.5 mg/m³ Effects: Systemic

DNEL - General population - Short term - Oral 0.025 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Oral 0.025 mg/kg bw/day Effects: Systemic

DNEL - Workers - Short term - Dermal 0.05 mg/kg bw/dav Effects: Systemic

DNEL - Workers - Long term - Dermal 0.05 mg/kg bw/day Effects: Systemic

DNEL - Workers - Short term - Inhalation 0.17 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Inhalation 0.17 mg/m³ Effects: Systemic

DNEL - General population - Long term - Dermal 0.345 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Dermal 0.966 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation 1.2 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Inhalation 6.81 mg/m³ Effects: Systemic

DNEL - General population - Long term - Inhalation 0.02 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation 0.02 mg/m³ Effects: Local

DNEL - General population - Short term - Inhalation 0.04 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation 0.04 mg/m³

Date of issue/Date of revision :07/03/2025 TEKNOCOAT AQUA 1878-81 - All variants

reaction mass of: 5-chloro-2-methyl-

2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

4-isothiazolin-3-one [EC no. 247-500-7] and

Date of previous issue

Effects: Local

DNEL - General population - Long term - Oral 0.09 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Oral 0.11 mg/kg bw/day <u>Effects</u>: Systemic

PNECs

Not available.

8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	ures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and	:
boiling range	

Ingredient name	°C	°F	Method
water	100	212	
3-Butoxypropan-2-ol	171	339.8	OECD 103

Flammability

: Not available.

: Lower: Not applicable. Upper: Not applicable.

Lower and upper explosion
limit
Flash point

: Closed cup: >100°C (>212°F)

Auto-ignition temperature

	Ingredient name	°C	°F	Method
	Propylenglycoldimethylether	165	329	
	3-Butoxypropan-2-ol	260	500	EU A.15
_	Not see the second s			

Decomposition temperature	: Not available.
рН	: <mark>廖</mark> to 8.7 [Conc. (% w/w): 100%]
Viscosity	: Not available.
Solubility(ies)	:
Not available.	
Solubility in water	: Not available.

ŝ

ŝ,

· · · · · · · · · · · · · · · · · · ·		
Partition coefficient: n-octanol/	:	Not applicable.
water		

Vapour pressure

	Va	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
3-Butoxypropan-2-ol	1.05	0.14	OECD 104				
elative density	: Not	available.					

Relative density	Not available.
Density	: 1.2 g/cm ³
Vapour density	: Not available.
Particle characteristics	
Median particle size	: Not applicable

: Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

- **Explosive properties** : Not available.
- : Not available. **Oxidising properties**

9.2.2 Other safety characteristics

Not applicable.

Date of previous issue

SECTION 10: Stabilit	SECTION 10: Stability and reactivity					
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.					
10.2 Chemical stability	: The product is stable.					
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.					
10.4 Conditions to avoid	: No specific data.					
10.5 Incompatible materials	: No specific data.					
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.					

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined i Acute toxicity	in Regulation (EC) No 1272/2008
Product/ingredient name	Result
₿-Butoxypropan-2-ol	Rabbit - Dermal - LD50 3100 mg/kg
2-mercaptoethanol	Rat - Oral - LD50 244 mg/kg <u>Toxic effects</u> : Behavioral - Excitement Behavioral - Muscle contraction or spasticity Lung, Thorax, or Respiration - Respiratory depression
1,2-benzisothiazol-3(2H)-one	Rat - Oral - LD50 1020 mg/kg
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Rat - Oral - LD50 53 mg/kg <u>Toxic effects</u> : Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
ℬ-Butoxypropan-2-ol	N/A	3100	N/A	N/A	N/A
2-mercaptoethanol	244	50	N/A	3	N/A
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	53	50	N/A	0.5	N/A

Skin corrosion/irritation

Product/ingredient name

Result

Date of previous issue

titanium dioxide	Human - Skin - Mild irritant
	Duration of treatment/exposure: 72 hours Amount/concentration applied: 300 ug I
3-Butoxypropan-2-ol	Rabbit - Skin - Moderate irritant
1,2-benzisothiazol-3(2H)-one	Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Human - Skin - Severe irritant Amount/concentration applied: 0.01 %
Conclusion/Summary [Product] : Not availab	ble.
Ingredient name 3-Butoxypropan-2-ol	Conclusion/Summary Slightly irritating to the skin.
Serious eye damage/eye irritation	
Product/ingredient name	Result
✓mercaptoethanol	Rabbit - Eyes - Severe irritant Amount/concentration applied: 2 mg
Conclusion/Summary [Product] : Not availab	ble.
Respiratory corrosion/irritation	
Not available.	
Conclusion/Summary [Product] : Not availab	ble.
Respiratory or skin sensitization Not available.	
Skin	
Conclusion/Summary [Product] : Not availab	ble.
Respiratory	
Conclusion/Summary [Product] : Not availab	de.
<mark>Germ cell mutagenicity</mark> Not available.	
Conclusion/Summary [Product] : Not availab	ble.
Carcinogenicity	
It has been observed that the carcinogenic hazard of leading to significant impairment of particle clearand Not available.	of this product arises when respirable dust is inhaled in quantition ce mechanisms in the lung.
Conclusion/Summary [Product] : Not availab	ble.

Not available.

SECTION 11: Toxico	-
Conclusion/Summary [Pro	oduct] : Not available.
Specific target organ toxicit	ty (single exposure)
Not available.	
Specific target organ toxicit	t <u>y (repeated exposure)</u>
Product/ingredient name	Result
2-mercaptoethanol	STOT RE 2, H373
Aspiration hazard	
Not available.	
Information on likely routes	s of exposure
Not available.	
Potential acute health effec	<u>ts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	nysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effe	ects as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	<u>ects</u>
Not available.	
Conclusion/Summary [Pro	oduct] : Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
11.2 Information on other ha	zards
11.2.1 Endocrine disrupting Not available.	J properties
Conclusion/Summary [Pro	oduct] : The product does not meet the criteria to be considered as having endocrine
	disrupting properties according to the criteria set out in either Regulation (F

11.2.2 Other information

Not available.

/2025 Date of previous issue

disrupting properties according to the criteria set out in either Regulation (EC)

No. 1907/2006 or Regulation (EC) No 1272/2008.

SECTION 12: Ecological information

2.1 Toxicity	
Product/ingredient name	Result
Manium dioxide	Acute - LC50 - Marine water Fish - Mummichog - <i>Fundulus heteroclitus</i>
	>100000 μg/l [96 hours] <u>Effect</u> : Mortality
	Acute - LC50 - Fresh water
	Crustaceans - Water flea - <i>Ceriodaphnia dubia</i> - Neonate Age: <24 hours
	3 mg/l [48 hours] <u>Effect</u> : Mortality
1,2-benzisothiazol-3(2H)-one	Acute - LC50 - Fresh water
	OECD [Fish, Acute Toxicity Test] Fish - Trout - <i>Onorhynchus Mykiss</i>
	1.9 mg/l [96 hours]
	Acute - EC50
	OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test]
	Daphnia - Daphnia - <i>Daphnia Magna</i> 3.7 mg/l [48 hours]
	Acute - EC50 - Marine water
	OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i>
	0.36 mg/l [72 hours]
	Acute - NOEC - Marine water
	OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i> 0.15 mg/l [72 hours]
Conclusion/Summary [Product] : No	ot available.

12.2 Persistence and degradability Product/ingredient name

7,2-benzisothiazol-3(2H)-one

Result

EU 24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
7,2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
 Butoxypropan-2-ol 2-mercaptoethanol 1,2-benzisothiazol-3(2H)-one 	1.2 -0.056 -	-	Low Low Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
B-Butoxypropan-2-ol	1.46	28.6002
adipohydrazide	1.74	55.2165
2-mercaptoethanol	0.98	9.63243
1,2-benzisothiazol-3(2H)-one	1.86	73.142

Date of issue/Date of revision

: 07/03/2025 Date of previous issue

: 25/10/2023

TEKNOCOAT AQUA 1878-81 - All variants

SECTION 12: Ecological information

Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	М	т	vPvM	vP	vM
I tanium dioxide	No	No	No	No	No	No	No
3-Butoxypropan-2-ol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
2-mercaptoethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No
Mobility	: Not av	ailable.			1		

Conclusion/Summary

: The product does not meet the criteria to be considered as a PMT or vPvM.

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
tit anium dioxide	No	No	No	No	No	No	No
3-Butoxypropan-2-ol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
2-mercaptoethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin-	No	No	No	No	No	No	No
3-one [EC no. 247-500-7]							
and 2-methyl-2H-isothiazol-							
3-one [EC no. 220-239-6] (3: 1)							

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
3-Butoxypropan-2-ol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
2-mercaptoethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

Date of issue/Date of revision	: 07/03/2025	Date of previous issue	: 25/10
TEKNOCOAT AQUA 1878-81 - A	ll variants		

SECTION 13: Disposal considerations

13.1 Waste treatment meth	ods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
European waste catalogue (EWC)	: 080112
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

- **14.6 Special precautions for** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
- 14.7 Maritime transport in bulk according to IMO instruments
- : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Date of issue/Date of revision	: 07/03/2025	Date of previous issue
TEKNOCOAT AQUA 1878-81 - A	ll variants	

SECTION 15: Regulatory information

SECTION 15: Regulatory information
Labelling :
Other EU regulations
Industrial emissions : Not listed (integrated pollution prevention and control) - Air
Industrial emissions : Not listed (integrated pollution prevention and control) - Water
Explosive precursors : Not applicable.
Ozone depleting substances (EU 2024/590)
Not listed.
Prior Informed Consent (PIC) (649/2012/EU)
Not listed.
Persistent Organic Pollutants Not listed.
Seveso Directive
This product is not controlled under the Seveso Directive.
International regulations
Chemical Weapon Convention List Schedules I, II & III Chemicals
Not listed.
Montreal Protocol
Not listed.
Stockholm Convention on Persistent Organic Pollutants
Not listed.
Potterdem Convention on Brier Informed Concent (DIC)
Rotterdam Convention on Prior Informed Consent (PIC) Not listed.
UNECE Aarhus Protocol on POPs and Heavy Metals
Not listed.

15.2 Chemical safety : Not applicable. assessment

SECTION 16: Other information

Indicates information t	hat has changed from previously issued version.
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
Broodure used to deriv	a the electrification apporting to Regulation (EC) No. 1272/2008 [CL D/CHS]

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

Full text of abbreviated H statements

Date of issue/Date of revision	: 07/03/2025	Date of previous issue	: 25/10/2023	Version	:2	15/17
TEKNOCOAT AQUA 1878-81	All variants			Label No :	<mark>9</mark> 849	6

SECTION 1	6: Other information
⊮ 301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
Date of issue/ Date of	: 07/03/2025
revision	
Date of previous issue	e : 25/10/2023
Version	: 2
	TEKNOCOAT AQUA 1878-81 All variants

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 07/03/2025ITEKNOCOAT AQUA 1878-81 - All variants

: 07/03/2025 Date of previous issue