Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

SAFETY DATA SHEET



TEKNOCOAT AQUA 1879-03 - TS 0025 CLEAR (T)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1	Product	identifier	
-----	---------	------------	--

Product name : TEKNOCOAT AQUA 1879-03 - TS 0025 CLEAR (T)

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

- Telephone number
- Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.
 Members of the public Number (8 am-10 pm): +353 (0)1 809 2166 Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	:	Warning
Hazard statements	:	H317 - May cause an allergic skin reaction.
Precautionary statements		
Prevention	:	P280 - Wear protective gloves. P261 - Avoid breathing vapour.
Response	:	 ₱302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P362 + P364 - Take off contaminated clothing and wash it before reuse.
Storage	:	Not applicable.
Disposal	1	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Date of issue/Date of revision	: 23/07/2025	Date of previous issue	: 11/10/2023	Version	:2	1/19
TEKNOCOAT AQUA 1879-03 -	TS 0025 CLEA	R (T)		Label No	<mark>9</mark> 876	9

SECTION 2: Hazards identification

Hazardous ingredients	 Contains: adipohydrazide; 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)
Supplemental label elements	:
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤3	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
3-Butoxypropan-2-ol	REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319	-	[1]
adipohydrazide	EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1B, H317 Aquatic Chronic 2, H411	-	[1]
2-Dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	≤0.3	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	ATE [Oral] = 2000 mg/kg ATE [Dermal] = 1100 mg/kg ATE [Inhalation (gases)] = 1641 ppm STOT SE 3, H335: $C \ge 5\%$	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C $\ge 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]
reaction mass of: 5-chloro-	EC: 911-418-6	<0.0025	Acute Tox. 3, H301	ATE [Oral] = 53 mg/	[1]
Date of issue/Date of revision		e of previous is	sue : 11/10/2023	Version : 2	2/19
TEKNOCOAT AQUA 1879-0	3 - TS 0025 CLEAR (T)		Label No :9876	69

SECTION 3: Composition/information on ingredients

SECTION 5. Compo	Sillon/informati	on on ingreatents	
2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 See Section 16 for the full text of the H statements declared above.	kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100

There are no additional ingredients present which, within the current knowledge of the supplier and in the

concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed <u>Over-exposure signs/symptoms</u>

Date of issue/Date of revision	: 23/07/2025	Date of previous issue	: 11/10/2023	Version	:2	3/19
TEKNOCOAT AQUA 1879-03 -	TS 0025 CLEA	R (T)		Label No	<mark>9</mark> 876	9

Eye contact	: No specific data.	
Inhalation	: No specific data.	
Skin contact	: Adverse symptoms may include the following: irritation redness	
Ingestion	: No specific data.	
4.3 Indication of any immedia	e medical attention and special treatment needed	
Notes to physician	ysician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	
Specific treatments	: No specific treatment.	
SECTION 5: Firefight	ng measures	
5.1 Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	
5.2 Special hazards arising f	m the substance or mixture	
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.	
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incider there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection f chemical incidents.	

6.1 Personal precautions, protective equipment and emergency procedures

6.1 Personal precautions, pro	ective equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	ontainment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert

spill : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision	: 23/07/2025	Date of previous issue	: 11/10/2023	Version	:2	4/19
TEKNOCOAT AQUA 1879-03 -	TS 0025 CLEA	NR (T)		Label No	<mark>9</mark> 876	69

SECTION 6: Accidental release measures

Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occu	pational	exposure	limits

Product/ingredient name	Exposure limit values
2-Butoxyethanol	 NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 20 ppm. OELV 8 hours: 98 mg/m³. OELV 15 minutes: 50 ppm. OELV 15 minutes: 246 mg/m³.

Biological exposure indices

Date of issue/Date of revision	: 23/07/2025	Date of previous issue	: 11/10/2023	Version	:2	5/19
TEKNOCOAT AQUA 1879-03 -	TS 0025 CLEA	NR (T)		Label No :	<mark>9</mark> 876	9

Product/ingredient name P-Butoxyethanol		Exposure indices		
		NAOSH BGVs (Ireland, 1/2011) BMGV: 200 mg/g creatinine, BAA [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.		
Recommended monitoring : procedures	European Stand assessment of e values and mea atmospheres - 0 of exposure to o (Workplace atm for the measure	Id be made to monitoring standards, such as the following: lard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit surement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 ospheres - General requirements for the performance of procedure ment of chemical agents) Reference to national guidance nethods for the determination of hazardous substances will also be		
DNELs/DMELs				
Product/ingredient name		Result		
₽-Butoxyethanol		DNEL - General population - Long term - Oral 6.3 mg/kg bw/day <u>Effects</u> : Systemic		
		DNEL - General population - Short term - Oral 26.7 mg/kg bw/day <u>Effects</u> : Systemic		
		DNEL - General population - Long term - Inhalation 59 mg/m ³ <u>Effects</u> : Systemic		
		DNEL - Workers - Long term - Inhalation 98 mg/m ³ Effects: Systemic		
		DNEL - General population - Short term - Inhalation 147 mg/m ³ Effects: Local		
		DNEL - Workers - Short term - Inhalation 246 mg/m³ <u>Effects</u> : Local		
		DNEL - General population - Short term - Inhalation 426 mg/m ³ Effects: Systemic		
		DNEL - Workers - Short term - Inhalation 1091 mg/m ³ <u>Effects</u> : Systemic		
3-Butoxypropan-2-ol		DNEL - General population - Long term - Oral 12.5 mg/kg bw/day <u>Effects</u> : Systemic		
		DNEL - General population - Long term - Dermal 22 mg/kg bw/day <u>Effects</u> : Systemic		
		DNEL - General population - Long term - Inhalation 43 mg/m ³ <u>Effects</u> : Systemic		
		DNEL - Workers - Long term - Dermal 52 mg/kg bw/day <u>Effects</u> : Systemic		

SECTION 8: Exposure controls/personal protection

adipohydrazide

2-Dimethylaminoethanol

DNEL - Workers - Long term - Inhalation 147 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Inhalation 17.5 mg/m³ <u>Effects</u>: Systemic

DNEL - Workers - Short term - Dermal 100 µg/cm² <u>Effects</u>: Local

DNEL - General population - Long term - Oral 0.148 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Long term - Dermal 0.25 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation 0.43755 mg/m³ <u>Effects</u>: Systemic

DNEL - Workers - Short term - Dermal 1.2 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Long term - Inhalation 1.76 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation 1.76 mg/m³ <u>Effects</u>: Systemic

DNEL - Workers - Short term - Inhalation 5.28 mg/m³ <u>Effects</u>: Systemic

DNEL - Workers - Short term - Inhalation 13.53 mg/m³ Effects: Local

DNEL - General population - Long term - Dermal 0.345 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Long term - Dermal 0.966 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation 1.2 mg/m³ <u>Effects</u>: Systemic

DNEL - Workers - Long term - Inhalation 6.81 mg/m³ Effects: Systemic

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) **DNEL - General population - Long term - Inhalation** 0.02 mg/m³ <u>Effects</u>: Local

DNEL - Workers - Long term - Inhalation

Date of issue/Date of revision	: 23/07/2025	Date of previous issue	: 11/10/2023	Version : 2	7/19
TEKNOCOAT AQUA 1879-03 -	TS 0025 CLEA	NR (T)		Label No :9876	,9

1,2-benzisothiazol-3(2H)-one

SECTION 8: Exposure controls/personal protection

0.02 mg/m³ Effects: Local

DNEL - General population - Short term - Inhalation 0.04 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation 0.04 mg/m³ Effects: Local

DNEL - General population - Long term - Oral 0.09 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral 0.11 mg/kg bw/day Effects: Systemic

PNECs

Not available.

Appropriate engineering controls	ood general ventilation should be ontaminants.	sufficient to control worker exposure to airborne	
Individual protection measure			
Hygiene measures	efore eating, smoking and using th ppropriate techniques should be u ontaminated work clothing should	oroughly after handling chemical products, he lavatory and at the end of the working period. used to remove potentially contaminated clothing I not be allowed out of the workplace. Wash ng. Ensure that eyewash stations and safety on location.	
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.		
Skin protection			
Hand protection	e worn at all times when handling is is necessary. Considering the p neck during use that the gloves are hould be noted that the time to bre fferent for different glove manufac everal substances, the protection t stimated.	ves complying with an approved standard should chemical products if a risk assessment indicates parameters specified by the glove manufacturer re still retaining their protective properties. It eakthrough for any glove material may be cturers. In the case of mixtures, consisting of time of the gloves cannot be accurately	
	ecommendations :Wear suitable	-	
		itrile gloves. thickness > 0.3 mm	
	•	olyvinyl alcohol (PVA) gloves	
Body protection		he body should be selected based on the task lved and should be approved by a specialist	
Other skin protection		ional skin protection measures should be	
	pproved by a specialist before han	erformed and the risks involved and should be ndling this product.	
Respiratory protection	pproved by a specialist before han ased on the hazard and potential f ppropriate standard or certification		

SECTION 8: Exposure controls/personal protection

	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process
	equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Clear.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

	Ingredient name	°C	°F	Method
	water	100	212	
	2-Butoxyethanol	171 to 171.5	339.8 to 340.7	IP 123-93
Flammability : Not av		ilable.		

Lower and upper explosion limit	: Lower: Not applicable. Upper: Not applicable.
Flash point	: Closed cup: >100°C (>212°F)
Auto-ignition temperature	: · · · · · · · · · · · · · · · · · · ·

Auto-ignition temperature

Ingredient name		°C	°F	Method	
2-Butoxyethanol		230	446	DIN 51794	
3-Butoxypropan-2-ol		260	500	EU A.15	
Decomposition temperature	: Not ava	ilable.			
рН	: 7.8 to 8	.4 [Conc. (% v	v/w): 100%]		
Viscosity	: Not ava	ilable.			
Solubility(ies)	:				
Not available.					
Solubility in water	: Not ava	ilable.			
Partition coefficient: n-octanol/ water	: Not app	licable.			

Vapour pressure

Va	Vapour Pressure at 20°C		V	apour pres	pour pressure at 50°C	
mm Hg	kPa	Method	mm Hg	kPa	Method	
17.5	2.3					
1.05	0.14	OECD 104				
: Not	available.		ŧ			
: 1 g/	cm³					
: Not	available.					
: Not	applicable.					
	mm Hg 17.5 1.05 : Not : 1 g/ : Not	mm Hg kPa 17.5 2.3	mm HgkPaMethod17.52.31.050.14OECD 104: Not available.: 1 g/cm³: Not available.	mm HgkPaMethodmm Hg17.52.30.140ECD 1041.050.140ECD 1040ECD 104: Not available.: 1 g/cm³: Not available.	mm HgkPaMethodmm HgkPa17.52.30.14OECD 10401.050.14OECD 10400: Not available.: 1 g/cm³: Not available.: Not available.	

9.2 Other information

Date of issue/Date of revision	: 23/07/2025	Date of previous issue	: 11
TEKNOCOAT AQUA 1879-03 -	TS 0025 CLEA	R (T)	

÷.

SECTION 9: Physical and chemical properties

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

Oxidising properties : Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredie	ients.
10.2 Chemical stability	The product is stable.	
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occu	Jr.
10.4 Conditions to avoid	No specific data.	
10.5 Incompatible materials	No specific data.	
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition product should not be produced.	ots

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in	n Regulation (EC) No 1272/2008
Acute toxicity Product/ingredient name	Result
<mark>3</mark> -Butoxypropan-2-ol	Rabbit - Dermal - LD50 3100 mg/kg
2-Dimethylaminoethanol	Rat - Oral - LD50 2 g/kg
	Rat - Inhalation - LC50 Gas. 1641 ppm [4 hours] <u>Toxic effects</u> : Eye - Lacrimation Behavioral - Ataxia Lung, Thorax, or Respiration - Dyspnea
1,2-benzisothiazol-3(2H)-one	Rat - Oral - LD50 1020 mg/kg
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Rat - Oral - LD50 53 mg/kg <u>Toxic effects</u> : Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient	t name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
	02/07/0005		- 44/40	(2002		
Date of issue/Date of revision TEKNOCOAT AQUA 1879-03 - TS		Date of previous issue (T)	: 11/10,	/2023	Version Label No :	:2 10/19 9 8769

SECTION 11: Toxicological information

FEKNOCOAT AQUA 1879-03	44061.3	N/A	1007882.3	110.2	N/A	
2-Butoxyethanol	1200	N/A	N/A	3	N/A	
3-Butoxypropan-2-ol	N/A	3100	N/A	N/A	N/A	
2-Dimethylaminoethanol	2000	1100	1641	N/A	N/A	
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21	
reaction mass of: 5-chloro-2-methyl-4-isothiazolin	- 53	50	N/A	0.5	N/A	
3-one [EC no. 247-500-7] and 2-methyl-2H-						
isothiazol-3-one [EC no. 220-239-6] (3:1)						

Skin corrosion/irritation

Product	/ingred	ient ı	name
---------	---------	--------	------

2-Butoxyethanol

3-Butoxypropan-2-ol

2-Dimethylaminoethanol

1,2-benzisothiazol-3(2H)-one

Result

Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg

Rabbit - Skin - Moderate irritant

Human - Skin - Severe irritant

Amount/concentration applied: 0.01 %

Rabbit - Skin - Mild irritant Amount/concentration applied: 445 mg

Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Conclusion/Summary [Product]	: Not available.
Ingredient name	Conclusion/Summary
ℬ-Butoxypropan-2-ol	Slightly irritating to the skin.

Serious eye damage/eye irritation

Product/ingredient name

2-Butoxyethanol

Result Rabbit - Eyes - Moderate irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 100 mg

Rabbit - Eyes - Severe irritant Amount/concentration applied: 100 mg

2-Dimethylaminoethanol

Rabbit - Eyes - Severe irritant Amount/concentration applied: 5 uL

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Date of issue/Date of revision: 23/07/2025Date of previous issueTEKNOCOAT AQUA 1879-03 - TS 0025 CLEAR (T)

SECTION 11: Toxico	logical informati	on	
Conclusion/Summary [Pro	oduct] : Not available		
Germ cell mutagenicity Not available.			
Not available.			
Conclusion/Summary [Pro	oduct] : Not available		
Carcinogenicity			
Not available.			
Conclusion/Summary [Pro	oduct] : Not available		
Reproductive toxicity			
Not available.			
Conclusion/Summary [Pro	oduct] : Not available		
Specific target organ toxicit	ty (single exposure)		
Product/ingredient name	y (Single exposule)	Result	
2-Dimethylaminoethanol		STOT SE 3, H335 (Respi	ratory tract irritation)
Specific target organ toxicit	ty (repeated exposure)		
Not available.			
Aspiration hazard Not available.			
Information on likely routes	of exposure		
Not available.			
Potential acute health effect		• • • • • • • • • • • • • • • • • • •	
Eye contact Inhalation	-	t effects or critical hazards	
Skin contact	: May cause an aller	t effects or critical hazards	›.
Ingestion	,	t effects or critical hazards	
Symptoms related to the ph	-		
Eye contact	: No specific data.		<u> </u>
Inhalation	: No specific data.		
Skin contact	: Adverse symptoms irritation redness	may include the following:	
Ingestion	: No specific data.		
Delayed and immediate effe	•	effects from short and lo	ng-term exposure
Short term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Long term exposure Potential immediate effects	: Not available.		
Potential delayed effects Potential chronic health effe	: Not available.		
Not available.	_		
Conclusion/Summary [Pro	oduct] : Not available.		
Date of issue/Date of revision TEKNOCOAT AQUA 1879-03	: 23/07/2025 Date of J	previous issue : 11/10/	2023 Version : 2 12/19 Label No : 98769

SECTION 11: Toxicological information

	-
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information 12.1 Toxicity Product/ingredient name Z-Butoxyethanol Result

Acute - LC50 - Marine water Fish - Inland silverside - *Menidia beryllina* <u>Size</u>: 40 to 100 mm 1250000 μg/l [96 hours] <u>Effect</u>: Mortality

Acute - LC50 - Marine water Crustaceans - Common shrimp, sand shrimp - *Crangon* 800000 μg/l [48 hours] Effect: Mortality

1,2-benzisothiazol-3(2H)-one

Acute - LC50 - Fresh water OECD [Fish, Acute Toxicity Test] Fish - Trout - Onorhynchus Mykiss 1.9 mg/l [96 hours]

Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - *Daphnia Magna* 3.7 mg/l [48 hours]

Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.36 mg/l [72 hours]

Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.15 mg/l [72 hours]

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name

2-benzisothiazol-3(2H)-one

Result

EU 24% [28 days]

Conclusion/Summary [Product] : Not available.

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
7,2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-Butoxyethanol	0.81	-	Low
3-Butoxypropan-2-ol	1.2	-	Low
2-Dimethylaminoethanol	-0.55	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
2-Butoxyethanol	1.8	67.3685
3-Butoxypropan-2-ol	1.5	28.6002
adipohydrazide	1.7	55.2165
2-Dimethylaminoethanol	1.7	44.8862
1,2-benzisothiazol-3(2H)-one	1.9	73.142

Results of PMT and vPvM assessment

Product/ingredient name	PMT	Ρ	Μ	т	vPvM	vP	vM
2-Butoxyethanol	No	No	No	No	No	No	No
3-Butoxypropan-2-ol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
2-Dimethylaminoethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Mobility

: Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
2-Butoxyethanol	No	N/A	N/A	No	N/A	N/A	N/A
3-Butoxypropan-2-ol	No	N/A	N/A	No	N/A	N/A	N/A
adipohydrazide	No	N/A	N/A	No	N/A	N/A	N/A
2-Dimethylaminoethanol	No	N/A	N/A	No	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	No	N/A	No	No	No	N/A	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	N/A	N/A	No	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

SECTION 12: Ecolog	ical inf	formation		
Product/ingredient name	PRT	P	B	т

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
2-Butoxyethanol	No	No	No	No	No	No	No
3-Butoxypropan-2-ol	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
2-Dimethylaminoethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

```
Conclusion/Summary [Product]
```

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalogue (EWC)	: 080112
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
Date of issue/Date of revi	ision : 23/07/2025	Date of previous issue	: 11/10/2023	Version : 2 15/19
TEKNOCOAT AQUA	1879-03 - TS 0025 CLE	AR (T)		Label No :98769

SECTION 14: Transport information				
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous

substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]	
TEKNOCOAT AQUA 1879-03	≥90	3	
Labelling :	·		
Other EU regulations			
Industrial emissions : Not lister (integrated pollution prevention and control) - Air	d		
Industrial emissions : Not liste (integrated pollution prevention and control) - Water	d		
Explosive precursors : Not app	licable.		
Ozone depleting substances (EU 202	<u>4/590)</u>		
Not listed.			
Prior Informed Consent (PIC) (649/20	12/EU)		
Not listed.			
Persistent Organic Pollutants Not listed.			
Seveso Directive			
This product is not controlled under the	Seveso Directiv	ve.	
nternational regulations			
Chemical Weapon Convention List Sch	nedules I, II &	III Chemicals	
ate of issue/Date of revision : 23/07/2	025 Date of pre	evious issue : 11/10/2023	Version : 2 16/19
EKNOCOAT AQUA 1879-03 - TS 0025 C	LEAR (T)		Label No :98769

SECTION 15: Regulatory information

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety : Not applicable	15.2 Chemical	safety	: Not applicable
	E 2 Chamical	opfoty	Not oppligable

assessment

SECTION 16: Other information

✓ Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
-	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method

Full text of abbreviated H statements

r	
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

SECTION 16: Other information

OLOTION 10. Other information		
Acute Tox. 2	ACUTE TOXICITY - Category 2	
Acute Tox. 3	ACUTE TOXICITY - Category 3	
Acute Tox. 4	ACUTE TOXICITY - Category 4	
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1	
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1	
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2	
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2	
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3	
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B	
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
Skin Sens. 1	SKIN SENSITISATION - Category 1	
Skin Sens. 1A	SKIN SENSITISATION - Category 1A	
Skin Sens. 1B	SKIN SENSITISATION - Category 1B	
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3	
Date of issue/ Date of	: 23/07/2025	
revision		
Date of previous issue	: 11/10/2023	
Version	: 2	

EKNOCOAT AQUA 1879-03_TS 0025 CLEAR (T) TS 0025 CL

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.