SAFETY DATA SHEET



TEKNOCOAT AQUA 2577-11 - RAL 9003

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : TEKNOCOAT AQUA 2577-11 - RAL 9003

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: Prod-safe@teknos.com

responsible for this o

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable.
Response : Not applicable.
Storage : Not applicable.
Disposal : Not applicable.

Supplemental label

elements

: Contains 2,4,7,9-tetramethyl-5-decyne-4,7-diol, 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:

1). May produce an allergic reaction. Safety data sheet available on request.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Date of issue/Date of revision: 11/09/2023Date of previous issue: No previous validationVersion: 11/15

TEKNOCOAT AQUA 2577-11 - RAL 9003 Label No :49928

SECTION 2: Hazards identification

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Туре |
|---|--|-----------|---|---|---------|
| titanium dioxide | REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 | ≥10 - ≤25 | Carc. 2, H351 (inhalation) | - | [1] [*] |
| Dipropyleneglycolmethylether | REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8 | ≤5 | Not classified. | - | [2] |
| 3-Butoxypropan-2-ol | REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8 | ≤3 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 | - | [1] |
| 2,4,7,9-tetramethyl- 5-decyne-4,7-diol | REACH #: 01-2119954390-39 EC: 204-809-1 CAS: 126-86-3 | ≤0.3 | Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412 | - | [1] |
| 1,2-benzisothiazol-3(2H)- one | EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6 | <0.05 | Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 | ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1 | [1] |
| 2-methyl-2H-isothiazol- 3-one | EC: 220-239-6 CAS: 2682-20-4 | <0.0015 | Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 | ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1 | [1] |
| reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1) | CAS: 55965-84-9 Index: 613-167-00-5 | <0.001 | Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 | ATE [Oral] = 53 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: C ≥ 0.6% Eye Dam. 1, H318: | [1] |

Date of issue/Date of revision: 11/09/2023Date of previous issue: No previous validationVersion: 12/15

TEKNOCOAT AQUA 2577-11 - RAL 9003 Label No :49928

| SECTION 3: Compos | on/information on ingredients | |
|--------------------------|--|---|
| | $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H31: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100 See Section 16 for the full text of the H statements declared above. | 1 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention if symptoms occur.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Ingestion : Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms

occur.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Date of issue/Date of revision: 11/09/2023Date of previous issue: No previous validationVersion: 13/15TEKNOCOAT AQUA 2577-11 - RAL 9003Label No :49928

SECTION 5: Firefighting measures

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

metal oxide/oxides

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/Date of revision : 11/09/2023 Version:1 4/15 Date of previous issue : No previous validation **Label No: 49928**

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|------------------------------|--|
| Dipropyleneglycolmethylether | EU OEL (Europe, 10/2019). [(2-Methoxymethylethoxy)-propanol] Absorbed through skin. Notes: list of indicative occupational exposure limit values |
| | TWA: 50 ppm 8 hours. TWA: 308 mg/m³ 8 hours. |

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|------------------------------|-------|-------------------------|------------------------|------------|-----------|
| Dipropyleneglycolmethylether | DNEL | Long term Oral | 36 mg/kg | General | Systemic |
| | | | bw/day | population | |
| | DNEL | Long term | 37.2 mg/m ³ | General | Systemic |
| | DATE | Inhalation | 404 " | population | |
| | DNEL | Long term Dermal | 121 mg/kg | General | Systemic |
| | DAIEL | | bw/day | population | 0 |
| | DNEL | Long term Dermal | 283 mg/kg | Workers | Systemic |
| | DNEL | Long torm | bw/day | Workers | Cuatamia |
| | DINEL | Long term Inhalation | 308 mg/m ³ | VVOIKEIS | Systemic |
| 3-Butoxypropan-2-ol | DNEL | Long term | 147 mg/m³ | Workers | Systemic |
| o Butoxypropuri 2 or | DIVLE | Inhalation | 147 mg/m | VVOINGIS | O yotomio |
| | DNEL | Long term Oral | 12.5 mg/ | General | Systemic |
| | | | kg bw/day | population | -, |
| | DNEL | Long term Dermal | 22 mg/kg | General | Systemic |
| | | | bw/day | population | |
| | DNEL | Long term | 43 mg/m³ | General | Systemic |
| | | Inhalation | | population | |
| | DNEL | Long term Dermal | 52 mg/kg | Workers | Systemic |
| | | | bw/day | | |
| | DNEL | Short term Dermal | 50 % | General | Local |

Date of issue/Date of revision: 11/09/2023Date of previous issue: No previous validationVersion: 15/15TEKNOCOAT AQUA 2577-11 - RAL 9003Label No :49928

SECTION 8: Exposure controls/personal protection

| | ₋ | | | | |
|---------------------------------------|--------------|-------------------|---------------------------------------|-----------------|----------|
| | | | | population | |
| | DNEL | Long term Dermal | 50 % | General | Local |
| | | | | population | |
| | DNEL | Short term Dermal | 50 % | Workers | Local |
| | DNEL | Long term Dermal | 50 % | Workers | Local |
| 2,4,7,9-tetramethyl-5-decyne-4,7-diol | DNEL | Long term Oral | 0.25 mg/ | General | Systemic |
| | | | kg bw/day | population | |
| | DNEL | Long term Dermal | 0.25 mg/ | General | Systemic |
| | | | kg bw/day | population | |
| | DNEL | Long term | 0.43 mg/m ³ | General | Systemic |
| | | Inhalation | | population | |
| | DNEL | Long term Dermal | 0.5 mg/kg | Workers | Systemic |
| | | | bw/day | | |
| | DNEL | Short term Oral | 0.75 mg/ | General | Systemic |
| | | | kg bw/day | population | |
| | DNEL | Short term Dermal | 0.75 mg/ | General | Systemic |
| | | | kg bw/day | population | |
| | DNEL | Short term | 1.29 mg/m ³ | General | Systemic |
| | | Inhalation | | population | |
| | DNEL | Short term Dermal | 1.5 mg/kg | Workers | Systemic |
| | | | bw/day | | - |
| | DNEL | Long term | 1.76 mg/m³ | Workers | Systemic |
| | | Inhalation | | | = |
| | DNEL | Short term | 5.28 mg/m ³ | Workers | Systemic |
| | | Inhalation | J | | , |
| 1,2-benzisothiazol-3(2H)-one | DNEL | Long term Dermal | 0.345 mg/ | General | Systemic |
| | | | kg bw/day | population | , |
| | DNEL | Long term Dermal | 0.966 mg/ | Workers | Systemic |
| | | | kg bw/day | | , |
| | DNEL | Long term | 1.2 mg/m ³ | General | Systemic |
| | | Inhalation | 3 | population | , |
| | DNEL | Long term | 6.81 mg/m ³ | Workers | Systemic |
| | | Inhalation | J | | , |
| 2-methyl-2H-isothiazol-3-one | DNEL | Long term | 0.021 mg/ | General | Local |
| , | | Inhalation | m³ | population | |
| | DNEL | Long term | 0.021 mg/ | Workers | Local |
| | | Inhalation | m³ | | |
| | DNEL | Long term Oral | 0.027 mg/ | General | Systemic |
| | | | kg bw/day | population | * |
| | DNEL | Short term | 0.043 mg/ | General | Local |
| | | Inhalation | m³ | population | |
| | DNEL | Short term | 0.043 mg/ | Workers | Local |
| | | Inhalation | m³ | | |
| | DNEL | Short term Oral | 0.053 mg/ | General | Systemic |
| | | <u></u> | kg bw/day | population | * |
| reaction mass of: 5-chloro-2-methyl- | DNEL | Long term | 0.02 mg/m ³ | General | Local |
| 4-isothiazolin-3-one [EC no. | | Inhalation | J | population | |
| 247-500-7] and 2-methyl-2H- | | | | | |
| isothiazol-3-one [EC no. 220-239-6] | | | | | |
| (3:1) | | | | | |
| () | DNEL | Long term | 0.02 mg/m ³ | Workers | Local |
| | | Inhalation | , , , , , , , , , , , , , , , , , , , | | |
| | DNEL | Short term | 0.04 mg/m ³ | General | Local |
| | - | Inhalation | | population | |
| | DNEL | Short term | 0.04 mg/m ³ | Workers | Local |
| | | Inhalation | , , , , , , , , , , , , , , , , , , , | | |
| | DNEL | Long term Oral | 0.09 mg/ | General | Systemic |
| | | | kg bw/day | population | , |
| | DNEL | Short term Oral | 0.11 mg/ | General | Systemic |
| | | | kg bw/day | population | , |
| | | | g ~, aay | F 5 P 41 41 511 | |

PNECs

No PNECs available

8.2 Exposure controls

Date of issue/Date of revision: 11/09/2023Date of previous issue: No previous validationVersion: 16/15TEKNOCOAT AQUA 2577-11 - RAL 9003Label No :49928

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommendations: Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm polyvinyl alcohol (PVA) gloves Not recommended

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Colour White. **Odour** Slight

Odour threshold Not available. Melting point/freezing point : Not available.

Initial boiling point and boiling range

| Ingredient name | °C | °F | Method |
|---------------------|-----|-------|----------|
| water | 100 | 212 | |
| 3-Butoxypropan-2-ol | 171 | 339.8 | OECD 103 |

Flammability : Not available. Lower and upper explosion : Lower: 1.1% Upper: 14% limit

Closed cup: >100°C (>212°F) Flash point

Auto-ignition temperature

Date of issue/Date of revision : 11/09/2023 Version:1 7/15 Date of previous issue : No previous validation **Label No: 49928**

SECTION 9: Physical and chemical properties

| Ingredient name | °C | °F | Method |
|------------------------------|-----|-------|---------|
| Dipropyleneglycolmethylether | 207 | 404.6 | EU A.15 |
| 3-Butoxypropan-2-ol | 260 | 500 | EU A.15 |

Decomposition temperature : Not available. 7.4 to 8 pН **Viscosity** : Not available.

Solubility(ies)

Not available.

Solubility in water : Not available. Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

| | Vapour Pressure at 20°C | | | Va | oour pressu | re at 50°C |
|---------------------|-------------------------|------|----------|-------|-------------|------------|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method |
| water | 17.5 | 2.3 | | | | |
| 3-Butoxypropan-2-ol | 1.05 | 0.14 | OECD 104 | | | |

Relative density : Not available. **Density** : 1.2 g/cm³ Vapour density : Not available. **Explosive properties** : Not available. **Oxidising properties** : Not available.

Particle characteristics

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 **Acute toxicity**

Date of issue/Date of revision : 11/09/2023 Date of previous issue Version :1 8/15 : No previous validation **Label No: 49928**

SECTION 11: Toxicological information

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|---------------------------------|---------------|--------------------------|----------|
| 3-Butoxypropan-2-ol 1,2-benzisothiazol-3(2H)- | LD50 Dermal LD50 Oral | Rabbit Rat | 3100 mg/kg 1020 mg/kg | - |
| one 2-methyl-2H-isothiazol- 3-one | LC50 Inhalation Dusts and mists | Rat | 0.11 mg/l | 4 hours |
| reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1) | LD50 Oral | Rat | 53 mg/kg | - |

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

| Route | ATE value |
|----------------|-----------|
| Not available. | |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|------------------------------|--------------------------|---------|-------|--------------|-------------|
| titanium dioxide | Skin - Mild irritant | Human | - | 72 hours 300 | - |
| | | | | ug I | |
| Dipropyleneglycolmethylether | | Human | - | 8 mg | - |
| | Eyes - Mild irritant | Rabbit | - | 24 hours 500 | - |
| | | | | mg | |
| | Skin - Mild irritant | Rabbit | - | 500 mg | - |
| 3-Butoxypropan-2-ol | Skin - Moderate irritant | Rabbit | - | - | - |
| 2,4,7,9-tetramethyl- | Eyes - Severe irritant | Rabbit | - | 0.1 MI | - |
| 5-decyne-4,7-diol | | | | | |
| | Skin - Mild irritant | Rabbit | - | 0.5 g | - |
| 1,2-benzisothiazol-3(2H)-one | Skin - Mild irritant | Human | - | 48 hours 5 % | - |
| reaction mass of: 5-chloro- | Skin - Severe irritant | Human | - | 0.01 % | - |
| 2-methyl-4-isothiazolin- | | | | | |
| 3-one [EC no. 247-500-7] | | | | | |
| and 2-methyl-2H-isothiazol- | | | | | |
| 3-one [EC no. 220-239-6] (3: | | | | | |
| 1) | | | | | |

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Sensitisation

Conclusion/Summary : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Date of issue/Date of revision Version :1 9/15 : 11/09/2023 Date of previous issue : No previous validation **Label No: 49928**

SECTION 11: Toxicological information

Information on likely routes: Not available.

of exposure

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|---|--|----------------------------------|
| titanium dioxide | Acute LC50 3 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 6.5 mg/l Fresh water | Daphnia - <i>Daphnia pulex</i> - Neonate | 48 hours |
| | Acute LC50 >1000000 μg/l Marine water | Fish - Fundulus heteroclitus | 96 hours |
| 2,4,7,9-tetramethyl- 5-decyne-4,7-diol | EC50 91 mg/l | Daphnia - <i>Daphnia magna</i> | 48 hours |
| | LC50 42 mg/l | Fish - Cyprinus carpio | 96 hours |
| 1,2-benzisothiazol-3(2H)-one | Acute EC50 0.36 mg/l Marine water Acute EC50 3.7 mg/l Acute LC50 1.9 mg/l Fresh water | Algae - Skeletonema Costatum Daphnia - Daphnia Magna Fish - Onorhynchus Mykiss | 72 hours 48 hours 96 hours |

Date of issue/Date of revision: 11/09/2023Date of previous issue: No previous validationVersion: 110/15TEKNOCOAT AQUA 2577-11 - RAL 9003Label No :49928

SECTION 12: Ecological information

| | | Acute NOEC 0.15 mg/l Marine water | Algae - Skeletonema Costatum | 72 hours |
|----|----------------------------|-----------------------------------|--------------------------------|----------|
| 2- | methyl-2H-isothiazol-3-one | Acute EC50 0.18 ppm Fresh water | Daphnia - <i>Daphnia magna</i> | 48 hours |
| | - | Acute LC50 0.07 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |

Conclusion/Summary

: Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|------------------------------|------|----------------|------|----------|
| 1,2-benzisothiazol-3(2H)-one | EU | 24 % - 28 days | - | - |

: This product has not been tested for biodegradation. Conclusion/Summary

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|------------------------------|-------------------|------------|------------------|
| 1,2-benzisothiazol-3(2H)-one | - | - | Inherent |

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|------------------------------|--------|-----|-----------|
| Dipropyleneglycolmethylether | 0.004 | - | Low |
| 3-Butoxypropan-2-ol | 1.2 | - | Low |
| 1,2-benzisothiazol-3(2H)-one | - | 3.2 | Low |

12.4 Mobility in soil

Soil/water partition

: Not available.

coefficient (Koc)

: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

Mobility

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

European waste catalogue (EWC) : 080112, 200128

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Date of issue/Date of revision Version :1 11/15 : 11/09/2023 Date of previous issue : No previous validation **Label No: 49928**

SECTION 13: Disposal considerations

Special precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|------------------------------------|----------------|----------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - | - |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. | No. |

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Labelling

Other EU regulations

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

: Not applicable. **Explosive precursors** Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Date of issue/Date of revision 12/15 : 11/09/2023 Date of previous issue Version :1 : No previous validation **Label No: 49928**

SECTION 15: Regulatory information

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

Full text of abbreviated H statements

| H301 | Toxic if swallowed. |
|--------|---|
| H302 | Harmful if swallowed. |
| H310 | Fatal in contact with skin. |
| | . 5.5 |
| H311 | Toxic in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H330 | Fatal if inhaled. |
| H351 | Suspected of causing cancer. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

Full text of classifications [CLP/GHS]

Date of issue/Date of revision: 11/09/2023Date of previous issue: No previous validationVersion: 1 3/15TEKNOCOAT AQUA 2577-11 - RAL 9003Label No :49928

SECTION 16: Other information

Acute Tox. 2 **ACUTE TOXICITY - Category 2** Acute Tox. 3 **ACUTE TOXICITY - Category 3** Acute Tox. 4 **ACUTE TOXICITY - Category 4** Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 Aquatic Chronic 3 **CARCINOGENICITY - Category 2** Carc. 2 Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 Eye Irrit. 2 Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B Skin Corr. 1C SKIN CORROSION/IRRITATION - Category 1C Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1 SKIN SENSITISATION - Category 1 Skin Sens. 1A SKIN SENSITISATION - Category 1A SKIN SENSITISATION - Category 1B Skin Sens. 1B

Date of issue/ Date of : 11/09/2023

revision

Date of previous issue : No previous validation

Version : 1

TEKNOCOAT AQUA 2577-11 RAL 9003 RAL 9003

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 11/09/2023Date of previous issue: No previous validationVersion: 114/15

Label No: 49928

Date of issue/Date of revision: 11/09/2023Date of previous issue: No previous validationVersion: 115/15

TEKNOCOAT AQUA 2577-11 - RAL 9003 Label No :49928