

# SAFETY DATA SHEET



TEKNOCOAT AQUA 2577-11 - RAL 9003

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : TEKNOCOAT AQUA 2577-11 - RAL 9003

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : In an emergency, call 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** : H317 - May cause an allergic skin reaction.

#### Precautionary statements

**Prevention** : P280 - Wear protective gloves.  
P261 - Avoid breathing vapour.

**Response** : P302 + P352 - IF ON SKIN: Wash with plenty of water.  
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.  
P362 + P364 - Take off contaminated clothing and wash it before reuse.

**Storage** : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** : Contains: 2,4,7,9-tetramethyl-5-decyne-4,7-diol; 1,2-benzisothiazol-3(2H)-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) and 2-methyl-2H-isothiazol-3-one

## SECTION 2: Hazards identification

**Supplemental label elements** : Contains biocidal products for in-can preservation: BIT and C(M)IT/MIT (3:1) and MIT.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Diethyleneglycolmethylether	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤5	Not classified.	-	[2]
3-Butoxypropan-2-ol	REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319	-	[1]
2,4,7,9-tetramethyl-5-decyne-4,7-diol	REACH #: 01-2119954390-39 EC: 204-809-1 CAS: 126-86-3	≤0.3	Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1]
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C ≥ 0.036% M [Acute] = 1 M [Chronic] = 1	[1]
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0025	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: C ≥ 0.6% Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: 0.06% ≤ C < 0.6% Skin Sens. 1, H317:	[1]

**Date of issue/Date of revision** : 02/12/2025 **Date of previous issue** : 08/07/2025 **Version** : 4 **2/25**

TEKNOCOAT AQUA 2577-11 - RAL 9003

**Label No** : 35645

## SECTION 3: Composition/information on ingredients

2-methyl-2H-isothiazol-3-one	EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071  <b>See Section 16 for the full text of the H statements declared above.</b>	C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100  ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1	[1]
------------------------------	--	---------	---	---	-----

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.

## SECTION 4: First aid measures

- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## SECTION 6: Accidental release measures

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
Dipropyleneglycolmethylether	<b>Regulation on Limit Values - MAC (Austria, 12/2024)</b> <b>[Dipropylenglykolmonomethylether (Isomerengemisch)]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 307 mg/m <sup>3</sup> . CEIL 5 minutes: 100 ppm 8 times per shift. CEIL 5 minutes: 614 mg/m <sup>3</sup> 8 times per shift.
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and	<b>Regulation on Limit Values - MAC (Austria, 12/2024) [5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-di-</b>

## SECTION 8: Exposure controls/personal protection

2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	<b>hydroisothiazol-3-on (Gemisch im Verhältnis 3:1)</b> Skin sensitiser. TWA 8 hours: 0.05 mg/m <sup>3</sup> .
2-methyl-2H-isothiazol-3-one	<b>Regulation on Limit Values - MAC (Austria, 12/2024) [5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on (Gemisch im Verhältnis 3:1)]</b> Skin sensitiser. TWA 8 hours: 0.05 mg/m <sup>3</sup> .
Dipropyleneglycolmethylether	<b>Limit values (Belgium, 12/2023)</b> <b>[Dipropyleenglycolmonomethylether]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m <sup>3</sup> .
Dipropyleneglycolmethylether	<b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) [(2-Methoxymethyletoxy)propanol]</b> Absorbed through skin. Limit value 8 hours: 308 mg/m <sup>3</sup> . Limit value 8 hours: 50 ppm.
Dipropyleneglycolmethylether	<b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) [(2-metoksimetiletoksi)-propanol]</b> Absorbed through skin. ELV 8 hours: 308 mg/m <sup>3</sup> . ELV 8 hours: 50 ppm.
Dipropyleneglycolmethylether	<b>Department of labour inspection (Cyprus, 7/2021)</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m <sup>3</sup> .
Dipropyleneglycolmethylether	<b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) [(2-methoxymethylethoxy)propanol]</b> Absorbed through skin. TWA 8 hours: 270 mg/m <sup>3</sup> . TWA 8 hours: 43.8 ppm. STEL 15 minutes: 550 mg/m <sup>3</sup> . STEL 15 minutes: 89.3 ppm.
3-Butoxypropan-2-ol	<b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023)</b> Absorbed through skin. STEL 15 minutes: 550 mg/m <sup>3</sup> . TWA 8 hours: 270 mg/m <sup>3</sup> . TWA 8 hours: 49 ppm. STEL 15 minutes: 100 ppm.
Dipropyleneglycolmethylether	<b>Working Environment Authority (Denmark, 12/2024)</b> <b>[dipropylenglycolmethylether]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 309 mg/m <sup>3</sup> . STEL 15 minutes: 618 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm.
Dipropyleneglycolmethylether	<b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) [dipropüleenglükooli monometüüleeter]</b> Absorbed through skin. TWA 8 hours: 308 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm.
Dipropyleneglycolmethylether	<b>EU OEL (Europe, 1/2022) [(2-Methoxymethylethoxy)-propanol]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m <sup>3</sup> .
Dipropyleneglycolmethylether	<b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) [(2-Metoksimetyylietoksi)-propanoli]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 310 mg/m <sup>3</sup> .



## SECTION 8: Exposure controls/personal protection

Dipropyleneglycolmethylether	<b>Ministry of Labor (France, 6/2024) [(2-méthoxyméthyléthoxy)-propanol]</b> Absorbed through skin. TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 308 mg/m <sup>3</sup> . Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)
Dipropyleneglycolmethylether	<b>TRGS 900 OEL (Germany, 6/2024) [(2-Methoxymethylethoxy) propanol]</b> TWA 8 hours: 310 mg/m <sup>3</sup> . PEAK 15 minutes: 310 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm. PEAK 15 minutes: 50 ppm. <b>DFG MAC-values list (Germany, 7/2024) [Dipropylene glycol monomethyl ether]</b> Develop D. TWA 8 hours: 50 ppm. PEAK 15 minutes: 50 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 310 mg/m <sup>3</sup> . PEAK 15 minutes: 310 mg/m <sup>3</sup> 4 times per shift [Interval: 1 hour]. <b>DFG MAC-values list (Germany, 7/2024)</b> Skin sensitiser. <b>DFG MAC-values list (Germany, 7/2024)</b> Skin sensitiser. <b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 8/2024) [μεθοξυμεθυλ-αιθοξυ-προπανόλη, 2-]</b> Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 600 mg/m <sup>3</sup> . STEL 15 minutes: 150 ppm. STEL 15 minutes: 900 mg/m <sup>3</sup> .
1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazol-3-one Dipropyleneglycolmethylether	<b>5/2020. (II. 6.) ITM Decree (Hungary, 1/2025) [(2-metoximetiletoxi)-propanol]</b> TWA 8 hours: 308 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm.
Dipropyleneglycolmethylether	<b>Ministry of Welfare, List of Exposure Limits (Iceland, 11/2024) [Díprópýlenglýkólmetýleter]</b> Absorbed through skin. TWA 8 hours: 300 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm.
Dipropyleneglycolmethylether	<b>NAOSH (Ireland, 4/2024) [(2-methoxymethylethoxy)-1-propanol]</b> Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 50 ppm. OELV 8 hours: 308 mg/m <sup>3</sup> .
Dipropyleneglycolmethylether	<b>Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 9/2024)</b> Absorbed through skin. Limit value 8 hours: 50 ppm. Limit value 8 hours: 308 mg/m <sup>3</sup> .
Dipropyleneglycolmethylether	<b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) [Metoksipropoksi propanols]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m <sup>3</sup> .
Dipropyleneglycolmethylether	<b>Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)</b> Absorbed through skin. TWA 8 hours: 308 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm. STEL 15 minutes: 450 mg/m <sup>3</sup> . STEL 15 minutes: 75 ppm.
Dipropyleneglycolmethylether	<b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) [(2-méthoxyméthyléthoxy)-propanol]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m <sup>3</sup> .

## SECTION 8: Exposure controls/personal protection

Dipropyleneglycolmethylether	<b>EU OEL (Europe, 1/2022) [(2-Methoxymethylethoxy)-propanol]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m <sup>3</sup> .
Dipropyleneglycolmethylether	<b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) [dipropyleenglycolmethylether]</b> TWA 8 hours: 300 mg/m <sup>3</sup> . TWA 8 hours: 48.7 ppm.
Dipropyleneglycolmethylether	<b>FOR-2011-12-06-1358 (Norway, 5/2024) [(2-metoksymetyletoksy)-propanol]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 300 mg/m <sup>3</sup> .
Dipropyleneglycolmethylether	<b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024) [dipropylene glycol methyl ether]</b> Absorbed through skin. TWA 8 hours: 240 mg/m <sup>3</sup> . STEL 15 minutes: 480 mg/m <sup>3</sup> .
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	<b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 7/2024)</b> Absorbed through skin. TWA 8 hours: 0.2 mg/m <sup>3</sup> . STEL 15 minutes: 0.4 mg/m <sup>3</sup> .
Dipropyleneglycolmethylether	<b>Portuguese Institute of Quality (Portugal, 11/2014) [2-metoximetiletoxipropanol]</b> Absorbed through skin. TWA 8 hours: 100 ppm. STEL 15 minutes: 150 ppm. <b>Decree-Law 24/2012 - Occupational exposure limits for chemical agents (Portugal, 6/2021) [2-metoximetiletoxi propanol]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m <sup>3</sup> .
Dipropyleneglycolmethylether	<b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024)</b> Absorbed through skin. VLA 8 hours: 308 mg/m <sup>3</sup> . VLA 8 hours: 50 ppm.
Dipropyleneglycolmethylether	<b>Government regulation SR c. 355/2006 (Slovakia, 6/2024) [2-metoxymetyl-etoxipropanol]</b> Absorbed through skin , Inhalation sensitiser. TWA 8 hours: 308 mg/m <sup>3</sup> (2-methoxymetyl-ethoxypropanol). TWA 8 hours: 50 ppm (2-methoxymetyl-ethoxypropanol).
Dipropyleneglycolmethylether	<b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) [(2-metoksimitiletoksi)propanol]</b> Absorbed through skin. TWA 8 hours: 308 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm. KTV 15 minutes: 50 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 308 mg/m <sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].
Dipropyleneglycolmethylether	<b>National institute of occupational safety and health (Spain, 1/2024) [éter metílico de dipropilenglicol]</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 308 mg/m <sup>3</sup> .



## SECTION 8: Exposure controls/personal protection

Dipropyleneglycolmethylether	<p><b>Work environment authority Regulation 2018:1 (Sweden, 11/2022) [dipropylene glycol monomethyl ether]</b> Absorbed through skin.</p> <p>TWA 8 hours: 50 ppm.</p> <p>TWA 8 hours: 300 mg/m<sup>3</sup>.</p> <p>STEL 15 minutes: 75 ppm.</p> <p>STEL 15 minutes: 450 mg/m<sup>3</sup>.</p>
Dipropyleneglycolmethylether	<p><b>SUVA (Switzerland, 1/2025) [Dipropylenglycolmethylether (Isomerengemisch)]</b></p> <p>STEL 15 minutes: 50 ppm. Form: vapour and aerosols.</p> <p>STEL 15 minutes: 300 mg/m<sup>3</sup>. Form: vapour and aerosols.</p> <p>TWA 8 hours: 50 ppm. Form: vapour and aerosols.</p> <p>TWA 8 hours: 300 mg/m<sup>3</sup>. Form: vapour and aerosols.</p>
<p>reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)</p> <p>No exposure limit value known.</p>	<p><b>SUVA (Switzerland, 1/2025) Sensitiser.</b></p> <p>STEL 15 minutes: 0.4 mg/m<sup>3</sup>. Form: Inhalable fraction.</p> <p>TWA 8 hours: 0.2 mg/m<sup>3</sup>. Form: Inhalable fraction.</p>

## Biological exposure indices

[illegible]

## SECTION 8: Exposure controls/personal protection

No exposure indices known.

No exposure indices known.

No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

#### Product/ingredient name

Dipropyleneglycolmethylether

#### Result

##### DNEL - General population - Long term - Oral

36 mg/kg bw/day

Effects: Systemic

##### DNEL - General population - Long term - Inhalation

37.2 mg/m<sup>3</sup>

Effects: Systemic

##### DNEL - General population - Long term - Dermal

121 mg/kg bw/day

Effects: Systemic

##### DNEL - Workers - Long term - Dermal

283 mg/kg bw/day

Effects: Systemic

##### DNEL - Workers - Long term - Inhalation

308 mg/m<sup>3</sup>

Effects: Systemic

3-Butoxypropan-2-ol

##### DNEL - General population - Long term - Oral

12.5 mg/kg bw/day

Effects: Systemic

##### DNEL - General population - Long term - Dermal

22 mg/kg bw/day

Effects: Systemic

##### DNEL - General population - Long term - Inhalation

43 mg/m<sup>3</sup>

Effects: Systemic

##### DNEL - Workers - Long term - Dermal

52 mg/kg bw/day

Effects: Systemic

##### DNEL - Workers - Long term - Inhalation

147 mg/m<sup>3</sup>

Effects: Systemic

2,4,7,9-tetramethyl-5-decyne-4,7-diol

##### DNEL - General population - Long term - Oral

0.29 mg/kg bw/day

Effects: Systemic

##### DNEL - General population - Long term - Dermal

0.29 mg/kg bw/day

Effects: Systemic

## SECTION 8: Exposure controls/personal protection

### DNEL - General population - Long term - Inhalation

0.505 mg/m<sup>3</sup>

Effects: Systemic

### DNEL - Workers - Long term - Dermal

0.812 mg/kg bw/day

Effects: Systemic

### DNEL - Workers - Long term - Inhalation

2.86 mg/m<sup>3</sup>

Effects: Systemic

1,2-benzisothiazol-3(2H)-one

### DNEL - General population - Long term - Dermal

0.345 mg/kg bw/day

Effects: Systemic

### DNEL - Workers - Long term - Dermal

0.966 mg/kg bw/day

Effects: Systemic

### DNEL - General population - Long term - Inhalation

1.2 mg/m<sup>3</sup>

Effects: Systemic

### DNEL - Workers - Long term - Inhalation

6.81 mg/m<sup>3</sup>

Effects: Systemic

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

### DNEL - General population - Long term - Inhalation

0.02 mg/m<sup>3</sup>

Effects: Local

### DNEL - Workers - Long term - Inhalation

0.02 mg/m<sup>3</sup>

Effects: Local

### DNEL - General population - Short term - Inhalation

0.04 mg/m<sup>3</sup>

Effects: Local

### DNEL - Workers - Short term - Inhalation

0.04 mg/m<sup>3</sup>

Effects: Local

### DNEL - General population - Long term - Oral

0.09 mg/kg bw/day

Effects: Systemic

### DNEL - General population - Short term - Oral

0.11 mg/kg bw/day

Effects: Systemic

2-methyl-2H-isothiazol-3-one

### DNEL - General population - Long term - Inhalation

0.021 mg/m<sup>3</sup>

Effects: Local

### DNEL - Workers - Long term - Inhalation

0.021 mg/m<sup>3</sup>

Effects: Local

### DNEL - General population - Long term - Oral

0.027 mg/kg bw/day

Effects: Systemic

### DNEL - General population - Short term - Inhalation

## SECTION 8: Exposure controls/personal protection

0.043 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Short term - Inhalation**

0.043 mg/m<sup>3</sup>

Effects: Local

### **DNEL - General population - Short term - Oral**

0.053 mg/kg bw/day

Effects: Systemic

### PNECs

Not available.

## 8.2 Exposure controls

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Not recommended polyvinyl alcohol (PVA) gloves

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	: Liquid.
Colour	: White.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name	°C	°F	Method
Water	100	212	
3-Butoxypropan-2-ol	171	339.8	OECD 103

Flammability	: Not available.
Lower and upper explosion limit	: Lower: Not applicable. Upper: Not applicable.
Flash point	: Closed cup: >100°C (>212°F)
Auto-ignition temperature	:

Ingredient name	°C	°F	Method
Dipropyleneglycolmethylether	207	404.6	EU A.15
3-Butoxypropan-2-ol	260	500	EU A.15

Decomposition temperature	: Not available.
pH	: 7.4 to 8 [Conc. (% w/w): 100%]
Viscosity	: Not available.
Solubility(ies)	:
	Not available.

Solubility in water	: Not available.
Partition coefficient: n-octanol/ water	: Not applicable.
Vapour pressure	:

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	17.5	2.3				
3-Butoxypropan-2-ol	1.05	0.14	OECD 104			

Relative density	: Not available.
Density	: 1.2 g/cm³
Vapour density	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

### 9.2 Other information

#### 9.2.1 Information with regard to physical hazard classes

Explosive properties	: Not available.
Oxidising properties	: Not available.

#### 9.2.2 Other safety characteristics

Not applicable.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : No specific data.
- 10.5 Incompatible materials** : No specific data.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product/ingredient name

3-Butoxypropan-2-ol

##### Result

**Rabbit - Dermal - LD50**

3100 mg/kg

1,2-benzisothiazol-3(2H)-one

**Rat - Oral - LD50**

1020 mg/kg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

**Rat - Oral - LD50**

53 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

2-methyl-2H-isothiazol-3-one

**Rat - Inhalation - LC50 Dusts and mists**

0.11 mg/l [4 hours]

**Conclusion/Summary [Product]** : Not available.

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
3-Butoxypropan-2-ol	N/A	3100	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	53	50	N/A	0.5	N/A
2-methyl-2H-isothiazol-3-one	100	300	N/A	N/A	0.11

#### Skin corrosion/irritation

##### Product/ingredient name

2-propyleneglycolmethylether

##### Result

**Rabbit - Skin - Mild irritant**

Amount/concentration applied: 500 mg

3-Butoxypropan-2-ol

**Rabbit - Skin - Moderate irritant**

2,4,7,9-tetramethyl-5-decyne-4,7-diol

**Rabbit - Skin - Mild irritant**

Amount/concentration applied: 0.5 gm

1,2-benzisothiazol-3(2H)-one

**Human - Skin - Mild irritant**



## SECTION 11: Toxicological information

Duration of treatment/exposure: 48 hours

Amount/concentration applied: 5 %

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

**Human - Skin - Severe irritant**

Amount/concentration applied: 0.01 %

**Conclusion/Summary [Product]** : Not available.

**Ingredient name**

3-Butoxypropan-2-ol

**Conclusion/Summary**

Slightly irritating to the skin.

### Serious eye damage/eye irritation

**Product/ingredient name**

Dipropyleneglycolmethylether

**Result**

**Human - Eyes - Mild irritant**

Amount/concentration applied: 8 mg

**Rabbit - Eyes - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

2,4,7,9-tetramethyl-5-decyne-4,7-diol

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 0.1 MI

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

Not available.

### Skin

**Conclusion/Summary [Product]** : Not available.

### Respiratory

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

## SECTION 11: Toxicological information

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

### Information on likely routes of exposure

Not available.

### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
  - irritation
  - redness
- Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product/ingredient name

2,4,7,9-tetramethyl-5-decyne-4,7-diol

#### Result

##### LC50

Fish - *Cyprinus carpio*  
42 mg/l [96 hours]

##### EC50

Daphnia - *Daphnia magna*  
91 mg/l [48 hours]

1,2-benzisothiazol-3(2H)-one

##### Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test]  
Fish - Trout - *Onorhynchus Mykiss*  
1.9 mg/l [96 hours]

##### Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test]  
Daphnia - Daphnia - *Daphnia Magna*  
3.7 mg/l [48 hours]

##### Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test]  
Algae - Algae - *Skeletonema Costatum*  
0.36 mg/l [72 hours]

##### Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test]  
Algae - Algae - *Skeletonema Costatum*  
0.15 mg/l [72 hours]

2-methyl-2H-isothiazol-3-one

##### Acute - EC50 - Fresh water

US EPA  
Daphnia - Water flea - *Daphnia magna*  
Age: <24 hours  
0.18 ppm [48 hours]  
Effect: Intoxication

##### Acute - LC50 - Fresh water

US EPA  
Fish - Rainbow trout,donaldson trout - *Oncorhynchus mykiss*  
Weight: 0.73 g  
0.07 ppm [96 hours]  
Effect: Mortality

**Conclusion/Summary [Product]** : Not available.

### 12.2 Persistence and degradability

#### Product/ingredient name

2,2-benzisothiazol-3(2H)-one

#### Result

EU  
24% [28 days]

**Conclusion/Summary [Product]** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,2-benzisothiazol-3(2H)-one	-	-	Inherent

### 12.3 Bioaccumulative potential

## SECTION 12: Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Dipropyleneglycolmethylether	0.004	-	Low
3-Butoxypropan-2-ol	1.2	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

### 12.4 Mobility in soil

#### Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
3-Butoxypropan-2-ol	1.5	28.6002
2,4,7,9-tetramethyl-5-decyne-4,7-diol	1.9	83.8929
1,2-benzisothiazol-3(2H)-one	1.9	73.142
2-methyl-2H-isothiazol-3-one	1.7	54.9187

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Dipropyleneglycolmethylether	No	No	No	No	No	No	No
3-Butoxypropan-2-ol	No	No	No	No	No	No	No
2,4,7,9-tetramethyl-5-decyne-4,7-diol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	No	No	No	No	No	No	No
2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment

#### Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Dipropyleneglycolmethylether	No	N/A	N/A	No	N/A	N/A	N/A
3-Butoxypropan-2-ol	No	N/A	N/A	No	N/A	N/A	N/A
2,4,7,9-tetramethyl-5-decyne-4,7-diol	No	N/A	N/A	No	N/A	N/A	N/A
1,2-benzisothiazol-3(2H)-one	No	N/A	No	No	No	N/A	No
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	No	N/A	N/A	No	N/A	N/A	N/A
2-methyl-2H-isothiazol-3-one	No	N/A	N/A	No	N/A	N/A	N/A

#### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Dipropyleneglycolmethylether	No	No	No	No	No	No	No
3-Butoxypropan-2-ol	No	No	No	No	No	No	No
2,4,7,9-tetramethyl-5-decyne-4,7-diol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	No	No	No	No	No	No	No

## SECTION 12: Ecological information

2-methyl-2H-isothiazol-3-one	No	No	No	No	No	No	No
------------------------------	----	----	----	----	----	----	----

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PBT or vPvB.  
**Regulation (EC) No. 1272/2008**  
**[CLP]**

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : Avoid release to the environment. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**European waste catalogue (EWC)** : 080112, 200128

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number or ID number</b>	Not regulated.	Not regulated.	Not regulated.	Not regulated.
<b>14.2 UN proper shipping name</b>	-	-	-	-
<b>14.3 Transport hazard class(es)</b>	-	-	-	-
<b>14.4 Packing group</b>	-	-	-	-
<b>14.5 Environmental hazards</b>	No.	No.	No.	No.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## SECTION 14: Transport information

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

Product/ingredient name	%	Designation [Usage]
TEKNOCOAT AQUA 2577-11	≥90	3

**Labelling** :

**Synthetic polymer microparticles - Designation 78**

**Generic identity of polymer(s)** : 3901 - Polymers of ethylene., 3906 - Acrylic polymers., 3910 - Silicones.

**Total percentage of synthetic polymer microparticles** : 5.6%

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

**Other EU regulations**

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**Explosive precursors** : Not applicable.

**Ozone depleting substances (EU 2024/590)**

Not listed.

**Prior Informed Consent (PIC) (649/2012/EU)**

Not listed.

**Persistent Organic Pollutants**

Not listed.

**Seveso Directive**

This product is not controlled under the Seveso Directive.

**National regulations**

**Austria**

**Limitation of the use of organic solvents** : Permitted.

**Belgium**

**Book VI carcinogenic agents annex VI.2-1 - VI.2-3**



## SECTION 15: Regulatory information

Ingredient name	Status
Noirs de charbon	Listed

### Czech Republic

Storage code : IV

### Denmark

Fire class : IV-1

### Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
titanium dioxide	Listed	-

MAL-code : 0-1

**Protection based on MAL :** According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

 MAL-code: 0-1

**Application:** When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Arm protectors must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Gas filter mask must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Full mask with combined filter, coveralls and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

**Restrictions on use :** Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

**List of undesirable substances :** Not listed

## SECTION 15: Regulatory information

**Carcinogenic waste** : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

### Finland

### France

**Social Security Code, Articles L 461-1 to L 461-7** : Dipropyleneglycolmethylether RG 84  
3-Butoxypropan-2-ol RG 84

**Reinforced medical surveillance** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

### Germany

**Storage class (TRGS 510)** : 10

### Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

**Hazard class for water** : 2

### Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
5.2.1	Total dust	41.9
5.2.5	Organic substances	9.6
5.2.5 [I]	Organic substances	4.5

**AOX** : The product contains organically bound halogens and can contribute to the AOX value in waste water.

### Italy

**D.Lgs. 152/06** : Not determined.

### Netherlands

**Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances**

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development	Harmful via breastfeeding
(complexe) aardolie- en steenkoolderivaten EG nrs. beginnend met 232, 263, 265-275, 277, 278, 283-285, 287, 289, 291-298, 300, 302, 305-310	Listed	-	-	-	-

**Water Discharge Policy (ABM)** : Z(1) Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioacumulative potential/ toxicity or persistence). Decontamination effort: Z

### Norway

### Sweden

### Switzerland

**VOC content** : VOC (w/w): 6.3%

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

## SECTION 15: Regulatory information

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

#### 15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

#### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method

#### Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

#### Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B

Date of issue/ Date of revision : 02/12/2025

Date of previous issue : 08/07/2025

Version : 4

TEKNOCOAT AQUA 2577-11\_RAL 9003

RAL 9003

Date of issue/Date of revision : 02/12/2025 Date of previous issue : 08/07/2025

Version : 4 23/25

TEKNOCOAT AQUA 2577-11 - RAL 9003

Label No : 35645

## SECTION 16: Other information

### [Notice to reader](#)

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

