Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Malta

# **SAFETY DATA SHEET**



TEKNOCOAT AQUA PRIMER 1868-00 - TS 0100

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

## 1.1 Product identifier

Product name :

: TEKNOCOAT AQUA PRIMER 1868-00 - TS 0100

**1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use**: Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

responsible for this SDS

### **National contact**

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### 1.4 Emergency telephone number

### National advisory body/Poison Centre

 Telephone number
 : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

## **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Contains adipohydrazide, 2-mercaptoethanol and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and Bronopol and C(M)IT/MIT (3:1) and DTBMA and MBIT.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	

## **SECTION 2: Hazards identification**

### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
<mark>i</mark> tanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
Dipropyleneglycolmethylether	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤3	Not classified.	-	[2]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
2-mercaptoethanol	EC: 200-464-6 CAS: 60-24-2	<0.1	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 2, H361 STOT RE 2, H373 Aquatic Acute 1, H400	ATE [Oral] = 244 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 3 mg/l M [Acute] = 1	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq$  10 µm not bound within a matrix. Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

4.1 Description of first aid measures					
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.				
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.				
Skin contact	<ul> <li>Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.</li> </ul>				
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.				
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.				

### 4.2 Most important symptoms and effects, both acute and delayed <u>Over-exposure signs/symptoms</u>

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

## SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising f	ron	the substance or mixture
Hazards from the substance or mixture	1	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## **SECTION 6: Accidental release measures**

OECHICIT C. Accident	
6.1 Personal precautions, pro	otective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s) Recommendations Industrial sector specific solutions

- : Not available.
- : Not available.

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
	EU OEL (Europe, 1/2022). [(2-Methoxymethylethoxy)-propanol] Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. TWA: 308 mg/m <sup>3</sup> 8 hours.

#### **Biological exposure indices**

Product/ingredient name		Exposure indices	
No exposure indices known.			
procedures	European Stand assessment of e values and mea atmospheres - C of exposure to c (Workplace atm for the measure	Id be made to monitoring standards, such as the following: dard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit isurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 isospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be	

### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
<b>D</b> ipropyleneglycolmethylether	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	37.2 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	121 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	283 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	308 mg/m <sup>3</sup>	Workers	Systemic
adipohydrazide	DNEL	Long term Inhalation	17.5 mg/m <sup>3</sup>	Workers	Systemic
2-mercaptoethanol	DNEL	Short term Oral	0.025 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.025 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.05 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0.05 mg/ kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	0.17 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	0.17 mg/m <sup>3</sup>	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m³	Workers	Systemic

#### **PNECs**

Date of issue/Date of revision: 20/11/2023Date of previous issueTEKNOCOAT AQUA PRIMER 1868-00 - TS 0100

## **SECTION 8: Exposure controls/personal protection**

No PNECs available

8.2 Exposure controls			
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airbor contaminants.	ne	
Individual protection measure	<u>ires</u>		
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a rist assessment indicates this is necessary to avoid exposure to liquid splashes, mist gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses w side-shields.	ts,	
Skin protection			
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.		
	Recommendations : Wear suitable gloves tested to EN374.		
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm		
	Not recommended polyvinyl alcohol (PVA) gloves		
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	(	
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	Э	
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets th appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other importa aspects of use.		
	Filter type (spray application): A P		
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation In some cases, fume scrubbers, filters or engineering modifications to the proces equipment will be necessary to reduce emissions to acceptable levels.		

### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

Ingradiant name	°C	0 <b>E</b>
Initial boiling point and boiling range	:	
Melting point/freezing point	: Not available.	
Odour threshold	: Not available.	
Odour	: Slight	
Colour	: White.	
Physical state	: Liquid.	
<u>Appearance</u>		

Ingredient name		°C	°F	Method
water		100	212	
Dipropyleneglycolmeth	ylether	189.6	373.3	EU A.2
Flammability	: Not ava	ilable.	1	

```
Date of issue/Date of revision
                                                                         :05/09/2022
                                                                                                Version : 1.01 6/14
                                  : 20/11/2023 Date of previous issue
                                                                                             Label No :74181
TEKNOCOAT AQUA PRIMER 1868-00 - TS 0100
```

SECTION 9: Physical ar	nd ch	emical pro	perties		
Lower and upper explosion limit		ver: 1.1% per: 14%			
Flash point	: Clo	sed cup: >100°C	C(>212°F)		
Auto-ignition temperature	:				
Ingredient name		°C	°F	Method	
Dipropyleneglycolmethylether		207	404.6	EU A.15	
Decomposition temperature	: Not	available.		I	
рН	: Not	available.			
Viscosity	: Not	available.			
Solubility(ies)	:				
Not available.					
Solubility in water	: Not	available.			
Partition coefficient: n-octanol/ water	: Not	applicable.			
Vapour pressure	:				

	Va	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
Relative density	: Not	available.			I		
Density	: 1.3	: 1.3 g/cm <sup>3</sup>					
Vapour density	: Not available.						
Explosive properties	: Not available.						
Oxidising properties	: Not available.						
Particle characteristics							
Median particle size	: Not	applicable.					

SECTION 10: Stability and reactivity						
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.					
10.2 Chemical stability	: The product is stable.					
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.					
10.4 Conditions to avoid	: No specific data.					
10.5 Incompatible materials	: No specific data.					
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.					

## **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-mercaptoethanol 1,2-benzisothiazol-3(2H)- one	LD50 Oral LD50 Oral	Rat Rat	244 mg/kg 1020 mg/kg	-
Conclusion/Summary Acute toxicity estimates	: Based on available data, the c	assification crite	eria are not met.	•
	Route		ATE va	lue

### Irritation/Corrosion

Not available.

Product/ingredient name	Result	Species	Score	Exposure	Observation		
<b>ii</b> tanium dioxide	Skin - Mild irritant	Human	-	72 hours 300	-		
				ug l			
Dipropyleneglycolmethylether	Eyes - Mild irritant	Human	-	8 mg	-		
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-		
				mg			
	Skin - Mild irritant	Rabbit	-	500 mg	-		
2-mercaptoethanol	Eyes - Severe irritant	Rabbit	-	2 mg	-		
1,2-benzisothiazol-3(2H)-one	Skin - Mild irritant	Human	-	48 hours 5 %	-		
Conclusion/Summary	: Based on available data, the	classification cr	riteria are	not met.			
<u>Sensitisation</u>							
Conclusion/Summary	: Based on available data, the classification criteria are not met.						
<u>Mutagenicity</u>							
Conclusion/Summary	: Based on available data, the classification criteria are not met.						
Carcinogenicity							
It has been abeen ad that the	parainagania bazard of this produ	et origon when	roopirab	la duat ia inhala	d in quantition		

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

<b>Conclusion/Summary</b>	: Based on available data, the classification criteria are not met.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: Based on available data, the classification criteria are not met.
Teratogenicity	
<b>Conclusion/Summary</b>	: Based on available data, the classification criteria are not met.
Specific target organ toxic	<u>ity (single exposure)</u>
Not available.	

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
₽-mercaptoethanol	Category 2	-	-

### **Aspiration hazard**

Not available.

Information on likely routes of exposure	1	Not available.
Potential acute health effects	<u>)</u>	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the	physical, chemical and toxicological characteristics
Eye contact	: No specific data.

Date of issue/Date of revision	: 20/11/2023	Date of previous issue	: 05/09/2022	Version : 1.01 8/14
TEKNOCOAT AQUA PRIMER 1	868-00 - TS 07	100		Label No :74181

## **SECTION 11: Toxicological information**

Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure	_
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
<b>Conclusion/Summary</b>	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

#### 11.2 Information on other hazards

**11.2.1 Endocrine disrupting properties** 

Not available. 11.2.2 Other information

Not available.

## **SECTION 12: Ecological information**

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure	
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours	
	Acute LC50 6.5 mg/l Fresh water	Daphnia - <i>Daphnia pulex</i> - Neonate	48 hours	
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours	
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.36 mg/l Marine water Acute EC50 3.7 mg/l Acute LC50 1.9 mg/l Fresh water Acute NOEC 0.15 mg/l Marine water	Algae - Skeletonema Costatum Daphnia - Daphnia Magna Fish - Onorhynchus Mykiss Algae - Skeletonema Costatum	72 hours 48 hours 96 hours 72 hours	

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

Product/ingredient name	Test Result			Dose	Inoculum		
7,2-benzisothiazol-3(2H)-one	EU	24 % - 28 days		-	-		
<b>Conclusion/Summary</b> : This product has not been tested for biodegradation.							
Product/ingredient name	Aquatic half-life	Aquatic half-life		atic half-life Photolysis		5	Biodegradability
7,2-benzisothiazol-3(2H)-one	-		-		Inherent		

### **12.3 Bioaccumulative potential**

Date of issue/Date of revision	: 20/11/2023	Date of previous issue	: 05/09/2022	Version	:1.01	9/14
TEKNOCOAT AQUA PRIMER 18	68-00 - TS 0 <sup>-</sup>	100		Label No	: <b>7⁄</b> 418′	1

SECTION 12: Ecologi	cal informati	on	
Product/ingredient name	LogPow	BCF	Potential
<b>D</b> ipropyleneglycolmethylether	0.004	-	Low
2-mercaptoethanol	-0.056	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods **Product** Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. : Within the present knowledge of the supplier, this product is not regarded as Hazardous waste hazardous waste, as defined by EU Directive 2008/98/EC. : 080112.200128 **European waste** catalogue (EWC) Packaging Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. **Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

ADR/RID	ADN	IMDG	IATA		
Not regulated.	Not regulated.	Not regulated.	Not regulated.		
-	-	-	-		
-	-	-	-		
-	-	-	-		
	D23 Date of previous issu	e : 05/09/2022	Version : 1.01 10/14 Label No :7∕4181		
	Not regulated	Not regulated.       Not regulated.         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -         -       -	Not regulated.       Not regulated.       Not regulated.         -       -       -         -       -       -         -       -       -         -       -       -         -       -       -         -       -       -         -       -       -		

SECTION 14:	ransport ir	itormation			
14.5 Environmental hazards	No.	No.	No.	No.	
14.6 Special precau user	upr		e that persons transporti	ort in closed containers tha ng the product know what to	
14.7 Maritime trans bulk according to IN instruments		t relevant/applicable du	e to nature of the produc	t.	
SECTION 15: I	Regulatory	information			
15.1 Safety, health a	and environmen	tal regulations/legisla	tion specific for the su	bstance or mixture	
EU Regulation (EC	<u>) No. 1907/2006</u>	(REACH)			
Annex XIV - List o	of substances su	ubject to authorisation	1		
Annex XIV					
None of the com	ponents are liste	d.			
Substances of v	<mark>ery high concer</mark>	<u>n</u>			
None of the com	ponents are liste	d.			
Annex XVII - Restri substances, mixtu Labelling		anufacture, placing o	n the market and use c	<u>f certain dangerous</u>	
Other EU regulatio	inc				
Industrial emission (integrated pollut prevention and contain Air	ons : Not ion	t listed			
Industrial emission (integrated pollut prevention and co Water	ion	t listed			
Explosive precurs		t applicable. <mark>)5/2009/EU)</mark>			
Not listed.					
Prior Informed Co Not listed.	onsent (PIC) (64	<u>9/2012/EU)</u>			
Persistent Organ Not listed.	<u>ic Pollutants</u>				
Seveso Directive This product is not		the Seveso Directive.			
International regul	ations				
Chemical Weapon Not listed.	Convention Lis	t Schedules I, II & III C	<u>hemicals</u>		
Montreal Protocol Not listed.					
Stockholm Conver Not listed.	ntion on Persiste	ent Organic Pollutants	ž		

## **SECTION 15: Regulatory information**

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

## 15.2 Chemical safety assessment

: Not applicable.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative</li> </ul>

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

### Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

### Full text of classifications [CLP/GHS]

		05/09/2022				
Date of issue/ Date of revision	:	20/11/2023				
Eye Irrit. 2 Repr. 2 Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A STOT RE 2	SERIOUS REPROD SKIN CO SKIN SEI SKIN SEI	S EYE DAMA DUCTIVE TOX RROSION/IR NSITISATION NSITISATION	AGE/EYE IRRITATION - Cate XICITY - Category 2 RRITATION - Category 2 N - Category 1 N - Category 1A DRGAN TOXICITY - REPEA	egory 2	- Category 2	
Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 2 Carc. 2 Eye Dam. 1	ACUTE T SHORT-T LONG-TE CARCING	ERM (ĈHRON DGENICITY -	Category 4 TE) AQUATIC HAZARD - Ca NIC) AQUATIC HAZARD - C	Category 2		

Date of issue/Date of revision	. 20/11/2023	Date of previous issue	. 03/09/2022	Version	. 1.01
TEKNOCOAT AQUA PRIMER 18	368-00 - TS 01	100		Label No	: <mark>7</mark> 4181

## **SECTION 16: Other information**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.