Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

SAFETY DATA SHEET



TEKNOCOAT AQUA PRIMER 1875-98 - TS 14656 WHITE

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product ident	ifier
-------------------	-------

Product name : TEKNOCOAT AQUA PRIMER 1875-98 - TS 14656 WHITE

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

- Telephone number
- Emergency medical information: (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.
 Members of the public Number (8 am-10 pm): +353 (0)1 809 2166 Healthcare professional telephone Number (24hrs): +353 (0)1 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Contains adipohydrazide, 2-mercaptoethanol, 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and C (M)IT/MIT (3:1) and Bronopol and 2,2'-dithiobis[N-methylbenzamide] and MBIT.

SECTION 2: Hazards identification

CECTION E. Hazardo		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures Product/ingredient name	: Mixture	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
ifanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
Dipropyleneglycolmethylether	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤3	Not classified.	-	[2]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
2-mercaptoethanol	EC: 200-464-6 CAS: 60-24-2	<0.1	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 2, H361 STOT RE 2, H373 Aquatic Acute 1, H400	ATE [Oral] = 244 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 3 mg/l M [Acute] = 1	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: $C \ge 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1,	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C,	[1]
Date of issue/Date of revision	: 10/04/2025 Date	e of previous is	: 25/06/2024	Version : 2	2/17

SECTION 3: Composition/information on ingredients

SECTION 3. Composition/in	normation on ingredients	
	H410 EUH071 See Section 16 for	H314: C \ge 0.6% Eye Dam. 1, H318: C \ge 0.6% Eye Irrit. 2, H319: 0.06% \le C < 0.6% Skin Sens. 1, H317: C \ge 0.0015% M [Acute] = 100 M [Chronic] = 100
	the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/s	symptoms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

SECTION 5: Firefighting measures

 Hazards from the substance or mixture Hazardous combustion products Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides 	from the substance or mixture	
products carbon dioxide carbon monoxide metal oxide/oxides	: In a fire or if heated, a pressure in	ase will occur and the container may burst.
	carbon dioxide carbon monoxide	the following materials:
5.3 Advice for firefighters		
Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident there is a fire. No action shall be taken involving any personal risk or without suitable training.	there is a fire. No action shall be	
Special protective equipment for fire-fighters is Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	breathing apparatus (SCBA) with a mode. Clothing for fire-fighters (ir conforming to European standard	Ill face-piece operated in positive pressure iding helmets, protective boots and gloves)

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	otec	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	co	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill		Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/Date of revision	: 10/04/2025	Date of previous issue	: 25/06/2024	Version	:2	4/17
TEKNOCOAT AQUA PRIMER 187	'5-98 - TS 14	1656 WHITE		Label No	: <mark>1</mark> 13	739

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations Industrial sector specific solutions

: Not available.

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
	NAOSH (Ireland, 4/2024) [(2-methoxymethylethoxy)-1-propanol] Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values OELV 8 hours: 50 ppm. OELV 8 hours: 308 mg/m ³ .

Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	

Recommended monitoring procedures

DNELs/DMELs

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Product/ingredient name		<mark>Result</mark> DNEL - Genera 28 μg/m³ <u>Effects</u> : Local	al population - Lon	g term - Inhalation
		DNEL - Worke 170 μg/m³ <u>Effects</u> : Local	rs - Long term - Inl	halation
Dipropyleneglycolmethylether		DNEL - Gener 36 mg/kg bw/da <u>Effects</u> : System		ig term - Oral
		DNEL - Gener a 37.2 mg/m³ <u>Effects</u> : System		g term - Inhalation
		DNEL - Gener a 121 mg/kg bw/e	al population - Lon day	ig term - Dermal
Date of issue/Date of revision	: 10/04/2025	Date of previous issue	: 25/06/2024	Version :2 5/

SECTION 8: Exposure controls/pers	onal protection
	Effects: Systemic
	DNEL - Workers - Long term - Dermal 283 mg/kg bw/day <u>Effects</u> : Systemic DNEL - Workers - Long term - Inhalation
	308 mg/m ³ Effects: Systemic
adipohydrazide	DNEL - Workers - Long term - Inhalation 17.5 mg/m³ <u>Effects</u> : Systemic
2-mercaptoethanol	DNEL - General population - Short term - Oral 0.025 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Oral 0.025 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Short term - Dermal 0.05 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 0.05 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Short term - Inhalation 0.17 mg/m³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 0.17 mg/m ³ Effects: Systemic
1,2-benzisothiazol-3(2H)-one	DNEL - General population - Long term - Dermal 0.345 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 0.966 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 1.2 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 6.81 mg/m ³ <u>Effects</u> : Systemic
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL - General population - Long term - Inhalation 0.02 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Inhalation 0.02 mg/m³ <u>Effects</u> : Local
	DNEL - General population - Short term - Inhalation 0.04 mg/m ³

SECTION 8: Exposure controls/personal protection

Effects: Local

DNEL - Workers - Short term - Inhalation 0.04 mg/m³ <u>Effects</u>: Local

DNEL - General population - Long term - Oral 0.09 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Oral 0.11 mg/kg bw/day <u>Effects</u>: Systemic

PNECs

Not available.

8.2 Exposure controls		
Appropriate engineering controls		Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measured	<u>ires</u>	
Hygiene measures	b A V	Vash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Vash contaminated clothing before reusing. Ensure that eyewash stations and afety showers are close to the workstation location.
Eye/face protection	a g u	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, pases or dusts. If contact is possible, the following protection should be worn, inless the assessment indicates a higher degree of protection: safety glasses with ide-shields.
Skin protection		
Hand protection	b	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates his is necessary.
	F	Recommendations : Wear suitable gloves tested to EN374.
	>	\cdot 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	Ν	lot recommended polyvinyl alcohol (PVA) gloves
Body protection	b	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	S	Appropriate footwear and any additional skin protection measures should be elected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	a re	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a espiratory protection program to ensure proper fitting, training, and other important aspects of use.
	F	ilter type (spray application): A P
Environmental exposure controls	e Ir	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: White.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name	°C	°F	Method
water	100	212	
Dipropyleneglycolmethylether	189.6	373.3	EU A.2

Flamn	nability		1

Auto-ignition temperature

Not available.

Lower and upper explosion: Lower: Not applicable.limitUpper: Not applicable.

Flash point

: Closed cup: >100°C (>212°F) :

Ingredient name	°C	°F	Method
Dipropyleneglycolmethylether	207	404.6	EU A.15

Decomposition temperature	: Not available.
рН	: <mark>廖</mark> to 8.9 [Conc. (% w/w): 100%]
Viscosity	: Not available.
Solubility(ies)	:
Not available.	
Solubility in water	: Not available.
Partition coefficient: n-octanol/ water	: Not applicable.

ż

: Not available.

Vapour pressure

	Va	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
Relative density	: Not	available.					
Density	: 1.3	g/cm³					

Vapour density	
Particle characteristics	

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes			
Explosive properties	: Not available.		
Oxidising properties	: Not available.		
9.2.2 Other safety characteristics			

Not applicable.

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: No specific data.			
10.5 Incompatible materials	: No specific data.			
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.			

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined i	in Regulation (EC) No 1272/2008
Acute toxicity	
Product/ingredient name	Result
2-mercaptoethanol	Rat - Oral - LD50
	244 mg/kg
	<u>Toxic effects</u> : Behavioral - Excitement Behavioral - Muscle contraction or spasticity Lung, Thorax, or Respiration -
	Respiratory depression
1,2-benzisothiazol-3(2H)-one	Rat - Oral - LD50
	1020 mg/kg
reaction mass of: 5-chloro-2-methyl-	Rat - Oral - LD50
4-isothiazolin-3-one [EC no. 247-500-7] and	53 mg/kg
2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	<u>Toxic effects</u> : Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
2-mercaptoethanol	244	50	N/A	3	N/A
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	53	50	N/A	0.5	N/A

Product/ingredient name	Result
titanium dioxide	Human - Skin - Mild irritant
	Duration of treatment/exposure: 72 hours
	Amount/concentration applied: 300 ug l
Dipropyleneglycolmethylether	Rabbit - Skin - Mild irritant
	Amount/concentration applied: 500 mg
1,2-benzisothiazol-3(2H)-one	Human - Skin - Mild irritant
	Duration of treatment/exposure: 48 hours

SECTION 11: Toxicological information

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) <u>Amount/concentration applied</u>: 5 %

Human - Skin - Severe irritant Amount/concentration applied: 0.01 %

:	1	Not avai	lable	
				Result Human - Eyes - Mild irritant Amount/concentration applied: 8 mg
				Rabbit - Eyes - Mild irritant <u>Duration of treatment/exposure</u> : 24 hours <u>Amount/concentration applied</u> : 500 mg
				Rabbit - Eyes - Severe irritant Amount/concentration applied: 2 mg
:	1	Not avail	lable.	
:	1	Not avail	lable.	
:	1	Not avail	lable.	
:	1	Not avail	lable.	
:	1	Not avail	lable.	
	:	: 1	: Not avai : Not avai : Not avai	 Not available

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Date of issue/Date of revision: 10/04/2025Date of previous issueTEKNOCOAT AQUA PRIMER 1875-98 - TS 14656 WHITE

: 25/06/2024

SECTION 11: Toxicological information

Not available.

Specific target organ toxicit	<u>y (repeated exposure)</u>
Product/ingredient name	Result
Percaptoethanol	STOT RE 2, H373
Aspiration hazard	
Not available.	
Information on likely routes	<u>of exposure</u>
Not available.	
Potential acute health effect	_
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the phy	ysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effe	cts as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
Potential chronic health effe	<u>ects</u>
Not available.	
Conclusion/Summary [Pro	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

. . .

Conclusion/Summary [Product]

: In product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

2.1 Toxicity	
Product/ingredient name	Result
titanium dioxide	Acute - LC50 - Marine water
	Fish - Mummichog - <i>Fundulus heteroclitus</i> >1000000 µg/l [96 hours]
	Effect: Mortality
	Acute - LC50 - Fresh water
	Crustaceans - Water flea - <i>Ceriodaphnia dubia</i> - Neonate Age: <24 hours
	<u>Age</u> . <24 hours 3 mg/l [48 hours]
	Effect: Mortality
1,2-benzisothiazol-3(2H)-one	Acute - LC50 - Fresh water
	OECD [Fish, Acute Toxicity Test] Fish - Trout - <i>Onorhynchus Mykiss</i>
	1.9 mg/l [96 hours]
	Acute - EC50
	OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test]
	Daphnia - Daphnia - Daphnia Magna
	3.7 mg/l [48 hours]
	Acute - EC50 - Marine water
	OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i>
	0.36 mg/l [72 hours]
	Acute - NOEC - Marine water
	OECD 201 [Alga, Growth Inhibition Test]
	Algae - Algae - <i>Skeletonema Costatum</i> 0.15 mg/l [72 hours]
Conclusion/Summary [Product] : No	t available.

12.2 Persistence and degradability Product/ingredient name

2-benzisothiazol-3(2H)-one

Result EU

24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Dipropyleneglycolmethylether	-0.056	-	Low
2-mercaptoethanol		-	Low
1,2-benzisothiazol-3(2H)-one		3.2	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
adipohydrazide	1.74	55.2165
2-mercaptoethanol	0.98	9.63243
1,2-benzisothiazol-3(2H)-one	1.86	73.142

Results of PMT and vPvM assessment

Date of issue/Date of revision: 10/04/2025Date of previous issue: 25/06/2024VTEKNOCOAT AQUA PRIMER 1875-98 - TS 14656WHITELate

SECTION 12: Ecological information

Product/ingredient name	PMT	Р	Μ	Т	vPvM	vP	vM
titanium dioxide	No	No	No	No	No	No	No
Dipropyleneglycolmethylether	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
2-mercaptoethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Mobility Conclusion/Summary : Not available.

: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
Dipropyleneglycolmethylether	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
2-mercaptoethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
Dipropyleneglycolmethylether	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
2-mercaptoethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment meth	ods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
European waste catalogue (EWC)	: 080112
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ		
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.		
14.2 UN proper shipping name	-	-	-	-		
14.3 Transport hazard class(es)	-	-	-	-		
14.4 Packing group	-	-	-	-		
14.5 Environmental hazards	No.	No.	No.	No.		

user

- **14.6 Special precautions for** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
- 14.7 Maritime transport in bulk according to IMO instruments
- : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Date of issue/Date of revision	: 10/04/2025	Date of previous issue
TEKNOCOAT AQUA PRIMER	R 1875-98 - TS 14	4656 WHITE

: 25/06/2024

SECTION 15: Regulatory information

15.2 Chemical safety : Not applicable. assessment

SECTION 16: Other information

Indicates information the	hat has changed from previously issued version.
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
Dressedure used to derive	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

Full text of abbreviated H statements

Date of issue/Date of revision	: 10/04/2025	Date of previous issue	: 25/06/2024	Version	:2	15/17
TEKNOCOAT AQUA PRIMER 18	75-98 - TS 14	4656 WHITE		Label No	1137	39

SECTION	SECTION 16: Other information				
H301	Toxic if swallowed.				
H302	Harmful if swallowed.				
H310	Fatal in contact with skin.				
H314	Causes severe skin burns and eye damage.				
H315	Causes skin irritation.				
H317	May cause an allergic skin reaction.				
H318	Causes serious eye damage.				
H319	Causes serious eye irritation.				
H330	Fatal if inhaled.				
H331	Toxic if inhaled.				
H351	Suspected of causing cancer.				
H361	Suspected of damaging fertility or the unborn child.				
H373	May cause damage to organs through prolonged or repeated exposure.				
H400	Very toxic to aquatic life.				
H410	Very toxic to aquatic life with long lasting effects.				
H411	Toxic to aquatic life with long lasting effects.				
EUH071	Corrosive to the respiratory tract.				

Full text of classifications [CLP/GHS]

Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Carc. 2 Eye Dam. 1 Eye Irrit. 2 Repr. 2 Skin Corr. 1C Skin Irrit. 2	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 REPRODUCTIVE TOXICITY - Category 2 SKIN CORROSION/IRRITATION - Category 1C SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1 Skin Sens. 1A STOT RE 2	SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
Date of issue/ Date of revision	: 10/04/2025
Date of previous issue	: 25/06/2024
Version	: 2
	TEKNOCOAT AQUA PRIMER 1875-98_TS 14656 TS 14656 WHITE WHITE

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 10/04/2025Date of previous issueTEKNOCOAT AQUA PRIMER 1875-98 - TS 14656 WHITE

: 25/06/2024