Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - United Kingdom: Northern Ireland

# **SAFETY DATA SHEET**



TEKNOCOAT AQUA PRIMER 1875-98 - TS 14656 WHITE

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product ide	entifier
-----------------	----------

Product name : TEKNOCOAT AQUA PRIMER 1875-98 - TS 14656 WHITE

**1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use**: Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

```
responsible for this SDS
```

### **National contact**

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

### **1.4 Emergency telephone number**

National advisory body/Poison Centre

Telephone number : NHS: 111

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Contains adipohydrazide, 2-mercaptoethanol, 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and C (M)IT/MIT (3:1) and Bronopol and 2,2'-dithiobis[N-methylbenzamide] and MBIT.

## **SECTION 2: Hazards identification**

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

## **SECTION 3: Composition/information on ingredients**

Iffanium dioxide         REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7         ≥10 - ≤25         Carc. 2, H351 (inhalation)           adipohydrazide         REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8         <1         Skin Sens. 1, H317 Aquatic Chronic 2, H411           2-mercaptoethanol         EC: 200-464-6 CAS: 60-24-2         <0.1         Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Irrit. 2, H315 Eye Irrit. 2, H315 Sin Sens. 1A, H317 Repr. 2, H319 Skin Sens. 1A, H317 Repr. 2, H319 Skin Sens. 1A, H317 Repr. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410           reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazoli- 3-one [EC no. 220-239-6] (3:1)         EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5         <0.0015         Acute Tox. 3, H301 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Acute Tox. 2, H330	Specific Conc. Limits, M-factors and ATEs	Туре
01-2119962900-36       Aquatic Chronic 2, H411         2-mercaptoethanol       EC: 213-999-5         2-mercaptoethanol       EC: 200-464-6         CAS: 60-24-2       <0.1	-	[1] [*]
CAS: 60-24-2       Acute Tox. 2, H310         Acute Tox. 3, H331       Skin Irrit. 2, H315         Eye Irrit. 2, H319       Skin Sens. 1A, H317         Repr. 2, H361       STOT RE 2, H373         Aquatic Acute 1, H400       Acute Tox. 4, H302         Acute Tox. 2, H310       Acute Tox. 4, H302         Acute Tox. 2, H315       Eye Dam. 1, H315         Eye Dam. 1, H318       Skin Irrit. 2, H315         Eye Dam. 1, H318       Skin Sens. 1A, H317         Aquatic Acute 1, H400       Aquatic Chronic 1, H410         reaction mass of: 5-chloro-       EC: 911-418-6         2-methyl-4-isothiazolin-       CAS: 55965-84-9         3-one [EC no. 247-500-7]       Index: 613-167-00-5         and 2-methyl-2H-isothiazol-       Acute Tox. 2, H310         3-one [EC no. 220-239-6]       Index: 613-167-00-5         (3:1)       CAS: 25965-84-9         Index: 613-167-00-5       Skin Sens. 1A, H317         Aquatic Acute 1, H400       Acute Tox. 2, H310         Acute Tox. 2, H310       Acute Tox. 2, H310         Acute Tox. 2, H316       Skin Sens. 1A, H317 <td< td=""><td>-</td><td>[1]</td></td<>	-	[1]
one         CAS: 2634-33-5 Index: 613-088-00-6         Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410           reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)         EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5         <0.0015	ATE [Oral] = 244 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 3 mg/l M [Acute] = 1	[1]
2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1) CAS: 55965-84-9 Index: 613-167-00-5 Acute Tox. 2, H310 Acute Tox. 2, H310 Acute Tox. 2, H310 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = $0.21 \text{ mg/l}$ Skin Sens. 1, H317: $C \ge 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]
	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: 0.06% $\le C < 0.6\%$	[1]
Date of issue/Date of revision         : 10/04/2025         Date of previous issue         : 25/06/2024	Version : 2	2/17

SECTION 3: Composition/ir	nformation on ingredients	
	Skin Sens. 1 C ≥ 0.0015% M [Acute] = M [Chronic] the full text of the H statements declared above.	100

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

Substance classified with a health or environmental hazard

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq$  10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	<ul> <li>Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.</li> </ul>
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most important symptoms and effects, both acute and delayed

### Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the : In a fire or if heated, a pressure increase will occur and the container may burst. substance or mixture

SECTION 5: Firefighting measures		
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

## **SECTION 7: Handling and storage**

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

Product/ingredient	name	Exposure limit values
No exposure limit value known.		
Biological exposure indices		
Product/ingredient	name	Exposure indices
No exposure indices known.		
Recommended monitoring : procedures	European Stand assessment of e values and mea atmospheres - ( of exposure to o (Workplace atm for the measure	Id be made to monitoring standards, such as the following: dard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit isurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedure ment of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be
DNELs/DMELs		
Product/ingredient name		Result
titanium dioxide		<b>DNEL - General population - Long term - Inhalation</b> 28 µg/m <sup>3</sup> <u>Effects</u> : Local
		<b>DNEL - Workers - Long term - Inhalation</b> 170 μg/m³ <u>Effects</u> : Local
Dipropyleneglycolmethylether		<b>DNEL - General population - Long term - Oral</b> 36 mg/kg bw/day <u>Effects</u> : Systemic
		<b>DNEL - General population - Long term - Inhalation</b> 37.2 mg/m <sup>3</sup> <u>Effects</u> : Systemic
		<b>DNEL - General population - Long term - Dermal</b> 121 mg/kg bw/day <u>Effects</u> : Systemic
		<b>DNEL - Workers - Long term - Dermal</b> 283 mg/kg bw/day <u>Effects</u> : Systemic
		DNEL - Workers - Long term - Inhalation
ate of issue/Date of revision	: 10/04/2025 Da	te of previous issue : 25/06/2024 Version : 2 5/17

## **SECTION 8: Exposure controls/personal protection**

	308 mg/m³ <u>Effects</u> : Systemic
adipohydrazide	<b>DNEL - Workers - Long term - Inhalation</b> 17.5 mg/m³ <u>Effects</u> : Systemic
2-mercaptoethanol	<b>DNEL - General population - Short term - Oral</b> 0.025 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - General population - Long term - Oral</b> 0.025 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - Workers - Short term - Dermal</b> 0.05 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - Workers - Long term - Dermal</b> 0.05 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - Workers - Short term - Inhalation</b> 0.17 mg/m <sup>3</sup> <u>Effects</u> : Systemic
	<b>DNEL - Workers - Long term - Inhalation</b> 0.17 mg/m <sup>3</sup> <u>Effects</u> : Systemic
1,2-benzisothiazol-3(2H)-one	<b>DNEL - General population - Long term - Dermal</b> 0.345 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - Workers - Long term - Dermal</b> 0.966 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - General population - Long term - Inhalation</b> 1.2 mg/m <sup>3</sup> <u>Effects</u> : Systemic
	<b>DNEL - Workers - Long term - Inhalation</b> 6.81 mg/m <sup>3</sup> <u>Effects</u> : Systemic
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	<b>DNEL - General population - Long term - Inhalation</b> 0.02 mg/m <sup>3</sup> <u>Effects</u> : Local
	<b>DNEL - Workers - Long term - Inhalation</b> 0.02 mg/m³ <u>Effects</u> : Local
	<b>DNEL - General population - Short term - Inhalation</b> 0.04 mg/m <sup>3</sup> <u>Effects</u> : Local
	<b>DNEL - Workers - Short term - Inhalation</b> 0.04 mg/m <sup>3</sup> <u>Effects</u> : Local
	DNEL - General population - Long term - Oral 0.09 mg/kg bw/day

## **SECTION 8: Exposure controls/personal protection**

Effects: Systemic

**DNEL - General population - Short term - Oral** 0.11 mg/kg bw/day <u>Effects</u>: Systemic

### **PNECs**

Not available.

8.2 Exposure controls		
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborn contaminants.	е
Individual protection measu	<u>es</u>	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.	
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.	
Skin protection		
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard shoul be worn at all times when handling chemical products if a risk assessment indicate this is necessary.	
	Recommendations : Wear suitable gloves tested to EN374.	
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm	
	Not recommended polyvinyl alcohol (PVA) gloves	
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.	
	Filter type (spray application): A P	
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	

## **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physic	cal and chemical properties	
Appearance		
Physical state	: Liquid.	
Colour	: White.	
Odour	: Slight	
Odour threshold	: Not available.	
Melting point/freezing point	: Not available.	
Date of issue/Date of revision	: 10/04/2025 Date of previous issue	: 25/

```
TEKNOCOAT AQUA PRIMER 1875-98 - TS 14656 WHITE
```

25/06/2024

Version : 2 7/17

## **SECTION 9: Physical and chemical properties**

1

## Initial boiling point and

### boiling range

Ingredient name			°C	°F	Method	
water			100	212		
Dipropyleneglycolmethylether			189.6	373.3	EU A.2	
Flammability	:	Not ava	ilable.	1	1	
Lower and upper explosion limit	:		Not applicat Not applicat			
Flash point	:	Closed	cup: >100°0	C (>212°F)		
Auto-ignition temperature	:					
Ingredient name			°C	°F	Method	
Dipropyleneglycolmethylether			207	404.6	EU A.15	
Decomposition temperature	:	Not ava	ilable.			
pH	:	<mark>8</mark> to 8.9	[Conc. (% \	w/w): 100%]		
Viscosity	1	Not ava	ilable.			
Solubility(ies)	1					
Not available.						
Solubility in water	:	Not ava	ilable.			
Partition coefficient: n-octanol/ water	:	Not app	olicable.			
Vapour pressure	÷					

	Va	apour Pres	sure at 20°C	Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
Relative density	: Not	available.	I				
Density	: 1.3	g/cm³					
Vapour density	: Not	available.					

vapour density	i Not available.
Particle characteristics	
Median particle size	: Not applicable.

### 9.2 Other information

9.2.1 Information with regard to physical hazard classes						
Explosive properties	: Not available.					
Oxidising properties	: Not available.					
0.2.2 Other enfety character	inting					

### 9.2.2 Other safety characteristics

Not applicable.

## **SECTION 10: Stability and reactivity**

10.1 Reactivity	: No sp	ecific t	est data rela	ted to react	ivity available for	this product or its	ingred	lients.
10.2 Chemical stability	: The p	oroduct	is stable.					
10.3 Possibility of hazardous reactions	: Unde	r norma	al conditions	of storage	and use, hazardo	ous reactions will i	not occ	ur.
10.4 Conditions to avoid	: No sp	ecific o	lata.					
10.5 Incompatible materials	: No sp	ecific o	lata.					
Date of issue/Date of revision	: 10/0	4/2025	Date of previo	ous issue	: 25/06/2024	Version	:2	8/17
TEKNOCOAT AQUA PRIMER	1875-98	- TS 14	656 WHITE			Label No	:1137	39

## **SECTION 10: Stability and reactivity**

- 10.6 Hazardous decomposition products
- : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

Product/ingredient name	Result
2-mercaptoethanol	<b>Rat - Oral - LD50</b> 244 mg/kg <u>Toxic effects</u> : Behavioral - Excitement Behavioral - Muscle contraction or spasticity Lung, Thorax, or Respiration - Respiratory depression
1,2-benzisothiazol-3(2H)-one	<b>Rat - Oral - LD50</b> 1020 mg/kg
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	<b>Rat - Oral - LD50</b> 53 mg/kg <u>Toxic effects</u> : Behavioral - Somnolence (general depresse activity) Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression

### Conclusion/Summary [Product] : Not available.

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
2-mercaptoethanol	244	50	N/A	3	N/A
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	53	50	N/A	0.5	N/A

#### **Skin corrosion/irritation**

Product/ingredient name titanium dioxide	Result Human - Skin - Mild irritant Duration of treatment/exposure: 72 hours Amount/concentration applied: 300 ug l
Dipropyleneglycolmethylether	Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg
1,2-benzisothiazol-3(2H)-one	Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Human - Skin - Severe irritant Amount/concentration applied: 0.01 %
Conclusion/Summary [Product] : Not availab	le.
Serious eye damage/eye irritation	
Product/ingredient name	Result
Pote of issue (Pote of revision 10/04/2025 Pote	

: 25/06/2024

SECTION 11: Toxicological informati	on
Dipropyleneglycolmethylether	Human - Eyes - Mild irritant Amount/concentration applied: 8 mg
	Rabbit - Eyes - Mild irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 500 mg
2-mercaptoethanol	Rabbit - Eyes - Severe irritant Amount/concentration applied: 2 mg
Conclusion/Summary [Product] : Not available	
Respiratory corrosion/irritation Not available.	
Conclusion/Summary [Product] : Not available	
Respiratory or skin sensitization Not available.	
Skin	
Conclusion/Summary [Product] : Not available	
Respiratory	
Conclusion/Summary [Product] : Not available	
<u>Germ cell mutagenicity</u> Not available.	
Conclusion/Summary [Product] : Not available	
Carcinogenicity It has been observed that the carcinogenic hazard of leading to significant impairment of particle clearance Not available.	this product arises when respirable dust is inhaled in quantities mechanisms in the lung.
Conclusion/Summary [Product] : Not available	
Reproductive toxicity Not available.	
Conclusion/Summary [Product] : Not available	
<u>Specific target organ toxicity (single exposure)</u> Not available.	
Specific target organ toxicity (repeated exposure)	
Product/ingredient name	Result
2-mercaptoethanol	STOT RE 2, H373
Aspiration hazard	
Not available.	
Information on likely routes of exposure Not available.	
Date of issue/Date of revision : 10/04/2025 Date of	previous issue : 25/06/2024 Version : 2 10/17
TEKNOCOAT AQUA PRIMER 1875-98 - TS 14656 WH	HITE Label No : 13739

## **SECTION 11: Toxicological information**

	•
Potential acute health effect	<u>is</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	ysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effe	cts as well as chronic effects from short and long-term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	
Potential chronic health effe	
Not available.	
Conclusion/Summary [Pro	
	-
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

### 11.2 Information on other hazards

### **11.2.1 Endocrine disrupting properties**

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 11.2.2 Other information

Not available.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity **Product/ingredient name** titanium dioxide

#### Result

Acute - LC50 - Marine water Fish - Mummichog - Fundulus heteroclitus >1000000 µg/l [96 hours] Effect: Mortality

### Acute - LC50 - Fresh water

Crustaceans - Water flea - Ceriodaphnia dubia - Neonate Age: <24 hours 3 mg/l [48 hours] Effect: Mortality

1,2-benzisothiazol-3(2H)-one

### Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test] Fish - Trout - Onorhynchus Mykiss 1.9 mg/l [96 hours]

### Acute - EC50

Date of issue/Date of revision	: 10/04/2025	Date of previous issue	: 25/06/2024	Version ::	2 11/17
TEKNOCOAT AQUA PRIMER 1	875-98 - TS 14	4656 WHITE		Label No :ք	13739

## **SECTION 12: Ecological information**

OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - *Daphnia Magna* 3.7 mg/l [48 hours]

Acute - EC50 - Marine water OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.36 mg/l [72 hours]

Acute - NOEC - Marine water OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.15 mg/l [72 hours]

Conclusion/Summary [Product] : Not available.

### 12.2 Persistence and degradability Product/ingredient name

7,2-benzisothiazol-3(2H)-one

Result

EU 24% [28 days]

### Conclusion/Summary [Product] : Not available.

Product/ingredie	nt name	Aquatic half-life	Photolysis	Biodegradability
7,2-benzisothiazol	-3(2H)-one -	-	-	Inherent

#### **12.3 Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
<b>D</b> ipropyleneglycolmethylether	0.004	-	Low
2-mercaptoethanol	-0.056	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

### 12.4 Mobility in soil

### Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
adipohydrazide 2-mercaptoethanol 1,2-benzisothiazol-3(2H)-one		55.2165 9.63243 73.142

### Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	Μ	т	vPvM	vP	٧M
titanium dioxide	No	No	No	No	No	No	No
Dipropyleneglycolmethylether	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Mobility

: Not available.

**Conclusion/Summary** 

: The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Date of issue/Date of revision: 10/04/2025Date of previous issueTEKNOCOAT AQUA PRIMER 1875-98 - TS 14656 WHITE

: 25/06/2024

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
Dipropyleneglycolmethylether	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
2-mercaptoethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
titanium dioxide	No	No	No	No	No	No	No
Dipropyleneglycolmethylether	No	No	No	No	No	No	No
adipohydrazide	No	No	No	No	No	No	No
2-mercaptoethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro-	No	No	No	No	No	No	No
2-methyl-4-isothiazolin-							
3-one [EC no. 247-500-7]							
and 2-methyl-2H-isothiazol-							
3-one [EC no. 220-239-6] (3:							
1)							
Conclusion/Summary	•	: The produc	t does not n	neet the crite	eria to be cons	idered as a	PBT or vPv
		•					

**Regulation (EC) No. 1272/2008** 

[CLP]

### **12.6 Endocrine disrupting properties**

Not available.

```
Conclusion/Summary [Product]
```

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
European waste catalogue (EWC)	: 080112
Packaging	
Methods of disposal	<ul> <li>The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.</li> </ul>
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
Date of issue/Date of revision	: 10/04/2025 Date of previous issue : 25/06/2024 Version : 2 13/17

## **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

: Not relevant/applicable due to nature of the product.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14/17

#### 14.7 Maritime transport in bulk according to IMO instruments

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

### **Annex XIV**

None of the components are listed.

### Substances of very high concern

None of the components are listed.

EKNOCOAT AQUA PRIMER	875-98 - TS 14656 WH	HITE		Label No	:1137	39
Date of issue/Date of revision	: 10/04/2025 Date of	previous issue	: 25/06/2024	Version	:2	14
Seveso Directive						
Persistent Organic Pollutar Not listed.	<u>ts</u>					
Not listed.						
Prior Informed Consent (PI	C) (649/2012/EU)					
Not listed.						
Explosive precursors Ozone depleting substance	: Not applicable.					
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed					
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed					
Other EU regulations						
Labelling	:					
substances, mixtures and a	licies					

## **SECTION 15: Regulatory information**

This product is not controlled under the Seveso Directive.

### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

**15.2 Chemical safety**: Not applicable.assessment

### **SECTION 16: Other information**

✓ Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

## **SECTION 16: Other information**

SECTION 10. OU	
Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
Date of issue/ Date of revision	: 10/04/2025
Date of previous issue	: 25/06/2024
-	: 2
Version	
	TEKNOCOAT AQUA PRIMER 1875-98_TS 14656 TS 14656 WHITE

#### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 10/04/2025Date of previous issueTEKNOCOAT AQUA PRIMER 1875-98 - TS 14656 WHITE

: 25/06/2024